

Algorithms

Insertion sort

Emanuele Rodolà
rodola@di.uniroma1.it



Exercises

In pseudocode or in your favorite language, write an algorithm to solve each of the following problems.

- ① Reverse any given sequence of length n :

$$(3, 7, 9, 14) \rightarrow (14, 9, 7, 3)$$

- ② Given a number x and a sequence $(a_i)_{i=1}^n$, find the closest number to x in the sequence.

$$12.1, (3, 31, 7, 11, 52) \rightarrow 11$$

- ③ Given a sequence $(a_i)_{i=1}^n$ and a smaller sequence $(b_i)_{i=1}^m$, $m < n$, find the latter inside the former, and return the index of the first occurrence as output.

$$(C, G, A, T, T, G, C, \dots), (T, T, G \dots) \rightarrow 4$$

Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.

Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.

(a)

1	2	3	4	5	6
5	2	4	6	1	3


Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.





Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.





Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.






Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.







Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.








Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.









Insertion sort

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Intuition: Take one **key** at a time from the sequence, and insert it into the correct position in the new sequence.



Pseudocode

INSERTION-SORT(A)

```
1  for  $j \leftarrow 2$  to  $\text{length}[A]$ 
2      do  $\text{key} \leftarrow A[j]$ 
3           $\triangleright$  Insert  $A[j]$  into the sorted sequence  $A[1 \dots j - 1]$ .
```

Remark: The sequence is sorted **in-place**.

Pseudocode

INSERTION-SORT(A)

```
1  for  $j \leftarrow 2$  to  $\text{length}[A]$ 
2      do  $\text{key} \leftarrow A[j]$ 
3           $\triangleright$  Insert  $A[j]$  into the sorted sequence  $A[1 \dots j - 1]$ .
4           $i \leftarrow j - 1$ 
5          while  $i > 0$  and  $A[i] > \text{key}$ 
6              do  $A[i + 1] \leftarrow A[i]$ 
7                   $i \leftarrow i - 1$ 
8           $A[i + 1] \leftarrow \text{key}$ 
```

Remark: The sequence is sorted **in-place**.

Analysis

We want to predict the **resources** that the algorithm requires.

- Memory
- Bandwidth
- Time
- ...

Analysis

We want to predict the **resources** that the algorithm requires.

- Memory
- Bandwidth
- Time
- ...

Most of these factors ultimately depend on the **size of the input**.

As we have seen, we will measure the running time (i.e., the **number of steps**) as a function of size.

Analysis

INSERTION-SORT(A)

1 **for** $j \leftarrow 2$ **to** $\text{length}[A]$

cost *times*

c_1 n

Analysis

INSERTION-SORT(A)

1 **for** $j \leftarrow 2$ **to** $\text{length}[A]$

2 **do** $\text{key} \leftarrow A[j]$

cost *times*

c_1 n

c_2 $n - 1$

Analysis

INSERTION-SORT(A)	<i>cost</i>	<i>times</i>
1 for $j \leftarrow 2$ to $\text{length}[A]$	c_1	n
2 do $\text{key} \leftarrow A[j]$	c_2	$n - 1$
3 \triangleright Insert $A[j]$ into the sorted sequence $A[1 \dots j - 1]$.	0	$n - 1$

Analysis

INSERTION-SORT(A)		<i>cost</i>	<i>times</i>
1	for $j \leftarrow 2$ to $\text{length}[A]$	c_1	n
2	do $\text{key} \leftarrow A[j]$	c_2	$n - 1$
3	\triangleright Insert $A[j]$ into the sorted sequence $A[1 \dots j - 1]$.	0	$n - 1$
4	$i \leftarrow j - 1$	c_4	$n - 1$

Analysis

INSERTION-SORT(A)	<i>cost</i>	<i>times</i>
1 for $j \leftarrow 2$ to $\text{length}[A]$	c_1	n
2 do $\text{key} \leftarrow A[j]$	c_2	$n - 1$
3 \triangleright Insert $A[j]$ into the sorted sequence $A[1..j-1]$.	0	$n - 1$
4 $i \leftarrow j - 1$	c_4	$n - 1$
5 while $i > 0$ and $A[i] > \text{key}$	c_5	
6 do $A[i+1] \leftarrow A[i]$	c_6	
7 $i \leftarrow i - 1$	c_7	

Analysis

INSERTION-SORT(A)	<i>cost</i>	<i>times</i>
1 for $j \leftarrow 2$ to $\text{length}[A]$	c_1	n
2 do $\text{key} \leftarrow A[j]$	c_2	$n - 1$
3 \triangleright Insert $A[j]$ into the sorted sequence $A[1 \dots j - 1]$.	0	$n - 1$
4 $i \leftarrow j - 1$	c_4	$n - 1$
5 while $i > 0$ and $A[i] > \text{key}$	c_5	
6 do $A[i + 1] \leftarrow A[i]$	c_6	
7 $i \leftarrow i - 1$	c_7	
8 $A[i + 1] \leftarrow \text{key}$	c_8	$n - 1$

Analysis

INSERTION-SORT(A)		<i>cost</i>	<i>times</i>
1	for $j \leftarrow 2$ to $\text{length}[A]$	c_1	n
2	do $\text{key} \leftarrow A[j]$	c_2	$n - 1$
3	\triangleright Insert $A[j]$ into the sorted sequence $A[1 \dots j - 1]$.	0	$n - 1$
4	$i \leftarrow j - 1$	c_4	$n - 1$
5	while $i > 0$ and $A[i] > \text{key}$	c_5	
6	do $A[i + 1] \leftarrow A[i]$	c_6	
7	$i \leftarrow i - 1$	c_7	
8	$A[i + 1] \leftarrow \text{key}$	c_8	$n - 1$

The **while** instruction is not executed a fixed number of times. It depends on the current number j .

Analysis

INSERTION-SORT(A)		<i>cost</i>	<i>times</i>
1	for $j \leftarrow 2$ to $\text{length}[A]$	c_1	n
2	do $\text{key} \leftarrow A[j]$	c_2	$n - 1$
3	\triangleright Insert $A[j]$ into the sorted sequence $A[1 \dots j - 1]$.	0	$n - 1$
4	$i \leftarrow j - 1$	c_4	$n - 1$
5	while $i > 0$ and $A[i] > \text{key}$	c_5	
6	do $A[i + 1] \leftarrow A[i]$	c_6	
7	$i \leftarrow i - 1$	c_7	
8	$A[i + 1] \leftarrow \text{key}$	c_8	$n - 1$

The **while** instruction is not executed a fixed number of times. It depends on the current number j .

We define t_j the number of times **while** is executed for the value j .

Analysis

INSERTION-SORT(A)		<i>cost</i>	<i>times</i>
1	for $j \leftarrow 2$ to $\text{length}[A]$	c_1	n
2	do $\text{key} \leftarrow A[j]$	c_2	$n - 1$
3	\triangleright Insert $A[j]$ into the sorted sequence $A[1 \dots j - 1]$.	0	$n - 1$
4	$i \leftarrow j - 1$	c_4	$n - 1$
5	while $i > 0$ and $A[i] > \text{key}$	c_5	$\sum_{j=2}^n t_j$
6	do $A[i + 1] \leftarrow A[i]$	c_6	$\sum_{j=2}^n (t_j - 1)$
7	$i \leftarrow i - 1$	c_7	$\sum_{j=2}^n (t_j - 1)$
8	$A[i + 1] \leftarrow \text{key}$	c_8	$n - 1$

The **while** instruction is not executed a fixed number of times.
It depends on the current number j .

We define t_j the number of times **while** is executed for the value j .

Analysis

	<i>cost</i>	<i>times</i>
INSERTION-SORT(<i>A</i>)		
1 for <i>j</i> ← 2 to <i>length</i> [<i>A</i>]	c_1	n
2 do <i>key</i> ← <i>A</i> [<i>j</i>]	c_2	$n - 1$
3 ▷ Insert <i>A</i> [<i>j</i>] into the sorted sequence <i>A</i> [1 .. <i>j</i> − 1].	0	$n - 1$
4 <i>i</i> ← <i>j</i> − 1	c_4	$n - 1$
5 while <i>i</i> > 0 and <i>A</i> [<i>i</i>] > <i>key</i>	c_5	$\sum_{j=2}^n t_j$
6 do <i>A</i> [<i>i</i> + 1] ← <i>A</i> [<i>i</i>]	c_6	$\sum_{j=2}^n (t_j - 1)$
7 <i>i</i> ← <i>i</i> − 1	c_7	$\sum_{j=2}^n (t_j - 1)$
8 <i>A</i> [<i>i</i> + 1] ← <i>key</i>	c_8	$n - 1$

Total running time $T(n)$:

$$c_1n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n t_j + c_6 \sum_{j=2}^n (t_j - 1) + c_7 \sum_{j=2}^n (t_j - 1) + c_8(n-1)$$

Best-case analysis

“We define t_j the number of times **while** is executed for the value j ”

This means that there is a **best-case** running time, obtained with $t_j = 1$.

Best-case analysis

“We define t_j the number of times **while** is executed for the value j ”

This means that there is a **best-case** running time, obtained with $t_j = 1$.

$$\begin{aligned} T(n) = & c_1n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n t_j \\ & + c_6 \sum_{j=2}^n (t_j - 1) + c_7 \sum_{j=2}^n (t_j - 1) + c_8(n-1) \end{aligned}$$

Best-case analysis

“We define t_j the number of times **while** is executed for the value j ”

This means that there is a **best-case** running time, obtained with $t_j = 1$.

$$T(n) = c_1n + c_2(n - 1) + c_4(n - 1) + c_5(n - 1) + c_8(n - 1)$$

Best-case analysis

“We define t_j the number of times **while** is executed for the value j ”

This means that there is a **best-case** running time, obtained with $t_j = 1$.

$$T(n) = (c_1 + c_2 + c_4 + c_5 + c_8)n - (c_2 + c_4 + c_5 + c_8)$$

Best-case analysis

“We define t_j the number of times **while** is executed for the value j ”

This means that there is a **best-case** running time, obtained with $t_j = 1$.

$$T(n) = \underbrace{(c_1 + c_2 + c_4 + c_5 + c_8)}_a n - \underbrace{(c_2 + c_4 + c_5 + c_8)}_b$$

Best-case analysis

“We define t_j the number of times **while** is executed for the value j ”

This means that there is a **best-case** running time, obtained with $t_j = 1$.

$$T(n) = an + b$$

where a and b are **constants**.

The best-case cost of insertion sort is **linear in n** .

Best-case analysis

“We define t_j the number of times **while** is executed for the value j ”

This means that there is a **best-case** running time, obtained with $t_j = 1$.

$$T(n) = an + b$$

where a and b are **constants**.

The best-case cost of insertion sort is **linear in n** .

When does the best case happen?

Best-case analysis

“We define t_j the number of times **while** is executed for the value j ”

This means that there is a **best-case** running time, obtained with $t_j = 1$.

$$T(n) = an + b$$

where a and b are **constants**.

The best-case cost of insertion sort is **linear in n** .

When does the best case happen?

When the input sequence is **already sorted**.

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$\begin{aligned} T(n) = & c_1 n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n t_j \\ & + c_6 \sum_{j=2}^n (t_j - 1) + c_7 \sum_{j=2}^n (t_j - 1) + c_8(n-1) \end{aligned}$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$\begin{aligned} T(n) = & c_1 n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n j \\ & + c_6 \sum_{j=2}^n (j-1) + c_7 \sum_{j=2}^n (j-1) + c_8(n-1) \end{aligned}$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$T(n) = c_1n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n j \\ + c_6 \sum_{j=2}^n (j-1) + c_7 \sum_{j=2}^n (j-1) + c_8(n-1)$$

$$\sum_{i=1}^n i =$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$\begin{aligned} T(n) = & c_1 n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n j \\ & + c_6 \sum_{j=2}^n (j-1) + c_7 \sum_{j=2}^n (j-1) + c_8(n-1) \end{aligned}$$

$$\sum_{i=1}^n i = (1+n) +$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$\begin{aligned} T(n) = & c_1 n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n j \\ & + c_6 \sum_{j=2}^n (j-1) + c_7 \sum_{j=2}^n (j-1) + c_8(n-1) \end{aligned}$$

$$\sum_{i=1}^n i = (1+n) + \underbrace{(2+(n-1))}_{1+n} +$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$T(n) = c_1n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n j \\ + c_6 \sum_{j=2}^n (j-1) + c_7 \sum_{j=2}^n (j-1) + c_8(n-1)$$

$$\sum_{i=1}^n i = (1+n) + \underbrace{(2+(n-1))}_{1+n} + \underbrace{(3+(n-2))}_{1+n} + \dots$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$T(n) = c_1n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n j \\ + c_6 \sum_{j=2}^n (j-1) + c_7 \sum_{j=2}^n (j-1) + c_8(n-1)$$

$$\sum_{i=1}^n i = (1+n) + \underbrace{(2+(n-1))}_{1+n} + \underbrace{(3+(n-2))}_{1+n} + \cdots = (1+n) \frac{n}{2}$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$\begin{aligned} T(n) = & c_1 n + c_2(n-1) + c_4(n-1) + c_5 \sum_{j=2}^n j \\ & + c_6 \sum_{j=2}^n (j-1) + c_7 \sum_{j=2}^n (j-1) + c_8(n-1) \end{aligned}$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$\begin{aligned} T(n) = & c_1 n + c_2(n-1) + c_4(n-1) + c_5 \left(\frac{n(n+1)}{2} - 1 \right) \\ & + c_6 \left(\frac{n(n-1)}{2} \right) + c_7 \left(\frac{n(n-1)}{2} \right) + c_8(n-1) \end{aligned}$$

Worst-case analysis

What if the input sequence is sorted in **decreasing order**?

In this case, $t_j = j$ since we will compare each number with the entire sorted subsequence.

$$T(n) = an^2 + bn + c$$

where a, b, c are **constants**.

The worst-case cost of insertion sort is **quadratic in n** .

Average-case analysis

For a given **random** sequence of numbers, we observe that, on average:

- $A[j] >$ half the elements in $A[1 \dots j - 1]$, and
- $A[j] <$ half the elements in $A[1 \dots j - 1]$

Average-case analysis

For a given **random** sequence of numbers, we observe that, on average:

- $A[j] >$ half the elements in $A[1 \dots j - 1]$, and
- $A[j] <$ half the elements in $A[1 \dots j - 1]$

So, on average, $t_j = \frac{j}{2}$.

Average-case analysis

For a given **random** sequence of numbers, we observe that, on average:

- $A[j] >$ half the elements in $A[1 \dots j - 1]$, and
- $A[j] <$ half the elements in $A[1 \dots j - 1]$

So, on average, $t_j = \frac{j}{2}$.

Following the steps from the worst case, we get again:

$$T(n) = an^2 + bn + c$$

for some constants a, b, c .

Average-case analysis

For a given **random** sequence of numbers, we observe that, on average:

- $A[j] >$ half the elements in $A[1 \dots j - 1]$, and
- $A[j] <$ half the elements in $A[1 \dots j - 1]$

So, on average, $t_j = \frac{j}{2}$.


Following the steps from the worst case, we get again:

$$T(n) = an^2 + bn + c$$

for some constants a, b, c .


In our analysis, we will often concentrate on studying the **worst case**, since it gives us a guaranteed **upper bound** on the total cost.

Order of growth



an^2 dominates the lower-order terms.

Order of growth



an^2 dominates the lower-order terms.

We say that insertion sort has worst-case running time of $\Theta(n^2)$.

Exercises

Solve the following exercises:

- 1 Write an algorithm in pseudocode to perform **linear search**.

Given a sequence of numbers $A = (a_1, \dots, a_n)$ and a number v , find an index i such that $v = A[i]$. Return a special number if v can not be found in the sequence.

The search must be done by simple linear scanning through the sequence.

- 2 How many elements must be checked on **average**, and in the **best** and **worst** cases?
- 3 What are the average-case, best-case, and worst-case running times of linear search in Θ -notation?

Suggested reading

“Introduction to Algorithms – 2nd Ed.”, Cormen et al.

- Chapter 2.1, skipping the “Loop invariants” and “Pseudocode conventions” paragraphs
- Chapter 2.2