

Algorithms

Divide et impera

Emanuele Rodolà
rodola@di.uniroma1.it



Breaking the problem

Overall idea:

- ① Break the main problem into many **subproblems**

Breaking the problem

Overall idea:

- ① Break the main problem into many **subproblems**
 - Each subproblem is similar to the original problem

Breaking the problem

Overall idea:

- ① Break the main problem into many **subproblems**
 - Each subproblem is similar to the original problem
 - Each subproblem is **smaller** in size

Breaking the problem

Overall idea:

- ➊ Break the main problem into many **subproblems**
 - Each subproblem is similar to the original problem
 - Each subproblem is **smaller** in size
- ➋ Solve each subproblem **recursively**

Breaking the problem

Overall idea:

- ① Break the main problem into many **subproblems**
 - Each subproblem is similar to the original problem
 - Each subproblem is **smaller** in size
- ② Solve each subproblem **recursively**
 - Each subproblem will be split into sub-subproblems, and so on...

Breaking the problem

Overall idea:

- ① Break the main problem into many **subproblems**
 - Each subproblem is similar to the original problem
 - Each subproblem is **smaller** in size
- ② Solve each subproblem **recursively**
 - Each subproblem will be split into sub-subproblems, and so on...
- ③ Combine the solutions

Breaking the problem

Overall idea:

- ① Break the main problem into many **subproblems (DIVIDE)**
 - Each subproblem is similar to the original problem
 - Each subproblem is **smaller** in size
- ② Solve each subproblem **recursively (CONQUER)**
 - Each subproblem will be split into sub-subproblems, and so on...
- ③ Combine the solutions **(COMBINE)**

Breaking the problem

Overall idea:

- ➊ Break the main problem into many **subproblems (DIVIDE)**
 - Each subproblem is similar to the original problem
 - Each subproblem is **smaller** in size
- ➋ Solve each subproblem **recursively (CONQUER)**
 - Each subproblem will be split into sub-subproblems, and so on...
- ➌ Combine the solutions **(COMBINE)**

This general approach is called **divide et impera** or also **divide and conquer**.

Merge sort

Again, we consider the sorting problem as a toy example.

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Merge sort

Again, we consider the sorting problem as a toy example.

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Divide-et-impera recipe:

- 1 Divide the n -element sequence into two $\frac{n}{2}$ -element sequences

Merge sort

Again, we consider the sorting problem as a toy example.

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Divide-et-impera recipe:

- 1 Divide the n -element sequence into two $\frac{n}{2}$ -element sequences
- 2 Sort each subsequence [using mergesort](#)

Merge sort

Again, we consider the sorting problem as a toy example.

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Divide-et-impera recipe:

- ➊ Divide the n -element sequence into two $\frac{n}{2}$ -element sequences
- ➋ Sort each subsequence [using mergesort](#)
- ➌ [Merge](#) the two sorted subsequences

Merge sort

Again, we consider the sorting problem as a toy example.

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Divide-et-impera recipe:

- ➊ Divide the n -element sequence into two $\frac{n}{2}$ -element sequences
- ➋ Sort each subsequence [using mergesort](#)
- ➌ [Merge](#) the two sorted subsequences

At some point, the generated subsequences will have length **1**
 \Rightarrow no more splitting needed!

We call this the [base case](#).

Merge sort

Again, we consider the sorting problem as a toy example.

Input: A sequence of n numbers (a_1, a_2, \dots, a_n)

Output: A reordered sequence $(a'_1, a'_2, \dots, a'_n)$ such that:

$$a'_1 \leq a'_2 \leq \dots \leq a'_n$$

Divide-et-impera recipe:

- ➊ Divide the n -element sequence into two $\frac{n}{2}$ -element sequences
- ➋ Sort each subsequence [using mergesort](#)
- ➌ [Merge](#) the two sorted subsequences ← **key step**

At some point, the generated subsequences will have length **1**
 \Rightarrow no more splitting needed!

We call this the [base case](#).

Divide-et-impera

We translate the original problem into a **different** and **easier** subproblem of smaller size.

Divide-et-impera

We translate the original problem into a **different** and **easier** subproblem of smaller size.

Sorting problem \Rightarrow Merging problem

Complete algorithm

MERGE-SORT(A, p, r)

1 **if** $p < r$

2 **then** $q \leftarrow \lfloor (p + r)/2 \rfloor$

3 MERGE-SORT(A, p, q)

4 MERGE-SORT($A, q + 1, r$)

5 MERGE(A, p, q, r)

Complete algorithm

MERGE-SORT(A, p, r)

```
1  if  $p < r$ 
2      then  $q \leftarrow \lfloor (p + r)/2 \rfloor$ 
3          MERGE-SORT( $A, p, q$ )
4          MERGE-SORT( $A, q + 1, r$ )
5          MERGE( $A, p, q, r$ )
```

- The procedure calls itself **recursively**.

Complete algorithm

MERGE-SORT(A, p, r)

```
1  if  $p < r$ 
2      then  $q \leftarrow \lfloor (p + r)/2 \rfloor$ 
3          MERGE-SORT( $A, p, q$ )
4          MERGE-SORT( $A, q + 1, r$ )
5          MERGE( $A, p, q, r$ )
```

- The procedure calls itself **recursively**.
- Start: call merge sort on $(A, 1, \text{length}[A])$.

Complete algorithm

MERGE-SORT(A, p, r)

```
1  if  $p < r$ 
2      then  $q \leftarrow \lfloor (p + r)/2 \rfloor$ 
3          MERGE-SORT( $A, p, q$ )
4          MERGE-SORT( $A, q + 1, r$ )
5          MERGE( $A, p, q, r$ )
```

- The procedure calls itself **recursively**.
- Start: call merge sort on $(A, 1, \text{length}[A])$.
- Keep splitting until $p < r$ is false...

Complete algorithm

```
MERGE-SORT( $A, p, r$ )  
1  if  $p < r$   
2      then  $q \leftarrow \lfloor (p + r)/2 \rfloor$   
3          MERGE-SORT( $A, p, q$ )  
4          MERGE-SORT( $A, q + 1, r$ )  
5          MERGE( $A, p, q, r$ )
```

- The procedure calls itself **recursively**.
- Start: call merge sort on $(A, 1, \text{length}[A])$.
- Keep splitting until $p < r$ is false...
- ...which is the **base case**: the two halves have **length 1**.

Complete algorithm

MERGE-SORT(A, p, r)

```
1  if  $p < r$ 
2      then  $q \leftarrow \lfloor (p + r)/2 \rfloor$ 
3          MERGE-SORT( $A, p, q$ )
4          MERGE-SORT( $A, q + 1, r$ )
5          MERGE( $A, p, q, r$ )
```


- The procedure calls itself **recursively**.
- Start: call merge sort on $(A, 1, \text{length}[A])$.
- Keep splitting until $p < r$ is false...
- ...which is the **base case**: the two halves have **length 1**.
- If $\text{length}[A]$ is a power of 2, we always split in equal halves.
Q: Why doesn't this happen for even $\text{length}[A]$?

Example




initial sequence


Example




Example




Example




Example




Example



Example



Example



Merge operation

Splitting is easy: just separate sequence A into two subsequences:

$$A[p \dots q] \quad A[q + 1 \dots r]$$

Merge operation

Splitting is easy: just separate sequence A into two subsequences:

$$A[p \dots q] \quad A[q + 1 \dots r]$$

Assume that the two subsequences are **sorted**.

We want to **merge** them and form a sorted subsequence

$$A[p \dots r]$$

Merge operation

Splitting is easy: just separate sequence A into two subsequences:

$$A[p \dots q] \quad A[q + 1 \dots r]$$

Assume that the two subsequences are **sorted**.

We want to **merge** them and form a sorted subsequence

$$A[p \dots r]$$

Main idea:

- 1 Compare only the **first** element of the two sequences

Merge operation

Splitting is easy: just separate sequence A into two subsequences:

$$A[p \dots q] \quad A[q + 1 \dots r]$$

Assume that the two subsequences are **sorted**.

We want to **merge** them and form a sorted subsequence

$$A[p \dots r]$$

Main idea:

- 1 Compare only the **first** element of the two sequences
- 2 Take out the **smaller** one, and put it in the output sequence

Merge operation

Splitting is easy: just separate sequence A into two subsequences:

$$A[p \dots q] \quad A[q + 1 \dots r]$$

Assume that the two subsequences are **sorted**.

We want to **merge** them and form a sorted subsequence

$$A[p \dots r]$$

Main idea:

- 1 Compare only the **first** element of the two sequences
- 2 Take out the **smaller** one, and put it in the output sequence
- 3 Go back to step (1) until **one** of the two sequences is empty

MERGE(A, p, q, r)

$$1 \quad n_1 \leftarrow q - p + 1$$

$$2 \quad n_2 \leftarrow r - q$$

MERGE(A, p, q, r)

1 $n_1 \leftarrow q - p + 1$

2 $n_2 \leftarrow r - q$

3 create arrays $L[1 \dots n_1 + 1]$ and $R[1 \dots n_2 + 1]$

MERGE(A, p, q, r)

1 $n_1 \leftarrow q - p + 1$

2 $n_2 \leftarrow r - q$

3 create arrays $L[1 \dots n_1 + 1]$ and $R[1 \dots n_2 + 1]$

4 **for** $i \leftarrow 1$ **to** n_1

5 **do** $L[i] \leftarrow A[p + i - 1]$

6 **for** $j \leftarrow 1$ **to** n_2

7 **do** $R[j] \leftarrow A[q + j]$

MERGE(A, p, q, r)

1 $n_1 \leftarrow q - p + 1$

2 $n_2 \leftarrow r - q$

3 create arrays $L[1 \dots n_1 + 1]$ and $R[1 \dots n_2 + 1]$

4 **for** $i \leftarrow 1$ **to** n_1

5 **do** $L[i] \leftarrow A[p + i - 1]$

6 **for** $j \leftarrow 1$ **to** n_2

7 **do** $R[j] \leftarrow A[q + j]$

8 $L[n_1 + 1] \leftarrow \infty$

9 $R[n_2 + 1] \leftarrow \infty$


MERGE(A, p, q, r)

```
1   $n_1 \leftarrow q - p + 1$ 
2   $n_2 \leftarrow r - q$ 
3  create arrays  $L[1 \dots n_1 + 1]$  and  $R[1 \dots n_2 + 1]$ 
4  for  $i \leftarrow 1$  to  $n_1$ 
5      do  $L[i] \leftarrow A[p + i - 1]$ 
6  for  $j \leftarrow 1$  to  $n_2$ 
7      do  $R[j] \leftarrow A[q + j]$ 
8   $L[n_1 + 1] \leftarrow \infty$ 
9   $R[n_2 + 1] \leftarrow \infty$ 
10  $i \leftarrow 1$ 
11  $j \leftarrow 1$ 
12 for  $k \leftarrow p$  to  $r$ 
13     do if  $L[i] \leq R[j]$ 
14         then  $A[k] \leftarrow L[i]$ 
15              $i \leftarrow i + 1$ 
16         else  $A[k] \leftarrow R[j]$ 
17              $j \leftarrow j + 1$ 
```

Merge example


	8	9	10	11	12	13	14	15	16	17
A	...	2	4	5	7	1	2	3	6	...
	k									

Merge example




The light gray numbers make up the original sequence

Merge example




The light gray numbers make up the original sequence

Merge example




The light gray numbers make up the original sequence

Merge example




The light gray numbers make up the original sequence

Merge example




The light gray numbers make up the original sequence

Merge example




The light gray numbers make up the original sequence

Merge example




The light gray numbers make up the original sequence

Merge example




The light gray numbers make up the original sequence

Merge example




The light gray numbers make up the original sequence

Merge example



The light gray numbers make up the original sequence

Merge example



The light gray numbers make up the original sequence

Order of growth (merge operation only)

```
MERGE( $A, p, q, r$ )  
constant || 1  $n_1 \leftarrow q - p + 1$   
           || 2  $n_2 \leftarrow r - q$   
           || 3 create arrays  $L[1 \dots n_1 + 1]$  and  $R[1 \dots n_2 + 1]$   
           || 4 for  $i \leftarrow 1$  to  $n_1$   
           || 5     do  $L[i] \leftarrow A[p + i - 1]$   
           || 6 for  $j \leftarrow 1$  to  $n_2$   
           || 7     do  $R[j] \leftarrow A[q + j]$   
constant || 8  $L[n_1 + 1] \leftarrow \infty$   
           || 9  $R[n_2 + 1] \leftarrow \infty$   
           || 10  $i \leftarrow 1$   
           || 11  $j \leftarrow 1$   
           || 12 for  $k \leftarrow p$  to  $r$   
           || 13     do if  $L[i] \leq R[j]$   
           || 14       then  $A[k] \leftarrow L[i]$   
           || 15          $i \leftarrow i + 1$   
           || 16     else  $A[k] \leftarrow R[j]$   
           || 17        $j \leftarrow j + 1$ 
```

Order of growth (merge operation only)

```
MERGE( $A, p, q, r$ )  
constant || 1  $n_1 \leftarrow q - p + 1$   
          || 2  $n_2 \leftarrow r - q$   
          || 3 create arrays  $L[1 \dots n_1 + 1]$  and  $R[1 \dots n_2 + 1]$   
linear in  $n_1$  || 4 for  $i \leftarrow 1$  to  $n_1$   
              || 5     do  $L[i] \leftarrow A[p + i - 1]$   
linear in  $n_2$  || 6 for  $j \leftarrow 1$  to  $n_2$   
              || 7     do  $R[j] \leftarrow A[q + j]$   
constant || 8  $L[n_1 + 1] \leftarrow \infty$   
          || 9  $R[n_2 + 1] \leftarrow \infty$   
          || 10  $i \leftarrow 1$   
          || 11  $j \leftarrow 1$   
          || 12 for  $k \leftarrow p$  to  $r$   
          || 13     do if  $L[i] \leq R[j]$   
          || 14         then  $A[k] \leftarrow L[i]$   
          || 15              $i \leftarrow i + 1$   
          || 16     else  $A[k] \leftarrow R[j]$   
          || 17          $j \leftarrow j + 1$ 
```

Order of growth (merge operation only)

```
MERGE( $A, p, q, r$ )  
constant || 1  $n_1 \leftarrow q - p + 1$   
          || 2  $n_2 \leftarrow r - q$   
          || 3 create arrays  $L[1 \dots n_1 + 1]$  and  $R[1 \dots n_2 + 1]$   
linear in  $n$  || 4 for  $i \leftarrow 1$  to  $n_1$   
          || 5     do  $L[i] \leftarrow A[p + i - 1]$   
          || 6 for  $j \leftarrow 1$  to  $n_2$   
          || 7     do  $R[j] \leftarrow A[q + j]$   
constant || 8  $L[n_1 + 1] \leftarrow \infty$   
          || 9  $R[n_2 + 1] \leftarrow \infty$   
          || 10  $i \leftarrow 1$   
          || 11  $j \leftarrow 1$   
          || 12 for  $k \leftarrow p$  to  $r$   
          || 13     do if  $L[i] \leq R[j]$   
          || 14         then  $A[k] \leftarrow L[i]$   
          || 15              $i \leftarrow i + 1$   
          || 16     else  $A[k] \leftarrow R[j]$   
          || 17          $j \leftarrow j + 1$ 
```


Order of growth (merge operation only)

```
MERGE( $A, p, q, r$ )  
constant || 1  $n_1 \leftarrow q - p + 1$   
          || 2  $n_2 \leftarrow r - q$   
          || 3 create arrays  $L[1 \dots n_1 + 1]$  and  $R[1 \dots n_2 + 1]$   
linear in  $n$  || 4 for  $i \leftarrow 1$  to  $n_1$   
          || 5     do  $L[i] \leftarrow A[p + i - 1]$   
          || 6 for  $j \leftarrow 1$  to  $n_2$   
          || 7     do  $R[j] \leftarrow A[q + j]$   
constant || 8  $L[n_1 + 1] \leftarrow \infty$   
          || 9  $R[n_2 + 1] \leftarrow \infty$   
          || 10  $i \leftarrow 1$   
          || 11  $j \leftarrow 1$   
linear in  $n$  || 12 for  $k \leftarrow p$  to  $r$   
          || 13     do if  $L[i] \leq R[j]$   
          || 14         then  $A[k] \leftarrow L[i]$   
          || 15              $i \leftarrow i + 1$   
          || 16     else  $A[k] \leftarrow R[j]$   
          || 17          $j \leftarrow j + 1$ 
```

Order of growth (merge operation only)

```
MERGE( $A, p, q, r$ )  
 $\Theta(1)$  1  $n_1 \leftarrow q - p + 1$   
2  $n_2 \leftarrow r - q$   
3 create arrays  $L[1 \dots n_1 + 1]$  and  $R[1 \dots n_2 + 1]$   
 $\Theta(n)$  4 for  $i \leftarrow 1$  to  $n_1$   
5     do  $L[i] \leftarrow A[p + i - 1]$   
6 for  $j \leftarrow 1$  to  $n_2$   
7     do  $R[j] \leftarrow A[q + j]$   
 $\Theta(1)$  8  $L[n_1 + 1] \leftarrow \infty$   
9  $R[n_2 + 1] \leftarrow \infty$   
10  $i \leftarrow 1$   
11  $j \leftarrow 1$   
12 for  $k \leftarrow p$  to  $r$   
13     do if  $L[i] \leq R[j]$   
14         then  $A[k] \leftarrow L[i]$   
15              $i \leftarrow i + 1$   
16     else  $A[k] \leftarrow R[j]$   
17          $j \leftarrow j + 1$   
 $\Theta(n)$ 
```

Order of growth (merge operation only)

$\Theta(n)$

```
MERGE( $A, p, q, r$ )
1   $n_1 \leftarrow q - p + 1$ 
2   $n_2 \leftarrow r - q$ 
3  create arrays  $L[1 \dots n_1 + 1]$  and  $R[1 \dots n_2 + 1]$ 
4  for  $i \leftarrow 1$  to  $n_1$ 
5      do  $L[i] \leftarrow A[p + i - 1]$ 
6  for  $j \leftarrow 1$  to  $n_2$ 
7      do  $R[j] \leftarrow A[q + j]$ 
8   $L[n_1 + 1] \leftarrow \infty$ 
9   $R[n_2 + 1] \leftarrow \infty$ 
10  $i \leftarrow 1$ 
11  $j \leftarrow 1$ 
12 for  $k \leftarrow p$  to  $r$ 
13     do if  $L[i] \leq R[j]$ 
14         then  $A[k] \leftarrow L[i]$ 
15              $i \leftarrow i + 1$ 
16     else  $A[k] \leftarrow R[j]$ 
17          $j \leftarrow j + 1$ 
```

Order of growth (complete merge sort algorithm)

$$T(n) =$$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \end{cases}$$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{split}} + \underbrace{C(n)}_{\text{merge}} & n > a \end{cases}$$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{split}} + \underbrace{2T(\frac{n}{2})}_{\text{cost on the two halves}} + \underbrace{C(n)}_{\text{merge}} & n > a \end{cases}$$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{divide}} + \underbrace{2T(\frac{n}{2})}_{\text{conquer}} + \underbrace{C(n)}_{\text{combine}} & n > a \end{cases}$$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{divide}} + \underbrace{2T(\frac{n}{2})}_{\text{conquer}} + \underbrace{C(n)}_{\text{combine}} & n > a \end{cases}$$

Divide: $\Theta(1)$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{divide}} + \underbrace{2T(\frac{n}{2})}_{\text{conquer}} + \underbrace{C(n)}_{\text{combine}} & n > a \end{cases}$$

Divide: $\Theta(1)$

Conquer: $2T(\frac{n}{2})$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{divide}} + \underbrace{2T(\frac{n}{2})}_{\text{conquer}} + \underbrace{C(n)}_{\text{combine}} & n > a \end{cases}$$

Divide: $\Theta(1)$

Conquer: $2T(\frac{n}{2})$

Combine: $\Theta(n)$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{divide}} + \underbrace{2T(\frac{n}{2})}_{\text{conquer}} + \underbrace{C(n)}_{\text{combine}} & n > a \end{cases}$$

Divide: $\Theta(1)$

Conquer: $2T(\frac{n}{2})$

Combine: $\Theta(n)$

$$T(n) = \begin{cases} \Theta(1) & n = 1 \\ 2T(\frac{n}{2}) + \Theta(n) & n > 1 \end{cases}$$

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{divide}} + \underbrace{2T(\frac{n}{2})}_{\text{conquer}} + \underbrace{C(n)}_{\text{combine}} & n > a \end{cases}$$

Divide: $\Theta(1)$

Conquer: $2T(\frac{n}{2})$

Combine: $\Theta(n)$

$$T(n) = \begin{cases} \Theta(1) & n = 1 \\ 2T(\frac{n}{2}) + \Theta(n) & n > 1 \end{cases}$$

We are not done yet!

Order of growth (complete merge sort algorithm)

$$T(n) = \begin{cases} \Theta(1) & n \leq a \\ \underbrace{D(n)}_{\text{divide}} + \underbrace{2T(\frac{n}{2})}_{\text{conquer}} + \underbrace{C(n)}_{\text{combine}} & n > a \end{cases}$$

Divide: $\Theta(1)$

Conquer: $2T(\frac{n}{2})$

Combine: $\Theta(n)$

$$T(n) = \begin{cases} c & n = 1 \\ 2T(\frac{n}{2}) + cn & n > 1 \end{cases}$$

We are not done yet!


Recursion tree

$T(n)$

(a)

Recursion tree

$T(n)$




(a)

(b)


Recursion tree

$T(n)$




(a)

(b)




(c)

Recursion tree




(d)

Recursion tree




(d)

Recursion tree



(d)

Recursion tree



(d)

Total: $cn \lg n + cn$

Order of growth (complete merge sort algorithm)

$$T(n) = cn \lg n + cn$$

Order of growth (complete merge sort algorithm)

$$T(n) = \underbrace{cn \lg n}_{\text{dominant}} + cn$$

Order of growth (complete merge sort algorithm)

$$T(n) = \underbrace{cn \lg n}_{\text{dominant}} + cn$$

Therefore, merge sort grows like:

$$\Theta(n \lg n)$$

Order of growth (complete merge sort algorithm)

$$T(n) = \underbrace{cn \lg n}_{\text{dominant}} + cn$$

Therefore, merge sort grows like:

$$\Theta(n \lg n)$$

We will see that this is true also if n is **not** a power of 2.

For now, we observe that **dividing** seems to be beneficial!

Exercises

Write pseudocode for **binary search**. The task is the same as the one for linear search:

Given a sequence of numbers $A = (a_1, \dots, a_n)$ and a number v , find an index i such that $v = A[i]$. Return a special number if v can not be found in the sequence.

However, the algorithm is different:

- 1 Assume that the sequence is **sorted**
- 2 Check at the midpoint, and eliminate half of the sequence
- 3 Keep halving, either **iteratively** or **recursively**
- 4 Check that the worst-case running time is $\Theta(\lg n)$. Is this more or less efficient than linear search?

Suggested reading

Chapters 2.3.1 and 2.3.2 of:

“Introduction to Algorithms – 2nd Ed.”, Cormen et al.