

# Deep Learning & Applied AI

Stochastic gradient descent

Emanuele Rodolà  
[rodola@di.uniroma1.it](mailto:rodola@di.uniroma1.it)



SAPIENZA  
UNIVERSITÀ DI ROMA


# Logistic regression

We got to the following **convex** loss:

$$\ell_{\Theta}(\{x_i, y_i\}) = - \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b))$$

Here,  $\sigma$  is the nonlinear **logistic sigmoid**:

$$\sigma(x) = \frac{1}{1 + e^{-x}}$$



$\sigma$  has a **saturation** effect as it maps  $\mathbb{R} \mapsto (0, 1)$ .

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \ell_{\Theta} = 0$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$\nabla_{\Theta} (y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)))$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$\nabla_{\Theta} y_i \ln(\sigma(ax_i + b)) + \nabla_{\Theta} (1 - y_i) \ln(1 - \sigma(ax_i + b))$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \ln(\sigma(ax_i + b)) + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \frac{\partial g}{\partial h} \cdot \frac{\partial h}{\partial \textcolor{red}{a}}$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \frac{\partial g}{\partial h} \cdot \frac{\partial}{\partial \textcolor{red}{a}} ax_i + b$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \frac{\partial g}{\partial h} \cdot x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial a} f(g(h(a, b))) = \frac{\partial f}{\partial g} \cdot \frac{\partial \sigma(ax_i + b)}{\partial (ax_i + b)} \cdot x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \frac{\partial}{\partial (\textcolor{blue}{ax}_i + \textcolor{blue}{b})} \frac{1}{1 + e^{-(\textcolor{blue}{ax}_i + \textcolor{blue}{b})}} \cdot x_i$$

# Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial a} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \frac{e^{-(\textcolor{blue}{ax_i}+\textcolor{blue}{b})}}{(1 + e^{-(\textcolor{blue}{ax_i}+\textcolor{blue}{b})})^2} \cdot x_i$$

# Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial a} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \frac{1}{1 + e^{-(\textcolor{blue}{ax_i} + b)}} \frac{e^{-(\textcolor{blue}{ax_i} + b)}}{1 + e^{-(\textcolor{blue}{ax_i} + b)}} \cdot x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the [chain rule](#) to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \frac{1}{1 + e^{-(\textcolor{blue}{ax}_i + b)}} \frac{(1 + e^{-(\textcolor{blue}{ax}_i + b)}) - 1}{1 + e^{-(\textcolor{blue}{ax}_i + b)}} \cdot x_i$$

# Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the [chain rule](#) to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \frac{1}{1 + e^{-(\textcolor{blue}{ax_i+b})}} \left(1 - \frac{1}{1 + e^{-(\textcolor{blue}{ax_i+b})}}\right) \cdot x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \sigma(ax_i + b)(1 - \sigma(ax_i + b)) \cdot x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial f}{\partial g} \cdot \sigma(\textcolor{red}{a}x_i + b)(1 - \sigma(\textcolor{red}{a}x_i + b)) \cdot x_i$$

# Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{\partial \ln(\sigma(ax_i + b))}{\partial \sigma(ax_i + b)} \cdot \sigma(ax_i + b)(1 - \sigma(ax_i + b)) \cdot x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{1}{\sigma(ax_i + b)} \cdot \sigma(\textcolor{red}{ax}_i + b)(1 - \sigma(\textcolor{red}{ax}_i + b)) \cdot x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the [chain rule](#) to each partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} f(g(h(\textcolor{red}{a}, b))) = \frac{1}{\sigma(\textcolor{red}{a}x_i + b)} \cdot \sigma(\textcolor{red}{a}x_i + b)(1 - \sigma(\textcolor{red}{a}x_i + b)) \cdot x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial a} \ln(\sigma(ax_i + b)) = (1 - \sigma(ax_i + b))x_i$$

## Logistic regression: Finding a solution

Since the loss is convex, the first-order conditions apply:

$$\nabla_{\Theta} \sum_{i=1}^n y_i \ln(\sigma(ax_i + b)) + (1 - y_i) \ln(1 - \sigma(ax_i + b)) = 0$$

where  $\Theta = \{a, b\}$ .

Consider the gradient of each term in the summation:

$$y_i \nabla_{\Theta} \underbrace{\ln(\sigma(ax_i + b))}_{f(g(h(\Theta)))} + (1 - y_i) \nabla_{\Theta} \ln(1 - \sigma(ax_i + b))$$

Apply the **chain rule** to each partial derivative:

$$\frac{\partial}{\partial a} \ln(\sigma(ax_i + b)) = (1 - \sigma(ax_i + b))x_i$$

And similarly for the **second term** and for all parameters.

## Logistic regression: Finding a solution

By looking at the partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} \ln(\sigma(\textcolor{red}{a}x_i + b)) = (1 - \sigma(\textcolor{red}{a}x_i + b))x_i$$

we see that the parameters enter the gradient in a **nonlinear** way.

## Logistic regression: Finding a solution

By looking at the partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} \ln(\sigma(\textcolor{red}{a}x_i + b)) = (1 - \sigma(\textcolor{red}{a}x_i + b))x_i$$

we see that the parameters enter the gradient in a **nonlinear** way.

Thus:

- $\nabla \ell_{\Theta} = 0$  is **not a linear system** to solve for the parameters.

# Logistic regression: Finding a solution

By looking at the partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} \ln(\sigma(\textcolor{red}{a}x_i + b)) = (1 - \sigma(\textcolor{red}{a}x_i + b))x_i$$

we see that the parameters enter the gradient in a **nonlinear** way.

Thus:

- $\nabla \ell_{\Theta} = 0$  is **not a linear system** to solve for the parameters.
- $\nabla \ell_{\Theta} = 0$  is a **transcendental equation**  $\Rightarrow$  no analytical solution.

# Logistic regression: Finding a solution

By looking at the partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} \ln(\sigma(ax_i + b)) = (1 - \sigma(ax_i + b))x_i$$

we see that the parameters enter the gradient in a **nonlinear** way.

Thus:

- $\nabla \ell_\Theta = 0$  is **not a linear system** to solve for the parameters.
- $\nabla \ell_\Theta = 0$  is a **transcendental equation**  $\Rightarrow$  no analytical solution.

model	loss	solution
linear regression		
linear regression + Tikhonov		
logistic regression		

# Logistic regression: Finding a solution

By looking at the partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} \ln(\sigma(ax_i + b)) = (1 - \sigma(ax_i + b))x_i$$

we see that the parameters enter the gradient in a **nonlinear** way.

Thus:

- $\nabla \ell_\Theta = 0$  is **not a linear system** to solve for the parameters.
- $\nabla \ell_\Theta = 0$  is a **transcendental equation**  $\Rightarrow$  no analytical solution.

model	loss	solution
linear regression	convex	
linear regression + Tikhonov	convex	
logistic regression	convex	

# Logistic regression: Finding a solution

By looking at the partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} \ln(\sigma(\textcolor{red}{a}x_i + b)) = (1 - \sigma(\textcolor{red}{a}x_i + b))x_i$$

we see that the parameters enter the gradient in a **nonlinear** way.

Thus:

- $\nabla \ell_{\Theta} = 0$  is **not a linear system** to solve for the parameters.
- $\nabla \ell_{\Theta} = 0$  is a **transcendental equation**  $\Rightarrow$  no analytical solution.

model	loss	solution
linear regression	convex	least squares
linear regression + Tikhonov	convex	
logistic regression	convex	

# Logistic regression: Finding a solution

By looking at the partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} \ln(\sigma(ax_i + b)) = (1 - \sigma(ax_i + b))x_i$$

we see that the parameters enter the gradient in a **nonlinear** way.

Thus:

- $\nabla \ell_\Theta = 0$  is **not a linear system** to solve for the parameters.
- $\nabla \ell_\Theta = 0$  is a **transcendental equation**  $\Rightarrow$  no analytical solution.

model	loss	solution
linear regression	convex	least squares
linear regression + Tikhonov	convex	least squares
logistic regression	convex	

# Logistic regression: Finding a solution

By looking at the partial derivative:

$$\frac{\partial}{\partial \textcolor{red}{a}} \ln(\sigma(\textcolor{red}{a}x_i + b)) = (1 - \sigma(\textcolor{red}{a}x_i + b))x_i$$

we see that the parameters enter the gradient in a **nonlinear** way.

Thus:

- $\nabla \ell_{\Theta} = 0$  is **not a linear system** to solve for the parameters.
- $\nabla \ell_{\Theta} = 0$  is a **transcendental equation**  $\Rightarrow$  no analytical solution.

model	loss	solution
linear regression	convex	least squares
linear regression + Tikhonov	convex	least squares
logistic regression	convex	<b>nonlinear optimization</b>


## Gradient descent: Intuition

Gradient descent is a **first-order** iterative minimization algorithm.

# Gradient descent: Intuition

Gradient descent is a **first-order** iterative minimization algorithm.


Example of a loss function  $\ell_{\Theta} : \mathbb{R}^2 \rightarrow \mathbb{R}$ :



# Gradient descent: Intuition

Gradient descent is a **first-order** iterative minimization algorithm.

Example of a loss function  $\ell_{\Theta} : \mathbb{R}^2 \rightarrow \mathbb{R}$ :




**Overall idea:** Move where the function decreases the most.

- ① Start from some point  $\Theta^{(0)} \in \mathbb{R}^2$ .

# Gradient descent: Intuition

Gradient descent is a **first-order** iterative minimization algorithm.

Example of a loss function  $\ell_{\Theta} : \mathbb{R}^2 \rightarrow \mathbb{R}$ :



**Overall idea:** Move where the function decreases the most.


- ① Start from some point  $\Theta^{(0)} \in \mathbb{R}^2$ .
- ② Iteratively compute:

$$\Theta^{(t+1)} = \Theta^{(t)} - \alpha \nabla \ell_{\Theta^{(t)}}$$

# Gradient descent: Intuition

Gradient descent is a **first-order** iterative minimization algorithm.

Example of a loss function  $\ell_{\Theta} : \mathbb{R}^2 \rightarrow \mathbb{R}$ :



**Overall idea:** Move where the function decreases the most.

- ① Start from some point  $\Theta^{(0)} \in \mathbb{R}^2$ .
- ② Iteratively compute:

$$\Theta^{(t+1)} = \Theta^{(t)} - \alpha \nabla \ell_{\Theta^{(t)}}$$


- ③ Stop when a minimum is reached.

# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$



# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$





# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$





# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$





# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$





# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$





# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$





# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$






# Gradient descent

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$



# Gradient descent: High dimensions

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$




All we say is also valid in  $\gg 2$  dimensions.

# Gradient descent: Orthogonality

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$


The gradient is **orthogonal** to level curves / level surfaces.



# Gradient descent: Orthogonality

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$


The gradient is **orthogonal** to level curves / level surfaces.



# Gradient descent: Orthogonality

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$


The gradient is **orthogonal** to level curves / level surfaces.



# Gradient descent: Orthogonality

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$


The gradient is **orthogonal** to level curves / level surfaces.



# Gradient descent: Orthogonality

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

The gradient is **orthogonal** to level curves / level surfaces.




The directional derivative is **zero** along isocurves.

# Gradient descent: Orthogonality

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

The gradient is **orthogonal** to level curves / level surfaces.



The directional derivative is **zero** along isocurves.

## Gradient descent: Differentiability

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

Gradient descent requires  $f$  to be **differentiable** at all points.

## Gradient descent: Differentiability

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

Gradient descent requires  $f$  to be **differentiable** at all points.

Recall:

$f$  has partial (or even directional) derivatives  $\not\Rightarrow f$  is differentiable

## Gradient descent: Differentiability

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

Gradient descent requires  $f$  to be **differentiable** at all points.

Recall:

$f$  has partial (or even directional) derivatives  $\not\Rightarrow f$  is differentiable


$f$  has **continuous gradient**  $\Rightarrow f$  is differentiable

# Gradient descent: Differentiability

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

Gradient descent requires  $f$  to be **differentiable** at all points.

**Example in  $\mathbb{R}^2$ :**  $f(x, y) = \begin{cases} 0 & \text{at } (0, 0) \\ \frac{x^2 y}{x^2 + y^2} & \text{elsewhere} \end{cases}$




# Gradient descent: Differentiability

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

Gradient descent requires  $f$  to be **differentiable** at all points.

**Example in  $\mathbb{R}^2$ :**  $f(x, y) = \begin{cases} 0 & \text{at } (0, 0) \\ \frac{x^2 y}{x^2 + y^2} & \text{elsewhere} \end{cases}$

$$\frac{\partial}{\partial y} f(x, 0) = 1 \text{ for } x \neq 0$$



# Gradient descent: Differentiability


$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

Gradient descent requires  $f$  to be **differentiable** at all points.

**Example in  $\mathbb{R}^2$ :**  $f(x, y) = \begin{cases} 0 & \text{at } (0, 0) \\ \frac{x^2 y}{x^2 + y^2} & \text{elsewhere} \end{cases}$

$$\frac{\partial}{\partial y} f(x, 0) = 1 \text{ for } x \neq 0$$

$$\frac{\partial}{\partial y} f(0, y) = 0 \text{ for } y \neq 0$$



# Gradient descent: Differentiability

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$


Gradient descent requires  $f$  to be **differentiable** at all points.

**Example in  $\mathbb{R}^2$ :**  $f(x, y) = \begin{cases} 0 & \text{at } (0, 0) \\ \frac{x^2 y}{x^2 + y^2} & \text{elsewhere} \end{cases}$

$$\frac{\partial}{\partial y} f(x, 0) = 1 \text{ for } x \neq 0$$

$$\frac{\partial}{\partial y} f(0, y) = 0 \text{ for } y \neq 0$$

$\Rightarrow \frac{\partial}{\partial y} f(x, y)$  discontinuous at  $(0, 0)$



# Gradient descent: Differentiability

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

Gradient descent requires  $f$  to be **differentiable** at all points.


**Example in  $\mathbb{R}^2$ :**  $f(x, y) = \begin{cases} 0 & \text{at } (0, 0) \\ \frac{x^2 y}{x^2 + y^2} & \text{elsewhere} \end{cases}$

$$\frac{\partial}{\partial y} f(x, 0) = 1 \text{ for } x \neq 0$$

$$\frac{\partial}{\partial y} f(0, y) = 0 \text{ for } y \neq 0$$

$\Rightarrow \frac{\partial}{\partial y} f(x, y)$  discontinuous at  $(0, 0)$

the partial derivatives of  $f$  are **defined everywhere**, but are **discontinuous** at the origin  
 $\Rightarrow f$  is **not differentiable**



## Gradient descent: Stationary points

A **stationary point** is such that:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})^0$$

Gradient descent “gets stuck” at stationary points.

# Gradient descent: Stationary points


A **stationary point** is such that:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})^0$$

Gradient descent “gets stuck” at stationary points.

However:

- Stationary point  $\not\Rightarrow$  local minimum



# Gradient descent: Stationary points


A **stationary point** is such that:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})^0$$

Gradient descent “gets stuck” at stationary points.

However:

- Stationary point  $\not\Rightarrow$  local minimum  $\not\Rightarrow$  global minimum.



# Gradient descent: Stationary points


A **stationary point** is such that:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})^0$$

Gradient descent “gets stuck” at stationary points.

However:

- Stationary point  $\not\Rightarrow$  local minimum  $\not\Rightarrow$  global minimum.
- Which stationary point depends on the **initialization**.



## Gradient descent: Learning rate

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

The parameter  $\alpha > 0$  is also called learning rate in ML.

## Gradient descent: Learning rate

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

The parameter  $\alpha > 0$  is also called learning rate in ML.

**Remark:** The length of a step is not simply  $\alpha$ , but  $\alpha \|\nabla f\|$ .


## Gradient descent: Learning rate

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

The parameter  $\alpha > 0$  is also called learning rate in ML.

**Remark:** The length of a step is not simply  $\alpha$ , but  $\alpha \|\nabla f\|$ .

- Too small: slow convergence speed




# Gradient descent: Learning rate

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

The parameter  $\alpha > 0$  is also called learning rate in ML.

**Remark:** The length of a step is not simply  $\alpha$ , but  $\alpha \|\nabla f\|$ .

- Too small: slow convergence speed
- Too big: risk of **overshooting**




# Gradient descent: Learning rate

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

The parameter  $\alpha > 0$  is also called learning rate in ML.

**Remark:** The length of a step is not simply  $\alpha$ , but  $\alpha \|\nabla f\|$ .

- Too small: slow convergence speed
- Too big: risk of **overshooting**
- Optimal values can be found via **line search** algorithms



$$\arg \min_{\alpha} f(\mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)}))$$

## Decay and momentum

The learning rate can be **adaptive** or follow a **schedule**.

# Decay and momentum

The learning rate can be **adaptive** or follow a **schedule**.

- Decrease  $\alpha$  according to a **decay** parameter  $\rho$ :

Examples:

$$\alpha^{(t+1)} = \left(1 - \frac{t}{\rho}\right)\alpha^{(0)} + \frac{t}{\rho}\alpha^{(\rho)}, \quad \alpha^{(t+1)} = \frac{\alpha^{(t)}}{1 + \rho t}, \quad \alpha^{(t+1)} = \alpha^{(0)}e^{-\rho t}$$

# Decay and momentum

The learning rate can be **adaptive** or follow a **schedule**.

- Decrease  $\alpha$  according to a **decay** parameter  $\rho$ :

Examples:

$$\alpha^{(t+1)} = \left(1 - \frac{t}{\rho}\right)\alpha^{(0)} + \frac{t}{\rho}\alpha^{(\rho)}, \quad \alpha^{(t+1)} = \frac{\alpha^{(t)}}{1 + \rho t}, \quad \alpha^{(t+1)} = \alpha^{(0)}e^{-\rho t}$$

- Accumulate past gradients and keep moving in their direction:

$$\mathbf{v}^{(t+1)} = \lambda \mathbf{v}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)}) \quad \text{momentum}$$

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} + \mathbf{v}^{(t+1)}$$

# Decay and momentum

The learning rate can be **adaptive** or follow a **schedule**.

- Decrease  $\alpha$  according to a **decay** parameter  $\rho$ :

Examples:

$$\alpha^{(t+1)} = \left(1 - \frac{t}{\rho}\right)\alpha^{(0)} + \frac{t}{\rho}\alpha^{(\rho)}, \quad \alpha^{(t+1)} = \frac{\alpha^{(t)}}{1 + \rho t}, \quad \alpha^{(t+1)} = \alpha^{(0)}e^{-\rho t}$$

- Accumulate past gradients and keep moving in their direction:

$$\mathbf{v}^{(t+1)} = \lambda \mathbf{v}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)}) \quad \text{momentum}$$

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} + \mathbf{v}^{(t+1)}$$

Step length  $\propto$  how **aligned** is the sequence of gradients.

$$\frac{1}{1 - \lambda} \alpha \|\nabla f\|$$

# Decay and momentum

The learning rate can be **adaptive** or follow a **schedule**.

- Decrease  $\alpha$  according to a **decay** parameter  $\rho$ :

Examples:

$$\alpha^{(t+1)} = \left(1 - \frac{t}{\rho}\right)\alpha^{(0)} + \frac{t}{\rho}\alpha^{(\rho)}, \quad \alpha^{(t+1)} = \frac{\alpha^{(t)}}{1 + \rho t}, \quad \alpha^{(t+1)} = \alpha^{(0)}e^{-\rho t}$$

- Accumulate past gradients and keep moving in their direction:

$$\mathbf{v}^{(t+1)} = \lambda \mathbf{v}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)}) \quad \text{momentum}$$


$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} + \mathbf{v}^{(t+1)}$$

Step length  $\propto$  how **aligned** is the sequence of gradients.

$$\frac{1}{1 - \lambda} \alpha \|\nabla f\|$$



**Acceleration** effect for big  $\lambda$  + escape from local minima.

# Momentum



Goh, "Why momentum really works", Distill 2017

# Momentum



Goh, "Why momentum really works", Distill 2017



# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(t)} - \alpha \nabla f(\mathbf{x}^{(t)})$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(1)} = \mathbf{x}^{(0)} - \alpha \nabla f(\mathbf{x}^{(0)})$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(1)} = \mathbf{x}^{(0)} - \alpha \nabla f(\mathbf{x}^{(0)})$$

$$\mathbf{x}^{(2)} = \mathbf{x}^{(1)} - \alpha \nabla f(\mathbf{x}^{(1)})$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\begin{aligned}\mathbf{x}^{(1)} &= \mathbf{x}^{(0)} - \alpha \nabla f(\mathbf{x}^{(0)}) \\ \mathbf{x}^{(2)} &= \mathbf{x}^{(1)} - \alpha \nabla f(\mathbf{x}^{(1)}) \\ &= \mathbf{x}^{(0)} - \alpha \nabla f(\mathbf{x}^{(0)}) - \alpha \nabla f(\mathbf{x}^{(1)})\end{aligned}$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(1)} = \mathbf{x}^{(0)} - \alpha \nabla f(\mathbf{x}^{(0)})$$

$$\mathbf{x}^{(2)} = \mathbf{x}^{(1)} - \alpha \nabla f(\mathbf{x}^{(1)})$$

$$= \mathbf{x}^{(0)} - \alpha \nabla f(\mathbf{x}^{(0)}) - \alpha \nabla f(\mathbf{x}^{(1)})$$

⋮

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} - \alpha \sum_{i=1}^t \nabla f(\mathbf{x}^{(i)})$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} - \alpha \sum_{i=1}^t \nabla f(\mathbf{x}^{(i)})$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} - \alpha \sum_{i=1}^t \nabla f(\mathbf{x}^{(i)})$$

With momentum:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} + \alpha \sum_{i=1}^t \frac{1 - \lambda^{t+1-i}}{1 - \lambda} \nabla f(\mathbf{x}^{(i)})$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} - \alpha \sum_{i=1}^t \nabla f(\mathbf{x}^{(i)})$$

With momentum:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} + \alpha \sum_{i=1}^t \frac{1 - \lambda^{t+1-i}}{1 - \lambda} \nabla f(\mathbf{x}^{(i)})$$

The more general form:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} + \alpha \sum_{i=1}^t \gamma_i^t \nabla f(\mathbf{x}^{(i)}) \quad \text{for some } \gamma_i$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} - \alpha \sum_{i=1}^t \nabla f(\mathbf{x}^{(i)})$$

With momentum:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} + \alpha \sum_{i=1}^t \frac{1 - \lambda^{t+1-i}}{1 - \lambda} \nabla f(\mathbf{x}^{(i)})$$

The more general form:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} + \alpha \sum_{i=1}^t \Gamma_i^t \nabla f(\mathbf{x}^{(i)}) \quad \text{for some diag. matrix } \Gamma_i$$

# First-order acceleration methods

Let us try to unroll gradient descent:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} - \alpha \sum_{i=1}^t \nabla f(\mathbf{x}^{(i)})$$

With momentum:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} + \alpha \sum_{i=1}^t \frac{1 - \lambda^{t+1-i}}{1 - \lambda} \nabla f(\mathbf{x}^{(i)})$$

The more general form:

$$\mathbf{x}^{(t+1)} = \mathbf{x}^{(0)} + \alpha \sum_{i=1}^t \Gamma_i^t \nabla f(\mathbf{x}^{(i)}) \quad \text{for some diag. matrix } \Gamma_i$$

generalizes optimization algorithms like ADAM, AdaGrad, etc.

# Gradient descent for deep learning

Gradient descent can be applied to **nonconvex** problems, without optimality guarantees.

## Gradient descent for deep learning

Gradient descent can be applied to **nonconvex** problems, without optimality guarantees.

In order to gain **generalization**, the following consideration is crucial:

We are rarely interested in the **global** optimum.

# Gradient descent for deep learning

Gradient descent can be applied to **nonconvex** problems, without optimality guarantees.

In order to gain **generalization**, the following consideration is crucial:

We are rarely interested in the **global** optimum.

Even for **convex** problems like:

- Linear regression
- Logistic regression

We get more **efficient** and **numerically stable** solutions.

# Gradient descent for deep learning

Gradient descent can be applied to **nonconvex** problems, without optimality guarantees.

In order to gain **generalization**, the following consideration is crucial:

We are rarely interested in the **global** optimum.

Even for **convex** problems like:

- Linear regression ( $\mathbf{X}$  can be huge and must be inverted/factorized)
- Logistic regression

We get more **efficient** and **numerically stable** solutions.

# Gradient descent for deep learning

Gradient descent can be applied to **nonconvex** problems, without optimality guarantees.

In order to gain **generalization**, the following consideration is crucial:

We are rarely interested in the **global** optimum.

Even for **convex** problems like:

- Linear regression ( $\mathbf{X}$  can be huge and must be inverted/factorized)
- Logistic regression (no closed form solution)

We get more **efficient** and **numerically stable** solutions.

# Gradient descent for deep learning

In the general DL setting:

Each parameter gets updated so as to **decrease the loss**:

$$\theta_i \leftarrow \theta_i - \alpha \frac{\partial \ell}{\partial \theta_i}$$

The gradient tells us how to modify the parameters.

# Gradient descent for deep learning

In the general DL setting:

Each parameter gets updated so as to **decrease the loss**:

$$\theta_i \leftarrow \theta_i - \alpha \frac{\partial \ell}{\partial \theta_i}$$

The gradient tells us how to modify the parameters.

- $\theta$  stores the neural network parameters, possibly **millions**

# Gradient descent for deep learning

In the general DL setting:

Each parameter gets updated so as to **decrease the loss**:

$$\theta_i \leftarrow \theta_i - \alpha \frac{\partial \ell}{\partial \theta_i}$$

The gradient tells us how to modify the parameters.

- $\theta$  stores the neural network parameters, possibly **millions**
- The loss can be **non-convex** and **non-differentiable**  
Cannot even apply gradient descent!

# Gradient descent for deep learning

In the general DL setting:

Each parameter gets updated so as to **decrease the loss**:

$$\theta_i \leftarrow \theta_i - \alpha \frac{\partial \ell}{\partial \theta_i}$$

The gradient tells us how to modify the parameters.

- $\theta$  stores the neural network parameters, possibly **millions**
- The loss can be **non-convex** and **non-differentiable**  
Cannot even apply gradient descent!
- Must address **computational complexity** and **numerical stability**

# Gradient descent for deep learning

In the general DL setting:

Each parameter gets updated so as to **decrease the loss**:

$$\theta_i \leftarrow \theta_i - \alpha \frac{\partial \ell}{\partial \theta_i}$$

The gradient tells us how to modify the parameters.

- $\theta$  stores the neural network parameters, possibly **millions**
- The loss can be **non-convex** and **non-differentiable**  
Cannot even apply gradient descent!
- Must address **computational complexity** and **numerical stability**

Very often in DL we confront problems that have well defined solutions in mathematical terms, but require extra care and tweaking in practice.

## Stochastic gradient descent

Recall that the loss is usually defined over  $n$  training examples:

$$\ell_{\Theta}(\{x_i, y_i\}) = \frac{1}{n} \sum_{i=1}^n (y_i - f_{\Theta}(x_i))^2$$

## Stochastic gradient descent

Recall that the loss is usually defined over  $n$  training examples:

$$\ell_{\Theta}(\{x_i, y_i\}) = \frac{1}{n} \sum_{i=1}^n \hat{\ell}_{\Theta}(\{x_i, y_i\})$$

## Stochastic gradient descent

Recall that the loss is usually defined over  $n$  training examples:

$$\ell_{\Theta}(\{x_i, y_i\}) = \frac{1}{n} \sum_{i=1}^n \hat{\ell}_{\Theta}(\{x_i, y_i\})$$

which requires computing the gradient for each term in the summation:

$$\nabla \ell_{\Theta}(\{x_i, y_i\}) = \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\{x_i, y_i\})$$

# Stochastic gradient descent

Recall that the loss is usually defined over  $n$  training examples:

$$\ell_{\Theta}(\{x_i, y_i\}) = \frac{1}{n} \sum_{i=1}^n \hat{\ell}_{\Theta}(\{x_i, y_i\})$$

which requires computing the gradient for each term in the summation:

$$\nabla \ell_{\Theta}(\{x_i, y_i\}) = \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\{x_i, y_i\})$$

Two **bottlenecks** make gradient descent impractical:

- Number of examples
- Number of parameters

Wilson and Martinez, "The general inefficiency of batch training for gradient descent learning", Neural Networks 2003

## Stochastic gradient descent

$$\nabla \ell_{\Theta}(\{x_i, y_i\}) = \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\{x_i, y_i\})$$

## Stochastic gradient descent

$$\nabla \ell_{\Theta}(\mathcal{T}) = \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\mathcal{T})$$

## Stochastic gradient descent

$$\nabla \ell_{\Theta}(\mathcal{T}) = \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\mathcal{T})$$

Compute  $\nabla \ell_{\Theta}$  for a **small** representative subset of  $m \ll n$  examples:

$$\frac{1}{m} \sum_{i=1}^m \nabla \hat{\ell}_{\Theta}(\mathcal{B}) \approx \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\mathcal{T})$$

The **mini-batch**  $\mathcal{B} \subset \mathcal{T}$  is drawn uniformly.

## Stochastic gradient descent

$$\nabla \ell_{\Theta}(\mathcal{T}) = \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\mathcal{T})$$

Compute  $\nabla \ell_{\Theta}$  for a **small** representative subset of  $m \ll n$  examples:

$$\frac{1}{m} \sum_{i=1}^m \nabla \hat{\ell}_{\Theta}(\mathcal{B}) \approx \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\mathcal{T})$$

The **mini-batch**  $\mathcal{B} \subset \mathcal{T}$  is drawn uniformly.

The true gradient  $\nabla \ell_{\Theta}$  is approximated, but with a significant **speed-up**.

**Example:** MNIST dataset

$$n = 60,000, \ m = 10 \quad \Rightarrow \quad 6,000 \times \text{speedup}$$

# Stochastic gradient descent

The algorithm is as follows:

- ➊ Initialize  $\theta$ .

# Stochastic gradient descent

The algorithm is as follows:

- ➊ Initialize  $\theta$ .
- ➋ Pick a mini-batch  $\mathcal{B}$ .

# Stochastic gradient descent

The algorithm is as follows:

- ➊ Initialize  $\theta$ .
- ➋ Pick a mini-batch  $\mathcal{B}$ .
- ➌ Update with the downhill step (use momentum if desired):

$$\theta \leftarrow \theta - \alpha \nabla \ell_{\theta}(\mathcal{B})$$

# Stochastic gradient descent

The algorithm is as follows:

- ➊ Initialize  $\theta$ .
- ➋ Pick a mini-batch  $\mathcal{B}$ .
- ➌ Update with the downhill step (use momentum if desired):

$$\theta \leftarrow \theta - \alpha \nabla \ell_{\theta}(\mathcal{B})$$

- ➍ Go back to step (2).

# Stochastic gradient descent

The algorithm is as follows:

- ➊ Initialize  $\theta$ .
- ➋ Pick a mini-batch  $\mathcal{B}$ .
- ➌ Update with the downhill step (use momentum if desired):

$$\theta \leftarrow \theta - \alpha \nabla \ell_{\theta}(\mathcal{B})$$

- ➍ Go back to step (2).

When steps (2)-(4) cover the entire training set  $\mathcal{T}$  we have an [epoch](#).

Like gradient descent, the algorithm proceeds for many epochs.

# Stochastic gradient descent

The algorithm is as follows:

- ➊ Initialize  $\theta$ .
- ➋ Pick a mini-batch  $\mathcal{B}$ .
- ➌ Update with the downhill step (use momentum if desired):

$$\theta \leftarrow \theta - \alpha \nabla \ell_{\theta}(\mathcal{B})$$


- ➍ Go back to step (2).

When steps (2)-(4) cover the entire training set  $\mathcal{T}$  we have an [epoch](#).


Like gradient descent, the algorithm proceeds for many epochs.

**Remark:** The update cost is [constant](#) regardless of the size of  $\mathcal{T}$ .

# Stochastic gradient descent





# Stochastic gradient descent



SGD does not stop at the minimum.

Oscillations are due to the noise induced by the random sampling.

# Stochastic gradient descent



SGD does not stop at the minimum.

Oscillations are due to the noise induced by the random sampling.

## Asymptotic upper bounds

$$\ell_{\Theta}(\{x_i, y_i\}) = \frac{1}{n} \sum_{i=1}^n (y_i - f_{\Theta}(x_i))^2$$

## Asymptotic upper bounds

$$\ell(\{f_{\Theta}(x_i), y_i\}) = \frac{1}{n} \sum_{i=1}^n (y_i - f_{\Theta}(x_i))^2$$

## Asymptotic upper bounds

$$\ell(\{f_{\Theta}(x_i), y_i\}) = \frac{1}{n} \sum_{i=1}^n \hat{\ell}(\{f_{\Theta}(x_i), y_i\})$$

## Asymptotic upper bounds

$$\ell(f_\Theta) = \frac{1}{n} \sum_{i=1}^n \hat{\ell}(f_\Theta)$$

## Asymptotic upper bounds

For a **convex** problem, there is a true minimizer:

$$f^* = \arg \min_f \ell(f)$$

## Asymptotic upper bounds

For a **convex** problem, consider the inequality:

$$|\ell(f_\Theta) - \ell(f^*)| < \rho$$

# Asymptotic upper bounds

For a **convex** problem, consider the inequality:

$$\left| \underbrace{\ell(f_\Theta)}_{\text{GD/SGD}} - \underbrace{\ell(f^*)}_{\text{true}} \right| < \underbrace{\rho}_{\text{accuracy}}$$

# Asymptotic upper bounds

For a **convex** problem, consider the inequality:

$$\left| \underbrace{\ell(f_\Theta)}_{\text{GD/SGD}} - \underbrace{\ell(f^*)}_{\text{true}} \right| < \underbrace{\rho}_{\text{accuracy}}$$

$n$  training examples

$d$  parameters

$\kappa, \nu$  are constants related to the conditioning of the problem

	<b>cost per iteration</b>	<b>iterations to reach <math>\rho</math></b>
GD	$O(nd)$	$O(\kappa \log \frac{1}{\rho})$
SGD	$O(d)$	$\frac{\nu \kappa^2}{\rho} + o(\frac{1}{\rho})$

# Asymptotic upper bounds

For a **convex** problem, consider the inequality:

$$\left| \underbrace{\ell(f_\Theta)}_{\text{GD/SGD}} - \underbrace{\ell(f^*)}_{\text{true}} \right| < \underbrace{\rho}_{\text{accuracy}}$$

$n$  training examples

$d$  parameters

$\kappa, \nu$  are constants related to the conditioning of the problem

	cost per iteration	iterations to reach $\rho$
GD	$O(nd)$	$O(\kappa \log \frac{1}{\rho})$
SGD	$O(d)$	$\frac{\nu \kappa^2}{\rho} + o(\frac{1}{\rho})$

SGD does not depend on the number of examples,  
implying better generalization

# Stochastic gradient descent

Some practical considerations:

- Needs the training data to be **shuffled** to avoid data bias.

# Stochastic gradient descent

Some practical considerations:

- Needs the training data to be **shuffled** to avoid data bias.

$$\frac{1}{m} \sum_{i=1}^m \nabla \hat{\ell}_{\Theta}(\mathcal{B}) \approx \frac{1}{n} \sum_{i=1}^n \nabla \hat{\ell}_{\Theta}(\mathcal{T})$$

# Stochastic gradient descent

Some practical considerations:

- Needs the training data to be **shuffled** to avoid data bias.
- Each mini-batch can be processed in **parallel**.  
Batch size is limited by hardware.

# Stochastic gradient descent

Some practical considerations:

- Needs the training data to be **shuffled** to avoid data bias.
- Each mini-batch can be processed in **parallel**.  
Batch size is limited by hardware.
- Large datasets: more steps to reach convergence.  
Remarkably rapid **initial progress** and slow asymptotic convergence.

# Stochastic gradient descent

Some practical considerations:

- Needs the training data to be **shuffled** to avoid data bias.
- Each mini-batch can be processed in **parallel**.  
Batch size is limited by hardware.
- Large datasets: more steps to reach convergence.  
Remarkably rapid **initial progress** and slow asymptotic convergence.
- Small mini-batches can offer a **regularizing** effect.  
Very small batches → high variance in the estimation of the gradient  
→ use a small learning rate to maintain stability.

# Stochastic gradient descent

Some practical considerations:

- Needs the training data to be **shuffled** to avoid data bias.
- Each mini-batch can be processed in **parallel**.  
Batch size is limited by hardware.
- Large datasets: more steps to reach convergence.  
Remarkably rapid **initial progress** and slow asymptotic convergence.
- Small mini-batches can offer a **regularizing** effect.  
Very small batches → high variance in the estimation of the gradient  
→ use a small learning rate to maintain stability.

SGD can find a **low value** of the loss quickly enough to be useful, even if it's not a minimum.

## Suggested reading

Approachable explanation of differentiability in higher dimensions:

[https://mathinsight.org/differentiability\\_multivariable\\_subtleties](https://mathinsight.org/differentiability_multivariable_subtleties)

Distill article on why momentum really works:

<https://distill.pub/2017/momentum/>

Seminal paper on using mini-batches for training:

<http://axon.cs.byu.edu/papers/Wilson.nn03.batch.pdf>

Seminal paper on GD vs. SGD performance:

<https://papers.nips.cc/paper/3323-the-tradeoffs-of-large-scale-learning.pdf>