

Industrial strength Java/JEE Career Companion to open more doors

search here ...

Go

Home

Java FAQs

600+ Java Q&As

Career

Tutorials

Member

Why?

Can u Debug?

Java 8 ready?

Top X

Productivity Tools

Judging Experience?

[Home](#) › [member-paid](#) › 08: Web.xml interview questions and answers

08: Web.xml interview questions and answers

Posted on May 14, 2015 by [Arulkumaran Kumaraswamipillai](#)

Since **Servlet 3.0 specification**, the web.xml file in a web application is **optional**. The Servlet 3.0 API introduced annotations to register servlets. Learn more at [Servlet Interview Questions and Answers](#).

Q1. What is a web.xml file?

A1. The **\$ROOT/WEB-INF/web.xml** file is the **Web Application Deployment Descriptor** of your application. This file is an XML document that defines everything about your application that a **web container** in the application server needs to know except the context path, which is configured via container specific deployment descriptor file. For example the “context path” for jboss web container is define as shown below in **jboss-web.xml** file

```
1 <!DOCTYPE jboss-web PUBLIC "-//JBoss//DTD Web Ap
2 <jboss-web>
```

600+ Full Stack Java/JEE Interview Q&As ♥Free ♦FAQs

open all | close all

+ Ice Breaker Interview

+ Core Java Interview C

+ JEE Interview Q&A (3

+ JEE Overview (2)

+ Web basics (8)

+ 01: ♦ 12 Web ba

+ 02: HTTP basics

+ 03: Servlet inter

+ 04: JSP overview

+ 05: Web patterns

+ 06: ♦ MVC0, MV

+ 07: When to use

+ 08: Web.xml inte

+ WebService (11)

+ JPA (2)

+ JTA (1)

+ JDBC (4)

+ JMS (5)

+ JMX (3)

+ JNDI and LDAP (1)

+ Pressed for time? Jav

```

3      <class-loading java2ClassLoadingCompliance="
4          <loader-repository>
5              org:archive=ecm-enabler-endpoint.war
6          <loader-repository-config>java2Paren
7          </loader-repository>
8      </class-loading>
9      <context-root>/my-enterprise-ws</context-roo
10 </jboss-web>

```

“/my-enterprise-ws” is the context root. So, you will access your application something like

```
1 http://localhost:8180/my-enterprise-ws/blah
```

Q2. Can you list some of the entries a typical web.xml file will have?

Q2.

1) Servlets: For a Java servlet to be accessible from a browser, you must tell the servlet container what servlets to deploy, and what URL's to map the servlets to. This is done in the web.xml file of your Java web application.

```

1 <servlet>
2     <servlet-name>logback-status</servlet-name>
3     <servlet-class>ch.qos.logback.classic.ViewStat
4 </servlet>
5
6 <servlet-mapping>
7     <servlet-name>logback-status</servlet-name>
8     <url-pattern>/logback-status</url-pattern>
9 </servlet-mapping>

```

and then in a browser you can access the servlet as









```
1 http://localhost:8180/my-enterprise-ws/logback-st
```

2. Context parameters: You can also set some context parameters which can be read from all servlets in your application.

```

















1 <context-param>
2     <param-name>logbackConfigLocation</param-nam
3     <param-value>classpath:caps-enterprise-servi
4 </context-param>

```

-  [SQL, XML, UML, JSC](#)
-  [Hadoop & BigData Int](#)
-  [Java Architecture Inte](#)
-  [Scala Interview Q&As](#)
-  [Spring, Hibernate, & I](#)
-  [Testing & Profiling/Sa](#)
-  [Other Interview Q&A 1](#)
-  [Free Java Interview](#)





16 Technical Key Areas

[open all](#) | [close all](#)

-  [Best Practice \(6\)](#)
-  [Coding \(26\)](#)
-  [Concurrency \(6\)](#)
-  [Design Concepts \(7\)](#)
-  [Design Patterns \(11\)](#)
-  [Exception Handling \(3\)](#)
-  [Java Debugging \(21\)](#)
-  [Judging Experience I](#)
-  [Low Latency \(7\)](#)
-  [Memory Managemen](#)
-  [Performance \(13\)](#)
-  [QoS \(8\)](#)
-  [Scalability \(4\)](#)
-  [SDLC \(6\)](#)
-  [Security \(13\)](#)
-  [Transaction Managen](#)

80+ step by step Java Tutorials

[open all](#) | [close all](#)

-  [Setting up Tutorial \(6\)](#)
-  [Tutorial - Diagnosis \(2](#)
-  [Akka Tutorial \(9\)](#)
-  [Core Java Tutorials \(2](#)

and it will be referred in the logback framework/library as

```
1 String myContextParam =
2     request.getSession()
3         .getServletContext()
4         .getInitParameter("logbackConfigLo
```

3) Servlet filters: A Servlet filter is an object that can intercept HTTP requests targeted at your web application. Servlet Filter is used for monitoring request and response from client to the servlet, or to modify the request and response, or to audit and log.

```
1 <filter>
2     <filter-name>UrlRewriteFilter</filter-name>
3     <filter-class>org.tuckey.web.filters.urlrewr
4 </filter>
5 <filter>
6     <filter-name>Seam Filter</filter-name>
7     <filter-class>org.jboss.seam.servlet.SeamFil
8 </filter>
9 <filter>
10    <filter-name>Request Logging Filter</filter-
11    <filter-class>com.myapp.filter.RequestLoggin
12    <init-param>
13        <param-name>excluded</param-name>
14        <param-value>.js,css,javax.faces.resourc
15    </init-param>
16 </filter>
```

4) Servlet listeners: Servlet Listener is used for listening to events in a web containers, such as when you create a session, or place an attribute in an session or if you passivate and activate in another container, to subscribe to these events you can configure listener in web.xml. With listeners you can track application-level, session-level, life-cycle changes, attribute changes etc.

```
1 <!-- Spring logback configuration listener -->
2 <listener>
3     <listener-class> com.myapp.logging.LogbackC
4 </listener>
```

```
1 package com.myapp.logging;
2
3 public class LogbackConfigListener implements Se
4
5     @Override
```

- [Hadoop & Spark Tuto](#)
- [JEE Tutorials \(19\)](#)
- [Scala Tutorials \(1\)](#)
- [Spring & Hibernate Ti](#)
- [Tools Tutorials \(19\)](#)
- [Other Tutorials \(45\)](#)

100+ Java pre-interview coding tests

[open all](#) | [close all](#)

- [Can you write code? \(](#)
- [♦ Complete the given](#)
- [Converting from A to I](#)
- [Designing your classe](#)
- [Java Data Structures](#)
- [Passing the unit tests](#)
- [What is wrong with th](#)
- [Writing Code Home A](#)
- [Written Test Core Jav](#)
- [Written Test JEE \(1\)](#)

How good are your?

[open all](#) | [close all](#)

- [Career Making Know-](#)
- [Job Hunting & Resur](#)

```
6     public void contextDestroyed(final ServletCo
7         //some logic
8     }
9
10    @Override
11    public void contextInitialized(final Servlet
12        //some logic
13    }
14 }
```

5) Resource mappings: The idea is that specifying resources in the web.xml has the advantage of separating the developer role from the deployer role. Let's say you want to lookup java:comp/env/jdbc/dataSource/mydb, the container finds that web.xml has a <resource-ref> element for jdbc/dataSource/mydb and it returns the object registered under the name of jdbc/dataSource/maindb.

```
1 <resource-ref>
2     <description>MyApp Data Source</description>
3     <res-ref-name>jdbc/dataSource/mydb</res-ref-na
4     <res-type>javax.sql.DataSource</res-type>
5     <jndi-name>jdbc/dataSource/maindb</jndi-name>
6     <res-auth>Container</res-auth>
7 </resource-ref>
```

6) Security: The web.xml is the most important Java EE configuration piece allowing configuration of web container security.

BASIC authentication

```
1 <login-config>
2     <auth-method>BASIC</auth-method>
3     <realm-name>default</realm-name>
4 </login-config>
```

FORM based authentication

```
1 <login-config>
2     <auth-method>FORM</auth-method>
3     <form-login-config>
4         <form-login-page>/login.html</form-login-page>
5         <form-error-page>/error.html</form-error-page>
6     </form-login-config>
7 </login-config>
```

Access control and constraints

```

1  <security-constraint>
2    <display-name>excluded</display-name>
3    <web-resource-collection>
4      <web-resource-name>No Access</web-resource
5      <url-pattern>/excluded/*</url-pattern>
6      <url-pattern>/restricted/customer/excluded
7      <url-pattern>/restricted/owner/excluded/*<
8    </web-resource-collection>
9    <web-resource-collection>
10     <web-resource-name>No Access</web-resource
11     <url-pattern>/restricted/*</url-pattern>
12     <http-method>DELETE</http-method>
13     <http-method>PUT</http-method>
14     <http-method>HEAD</http-method>
15     <http-method>OPTIONS</http-method>
16     <http-method>TRACE</http-method>
17     <http-method>GET</http-method>
18     <http-method>POST</http-method>
19   </web-resource-collection>
20   <auth-constraint />
21   <user-data-constraint>
22     <transport-guarantee>NONE</transport-guara
23   </user-data-constraint>
24 </security-constraint>

```

Q3. What are basic steps involved in bootstrapping Spring & Logback with the web container?

A3. Start with the **web.xml**

Step 1: web.xml

```

1  <?xml version="1.0" encoding="UTF-8"?>
2  <web-app version="2.5" xmlns="http://java.sun.com/xml/ns/j2ee"
3    xsi:schemaLocation="http://java.sun.com/xml/ns/j2ee http://java.sun.com/xml/ns/j2ee/web-app_2_5.xsd"
4
5    <display-name>Myapp Enterprise Service</display-name>
6
7    <context-param>
8      <param-name>logbackConfigLocation</param-name>
9      <param-value>classpath:myapp-enterprise-logback.xml</param-value>
10   </context-param>
11
12   <context-param>
13     <param-name>logbackExposeWebAppRoot</param-name>
14     <param-value>false</param-value>
15   </context-param>
16
17   <!-- Spring logback configuration listener -
18   <listener>
19     <listener-class> com.myapp.logging.LogbackConfigurationListener
20   </listener>
21
22   <servlet>
23     <servlet-name>myapp-enterprise-endpoint</servlet-name>
24     <servlet-class>org.springframework.web.servlet.mvc.annotation.AnnotationMethodHandler
25     <init-param>
26       <param-name>contextClass</param-name>
27       <param-value>org.springframework.web.servlet.mvc.annotation.AnnotationMethodHandler

```

```

28         </init-param>
29         <init-param>
30             <param-name>contextConfigLocation</p
31             <param-value>com.myapp.myapp.configu
32         </init-param>
33         <init-param>
34             <param-name>contextInitializerClasse
35             <param-value>com.myapp.myapp.Enterpr
36         </init-param>
37         <load-on-startup>1</load-on-startup>
38     </servlet>
39
40     <servlet-mapping>
41         <servlet-name>myapp-enterprise-endpoint<
42         <url-pattern>*</url-pattern>
43     </servlet-mapping>
44
45     <servlet>
46         <servlet-name>logback-status</servlet-na
47         <servlet-class>ch.qos.logback.classic.Vi
48     </servlet>
49
50     <servlet-mapping>
51         <servlet-name>logback-status</servlet-na
52         <url-pattern>/logback-status</url-patter
53     </servlet-mapping>
54 </web-app>

```

Step 2: Define the Java classes wired up above like

“LogbackConfigListener“,

“MyAppEnterpriseEndpointConfiguration“, and

MyAppEnterpriseApplicationContextInitializer.

```

1 //.....
2 public class LogbackConfigListener implements Se
3
4     @Override
5     public void contextDestroyed(final ServletCo
6         //logic
7     }
8
9     @Override
10    public void contextInitialized(final Servlet
11        //logic
12    }
13 }

```

```

1 //.....
2 @Configuration
3 @EnableWebMvc
4 @ComponentScan("com.myapp.endpoint")
5 public class MyAppEnterpriseEndpointConfiguratio
6
7     @Override
8     public void configureMessageConverters(final
9         converters.add(new Jaxb2RootElementHttpM
10
11         final MappingJackson2HttpMessageConverte
12         jsonConverter.setObjectMapper(ObjectMapp

```

```
13     converters.add(jsonConverter);
14 }
15
16 @Bean
17 public ObjectMapper objectMapper() {
18     final ObjectMapper objectMapper = new Ob
19     objectMapper.registerModule(new JodaModu
20     return objectMapper;
21 }
22 }
```

```
1 //.....
2
3 public class MyAppEnterpriseApplicationContextIn
4     ApplicationContextInitializer<ConfigurableAp
5
6     public static final String DEFAULT_APPLICATI
7
8     private static final Logger LOG = LoggerFact
9
10    @Override
11    public void initialize(final ConfigurableApp
12        final ConfigurableEnvironment environmen
13        final MutablePropertySources propertySou
14        propertySources.addAfter(SYSTEM_ENVIRONM
15    }
16
17    protected PropertySource<?> getApplicationPr
18        try {
19            final Resource propertiesResource =
20            final ResourcePropertySource propert
21            LOG.info("Configured application pro
22            return propertySource;
23        } catch (final IOException ex) {
24            throw new RuntimeException("Unable t
25                + DEFAULT_APPLICATION_PROPERTIES
26        }
27    }
28 }
```

Popular Posts

♦ 11 Spring boot interview questions & answers

825 views

♦ Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers

766 views

18 Java scenarios based interview Questions and Answers

400 views

001A: ♦ 7+ Java integration styles & patterns interview questions & answers

388 views

01b: ♦ 13 Spring basics Q8 – Q13 interview questions & answers

295 views

♦ 7 Java debugging interview questions & answers

293 views

01: ♦ 15 Ice breaker questions asked 90% of the time in Java job interviews with hints

285 views

♦ 10 ERD (Entity-Relationship Diagrams) Interview Questions and Answers

279 views

♦ Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers

239 views

001B: ♦ Java architecture & design concepts interview questions & answers

201 views

Bio

Latest Posts



Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site. **945+** paid members. [join my LinkedIn Group](#). [Reviews](#)



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java

interview Q&A books via [Amazon.com](#) in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site. **945+** paid members. [join my LinkedIn Group](#). [Reviews](#)

< ♥ Chrome Postman to test and debug RESTful Web Services

♥ Beginner array coding problems in Java >

Posted in member-paid, Web basics

Empowers you to open more doors, and fast-track

Technical Know Hows

☀ [Java generics in no time](#) ☀ [Top 6 tips to transforming your thinking from OOP to FP](#) ☀ [How does a HashMap internally work? What is a hashing function?](#)

☀ [10+ Java String class interview Q&As](#) ☀ [Java auto un/boxing benefits & caveats](#) ☀ [Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect](#)

Non-Technical Know Hows

☀ [6 Aspects that can motivate you to fast-track your career & go places](#) ☀ [Are you reinventing yourself as a Java developer?](#) ☀ [8 tips to safeguard your Java career against offshoring](#) ☀ [My top 5 career mistakes](#)

Prepare to succeed

☀ [Turn readers of your Java CV go from “Blah blah” to “Wow”?](#) ☀ [How to prepare for Java job interviews?](#) ☀ [16 Technical Key Areas](#) ☀ [How to choose from multiple Java job offers?](#)

Select Category ▼

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names

or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.