Java-Success.com

Industrial strength Java/JEE Career Companion for those who want to go places



Home > Interview > Core Java Interview Q&A > Generics > ♥ Java Generics in no time "? extends" & "? super" explained with a diagram

▼ Java Generics in no time "? extends" & "? super" explained with a diagram

Posted on June 25, 2015 by Arulkumaran Kumaraswamipillai



Generics in Java can be be a bit tricky to get your head around. Hope the explanation below enhances your understanding of generics. This complements 3 scenarios to get handle on Java generics.

Plain old List, List <Object>, and List<?>

9 tips to earn more | What can u do to go places? | 945+ members. LinkedIn Group. Reviews

600+ Full Stack Java/JEE Interview Q&As ♥Free ♦FAQs

open all | close all

- ince Breaker Interview
- Core Java Interview (
- ⊕ constructors-methc
- Reserved Key Wor
- ⊕ Classes (3)
- Objects (8)
- **⊕** OOP (10)
- ⊕ GC (2)
- Generics (5)

The plain old List: is a <u>heterogeneous mixture</u> or a mixed bag that contains elements of all types, for example Integer, String, Pet, Dog, etc.

The List<Object>: is also a <a href="https://example.com/https://e

The List<?>: is a <u>homogenous collection</u> that represents a family of generic instantiations of List like List<String>, List<Integer>, List<Pet>, List<Dog>, etc.

List<?> is the **super type** for all generic collection as Object[] is the super type for all arrays.

What can I assign to? What can I add to the Collection?

When working with Collection & Generics, you need to ask 4 important questions.

- 1) Can the RHS be assigned to the LHS?
- 2) What types of objects can I add to the collection?
- 3) Is it a read only or read & write collection?
- 4) When to use which wild card ("? extends", "? super")?

If you do the wrong thing, you will get "compile-time" errors. Also, note that you can't use wildcards on the RHS when assigning and Java 8 supports empty "<>" on the RHS.

Understanding Generics and assign-abilities


→ Java Generics ♥ Overloaded me → 12 Java Gener → 7 rules to reme 3 scenarios to ge ⊕-FP (8) **⊞** IO (7) ■ Multithreading (12) Annotations (2) **Differences Betwee** Event Driven Progr Exceptions (2) ∃ Java 7 (2) **∃** Java 8 (24) **∃** JVM (6) Reactive Programn ⊕ Swing & AWT (2) Pressed for time? Jav **⊞** SQL, XML, UML, JSC Hadoop & BigData Int Java Architecture Inte Scala Interview Q&As ■ Spring, Hibernate, & I Testing & Profiling/Sa

As a Java

Architect

Other Interview Q&A 1

Java architecture & design concepts interview Q&As with diagrams | What should be a typical Java EE architecture?



Note: "?" is a wild card meaning <u>anything</u>. "? extends Pet" means "anything that extends a Pet".

Now let's see a code example based on the above diagram. Click on the diagram to expand.

```
package com.generics;
3
   import java.util.ArrayList;
   import java.util.List;
   public class GenericsAssignable {
6
8
       public static void main(String[] args) {
9
           new GenericsAssignable().create();
10
11
12
       public void create() {
13
14
           List<Object> objectsBad = new ArrayList<
15
           List<Pet> petsBad = new ArrayList<Dog>()
16
17
18
           //==== "?" and "? extends" - read only
19
           List<?> pets0k = new ArrayList<Pet>();
20
           List<? extends Pet> pets0k2 = new ArrayL
21
           List<? extends Pet> pets0k3 = new ArrayL
22
           List<? extends Dog> pets0k4 = new Array
23
           List<? extends Dog> pets0k5 = new Array
24
25
           List<? extends Dog> petsBad2 = new Arra
26
           //==== "? super" - can add objects to c
27
28
           List<? super Dog> petsOk6 = new ArrayLis
29
           List<? super Dog> pets0k7 = new ArrayLis
           List<? super Dog> pets0k8 = new ArrayLis
30
31
32
           //can add Dog or any subclass of Dog
33
           pets0k6.add(new Dog());
34
           pets0k6.add(new SpanielDog());//polymorp
35
36
           pets0k6.add(new Pet()); //4. COMPILE ERR
```

Senior Java developers must have a good handle on

open all | close all

- ⊞ Best Practice (6)
- ⊞ Coding (26)
- ⊞ Concurrency (6)

- ⊞ Performance (13)
- **⊞** QoS (8)
- **⊞** SDLC (6)

80+ step by step Java Tutorials

open all | close all

- Setting up Tutorial (6)
- □ Tutorial Diagnosis (2)
- .
- Core Java Tutorials (2)
- Hadoop & Spark Tuto
- **∃** JEE Tutorials (19)
- **⊕** Scala Tutorials (1)
- Spring & HIbernate To
- **i** Tools Tutorials (19)
- Other Tutorials (45)

5 Compile Errors marked in the above code reasoning

- **#1.** List<Pet> is NOT the super type of List<Dog>. If it were the case, then you could add pets of any type including Cats, and it defeats the purpose of Generics. List<?> is the super type of List<Pet>. But read only. Can't add any objects.
- **#2.** Same as **#1**. If were not illegal, you could add a Cat to a Dog collection. Defeating the purpose of Generics.
- **#3.** List<? extends Dog> means assignable from any objects that are of type **Dog** or **subclasses** of Dog. Pet is a **superclass** of Dog.
- **#4.** You can only add objects of type **Dog** or **subclasses** of Dog. Subclasses are possible because of **polymorphism**, where a parent type reference can hold its subclass object type. So, you can add objects of type Dog or its subclasses like SpanielDog, but NOT its super classes.
- **#5.** List<? super Dog> means assignable from any objects that are of type **Dog** or **superclasses** of type Dog. Pet, Object, etc are valid superclasses. But SpanielDog is a subclass.

So, how to decide when to use a wild card, and when not to?

1. Use the ? extends wildcard if you need to retrieve object from a data structure. That is **read only**. You can't add elements to the collection.

Preparing for Java written & coding tests

open all | close all

- E Can you write code?
- Converting from A to I
- Designing your classe
- Passing the unit tests
- What is wrong with the
- Writing Code Home A

How good are your...to go places?

open all | close all

- Career Making Know-

- **2.** Use the ? super wildcard if you need to add objects to a data structure.
- **3.** If you need to do both things (i.e. read and add objects), don't use any wildcard.

More code examples to validate your understanding

```
package com.generics;
3
   import java.util.ArrayList;
   import java.util.List;
   public class GenericsByExample {
8
       public static void main(String[] args) {
9
            new GenericsByExample().create();
10
11
12
       public void create() {
13
14
            // dogs only
15
            List<Dog> dogs = new ArrayList<Dog>();
            dogs.add(new Dog());
16
            dogs.add(new SpanielDog()); //polymorphi
17
           dogs.add(new Pet()); // compile error
dogs.add(new Cat()); // compile error
18
19
20
21
            // cats only
22
           List<Cat> cats = new ArrayList<Cat>();
23
           cats.add(new Cat());
24
           // cats.add(new Dog()); //No can't add d
25
26
            // any pets can be added
27
            List<Pet> pets = new ArrayList<Pet>();
28
           pets.add(new Dog()); //polymorphism
           pets.add(new Cat()); //polymorphism
29
30
           pets.add(new Pet());
31
32
            // so, wrong to say List<Pet> is a super
33
           // defeats the purpose of having Generic
34
35
            // RHS allows Pet, Dog, Cat, SpanielDog,
36
            List<? extends Pet> petsOnlyForReading =
37
38
            // RHS allows Dog and SpaniellDog, but r
39
            List<? extends Dog> dogsOnlyForReadingy
40
41
           petsOnlyForReading.add(new Dog()); // col
42
            dogsOnlyForReadingy.add(new Cat()); // c
43
44
            List<Dog> dogsOnly = new ArrayList<Pet>(
45
46
            List<? super Dog> dogsOnly1 = new ArrayL
47
            dogsOnly1.add(new Dog());
48
            dogsOnly1.add(new SpanielDog()); // poly
49
            dogsOnly1.add(new Pet()); // compile err
```

```
50
51
             List<? super Dog> dogsOnly2 = new ArrayL
             dogsOnly2.add(new Dog());
dogsOnly2.add(new SpanielDog()); // poly
dogsOnly2.add(new Pet()); // compile err
52
53
54
55
56
             List<? super Dog> dogsOnly3 = new ArrayL
             doqsOnly3.add(new Dog());
57
58
             dogsOnly3.add(new SpanielDog()); // poly
             dogsOnly3.add(new Pet()); // compile err
59
60
             dogsOnly3.add(new Object()); // compile
61
62
             List<? <pre>super SpanielDog> spanielsOrSubcl
63
             spanielsOrSubclassesOnly.add(new Dog());
64
             spanielsOrSubclassesOnly.add(new Spaniel
65
             spanielsOrSubclassesOnly.add(new Pet());
        }
66
67
```

Popular Posts

◆ 11 Spring boot interview questions & answers

861 views

◆ Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers

829 views

18 Java scenarios based interview Questions and Answers

448 views

001A: ♦ 7+ Java integration styles & patterns interview questions & answers

407 views

◆ 7 Java debugging interview questions & answers

311 views

◆ 10 ERD (Entity-Relationship Diagrams) Interview Questions and Answers

303 views

01b: ♦ 13 Spring basics Q8 – Q13 interview questions & answers

294 views

01: ♦ 15 Ice breaker questions asked 90% of the time in Java job interviews with hints

288 views

♦ Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers

263 views

8 Git Source control system interview questions & answers

215 views

Bio

Latest Posts



Arulkumaran Kumaraswamipillai



Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers

to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.

Remote debugging in Java with Java Debug Wire Protocol (JDWP)
 03: ◆ ♥ Java autoboxing & unboxing – benefits & caveats interview

Q&A >

Posted in Generics

Tags: Free Content, Free FAQs

Empowers you to open more doors, and fast-track

Technical Know Hows

- * Java generics in no time * Top 6 tips to transforming your thinking from OOP to FP * How does a HashMap internally work? What is a hashing function?
- * 10+ Java String class interview Q&As * Java auto un/boxing benefits & caveats * Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect

Non-Technical Know Hows

* 6 Aspects that can motivate you to fast-track your career & go places * Are you reinventing yourself as a Java developer? * 8 tips to safeguard your Java career against offshoring * My top 5 career mistakes

Prepare to succeed

<u>★ Turn readers of your Java CV go from "Blah blah" to "Wow"? ★ How to prepare for Java job interviews? ★ 16 Technical Key Areas ★ How to choose from multiple Java job offers?</u>

Select Category

▼

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.

1

© 2016 Java-Success.com

Responsive Theme powered by WordPress