

Java-Success.com

Industrial strength Java/JEE Career Companion for those who want to go places

[Home](#)
[Java FAQs](#)
[600+ Java Q&As](#)
[Career](#)
[Tutorials](#)
[Member](#)
[Why?](#)
[Can u Debug?](#)
[Java 8 ready?](#)
[Top X](#)
[Productivity Tools](#)
[Judging Experience?](#)

[Home](#) › [member-paid](#) › Mocks, stubs, domain, and anemic objects interview Q&A

Mocks, stubs, domain, and anemic objects interview Q&A

Posted on [September 2, 2014](#) by [Arulkumaran Kumaraswamipillai](#) — No

[Comments](#) ↓



Q1. What are mock objects?

A1. Mock objects are used in unit testing to ensure that your tests don't fail due to volatility of the data changes. There are mocking frameworks like **EasyMock**, **Mockito**, and **PowerMock**.

The key point to remember regarding mock objects is the ability of the mock objects to **verify** if a particular method was invoked and if yes, **how many times was invoked**. This is demonstrated with the **last two lines with the verify**

[9 tips to earn more](#) | [What can u do to go places?](#) | **945+** members. [LinkedIn Group](#). [Reviews](#)

600+ Full Stack Java/JEE Interview Q&As ♥Free ♦FAQs

[open all](#) | [close all](#)

[Ice Breaker Interview](#)

[Core Java Interview C](#)

[Java Overview \(4\)](#)

[Data types \(6\)](#)

[constructors-methc](#)

[Reserved Key Wor](#)

[Classes \(3\)](#)

[Objects \(8\)](#)

[▶ Beginner Java](#)

[♥♦ HashMap & H](#)

[♦ 5 Java Object](#)

statement. This is one of the key differences between using a mock object versus a stub.

```

1  import static org.mockito.Matchers.any;
2  import static org.mockito.Mockito.mock;
3  import static org.mockito.Mockito.times;
4  import static org.mockito.Mockito.verify;
5  import static org.mockito.Mockito.when;
6
7  import org.junit.Before;
8  import org.junit.Test;
9  import org.mockito.Mock;
10 import org.mockito.Mockito;
11 import org.mockito.MockitoAnnotations;
12
13 public class MyAppControllerTest
14 {
15     private static final String PORTFOLIO_CODE =
16     private static final java.util.Date VALUATION
17
18     private MyAppService mockMyAppService;
19     private MyAppController controller;
20
21     @Mock
22     HttpServletResponse response;
23
24     @Before
25     public void setup() {
26         MockitoAnnotations.initMocks(this);
27         controller = new MyAppController();
28         mockMyAppService = mock(MyAppServiceImpl.class);
29         controller.setMyAppService(mockMyAppService);
30     }
31
32     @Test
33     public void testGetPositionFeedCSV() throws Exception {
34         String str = "dummyCSV";
35         //Set up behavior
36         when(mockMyAppService.getPositionFeedCSV(anyString(), anyDate()))
37         when(response.getWriter()).thenReturn(new PrintWriter());
38
39         //Invoke controller
40         controller.getPositionFeedCSV(PORTFOLIO_CODE, VALUATION);
41
42         //Verify behavior
43         verify(mockMyAppService, times(1)).getPositionFeedCSV(anyString(), anyDate());
44         verify(writer, times(1)).write(anyString());
45     }
46 }
47

```

Q2. What is the difference between fake objects, mock objects, and stubs?

A2. Fake objects build a very lightweight implementation of the same functionality as provided by a component that you are faking. Since they take some shortcut, they are not suitable for production.

- ◆ Java enum inter
- ◆ Java immutabl
- ◆♥ Object equals
- Java serialization
- Mocks, stubs, dc
- ☞ OOP (10)
- ☞ GC (2)
- ☞ Generics (5)
- ☞ FP (8)
- ☞ IO (7)
- ☞ Multithreading (12)
- ☞ Algorithms (5)
- ☞ Annotations (2)
- ☞ Collection and Data
- ☞ Differences Between
- ☞ Event Driven Progr
- ☞ Exceptions (2)
- ☞ Java 7 (2)
- ☞ Java 8 (24)
- ☞ JVM (6)
- ☞ Reactive Programn
- ☞ Swing & AWT (2)
- ☞ JEE Interview Q&A (3)
- ☞ Pressed for time? Jav
- ☞ SQL, XML, UML, JSC
- ☞ Hadoop & BigData Int
- ☞ Java Architecture Inte
- ☞ Scala Interview Q&As
- ☞ Spring, Hibernate, & I
- ☞ Testing & Profiling/Sa
- ☞ Other Interview Q&A 1
- ☞ 📺 Free Java Interview

As a Java Architect

[Java architecture & design concepts](#)
[interview Q&As with diagrams](#) | [What should](#)

Mocks are objects pre-programmed with expectations which form a specification of the calls they are expected to receive. You can use mocking frameworks like EasyMock, Mockito, PowerMock, etc to achieve this. When an actual service is invoked, a mock object is executed with a known outcome instead of the actual service. With mock objects, you can verify if expected method calls were made and how many times.

Stubs are like a mock class, except that they don't provide the ability to verify that methods have been called or not called. Generally services that are not ready or currently not stable are stubbed to make the test code more stable or to proceed with your development work to swap to the actual implementation when it is ready.

When to use what? You use a Mock when it's an object that returns values that you set to the tested class. You use a Stub to mimic an Interface or Abstract class to be tested. In fact, the difference is very subtle and it doesn't really matter what you call it, fake, mock, or stub, they are all objects that aren't used in production, and used for managing complexity to write quality tests.

Q3. What is a domain object?

A3. A domain object means a **business object**. Domain logic or business logic reside in "domain objects" and "business objects" that are **protocol independent**. You can access them via any protocol. Domain objects "store data" and "stored data specific business logic" and "domain services" will have business logic and manipulate the "domain objects". Domain services often make use of a DAO layer to retrieve and store persistent data.

Domain Object with business logic

```
1 @Entity
2 @Table(name = "account_rebalance")
3 public class Rebalance extends GenericDomainObj
4
5     @Id
6     @GeneratedValue(strategy = GenerationType.AUT
```

[be a typical Java EE architecture?](#)

Senior Java developers must have a good handle on

[open all](#) | [close all](#)

- [Best Practice \(6\)](#)
- [Coding \(26\)](#)
- [Concurrency \(6\)](#)
- [Design Concepts \(7\)](#)
- [Design Patterns \(11\)](#)
- [Exception Handling \(3\)](#)
- [Java Debugging \(21\)](#)
- [Judging Experience \(1\)](#)
- [Low Latency \(7\)](#)
- [Memory Management \(1\)](#)
- [Performance \(13\)](#)
- [QoS \(8\)](#)
- [Scalability \(4\)](#)
- [SDLC \(6\)](#)
- [Security \(13\)](#)
- [Transaction Management \(1\)](#)

80+ step by step Java Tutorials




[open all](#) | [close all](#)

- [Setting up Tutorial \(6\)](#)
- [Tutorial - Diagnosis \(2\)](#)
- [Akka Tutorial \(9\)](#)
- [Core Java Tutorials \(2\)](#)
- [Hadoop & Spark Tutorial \(1\)](#)
- [JEE Tutorials \(19\)](#)
- [Scala Tutorials \(1\)](#)

```











7  @Column(name = "acc_rebal_id")
8  private Long id;
9
10 @Column(name = "available_cash")
11 private Decimal cashAvailable = Decimal.ZERO;
12
13 @Column(name = "funding_method")
14 @Enumerated(EnumType.STRING)
15 private FundingMethod fundingMethod = Funding
16
17 @Column(name = "instrument_type")
18 @Enumerated(EnumType.STRING)
19 private InstrumentType instrumentType;
20
21 //..... other state variables
22
23 //getters and setters omitted
24
25 //domain or business logic
26 public boolean isCash(){
27     //logic to determine if cash product based
28 }
29
30 public boolean isInvestment(){
31     //logic to determine if cash product base
32 }
33
34 public String getMaxHedgeFundAmount() {
35     //business logic to determine max hedge
36 }
37
38 public getCashBalanceError() {
39     //business logic
40 }
41 }
42

```

-  [Spring & Hibernate Ti](#)
-  [Tools Tutorials \(19\)](#)
-  [Other Tutorials \(45\)](#)

Preparing for Java written & coding tests

[open all](#) | [close all](#)

-  [◆ Complete the given](#)
-  [Can you write code? \(](#)
-  [Converting from A to I](#)
-  [Designing your classe](#)
-  [Java Data Structures](#)
-  [Passing the unit tests](#)
-  [What is wrong with th](#)
-  [Writing Code Home A](#)
-  [Written Test Core Jav](#)
-  [Written Test JEE \(1\)](#)

Domain Service interface



```

1 public interface RebalanceService {
2     public Long saveRebalance(Rebalance rebalance
3     List<Rebalance> findRebalances(RebalanceSearc
4     Boolean cancelRebalance(Long id);
5     public BigDecimal calculateCashBalance(Rebala
6 }
7

```

How good are your...to go places?

[open all](#) | [close all](#)

-  [Career Making Know-](#)
-  [Job Hunting & Resum](#)

Domain Service implementation with business logic

```

1 public class RebalanceServiceImpl implements Re
2
3     @Resource
4     private RebalanceRepository rebalRepository;
5
6     public Long saveRebalance(Rebalance rebalanc
7         return rebalRepository.saveRebalance(reba
8     }
9
10    List<Rebalance> findRebalances(RebalanceSear

```

```
11         //business logic and data access via re
12     }
13     Boolean cancelRebalance(Long id) {
14         //business logic and data access via reb
15     }
16     public BigDecimal calculateCashBalance(Rebal
17         // calculation business logic
18     }
19 }
20
```

Q4. What are data transfer objects?

A4. A **Data Transfer Object** (DTO) is an object that is used to encapsulate data, and send it from one layer of an application to another. DTOs are most commonly used by the Services layer to transfer data to and from the UI layer. The main benefit is to map domain centric data to view centric data. There are frameworks like **Dozer** to map data from a domain object to a DTO. This conversion can be an expensive process and may not be useful if there are no remote calls involved. The domain objects themselves can be used as DTOs.

DTOs can be used as the **models** in the **MVC pattern**.

Another use for DTOs is to **encapsulate parameters for remote calls** to minimize the network round trips. DTOs have state variables and getter/setter methods.

Q5. What is an anemic model?

A5. Anemic domain model is the use of a domain model where the “domain objects” contain little or no business logic. This contradicts the notion of object-oriented design where you have well encapsulated logic.

An **anemic domain model is an anti-pattern** because in an anemic model, your domain logic exists somewhere else, probably in a class full of class(static) method or in multiple places, all with conflicting logic.

Q6. What is the purpose of Dozer framework?

A6. Convert Domain Objects to DTOs and DTOs back to Domain Objects in multi-tiered and multi-layered architecture.

Popular Posts

♦ 11 Spring boot interview questions & answers

857 views

♦ Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers

825 views

18 Java scenarios based interview Questions and Answers

447 views

001A: ♦ 7+ Java integration styles & patterns interview questions & answers

401 views

♦ 7 Java debugging interview questions & answers

311 views

♦ 10 ERD (Entity-Relationship Diagrams) Interview Questions and Answers

302 views

01b: ♦ 13 Spring basics Q8 – Q13 interview questions & answers

292 views

01: ♦ 15 Ice breaker questions asked 90% of the time in Java job interviews with hints

286 views

♦ Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers

263 views

8 Git Source control system interview questions & answers

215 views

Bio

Latest Posts



**Arulkumaran
Kumaraswamipillai**

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via [Amazon.com](https://www.amazon.com) in



2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.

**About** [Arulkumaran Kumaraswamipillai](#)

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via [Amazon.com](#) in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.

◀ ♦ Java Collection overview interview questions and answers

“In your Java experience” interview questions & answers ▶

Posted in member-paid, Objects

Tags: Core Java FAQs, Java/JEE FAQs

Leave a Reply

Logged in as [geethika](#). [Log out?](#)

Comment

Post Comment

Empowers you to open more doors, and fast-track

Technical Know Hows

☀ [Java generics in no time](#) ☀ [Top 6 tips to transforming your thinking from OOP to FP](#) ☀ [How does a HashMap internally work? What is a hashing function?](#)
☀ [10+ Java String class interview Q&As](#) ☀ [Java auto un/boxing benefits & caveats](#) ☀ [Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect](#)

Non-Technical Know Hows

☀ [6 Aspects that can motivate you to fast-track your career & go places](#) ☀ [Are you reinventing yourself as a Java developer?](#) ☀ [8 tips to safeguard your Java career against offshoring](#) ☀ [My top 5 career mistakes](#)

Prepare to succeed

☀ [Turn readers of your Java CV go from “Blah blah” to “Wow”?](#) ☀ [How to prepare for Java job interviews?](#) ☀ [16 Technical Key Areas](#) ☀ [How to choose from multiple Java job offers?](#)

Select Category ▼

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.