Register Login Logout Contact Us

Java-Success.com

Industrial strength Java/JEE Career Companion to open more doors



Home > member-paid > 10: Q66 - Q70 Pattern matching in Scala Interview Q&As

10: Q66 – Q70 Pattern matching in **Scala Interview Q&As**

Posted on September 21, 2016 by Arulkumaran Kumaraswamipillai



Q66. What is the purpose of pattern matching in Scala? A66. It is for the "flow control". Most imperative languages support "if-then-else", case statements, and loops like while, for, foreach, etc. Scala does support some of these, but the most often used "conditional expression" is based on pattern matching. In the example below, an integer input is matched against either 0 or any integer value.

```
2
  object Example2 extends App {
4
     def factorial(input: Int) : Int = input match
5
        case \emptyset \Rightarrow 1
        case n => n * factorial(n-1) //recursion
6
7
```

600+ Full Stack Java/JEE **Interview Q&As ♥Free ♦FAOs**

```
open all | close all
```

- in Ice Breaker Interview
- **E** Core Java Interview (
- **■** JEE Interview Q&A (3
- Pressed for time? Jav
- **⊞** SQL, XML, UML, JSC
- Hadoop & BigData Int
- Java Architecture Inte
- Scala Interview Q&As
- - Scala way of coding
 - 01: Coding Scale
 - --01: ♥ Q1 Q6 Scal
 - -02: Q6 Q12 Scala

 - -03: Q13 Q18 Sca
 - 04: Q19 Q26 Sca
 - -05: Q27 Q32 Sca

 - -06: Q33 Q40 Sca
 - -07: Q41 Q48 Sca
 - -08: Q49 Q58 Sca

 - --09: Q59 Q65 Hig
 - -10: Q66 Q70 Pat
 - --11: Q71 Q77 Sc

```
9 println(factorial(3)) // 3 * 2 * 1 = 6
10 }
11
```

Compared to Java's switch/case statements, Scala's pattern matching is an **expression** and not a statement, meaning that it always results in a value. Secondly, Scala's alternative expressions never "fall through" into the next case. Thirdly, if none of the patterns match, an exception named "MatchError" will be thrown. This means you always have to make sure that all

cases are covered or add a default case where there's nothing to do.

Q67. Can Scala's pattern matching used for the collections? A67. Yes. Here is an example of pattern matching in action for the flow control.

```
object Example2 extends App {
      val days = List("Sunday", "Monday", "Tuesday")
4
5
6
      def iter(list: List[String]) : List[String]= l
        case dayBeingProcessed :: remainingDays => {
  println("Processing: " + dayBeingProcessed
8
9
           iter(remainingDays)
10
11
        case Nil => Nil //when the list is empty
12
13
14
      iter(days)
15 }
16
17
```

Output:

```
1
2 Processing: Sunday
3 Processing: Monday
4 Processing: Tuesday
5
```

"dayBeingProcessed: remainingDays" is a notation meaning "head: tail", which means head (i.e. first element) followed by a tail (i.e. all the remaining elements except the head). You can also think of it as "first::rest".

```
□ 12: Q78 – Q80 Rec □ Spring, Hibernate, & I □ Testing & Profiling/Sa □ Other Interview Q&A I □ Free Java Interview
```

16 Technical Key Areas

open all | close all

- ⊞ Best Practice (6)
- **⊞** Coding (26)
- ⊞ Concurrency (6)

- **⊞ Judging Experience Ir**

- ⊞ Performance (13)
- **⊞** QoS (8)
- **⊞** SDLC (6)
- ⊞ Security (13)

80+ step by step Java Tutorials

open all | close all

- **⊞** Setting up Tutorial (6)
- ☐ Tutorial Diagnosis (2)
- E Core Java Tutorials (2
- Hadoop & Spark Tuto
- **∃** JEE Tutorials (19)
- ⊕ Scala Tutorials (1)

Q68. The following code will randomly fail by throwing an exception "The number is too big". How will you fix the code so that when the number is too big, it returns a value of 70.

```
⇒ Spring & HIbernate To

⇒ Tools Tutorials (19)

⇒ Other Tutorials (45)
```

```
import scala.util.Try
3
   object ServiceThatCanFail extends App {
6
     def getNextNumber:Long = {
       val number = Math.round(Math.random() * 100)
8
       if(number \ll 70) {
9
         number
10
       } else {
         throw new Exception("The number is too big
11
12
13
     }
14
15
     //write code
16
     println(getNextNumber)
17
18
19
```

A68. The "Try" with "Success" and "Failure" algebraic types with pattern matching as shown below.

```
1
   import scala.util.Try
   import scala.util.Failure
   import scala.util.Success
   object ServiceThatCanFail extends App {
6
8
     def getNextNumber: Try[Long] = Try {
        val number = Math.round(Math.random() * 100)
9
10
        if(number <= 70) {
11
          number
12
        } else {
13
          throw new Exception("The number is too big
14
15
     }
16
17
     getNextNumber match {
        case Failure(e) => println(70)
case Success(result) => println(result)
18
19
20
     }
21 }
22
```

Q69. Can Scala pattern match on objects?

A69. Yes. Case classes are Scala's way to allow pattern matching on objects without requiring much boilerplate code. Here is an example.

100+ Java pre-interview coding tests

open all | close all

- ⊕ Can you write code?
- Converting from A to I
- Designing your classe
- Passing the unit tests
- •What is wrong with th
- **Writing Code Home A**
- **Written Test Core Jav**
- Written Test JEE (1)

How good are your?

open all | close all

- Career Making Know-

```
object ShapeTest extends App {
  def whatShape(shape: Shape) = shape match {
    case Square(_) => println("Found a square")
    case Rectangle(_, _) => println("Found a rec
    case _ => println("NOT FOUND!")
4
5
6
8
9
       whatShape(new Square(5)) // Found a square
       whatShape(new Rectangle(6, 5))// Found a recta
10
11
       whatShape(null) // NOT FOUND!
12 }
13
14 trait Shape
15 case class Square(width: Double) extends Shape
16 case class Rectangle(width: Double, length: Doub
```

Q70. Can you replace the following code with pattern matching without the **if/else** and **isInstanceOf** statements?

```
object BetterMatching extends App {
4
     def f(x: Any): String = {
5
        if(x.isInstanceOf[Int]) {
         "integer: " + x
else if (x.isInstanceOf[Double]) {
6
           "a double"
8
9
        } else if (x.isInstanceOf[String]) {
10
           "It is a String value of " + x
11
        } else {
12
          throw new Exception("Unsupported type")
13
14
     }
15
16
     println(f("Java"))
     println(f(5))
17
18 }
19
```

A70.

```
2
   object BetterMatching extends App {
3
4
      def f(x: Any): String = x match {
5
         case i:Int => "integer: " + i
         case _:Double => "a double"
case s:String => "It is a String value of "
6
7
8
9
      println(f("Java")) //It is a String value of J
println(f(5)) //integer: 5
10
11
12 }
13
```

Popular Member Posts

◆ 11 Spring boot interview questions & answers

850 views

◆ Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers

769 views

001A: ♦ 7+ Java integration styles & patterns interview questions & answers

399 views

18 Java scenarios based interview Questions and Answers

387 views

♦ 7 Java debugging interview questions & answers

308 views

01b: ♦ 13 Spring basics Q8 – Q13 interview questions & answers

305 views

01: ♦ 15 Ice breaker questions asked 90% of the time in Java job interviews with hints

297 views

◆ 10 ERD (Entity-Relationship Diagrams) Interview Questions and Answers

294 views

◆ Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers

246 views

001B: ♦ Java architecture & design concepts interview questions & answers

204 views

Bio

Latest Posts



Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in



2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.**945+** paid members. join my LinkedIn Group. **Reviews**



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers

to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.945+ paid members. join my LinkedIn Group. Reviews

09: Q59 – Q65 Higher Order Functions in Scala Interview Q&As

11: Q71 – Q77 – Scala type parametrization & variance interview

Q&As >

Posted in member-paid, Scala Interview Q&As

Empowers you to open more doors, and fast-track

Technical Know Hows

- * Java generics in no time * Top 6 tips to transforming your thinking from OOP to FP * How does a HashMap internally work? What is a hashing function?
- * 10+ Java String class interview Q&As * Java auto un/boxing benefits & caveats * Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect

Non-Technical Know Hows

* 6 Aspects that can motivate you to fast-track your career & go places * Are you reinventing yourself as a Java developer? * 8 tips to safeguard your Java career against offshoring * My top 5 career mistakes

Prepare to succeed

<u>Turn readers of your Java CV go from "Blah blah" to "Wow"?</u> <u>★ How to prepare for Java job interviews?</u> <u>★ 16 Technical Key Areas</u> <u>★ How to choose from multiple Java job offers?</u>

Select Category ▼

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.

1

© 2016 Java-Success.com

Responsive Theme powered by WordPress