

Java-Success.com

Industrial strength Java/JEE Career Companion for those who want to go places

[Home](#)
[Java FAQs](#)
[600+ Java Q&As](#)
[Career](#)
[Tutorials](#)
[Member](#)
[Why?](#)
[Can u Debug?](#)
[Java 8 ready?](#)
[Top X](#)
[Productivity Tools](#)
[Judging Experience?](#)

[Home](#) › [Interview](#) › [Core Java Interview Q&A](#) › [Generics](#) › ♥ Overloaded methods

Vs Generic methods in Java with JD-GUI & javap to look under the covers

♥ Overloaded methods Vs Generic methods in Java with JD-GUI & javap to look under the covers

Posted on [December 15, 2015](#) by [Arulkumaran Kumaraswamipillai](#)

In an earlier post we looked at [Understanding Overriding, Hiding, and Overloading in Java?](#). We also discussed how “method overriding” gives **polymorphism**. In this post, let’s see how a “generic method” can replace a number of overloaded methods. Then see under the hood as to what happens to the compiled code.

Overloaded methods example

[9 tips to earn more](#) | [What can u do to go places?](#) | **945+** members. [LinkedIn Group](#). [Reviews](#)

600+ Full Stack Java/JEE Interview Q&As ♥Free ♦FAQs

[open all](#) | [close all](#)

 [Ice Breaker Interview](#)

 [Core Java Interview C](#)

 [Java Overview \(4\)](#)

 [Data types \(6\)](#)

 [constructors-methc](#)

 [Reserved Key Wor](#)

 [Classes \(3\)](#)

 [Objects \(8\)](#)

 [OOP \(10\)](#)

 [GC \(2\)](#)

 [Generics \(5\)](#)

3 overloaded methods to print 3 different types of data. If you notice it carefully, in all 3 methods the method signatures and the actual method body are the same except for the data types they work with like Integer, Character, and String.

```

1 package test;
2
3 public class OverLoadedMethods {
4
5     public static void main(String[] args) {
6         Integer[] numbers = new Integer[] { 1, 2
7         Character[] characters = new Character[]
8         String[] strings = new String[] { "AB",
9
10        print(numbers);
11        System.out.println();
12        print(characters);
13        System.out.println();
14        print(strings);
15    }
16
17    private static void print(Integer[] input) {
18        for (Integer in : input) {
19            System.out.printf("%s ", in);
20        }
21    }
22
23    private static void print(Character[] input)
24        for (Character in : input) {
25            System.out.printf("%s ", in);
26        }
27    }
28
29    private static void print(String[] input) {
30        for (String in : input) {
31            System.out.printf("%s ", in);
32        }
33    }
34 }
35
36 }
37
38

```

Output:

```

1 2 3 4
A B C
A B C D

```

Generic method example

1 generic method to replace 3 overloaded methods. It takes a generic type "T"

- ♥ Java Generics
- ♥ Overloaded m
- ♦ 12 Java Gener
- ♦ 7 rules to reme
- 3 scenarios to ge
- FP (8)
- IO (7)
- Multithreading (12)
- Algorithms (5)
- Annotations (2)
- Collection and Data
- Differences Between
- Event Driven Progr
- Exceptions (2)
- Java 7 (2)
- Java 8 (24)
- JVM (6)
- Reactive Programn
- Swing & AWT (2)
- JEE Interview Q&A (3)
- Pressed for time? Jav
- SQL, XML, UML, JSC
- Hadoop & BigData Int
- Java Architecture Inte
- Scala Interview Q&As
- Spring, Hibernate, & I
- Testing & Profiling/Sa
- Other Interview Q&A 1
- Free Java Interview

As a Java Architect

[Java architecture & design concepts](#)
[interview Q&As with diagrams](#) | [What should be a typical Java EE architecture?](#)

```

1
2 package test;
3
4 public class GenericMethod<T> {
5
6     public static void main(String[] args) {
7         Integer[] numbers = new Integer[] { 1, 2
8         Character[] characters = new Character[]
9         String[] strings = new String[] { "AB",
10
11         print(numbers);
12         System.out.println();
13         print(characters);
14         System.out.println();
15         print(strings);
16     }
17
18     //one generic method instead of 3 overloaded
19     private static <T> void print(T[] input) {
20         for (T in : input) {
21             System.out.printf("%s ", in);
22         }
23     }
24 }
25 }
26
27

```

Output:

```

1 2 3 4
A B C
AB BC CD

```

What is happening under the covers?

Isn't Java Generics a **compile-time** phenomenon? Yes. Let's dig a bit deeper with two handy tools **1)** JD-GUI (Java Decompiler GUI) **2)** javap.

JD-GUI

is used to de-compile a Java class file. open the JD-GUI, and drag and drop the **GenericMethod.class**. As you can see an `Object[]` is used to handle different types. The generic type "T" in the method body is **erased by the compiler**.

```

1
2 package test;

```

Senior Java developers must have a good handle on

[open all](#) | [close all](#)

- [Best Practice \(6\)](#)
- [Coding \(26\)](#)
- [Concurrency \(6\)](#)
- [Design Concepts \(7\)](#)
- [Design Patterns \(11\)](#)
- [Exception Handling \(3\)](#)
- [Java Debugging \(21\)](#)
- [Judging Experience It](#)
- [Low Latency \(7\)](#)
- [Memory Management](#)
- [Performance \(13\)](#)
- [QoS \(8\)](#)
- [Scalability \(4\)](#)
- [SDLC \(6\)](#)
- [Security \(13\)](#)
- [Transaction Managen](#)

80+ step by step Java Tutorials

[open all](#) | [close all](#)

- [Setting up Tutorial \(6\)](#)
- [Tutorial - Diagnosis \(2\)](#)
- [Akka Tutorial \(9\)](#)
- [Core Java Tutorials \(2\)](#)
- [Hadoop & Spark Tuto](#)
- [JEE Tutorials \(19\)](#)
- [Scala Tutorials \(1\)](#)
- [Spring & Hibernate T](#)
- [Tools Tutorials \(19\)](#)
- [Other Tutorials \(45\)](#)

```

3
4 import java.io.PrintStream;
5
6 public class GenericMethod<T>
7 {
8     public static void main(String[] args)
9     {
10         Integer[] numbers = { Integer.valueOf(1), Integer.valueOf(2), Integer.valueOf(3) };
11         Character[] characters = { Character.valueOf('A'), Character.valueOf('B'), Character.valueOf('C') };
12         String[] strings = { "AB", "BC", "CD" };
13
14         print(numbers);
15         System.out.println();
16         print(characters);
17         System.out.println();
18         print(strings);
19     }
20
21     private static <T> void print(T[] input)
22     {
23         Object[] arrayOfObject = input;
24         int j = input.length;
25         for (int i = 0; i < j; i++) {
26             Object in = arrayOfObject[i];
27             System.out.printf("%s ", new Object[] { in });
28         }
29     }
30 }
31
32

```

Preparing for Java written & coding tests

[open all](#) | [close all](#)

- ☒ ♦ Complete the given
- ☒ Can you write code? (
- ☒ Converting from A to I
- ☒ Designing your classe
- ☒ Java Data Structures
- ☒ Passing the unit tests
- ☒ What is wrong with th
- ☒ Writing Code Home A
- ☒ Written Test Core Jav
- ☒ Written Test JEE (1)

javap command

```

1
2
3 javap -c GenericMethod.class
4 Compiled from "GenericMethod.java"
5 public class test.GenericMethod<T> {
6     public test.GenericMethod();
7     Code:
8         0: aload_0
9         1: invokespecial #8                  // Method java.lang.Object.<init>()V
10        4: return
11
12     public static void main(java.lang.String[]);
13     Code:
14         0: iconst_4
15         1: anewarray      #18                // class java.lang.String[]
16         4: dup
17         5: iconst_0
18         6: iconst_1
19         7: invokestatic  #20                // Method java.lang.System.out:println(Ljava/lang/String;)V
20        10: astore
21        11: dup
22        12: iconst_1
23        13: iconst_2
24        14: invokestatic  #20                // Method java.lang.System.out:println(Ljava/lang/String;)V
25        17: astore
26        18: dup
27        19: iconst_2
28        20: iconst_3
29        21: invokestatic  #20                // Method java.lang.System.out:println(Ljava/lang/String;)V
30        24: astore

```

How good are your...to go places?

[open all](#) | [close all](#)

- ☒ Career Making Know-
- ☒ Job Hunting & Resum

```

31      25: dup
32      26: iconst_3
33      27: iconst_4
34      28: invokestatic #20          // M
35      31: astore
36      32: astore_1
37      33: iconst_3
38      34: anewarray    #24          // c
39      37: dup
40      38: iconst_0
41      39: bipush      65
42      41: invokestatic #26          // M
43      44: astore
44      45: dup
45      46: iconst_1
46      47: bipush      66
47      49: invokestatic #26          // M
48      52: astore
49      53: dup
50      54: iconst_2
51      55: bipush      67
52      57: invokestatic #26          // M
53      60: astore
54      61: astore_2
55      62: iconst_3
56      63: anewarray    #29          // c
57      66: dup
58      67: iconst_0
59      68: ldc          #31          // S
60      70: astore
61      71: dup
62      72: iconst_1
63      73: ldc          #33          // S
64      75: astore
65      76: dup
66      77: iconst_2
67      78: ldc          #35          // S
68      80: astore
69      81: astore_3
70      82: aload_1
71      83: invokestatic #37          // M
72      86: getstatic   #41          // F
73      89: invokevirtual #47          // M
74      92: aload_2
75      93: invokestatic #37          // M
76      96: getstatic   #41          // F
77      99: invokevirtual #47          // M
78     102: aload_3
79     103: invokestatic #37          // M
80     106: return
81 }
82
83

```

Note lines from **83**. The **#37** shows that “print” method is invoked with “java.lang.Object” and “**V**” means “void”. “**L**” means Object, and “[” means an array.

```

1
2 Method print:([Ljava/lang/Object;)V
3

```

1		
2	Type	Character
3	-----	
4	boolean	Z
5	byte	B
6	char	C
7	double	D
8	float	F
9	int	I
10	long	J
11	object	L
12	short	S
13	void	V
14	array	[
15		

javap with flag “-l” to relate to original code

```

1
2  javap -c -l GenericMethod.class
3  Compiled from "GenericMethod.java"
4  public class test.GenericMethod<T> {
5      public test.GenericMethod();
6      Code:
7          0: aload_0
8          1: invokespecial #8                //
9          4: return
10     LineNumberTable:
11         line 3: 0
12     LocalVariableTable:
13         Start Length Slot Name Signature
14             0      5      0  this  Ltest/Generic
15
16     public static void main(java.lang.String[]);
17     Code:
18         0: iconst_4
19         1: anewarray    #18                //
20         4: dup
21         5: iconst_0
22         6: iconst_1
23         7: invokestatic #20                //
24        10: astore
25        11: dup
26        12: iconst_1
27        13: iconst_2
28        14: invokestatic #20                //
29        17: astore
30        18: dup
31        19: iconst_2
32        20: iconst_3
33        21: invokestatic #20                //
34        24: astore
35        25: dup
36        26: iconst_3
37        27: iconst_4
38        28: invokestatic #20                //
39        31: astore
40        32: astore_1
41        33: iconst_3

```

```

42      34: anewarray      #24          //
43      37: dup
44      38: iconst_0
45      39: bipush      65
46      41: invokestatic  #26          //
47      44: astore
48      45: dup
49      46: iconst_1
50      47: bipush      66
51      49: invokestatic  #26          //
52      52: astore
53      53: dup
54      54: iconst_2
55      55: bipush      67
56      57: invokestatic  #26          //
57      60: astore
58      61: astore_2
59      62: iconst_3
60      63: anewarray      #29          //
61      66: dup
62      67: iconst_0
63      68: ldc          #31          //
64      70: astore
65      71: dup
66      72: iconst_1
67      73: ldc          #33          //
68      75: astore
69      76: dup
70      77: iconst_2
71      78: ldc          #35          //
72      80: astore
73      81: astore_3
74      82: aload_1
75      83: invokestatic  #37          //
76      86: getstatic     #41          //
77      89: invokevirtual #47          //
78      92: aload_2
79      93: invokestatic  #37          //
80      96: getstatic     #41          //
81      99: invokevirtual #47          //
82     102: aload_3
83     103: invokestatic  #37          //
84     106: return
85     LineNumberTable:
86         line 6: 0
87         line 7: 33
88         line 8: 62
89         line 10: 82
90         line 11: 86
91         line 12: 92
92         line 13: 96
93         line 14: 102
94         line 15: 106
95     LocalVariableTable:
96         Start  Length  Slot  Name  Signature
97             0      107     0  args  [Ljava/lang/S
98             33       74     1 numbers [Ljava/lang
99             62       45     2 characters [Ljava/l
100            82       25     3 strings  [Ljava/lang
101 }
102
103

```

Look at the “**LineNumberTable**“. For example:

The **line 6** in the source code

```
1  
2 Integer[] numbers = new Integer[] { 1, 2, 3, 4 };  
3
```

corresponds to dessembeld **line 0**:

```
1  
2 0: iconst_4  
3
```

You may also like: [javap for debugging and better understanding some Java concepts with 3 practical examples](#)

Popular Posts

♦ [11 Spring boot interview questions & answers](#)

861 views

♦ [Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers](#)

829 views

[18 Java scenarios based interview Questions and Answers](#)

448 views

001A: ♦ [7+ Java integration styles & patterns interview questions & answers](#)

407 views

♦ [7 Java debugging interview questions & answers](#)

311 views

♦ [10 ERD \(Entity-Relationship Diagrams\) Interview Questions and Answers](#)

303 views

01b: ♦ [13 Spring basics Q8 – Q13 interview questions & answers](#)

294 views

01: ♦ [15 Ice breaker questions asked 90% of the time in Java job interviews with hints](#)

288 views

♦ [Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers](#)

263 views

8 Git Source control system interview questions & answers

215 views

Bio

Latest Posts



Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via [Amazon.com](https://www.amazon.com) in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via [Amazon.com](https://www.amazon.com) in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.

◀ ▶ Beginner Java Object class interview Q&A

Reloading configuration files in Java without stopping the server ▶

Posted in Generics

Tags: Free Content

Empowers you to open more doors, and fast-track

Technical Know Hows

☀ [Java generics in no time](#) ☀ [Top 6 tips to transforming your thinking from OOP to FP](#) ☀ [How does a HashMap internally work? What is a hashing function?](#)
☀ [10+ Java String class interview Q&As](#) ☀ [Java auto un/boxing benefits & caveats](#) ☀ [Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect](#)

Non-Technical Know Hows

☀ [6 Aspects that can motivate you to fast-track your career & go places](#) ☀ [Are you reinventing yourself as a Java developer?](#) ☀ [8 tips to safeguard your Java career against offshoring](#) ☀ [My top 5 career mistakes](#)

Prepare to succeed

☀ [Turn readers of your Java CV go from “Blah blah” to “Wow”?](#) ☀ [How to prepare for Java job interviews?](#) ☀ [16 Technical Key Areas](#) ☀ [How to choose from multiple Java job offers?](#)

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.