

Java-Success.com

Industrial strength Java/JEE Career Companion for those who want to go places

[Home](#)
[Java FAQs](#)
[600+ Java Q&As](#)
[Career](#)
[Tutorials](#)
[Member](#)
[Why?](#)
[Can u Debug?](#)
[Java 8 ready?](#)
[Top X](#)
[Productivity Tools](#)
[Judging Experience?](#)

[Home](#) › [Interview](#) › [Core Java Interview Q&A](#) › [Objects](#) › ♦♥ Object equals Vs == and pass by reference Vs value

♦♥ Object equals Vs == and pass by reference Vs value

Posted on [August 16, 2014](#) by [Arulkumaran Kumaraswamipillai](#) — [4 Comments](#)

↓

14

Like

Share

3

G+1

Q1. What is the difference between “==” and equals(..) method when comparing 2 objects?

A1. It is important to understand the difference between identity (i.e. ==) comparison, which is a shallow comparison that compares only the object references, and the equals() comparison, which is a **deeper comparison** that compares the object attributes. The diagram below explains the difference between the two. There are some exceptional conditions when using primitives, String objects, and enums.

If the equals(..) method is not overridden, then the Object class's default implementation is invoked, which only

[9 tips to earn more](#) | [What can u do to go places?](#) | **945+** members. [LinkedIn Group](#). [Reviews](#)

600+ Full Stack Java/JEE Interview Q&As ♥Free ♦FAQs

[open all](#) | [close all](#)

☒ [Ice Breaker Interview](#)

☒ [Core Java Interview C](#)

☒ [Java Overview \(4\)](#)

☒ [Data types \(6\)](#)

☒ [constructors-methc](#)

☒ [Reserved Key Wor](#)

☒ [Classes \(3\)](#)


☒ [Objects \(8\)](#)

☒ [▶ Beginner Java](#)

☒ [♥♦ HashMap & H](#)

☒ [♦ 5 Java Object i](#)


compares the object references. Invoking the `equals(..)` method of the `Object` class is equivalent to making a shallow comparison with `"=="`. This is why it is imperative to override the **`equals()`** method, and the **`hashCode()`** methods in your custom classes like `Pet`. The Java API objects like `String`, and the wrapper classes like `Integer`, `Double`, `Float`, etc override the `equals(..)`, `hashCode()`, and the `toString(..)` methods. These methods are meant to be overridden as discussed in detail at [“5 Java Object class methods interview questions & answers”](#)



- ◆ Java enum inte
- ◆ Java immutabl
- ◆♥ Object equals
- Java serialization
- Mocks, stubs, dc
- ☞ OOP (10)
- ☞ GC (2)
- ☞ Generics (5)
- ☞ FP (8)
- ☞ IO (7)
- ☞ Multithreading (12)
- ☞ Algorithms (5)
- ☞ Annotations (2)
- ☞ Collection and Data
- ☞ Differences Between
- ☞ Event Driven Progr
- ☞ Exceptions (2)
- ☞ Java 7 (2)
- ☞ Java 8 (24)
- ☞ JVM (6)
- ☞ Reactive Programn
- ☞ Swing & AWT (2)
- ☞ JEE Interview Q&A (3
- ☞ Pressed for time? Jav
- ☞ SQL, XML, UML, JSC
- ☞ Hadoop & BigData Int
- ☞ Java Architecture Inte
- ☞ Scala Interview Q&As
- ☞ Spring, Hibernate, & I
- ☞ Testing & Profiling/Sa
- ☞ Other Interview Q&A 1
- ☞ 🎥 Free Java Interview

As a Java Architect

[Java architecture & design concepts](#)
[interview Q&As with diagrams](#) | [What should](#)



[be a typical Java EE architecture?](#)

Senior Java developers must have a good handle on

[open all](#) | [close all](#)

- [Best Practice \(6\)](#)
- [Coding \(26\)](#)
- [Concurrency \(6\)](#)
- [Design Concepts \(7\)](#)
- [Design Patterns \(11\)](#)
- [Exception Handling \(3\)](#)
- [Java Debugging \(21\)](#)
- [Judging Experience In](#)
- [Low Latency \(7\)](#)
- [Memory Management](#)
- [Performance \(13\)](#)
- [QoS \(8\)](#)
- [Scalability \(4\)](#)
- [SDLC \(6\)](#)
- [Security \(13\)](#)
- [Transaction Management](#)

If you were to implement the equals(...) and hashCode(...) methods:

```

1 public final class Pet {
2     int id;
3     String name;
4
5     @Override
6     public boolean equals(Object that){
7         if ( this == that ) return true;
8
9         if ( !(that instanceof Pet) ){
10             return false;
11         }
12
13         Pet pet = (Pet)that;

```

80+ step by step Java Tutorials

[open all](#) | [close all](#)

- [Setting up Tutorial \(6\)](#)
- [Tutorial - Diagnosis \(2\)](#)
- [Akka Tutorial \(9\)](#)
- [Core Java Tutorials \(2\)](#)
- [Hadoop & Spark Tuto](#)
- [JEE Tutorials \(19\)](#)
- [Scala Tutorials \(1\)](#)

```

14     return this.id == pet.id && this != nul
15     }
16
17     @Override
18     public int hashCode( ) {
19         int hash = 9;
20         hash = (31 * hash) + id;
21         hash = (31 * hash) + (null == name ? 0 :
22         return hash;
23     }
24 }
25

```

- [Spring & Hibernate Ti](#)
- [Tools Tutorials \(19\)](#)
- [Other Tutorials \(45\)](#)

You can learn more at [“Sorting objects in Java interview Q&As”](#)

Q2. What happens when you run the following code?

```

1 Boolean b1 = new Boolean(false);
2 Boolean b2 = Boolean.FALSE;
3
4 if(b1 == b2) {
5     System.out.println("Equal");
6 }
7 else{
8     System.out.println("Not Equal");
9 }
10

```

A2. Prints “Not Equal”.

The == is a shallow comparison that only compares the references. The references are not equal. If you want to print “Equal”, perform a deeper comparison as shown below, which compares the values.

```

1
2 If (b1.equals(b2)){
3     System.out.println("Equal");//gets printed
4 }
5 else {
6     System.out.println("Not Equal");
7 }
8

```

Or, you need to take advantage of the **flyweight design pattern** that reuses objects.

```

1 Boolean b1 = Boolean.valueOf("false"); // create
2 Boolean b2 = Boolean.FALSE; //points to the same

```

Preparing for Java written & coding tests

[open all](#) | [close all](#)

- [◆ Complete the given](#)
- [Can you write code? \(](#)
- [Converting from A to I](#)
- [Designing your classe](#)
- [Java Data Structures](#)
- [Passing the unit tests](#)
- [What is wrong with th](#)
- [Writing Code Home A](#)
- [Written Test Core Jav](#)
- [Written Test JEE \(1\)](#)

How good are your...to go places?

[open all](#) | [close all](#)

- [Career Making Know-](#)
- [Job Hunting & Resum](#)

3

or

```
1 Boolean b1 = Boolean.valueOf("false"); // create
2 Boolean b2 = Boolean.valueOf("false"); //points to
3
```

Q3. Can you discuss the output of the following code?

```
1
2 public class PrimitiveAndObjectEquals {
3
4     public static void main(String[] args) {
5         int a = 5;
6         int b = 5;
7
8         Integer c = new Integer(5);
9         Integer d = new Integer(5);
10
11        if (a == b) { //Line 1
12            System.out.println("primitives a and b are ==");
13        }
14
15        if (c == d) { //Line 2
16            System.out.println("Objects c and d are ==");
17        }
18
19        if (c.equals(d)) { //Line 3
20            System.out.println("Objects c and d are equals()");
21        }
22
23        if (a == d) { //Line 4
24            System.out.println("Primitive a and Object d are == due to auto unboxing");
25        }
26    }
27 }
28 }
```

A3. Output is:

```
1
2 primitives a and b are ==
3 Objects c and d are equals()
4 Primitive a and Object d are == due to auto unboxing
5
```

1) Line 1 is printed as both a and b are primitive data types, and primitives are compared with == as they don't have an equals() method.

2) Line 2 will not get printed as they are comparing the object references (shallow comparison). Line 3 will get printed as they are comparing the actual values (deeper comparison).

3) Line 4 is printed because the object reference "d" is auto-unboxed to a primitive int value and then compared with the primitive reference "a". This also illustrates a hidden chance of a **NullPointerException** being thrown if the reference "d" were to be null.

Q4. Can you discuss the output of the following code?

```

1 public class EnumEquals {
2
3     public enum Action {START, STOP, CONTINUE}
4
5     private static Action action = Action.STOP;
6
7     public static void main(String[] args) {
8
9         if(Action.STOP == action){
10             System.out.println("Enumerations can be compared to ==.");
11         }
12
13         if(Action.STOP.equals(action)){
14             System.out.println("Enumerations can be compared to equals() also.");
15         }
16     }
17 }
18

```

A4. Output is:

```

1
2 Enumerations can be compared to ==.
3 Enumerations can be compared to equals() also.
4

```


The best practice is to use the referential == for enums.

Q5. Explain the statement Java is always pass by value?

A5. Other languages use pass-by-reference or pass-by-pointer. But in Java, no matter what type of argument (i.e. a primitive variable or an object reference) you pass, the corresponding parameter will get a copy of that data, which is exactly how pass-by-value (i.e. copy-by-value) works. Even though the definition is quite straight forward, the way the


primitives and object references behave when passed by value, will be different.

For example, If the passed in argument was a primitive value like int, char, etc, the passed in primitive value is copied to the method parameter. Modifying the copied parameter will not modify the original primitive value.



pass-by-value primitive variables like int, long, etc

On the contrary, if the passed in argument was an object reference, the passed in reference is copied to the method parameter. The copied reference will still be pointing to the same object. So if you modify the object value through the copied reference, the original object will be modified.



pass by value for objects like int[], Pet, Car, etc

Q6. The value of Point p before the following method calls is (10,20). What will be the value of Point p after executing the following method calls?

Scenario 1:

```
1 static void mutatePoint(Point p) {  
2     p.x = 50;  
3     p.y=100;  
4 }  
5
```

Scenario 2:

```
1 static void mutatePoint(Point p) {  
2     p = new Point(50,100);  
3 }
```

A6.

Scenario 1:


Point p = (50,100), as the copied reference will still be pointing and modifying the original Point (10,20) object through the mutatePoint() method.

Scenario 2:

Point p = (10,20), as the copied reference will be creating and pointing to the newly created Point (50, 100) object.

Q7. If there is a source array list with 15MB of data, and then you create a new target empty array list and copy the source to target with target.addAll(source). How much memory will be consumed after invoking the addAll(...) method?

A7. The memory will still be 15MB because of “**pass-by-value**” where new objects are not created when addAll(...) is invoked. Only the references are copied, but the copied references will still be pointing to the source list objects. For example,



Java is pass by value

```

1
2 package com.test;
3
4 import java.util.ArrayList;
5 import java.util.Arrays;
6 import java.util.List;
7
8 public class PassByReference {
9
10
11     public static void main(String[] args) {
12         List<String> source = Arrays.asList("a", "b", "c", "d", "e");
13         List<String> target = new ArrayList<>();
14         target.addAll(source);
15         //memory will still be 15MB, why?
16         System.out.println(source.get(0) == target.get(0));
17         //This is because source and target both point to the same object in memory
18         //No new objects are created by addAll()
19         //Only the references are copied
20     }
21 }
22
23
24
25
26
27
28
29

```

Popular Posts

♦ 11 Spring boot interview questions & answers

857 views

♦ Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers

825 views

18 Java scenarios based interview Questions and Answers

447 views

001A: ♦ 7+ Java integration styles & patterns

interview questions & answers

401 views

♦ 7 Java debugging interview questions & answers

311 views

♦ 10 ERD (Entity-Relationship Diagrams) Interview Questions and Answers

302 views

01b: ♦ 13 Spring basics Q8 – Q13 interview questions & answers

292 views

01: ♦ 15 Ice breaker questions asked 90% of the time in Java job interviews with hints

286 views

♦ Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers

263 views

8 Git Source control system interview questions & answers

215 views

Bio

Latest Posts



Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job

interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.

< ♦ 5 Java Object class methods interview questions & answers

01: ♦ ♥ 17 Java overview interview questions and answers >

Posted in Objects

Tags: Core Java FAQs, Java/JEE FAQs, Novice FAQs

4 comments on “♦♥ Object equals Vs == and pass by reference Vs value”



Rishi Raj says:

February 22, 2016 at 4:10 pm

Hi ArulKumaran,
hashCode() and equals() are overridden in Integer. Also hashCode() returns same value for equal-valued Integer objects, and equals() compares “value” member of Integer objects. Then, why c == d does not come out to be true? Where and why is it established that c is not going to be equal to d – in hashCode() or in equals()?

[Reply](#)



Arulkumaran Kumaraswamipillai says:

February 22, 2016 at 8:13 pm

Hi Rishi,

If you create c & d as shown below

```
Integer c = new Integer(5);  
Integer d = new Integer(5);
```

Then c & d are NOT “==”, but equals().

If you create it as shown below then:

```
Integer c = Integer.valueOf(5);  
Integer d = Integer.valueOf(5);
```

Both “==” and equals() will return true. This is because the c & d will be pointing to the same single object. The references are ==, and so are the values (i.e. equals()).

[Reply](#)



Antonio Gil says:

February 20, 2016 at 9:25 am

I think your tutorials are great. Love your approach to java.

[Reply](#)



Arulkumaran Kumaraswamipillai says:

February 20, 2016 at 10:37 am

Thanks.

[Reply](#)

Leave a Reply

Logged in as geethika. [Log out?](#)

Comment

Empowers you to open more doors, and fast-track

Technical Know Hows

☀ [Java generics in no time](#) ☀ [Top 6 tips to transforming your thinking from OOP to FP](#) ☀ [How does a HashMap internally work? What is a hashing function?](#)

☀ [10+ Java String class interview Q&As](#) ☀ [Java auto un/boxing benefits & caveats](#) ☀ [Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect](#)

Non-Technical Know Hows

☀ [6 Aspects that can motivate you to fast-track your career & go places](#) ☀ [Are you reinventing yourself as a Java developer?](#) ☀ [8 tips to safeguard your Java career against offshoring](#) ☀ [My top 5 career mistakes](#)

Prepare to succeed

☀ [Turn readers of your Java CV go from “Blah blah” to “Wow”?](#) ☀ [How to prepare for Java job interviews?](#) ☀ [16 Technical Key Areas](#) ☀ [How to choose from multiple Java job offers?](#)

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.

