

[Home](#) › [Interview](#) › [Other Interview Q&A for Java Developers](#) › [JavaScript Interview Q&A](#) › [JavaScript Top Interview Q&A](#) › ♥ Q1 – Q10 JavaScript Interview Questions & Answers on variable scopes & context

♥ Q1 – Q10 JavaScript Interview Questions & Answers on variable scopes & context

Posted on [July 27, 2015](#) by [Arulkumaran Kumaraswamipillai](#)

You can try the code samples in this JavaScript interview questions and answers as follows:

1) In Goggle chrome or FireFox browser, you can bring up the developer tool with the “F12” on windows. You can also get to via the browser menu.

2) You can go to “<http://jsfiddle.net/>” on a browser. To get console.log(...) outputs, add

“<https://getfirebug.com/firebug-lite-debug.js>” to the “External Resources” on the LHS menu if using FireFox.

600+ Full Stack Java Interview Questions Answered ♥Free ♦FAQs [Mouse Hover for full title text]

[open all](#) | [close all](#)

- ☒ [Ice Breaker Interview](#)
- ☒ [Core Java Interview C](#)
- ☒ [JEE Interview Q&A \(3](#)
- ☒ [Pressed for time? Jav](#)
- ☒ [SQL, XML, UML, JSC](#)
- ☒ [Hadoop & BigData Int](#)
- ☒ [Java Architecture Inte](#)
- ☒ [Scala Interview Q&As](#)
- ☒ [Spring, Hibernate, & I](#)
- ☒ [Testing & Profiling/Sa](#)
- ☒ [Other Interview Q&A f](#)
- ☒ [Finance Domain In](#)
- ☒ [FIX Interview Q&A](#)
- ☒ [Groovy Interview C](#)
- ☒ [JavaScript Interview](#)
- ☒ [JavaScript Top I](#)
- ☒ [♥ Q1 – Q10 J](#)
- ☒ [♦ Q11 – Q20](#)
- ☒ [♦ Q21 – Q30](#)

Q1. Can you list which variables are accessible without any errors in locations marked **//1**, **//2**, **//3**, and **//4** in the code shown below?

```

1  var var1 = "I am var1"
2
3  function a() {
4      var var2 = "I am var2"
5      var3 = "I am var3"
6
7      function b() {
8          var var4 = "I am var4"
9          // 2 - inside function b()
10     }
11
12     if(var2){
13         var var5 = "I am var5"
14         // 3 inside block
15     }
16
17     // 1 inside function a()
18
19     b()//invoking function b()
20 }
21
22 a(); //invoking function a()
23
24 // 4 outside
25

```

A1. It is important to understand global variables and functional variables.

//1

1. var1 is accessible as it is defined in a global context outside the function. The “this” variable points to the window object of the browser window. Even if it is defined with “var” keyword.

2. var2 is locally defined within the function a(), and is accessible.

3. var3 is accessible as it is defined within function a(), but var3 is globally accessible outside as well as it is defined without the “var” keyword. var3 is a global variable. This is bad.

[Q31 – Q37 .](#)
[JavaScript mi](#)
[JavaScript Vs Ja](#)
[Unix Interview Q&A](#)
[Free Java Interview](#)

16 Technical Key Areas

[open all](#) | [close all](#)

- [Best Practice \(6\)](#)
- [Coding \(26\)](#)
- [Concurrency \(6\)](#)
- [Design Concepts \(7\)](#)
- [Design Patterns \(11\)](#)
- [Exception Handling \(3\)](#)
- [Java Debugging \(21\)](#)
- [Judging Experience \(1\)](#)
- [Low Latency \(7\)](#)
- [Memory Management \(1\)](#)
- [Performance \(13\)](#)
- [QoS \(8\)](#)
- [Scalability \(4\)](#)
- [SDLC \(6\)](#)
- [Security \(13\)](#)
- [Transaction Management \(1\)](#)

80+ step by step Java Tutorials

[open all](#) | [close all](#)

- [Setting up Tutorial \(6\)](#)
- [Tutorial - Diagnosis \(2\)](#)
- [Akka Tutorial \(9\)](#)
- [Core Java Tutorials \(2\)](#)
- [Hadoop & Spark Tuto](#)
- [JEE Tutorials \(19\)](#)
- [Scala Tutorials \(1\)](#)

4. The block variable “**var5**” is accessible as well. If it were defined with the newly introduced “set” keyword for the block only scope, it would not have been accessible.

//2

In this position the accessible variables are

1. **global variables** var1 and var3.
2. functional variables defined within “function b()” var4
3. any outer functional variables enclosing “function b()”, in this case “function a()” is enclosing “function b()”, hence var2 is accessible as well. But function a() can’t access any variables inside “function b()”.




//3

is a block scope. This is a “if” block. In this position the accessible variables are

1. **global variables** var1 and var3.
2. functional variables defined within “function a()”, i.e. var2 and var5.











//4

Only global variables var1 and var3 are accessible.

-  [Spring & Hibernate Ti](#)
-  [Tools Tutorials \(19\)](#)
-  [Other Tutorials \(45\)](#)



100+ Java pre-interview coding tests


[open all](#) | [close all](#)

-  [Can you write code? \(](#)
-  [♦ Complete the given](#)
-  [Converting from A to I](#)
-  [Designing your classe](#)
-  [Java Data Structures](#)
-  [Passing the unit tests](#)
-  [What is wrong with th](#)
-  [Writing Code Home A](#)
-  [Written Test Core Jav](#)
-  [Written Test JEE \(1\)](#)

How good are your?

[open all](#) | [close all](#)

-  [Career Making Know-](#)
-  [Job Hunting & Resum](#)




Q2. Is there a way to list all the global variables defined in the code?

A2. Yes.

```
1 Object.keys(window);
```

Output when run on Google Chrome console with F12 or Ctrl+Shift+J or More Tools -> JavaScript console.



Q3. Is there a "block level" scope in JavaScript like in other languages like Java? For example, In Java, if you define a variable within an "if" block, it is not accessible outside that block.

A3. The new “ECMAScript 2015 (ES6)” has introduced a “**let**” keyword. **let** allows you to declare variables that are limited in scope to the block, statement, or expression on which it is used. This is unlike the **var** keyword, which defines a variable globally, or locally to an entire function regardless of block scope. So, in the above code, if you had defined

```
1 if(var2){
2     let var5 = "I am var5"
3     // 3 inside block
4 }
5
```

The **var5** would have been accessible only in **//3**. The **//1** can't see it when defined with “**let**”. This keyword “**let**” is not still supported by the browsers at the time of writing. The support may be provided in the future.

Q4. Are JavaScript implicit variable “**this**” referring to the context and “scope” the same thing

A4. No. Scope is function-based, and context is object-based. In other words, scope pertains to the variable access of a function when it is invoked and is unique to each invocation. Context is always the value of the **this** keyword which is a reference to the object that “owns” the currently executing code.

If you take the above example, the code runs in the “window” object context.

```

> var var1 = "I am var1"

function a() {
  var var2 = "I am var2"
  var3 = "I am var3"

  function b() {
    var var4 = "I am var4"
    // 2 - inside function b()
    console.log("inside b(): " + this);

  }

  if(var2){
    var var5 = "I am var5"
    // 3 inside block
  }

  // 1 inside function a()
  console.log("inside a(): " + this);

  b();//invoking function b()
}

a(); //invoking function a()

// 4 outside
console.log("outside: " + this);
inside a(): [object Window]
inside b(): [object Window]
outside: [object Window]
< undefined
> |

```

"this" refers to the window object, which is a global object referring to the browser window that is open.

JavaScript Context

Q5. What do you think will be the output of the following code?

```


1  var arrayObject = ["Java", "JEE"]
2
3  var var1 = "I am var1"
4
5  function a() {
6    var var2 = "I am var2"
7    var3 = "I am var3"
8
9    function b() {
10     var var4 = "I am var4"
11     //2 - inside function b()
12     console.log("inside b(): " + this);
13   }
14
15   if(var2){
16     var var5 = "I am var5"
17     //3 inside block
18   }
19
20   //1 inside function a()
21   console.log("inside a(): " + this);
22
23   b.call(arrayObject) //invoking function b()
24   b.call(" again " + this) //invoking
25 }
26
27 this.a.call(arrayObject); //invoking function a()
28
29 // 4 outside
30 console.log("outside: " + this);

```

A5. An alternative approach to calling a function is with the “call(object)” method. It takes the object to call the function on as an argument.

```
1 this.a.call(arrayObject);
```

In the above snippet “this” refers to the object “window”. In other words, the context is “window”. The “function a()” is invoked on object “arrayObject” as the new context. Hence, within the “function a()” the implicit variable “this” points to the “arrayObject”. Even within “function b()”, the context is “arrayObject” as it was invoked with “b.call(arrayObject)”. It is the same result if you did call “b.call(” again ” + this) “. But if you had called with just “b()”, inside “function b()”, the context would be a “object window”.



JavaScript contexts

Q6. What is the difference between the .call(...) and .apply(...) methods?

A6. The difference is that **apply(argArray)** lets you invoke the function with arguments as an **array** whereas **call(arg1, arg2, arg3)** requires the parameters be listed explicitly.

call(...) and apply(...) methods of function object

```

1 var arrayObject = ["Java", "JEE"]
2
3 function a(arg1, arg2, arg3) {
4     console.log(this);
5     console.log(arg1 + " " + arg2 + " " + arg3)
6 }
7
8 a.call(arrayObject, "Hello", "Mr" , "John" ); //
9 a.apply(arrayObject, ["Hello", "Mr" , "John"]); //

```

Q7. What is the difference between undefined and null?

A7. The value of a variable with **no value** is undefined (i.e. it has been declared, but has not been initialized).

```

1 var a;
2 console.log(a) // undefined

```

Variables can be emptied by setting their value to **null**. For example, to get a variable or closure to be garbage collected to release the memory.

```

1 function doSomething(arg1) {
2     var local = "Some Text"
3
4     //a closure that has access to arg1 & local
5     return function() {
6         console.log(arg1 + " " + local);
7     }
8 }
9
10
11 var fn1 = doSomething("Printing..."); //closure
12 var fn2 = doSomething("Outputting..."); //closure
13
14 fn1(); //invoking - Printing... Some Text
15 fn2(); //invoking - Outputting... Some Text
16
17 //now clear the closure memory. Will be Garbage
18 fn1 = null;
19 fn2 = null;
20
21 fn1(); //error fn1 is not a function

```

Q8. What is the difference between “==” and “===” in JavaScript?

A8. The == operator will compare for equality after doing any necessary type conversions. The === operator will not do the conversion, so if two values are not the same type === will simply return false.


```
1 "abc" == new String("abc")    // true
2 "abc" === new String("abc")   // false
```

We are comparing a string literal with a string object. Hence “===” returns false.

Q9. How does “===” differ from “==” when checking for null or undefined?

A9.

===

```
1 if (nullRef === null) {
2     // executes this block only if null
3 }
4
5 if (undefinedRef === undefined) {
6     // executes this block only if undefined
7 }
```

==

Executes the block if the the “ref” is either null or undefined.

```
1 if (nullRef === null) {
2     // executes this block
3 }
4
5 if (undefinedRef === undefined) {
6     // executes this block
7 }
```

Q10. What is the purpose of “use strict” directive in JavaScript?

A10. Strict mode makes it easier to write “**secure**” JavaScript. Strict mode changes previously accepted “bad syntax” into real errors. For example, with strict mode you cannot use undeclared variables.

If “**use strict**” directive is declared at the top of the JavaScript file, it has a global scope. If declared within a function, it has a functional scope.

```
1 "use strict";
```

```
2 x = 3.14;           // ReferenceError. assignment to  
3 var y = 3.14;       //good
```

Key Points on JavaScript Interview Questions and Answers

1. Global variables are bad as they can conflict with third party library variable names.
2. **Functions are objects** in JavaScript as they can be nested, passed to another function, and you can invoke methods like `call(...)` and `apply(...)` on a function.
3. JavaScript has 3 scopes: **global**, **functional**, and **block**. The block scope was recently introduced.
4. Scope and context are different concepts. A context refers to an object that invokes a function with the keyword **"this"**. The "window" object is a global context. When you create an object in JavaScript, and invoke a function on that object, then "this" refers to the object that declares the function.
5. You can pass a different object to a function with the **call(...)** and **apply(...)** methods defined in the object function.

Popular Member Posts

01: ♦ 15+ Hibernate basics Q1 – Q7 interview questions & answers

1,819 views

♦ 11 Spring boot interview questions & answers

968 views

♦ Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers

855 views

01: ♦ 15 Beginner level Java multi-threading interview Q&A

548 views

001A: ♦ 7+ Java integration styles & patterns interview questions & answers

442 views

18 Java scenarios based interview Questions and Answers

418 views

♦ 7 Java debugging interview questions & answers

346 views

01b: ♦ 13 Spring basics Q8 – Q13 interview questions & answers

314 views

01: ♦ 15 Ice breaker questions asked 90% of the time in Java job interviews with hints

312 views

♦ 10 ERD (Entity-Relationship Diagrams) Interview Questions and Answers

310 views

11

Like

Share

Tweet

↑

submit

↓

reddit

3

G+1

1

Share

Bio

Latest Posts



Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. Published Java interview Q&A books via [Amazon.com](https://www.amazon.com) in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site. **945+** paid members. [join my LinkedIn Group](#) to get notified of special offers. User & expert [reviews](#).



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job



interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. Published Java interview Q&A books via [Amazon.com](https://www.amazon.com) in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site. **945+** paid members. [join my LinkedIn Group](#) to get notified of special offers. User & expert [reviews](#).

◀ Groovy method chaining for DSL explained

♦ Q11 – Q20 JavaScript Interview Q&A on “this” variable & context ▶

Posted in JavaScript Top Interview Q&A

Tags: JavaScript Interview Q&A

Empowers you to open more doors, and fast-track

Technical Know Hows

☀ [Java generics in no time](#) ☀ [Top 6 tips to transforming your thinking from OOP to FP](#) ☀ [How does a HashMap internally work? What is a hashing function?](#)

☀ [10+ Java String class interview Q&As](#) ☀ [Java auto un/boxing benefits & caveats](#) ☀ [Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect](#)

Non-Technical Know Hows

☀ [6 Aspects that can motivate you to fast-track your career & go places](#) ☀ [Are you reinventing yourself as a Java developer?](#) ☀ [8 tips to safeguard your Java career against offshoring](#) ☀ [My top 5 career mistakes](#)

Prepare to succeed

☀ [Turn readers of your Java CV go from “Blah blah” to “Wow”?](#) ☀ [How to prepare for Java job interviews?](#) ☀ [16 Technical Key Areas](#) ☀ [How to choose from multiple Java job offers?](#)

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.