

Industrial strength Java/JEE Career Companion to open more doors

search here ...

Go

[Home](#)[Java FAQs](#)[600+ Java Q&As](#)[Career](#)[Tutorials](#)[Member](#)[Why?](#)[Can u Debug?](#)[Java 8 ready?](#)[Top X](#)[Productivity Tools](#)[Judging Experience?](#)[Home](#) › [member-paid](#) › 07: When to use a ServletContextListener in Java EE?

Understanding ServletContext and ServletContextListener with examples

07: When to use a ServletContextListener in Java EE? Understanding ServletContext and ServletContextListener with examples

Posted on [October 27, 2014](#) by [Arulkumaran Kumaraswamipillai](#) — No[Comments](#) ↓

A **ServletContext** object refers to the whole web application, whilst a *ServletConfig* is for a Servlet. Once an application is deployed onto the web application, **ServletContextListener** may be configured using annotations or the configuration file named **web.xml**. A *ServletContext* object is initialized once while a web application is being deployed, and this object can be accessed from anywhere within the same web application.

600+ Full Stack Java/JEE Interview Q&As ♥Free ♦FAQs

[open all](#) | [close all](#)[+ Ice Breaker Interview](#)[+ Core Java Interview C](#)[+ JEE Interview Q&A \(3](#)[+ JEE Overview \(2\)](#)[+ Web basics \(8\)](#)[+ 01: ♦ 12 Web ba](#)[+ 02: HTTP basics](#)[+ 03: Servlet inter](#)[+ 04: JSP overview](#)[+ 05: Web patterns:](#)[+ 06: ♦ MVC0, MV](#)[+ 07: When to use](#)[+ 08: Web.xml inte](#)[+ WebService \(11\)](#)[+ JPA \(2\)](#)[+ JTA \(1\)](#)[+ JDBC \(4\)](#)[+ JMS \(5\)](#)[+ JMX \(3\)](#)[+ JNDI and LDAP \(1\)](#)[+ Pressed for time? Jav](#)

Q1 What are servlet lifecycle events?

A1 Servlet lifecycle events work like the Swing events. Any listener interested in observing the *ServletContext* lifecycle can implement the *ServletContextListener* interface and in the *ServletContext* attribute lifecycle can implement the *ServletContextAttributesListener* interface. The session listener model is similar to the *ServletContext* listener model (Refer Servlet spec 2.3 or later). Servlet contexts' and sessions' listener objects are notified when servlet contexts and sessions are initialized and destroyed, as well as when attributes are added or removed from a context or session.

Example 1: You can declare a listener in the **web.xml** deployment descriptor as follows:

```

1 <listener>
2   <listener-class>com.MyJDBCConnectionManager
3 </listener>
4

```

You can create a custom listener class as shown below:

```

1 public class MyJDBCConnectionManager implements
2
3     public void contextInitialized(ServletContextEvent e) {
4         Connection con = // create connection
5         event.getServletContext().setAttribute("c
6     }
7
8     public void contextDestroyed(ServletContextEvent e) {
9         Connection con = (Connection) e.getServlet
10        try { con.close(); } catch (SQLException
11    }
12 }
13

```

Example 2: bootstrapping spring into RESTEasy framework

A typical example where a ***ServletContextListener*** is used is in bootstrapping a spring ***applicationContext.xml*** file into a web application that is using RESTEasy for RESTful web services. For example, if under `com.mytutorial` you are having an ***applicationContext.xml***, which defines the beans for web service, POJO service, and dao layers.

- [SQL, XML, UML, JSC](#)
- [Hadoop & BigData Int](#)
- [Java Architecture Inte](#)
- [Scala Interview Q&As](#)
- [Spring, Hibernate, & I](#)
- [Testing & Profiling/Sa](#)
- [Other Interview Q&A 1](#)
- [Free Java Interview](#)

16 Technical Key Areas

[open all](#) | [close all](#)

- [Best Practice \(6\)](#)
- [Coding \(26\)](#)
- [Concurrency \(6\)](#)
- [Design Concepts \(7\)](#)
- [Design Patterns \(11\)](#)
- [Exception Handling \(3\)](#)
- [Java Debugging \(21\)](#)
- [Judging Experience \(1\)](#)
- [Low Latency \(7\)](#)
- [Memory Management \(1\)](#)
- [Performance \(13\)](#)
- [QoS \(8\)](#)
- [Scalability \(4\)](#)
- [SDLC \(6\)](#)
- [Security \(13\)](#)
- [Transaction Management \(1\)](#)

80+ step by step Java Tutorials

[open all](#) | [close all](#)

- [Setting up Tutorial \(6\)](#)
- [Tutorial - Diagnosis \(2\)](#)
- [Akka Tutorial \(9\)](#)
- [Core Java Tutorials \(2\)](#)

```

1 <?xml version="1.0" encoding="UTF-8"?>
2 <beans xmlns="http://www.springframework.org/sch
3   xmlns:aop="http://www.springframework.org/sc
4   xmlns:xsi="http://www.w3.org/2001/XMLSchema-
5   xsi:schemaLocation="http://www.springframewo
6   http://www.springframewo
7
8   <bean id="simpleRestWeb" class="com.mytutor
9   &nbsp;
10  ....
11 </beans>
12

```

The above spring context file needs to be bootstrapped via **web.xml** file when the web app is being deployed. This is accomplished via

org.jboss.resteasy.plugins.spring.**SpringContextLoaderListe**
ner for JBoss RESTEasy framework. This **SpringContextLoaderListener** is nothing but an implementation of **ServletContextListener**. In the web.xml file you will be defining

```

1 <!DOCTYPE web-app PUBLIC
2   "-//Sun Microsystems, Inc.//DTD Web Application
3   "http://java.sun.com/dtd/web-app_2_3.dtd" >
4
5 <web-app>
6   <display-name>Archetype Created Web Application
7
8
9   <context-param>
10    <param-name>contextConfigLocation</param-name>
11    <param-value>classpath:/com/mytutorial/applica
12  </context-param>
13
14  <listener>
15    <listener-class>org.jboss.resteasy.plugins.ser
16  </listener>
17  <listener>
18    <listener-class>org.jboss.resteasy.plugins.spr
19  </listener>
20
21
22  <servlet>
23    <servlet-name>resteasy-simple</servlet-name>
24    <servlet-class>org.jboss.resteasy.plugins.serv
25  </servlet>
26
27  <servlet-mapping>
28    <servlet-name>resteasy-simple</servlet-name>
29    <url-pattern>/rest/*</url-pattern>
30  </servlet-mapping>
31
32 </web-app>
33

```

- [Hadoop & Spark Tuto](#)
- [JEE Tutorials \(19\)](#)
- [Scala Tutorials \(1\)](#)
- [Spring & Hibernate Ti](#)
- [Tools Tutorials \(19\)](#)
- [Other Tutorials \(45\)](#)

100+ Java pre-interview coding tests

[open all](#) | [close all](#)

- [Can you write code? \(](#)
- [♦ Complete the given](#)
- [Converting from A to I](#)
- [Designing your classe](#)
- [Java Data Structures](#)
- [Passing the unit tests](#)
- [What is wrong with th](#)
- [Writing Code Home A](#)
- [Written Test Core Jav](#)
- [Written Test JEE \(1\)](#)

How good are your?

[open all](#) | [close all](#)

- [Career Making Know-](#)
- [Job Hunting & Resur](#)

Take note of the “*contextConfigLocation*” param definition where the spring context location is defined, and *SpringContextLoaderListener* is used to bootstrap this during deployment of the war file. Similar *ServletContextListener* based approach is used by other web frameworks for bootstrapping.

Example 3: copying a bean from spring context into servlet context for Yammer metrics

Another scenario that I came across recently where I had to provide my own implementation of the ***ServletContextListener*** when using yammer metrics to provide web based monitoring. If you register yammer via your spring *applicationContext.xml* file as shown below

```
1 <?xml version="1.0" encoding="UTF-8"?>
2 <beans xmlns="http://www.springframework.org/sch
3     xmlns:aop="http://www.springframework.org/sc
4     xmlns:metrics="http://www.yammer.com/schema/
5     xmlns:xsi="http://www.w3.org/2001/XMLSchema-
6     xsi:schemaLocation="http://www.springframewo
7                         http://www.springframewo
8                         http://www.yammer.com/sc
9
10     <metrics:metrics-registry id="rest-metrics"/
11     <metrics:health-check-registry id="rest-heal
12     <metrics:annotation-driven metrics-registry=
13
14     <bean id="simpleRestWeb" class="com.mytutori
15
16 </beans>
17
```

Now, I needed to get the ***MetricRegistry*** out of the Spring context and then put it on to the Servlet context so that the admin servlet that comes with Yammer can find it to report metrics via web URL like <http://localhost:8080/tutorial/admin>. Here is an implementation of *ServletContextListener*.

```
1 package com.mytutorial;
2
3 import javax.servlet.ServletContext;
4 import javax.servlet.ServletContextEvent;
5 import javax.servlet.ServletContextListener;
6
7 import org.springframework.web.context.WebApplic
8 import org.springframework.web.context.support.W
9
```

```

10 import com.yammer.metrics.core.MetricsRegistry;
11 import com.yammer.metrics.reporting.MetricsServlet
12
13 /**
14  * Application Lifecycle Listener for Metrics.
15  *
16  * I need to fetch the MetricsRegistry from the ServletContext
17  * for the yammer admin-servlet to be able to fetch metrics
18  */
19 */
20 public class MetricsContextLoaderListener implements ServletContextListener {
21
22     public MetricsContextLoaderListener() {
23
24     }
25
26     public void contextInitialized(ServletContextEvent event) {
27         ServletContext context = event.getServletContext();
28         MetricsRegistry metricsRegistry = getMetricsRegistry(context);
29         setMetricsRegistry(metricsRegistry, context);
30     }
31
32     public void contextDestroyed(ServletContextEvent event) {
33
34     }
35
36     protected MetricsRegistry getMetricsRegistry(ServletContext context) {
37         WebApplicationContext springContext = WebApplicationContextUtils.getWebApplicationContext(context);
38         return springContext.getBean(MetricsRegistry.class);
39     }
40
41     protected void setMetricsRegistry(MetricsRegistry metricsRegistry, ServletContext context) {
42         context.setAttribute(MetricsServlet.REGISTRY, metricsRegistry);
43     }
44 }
45
46
47
48

```

You can now define this listener and Yammer metrics servlet via the web.xml file

```

1 <!DOCTYPE web-app PUBLIC
2 "-//Sun Microsystems, Inc.//DTD Web Application
3 "http://java.sun.com/dtd/web-app_2_3.dtd" >
4
5 <web-app>
6   <display-name>Archetype Created Web Application</display-name>
7
8   <context-param>
9     <param-name>contextConfigLocation</param-name>
10    <param-value>classpath:/com/mytutorial/applica
11  </context-param>
12
13   <context-param>
14     <param-name>resteasy.servlet.mapping.prefix</param-name>
15     <param-value>/rest</param-value>
16   </context-param>
17
18
19

```

```
20 <listener>
21   <listener-class>org.jboss.resteasy.plugins.serv
22 </listener>
23 <listener>
24   <listener-class>org.jboss.resteasy.plugins.spr
25 </listener>
26 <listener>
27   <listener-class>com.mytutorial.MetricsContext
28 </listener>
29
30 <servlet>
31   <servlet-name>resteasy-simple</servlet-name>
32   <servlet-class>org.jboss.resteasy.plugins.serv
33 </servlet>
34 <servlet>
35   <servlet-name>admin-servlet</servlet-name>
36   <servlet-class>com.yammer.metrics.reporting.Ad
37   <load-on-startup>2</load-on-startup>
38 </servlet>
39
40
41 <servlet-mapping>
42   <servlet-name>resteasy-simple</servlet-name>
43   <url-pattern>/rest/*</url-pattern>
44 </servlet-mapping>
45 <servlet-mapping>
46   <servlet-name>admin-servlet</servlet-name>
47   <url-pattern>/admin/*</url-pattern>
48 </servlet-mapping>
49 </web-app>
50
```

Popular Posts

♦ 11 Spring boot interview questions & answers

825 views

♦ Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers

766 views

18 Java scenarios based interview Questions and Answers

400 views

001A: ♦ 7+ Java integration styles & patterns interview questions & answers

388 views

01b: ♦ 13 Spring basics Q8 – Q13 interview questions & answers

295 views

♦ 7 Java debugging interview questions & answers

293 views

01: ♦ 15 Ice breaker questions asked 90% of the time in Java job interviews with hints

285 views

♦ 10 ERD (Entity-Relationship Diagrams) Interview Questions and Answers

279 views

♦ Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers

239 views

001B: ♦ Java architecture & design concepts interview questions & answers

201 views

Bio

Latest Posts



Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.**945+** paid members. [join my LinkedIn Group](#). [Reviews](#)



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.**945+** paid members. [join my LinkedIn Group](#). [Reviews](#)

◀ RESTful Web Service Tutorial with RESTEasy, Spring, Maven, and Eclipse

♥ 01: Drools tutorial with Maven and Eclipse ▶

Posted in member-paid, Web basics

Leave a Reply

Logged in as geethika. [Log out?](#)

Comment

Post Comment

Empowers you to open more doors, and fast-track

Technical Know Hows

☀ [Java generics in no time](#) ☀ [Top 6 tips to transforming your thinking from OOP to FP](#) ☀ [How does a HashMap internally work? What is a hashing function?](#)
☀ [10+ Java String class interview Q&As](#) ☀ [Java auto un/boxing benefits & caveats](#) ☀ [Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect](#)

Non-Technical Know Hows

☀ [6 Aspects that can motivate you to fast-track your career & go places](#) ☀ [Are you reinventing yourself as a Java developer?](#) ☀ [8 tips to safeguard your Java career against offshoring](#) ☀ [My top 5 career mistakes](#)

Prepare to succeed

☀ [Turn readers of your Java CV go from “Blah blah” to “Wow”?](#) ☀ [How to prepare for Java job interviews?](#) ☀ [16 Technical Key Areas](#) ☀ [How to choose from multiple Java job offers?](#)

Select Category ▼

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.