

Industrial strength Java/JEE Career Companion to open more doors

[Home](#)
[Java FAQs](#)
[600+ Java Q&As](#)
[Career](#)
[Tutorials](#)
[Member](#)
[Why?](#)
[Can u Debug?](#)
[Java 8 ready?](#)
[Top X](#)
[Productivity Tools](#)
[Judging Experience?](#)

[Home](#) › [Interview](#) › [Pressed for time? Java/JEE Interview FAQs](#) › [Hibernate Job Interview Essentials](#) › 8 JPA interview questions and answers

8 JPA interview questions and answers

Posted on [August 27, 2014](#) by [Arulkumaran Kumaraswamipillai](#)


Q1. What is a JPA? What are its key components?

A1. The process of mapping Java objects to database tables and vice versa is called “Object-relational mapping” (ORM). The Java Persistence API provides Java developers with an object/relational mapping (ORM) facility for managing relational data in Java applications. JPA is a specification and several implementations are available like EJB, JDO, Hibernate, and Toplink. Using JPA and relevant implementation like Hibernate, developers can map, store, update and retrieve data from relational databases to Java objects and vice versa.

600+ Full Stack Java/JEE Interview Q&As ♥Free ♦FAQs

[open all](#) | [close all](#)

- [+ Ice Breaker Interview](#)
- [+ Core Java Interview C](#)
- [+ JEE Interview Q&A \(3](#)
- [+ JEE Overview \(2\)](#)
- [+ Web basics \(8\)](#)
- [+ WebService \(11\)](#)
- [+ JPA \(2\)](#)
- [+ 10: Spring, Java](#)
- [+ 8 JPA interview c](#)
- [+ JTA \(1\)](#)
- [+ JDBC \(4\)](#)
- [+ JMS \(5\)](#)
- [+ JMX \(3\)](#)
- [+ JNDI and LDAP \(1\)](#)
- [+ Pressed for time? Jav](#)
- [+ SQL, XML, UML, JSC](#)
- [+ Hadoop & BigData Int](#)
- [+ Java Architecture Inte](#)
- [+ Scala Interview Q&As](#)
- [+ Spring, Hibernate, & I](#)
- [+ Testing & Profiling/Sa](#)



[Other Interview Q&A 1](#)
[Free Java Interview](#)

16 Technical Key Areas

[open all](#) | [close all](#)

- [Best Practice \(6\)](#)
- [Coding \(26\)](#)
- [Concurrency \(6\)](#)
- [Design Concepts \(7\)](#)
- [Design Patterns \(11\)](#)
- [Exception Handling \(3\)](#)
- [Java Debugging \(21\)](#)
- [Judging Experience \(1\)](#)
- [Low Latency \(7\)](#)
- [Memory Management \(1\)](#)
- [Performance \(13\)](#)
- [QoS \(8\)](#)
- [Scalability \(4\)](#)
- [SDLC \(6\)](#)
- [Security \(13\)](#)
- [Transaction Management \(1\)](#)

Q2. What is the difference between `hibernate.cfg.xml` and `persistence.xml`?

A2. If you are using Hibernate's proprietary API, you'll need the `hibernate.cfg.xml`. If you are using JPA i.e. Hibernate **EntityManager**, you'll need the **`persistence.xml`**. You will not need both as you will be using either Hibernate proprietary API or JPA. However, if you had used Hibernate Proprietary API using `hibernate.cfg.xml` with `hbm.xml` mapping files, and now wanted to start using JPA, you can reuse the existing configuration files by referencing the `hibernate.cfg.xml` in the `persistence.xml` in the `hibernate.ejb.cfgfile` property and reuse the existing `hbm.xml` files. In a long run, migrate `hbm.xml` files to JPA annotations.

Q3. What are the 3 artifacts required to implement a JPA compliant project?

A3.

1. An entity class
2. A `persistence.xml` file

80+ step by step Java Tutorials

[open all](#) | [close all](#)

- [Setting up Tutorial \(6\)](#)
- [Tutorial - Diagnosis \(2\)](#)
- [Akka Tutorial \(9\)](#)
- [Core Java Tutorials \(2\)](#)
- [Hadoop & Spark Tutorial \(1\)](#)
- [JEE Tutorials \(19\)](#)
- [Scala Tutorials \(1\)](#)
- [Spring & Hibernate Tutorial \(1\)](#)
- [Tools Tutorials \(19\)](#)
- [Other Tutorials \(45\)](#)

3. An interface which you will use to perform CRUD operations like insert, update, or find an entity

Q4. What is an EntityManagerFactory and a Persistence unit?

A4. The **EntityManager** is created by the **EntityManagerFactory** which is configured by the persistence unit. The persistence unit is described via the file “**persistence.xml**” in the directory META-INF in the source folder. It defines a set of entities which are logically connected and the connection properties as shown below.

persistence.xml

```

1 <persistence version="1.0"
2   xmlns="http://java.sun.com/xml/ns/persistence"
3   xsi:schemaLocation="http://java.sun.com/xml/ns/
4
5   <persistence-unit name="myapp-server" transact
6
7   <provider>org.hibernate.ejb.HibernatePersist
8
9   <!-- import other mapping files if any -->
10  <mapping-file>META-INF/myApp2.xml</mapping-f
11
12  <class>com.mycompany.myapp.Person</class>
13
14  <exclude-unlisted-classes>true</exclude-unli
15
16  <properties>
17    <property name="javax.persistence.jdbc.d
18    <property name="javax.persistence.jdbc.u
19    <property name="javax.persistence.jdbc.u
20    <property name="javax.persistence.jdbc.p
21  </properties>
22
23  </persistence-unit>
24 </persistence>
25

```

Usually, JPA defines a persistence unit through the META-INF/persistence.xml file. Starting with Spring 3.1, this XML file is no longer necessary – the **LocalContainerEntityManagerFactoryBean** now supports a ‘packagesToScan’ property where the packages to scan for @Entity classes can be specified. The snippet below shows how you can bootstrap with or without persistence.xml.

```
1 //...
```

100+ Java pre-interview coding tests

[open all](#) | [close all](#)

- [Can you write code? \(1\)](#)
- [Complete the given code](#)
- [Converting from A to B](#)
- [Designing your class](#)
- [Java Data Structures](#)
- [Passing the unit tests](#)
- [What is wrong with this code?](#)
- [Writing Code Home A](#)
- [Written Test Core Java](#)
- [Written Test JEE \(1\)](#)

How good are your?

[open all](#) | [close all](#)

- [Career Making Knowledge](#)
- [Job Hunting & Resumes](#)

```
2 @Configuration
3 @PropertySource(value =
4 {"classpath:/common/jpa.properties"
5 })
6 @EnableTransactionManagement
7 public class JpaConfig
8 {
9     @Value("${my_app_common_jpa_showSql:false}")
10     private Boolean showSql;
11
12     @Value("${my_app_common_jpa_hibernateDialect}")
13     private String hibernateDialect;
14
15     @Value("${my_app_common_jpa_generateStatistics}")
16     private Boolean generateStatistics;
17
18     @Value("${my_app_common_jpa_generateDdl:false}")
19     private Boolean generateDdl;
20
21     @Value("${my_app_common_jpa_databasePlatform}")
22     private String databasePlatform;
23
24     @Resource(name = "myAppDataSource")
25     private DataSource dataSource;
26
27     @Bean
28     public Map<String, Object> jpaProperties()
29     {
30         Map<String, Object> props = new HashMap<
31         props.put("hibernate.dialect", hibernate
32         props.put("hibernate.generate_statistics
33
34         return props;
35     }
36
37     @Bean
38     public JpaVendorAdapter jpaVendorAdapter()
39     {
40         HibernateJpaVendorAdapter hibernateJpaVe
41         hibernateJpaVendorAdapter.setShowSql(sho
42         hibernateJpaVendorAdapter.setGenerateDdl
43         hibernateJpaVendorAdapter.setDatabasePla
44
45         return hibernateJpaVendorAdapter;
46     }
47
48     @Bean
49     public PlatformTransactionManager transactio
50     {
51         return new JpaTransactionManager(entityM
52     }
53
54     @Bean
55     public EntityManagerFactory entityManagerFac
56     {
57         LocalContainerEntityManagerFactoryBean l
58         lef.setDataSource(dataSource);
59         lef.setJpaPropertyMap(this.jpaProperties
60         lef.setJpaVendorAdapter(this.jpaVendorAd
61         lef.setPersistenceXmlLocation("META-INF/
62         lef.afterPropertiesSet();
63         return lef.getObject();
64     }
65
66     @Bean
67     public PersistenceExceptionTranslationPostPr
```

```

68     {
69         return new PersistenceExceptionTranslati
70     }
71
72     @Bean
73     public HibernateExceptionTranslator hibernat
74     {
75         return new HibernateExceptionTranslator(
76     }
77 }
78

```

The **jpa.properties** can be defined as shown below.

```

1 # properties for JPA
2 my_app_common_jpa_showSql=false
3 my_app_common_jpa_generateDdl=false
4
5 my_app_common_jpa_databasePlatform=SYBASE
6 my_app_common_jpa_hibernateDialect=org.hibernate.
7 my_app_common_jpa_generateStatistics=true
8 my_app_common_aesJndiName=java:comp/env/jdbc/my_d
9

```

Q5. What is an EntityManager?

A5. The entity manager `javax.persistence.EntityManager` provides the operations from and to the database, e.g. find objects, persists them, remove objects from the database, etc. Entities which are managed by an EntityManager will automatically propagate these changes to the database (if this happens within a commit statement). These objects are known as persistent object. If the Entity Manager is closed (via `close()`) then the managed entities are in a detached state. These are known as the detached objects. If you want synchronize them again with the database, the a Entity Manager provides the `merge()` method. Once merged, the object(s) becomes perstent objects again.

The **EntityManager** is the API of the persistence context, and an EntityManager can be injected directly in to a DAO without requiring a JPA Template. The Spring Container is capable of acting as a JPA container and of injecting the EntityManager by honoring the `@PersistenceContext` (both as field-level and a method-level annotation).

```

1 //...
2 import com.mycompany.myapplication.model.Person

```

```

3 import java.util.ArrayList;
4 import java.util.List;
5 import javax.persistence.EntityManager;
6 import javax.persistence.PersistenceContext;
7 import javax.persistence.Query;
8
9 import org.springframework.stereotype.Repository
10
11 @Repository("personDao")
12 public class PersonDaoImpl implements PersonDao
13 {
14     @PersistenceContext
15     private EntityManager em;
16
17     @Override
18     public List<Person> fetchPersonByFirstname(S
19     {
20         Query query = em.createQuery( "from Pers
21         query.setParameter("firstName", fName);
22
23         List<Person> persons = new ArrayList<Per
24         List<Person> results = query.getResultLi
25
26         return persons;
27     }
28
29     public Person find(Integer id)
30     {
31         return em.find(Person.class, id);
32     }
33 }
34

```

Q6. What is an Entity?

A6. A class which should be persisted in a database it must be annotated with javax.persistence.**Entity**. Such a class is called Entity. An instances of the class will be a row in the person table. So, the columns in the person table will be mapped to the Person java object annotated as @Entity. Here is the sample Person class.

```

1 @Entity
2 @Table(name = "person", schema = "dbo", catalog
3 @Where(clause = "inactiveFlag = 'N'")
4 @TypeDefs(
5     {@TypeDef(name = "IdColumn", typeClass = IdColumn
6     public class UnitTrustPrice implements java.io.S
7     {
8         private int id;
9         private String firstName;
10        private byte[] timestamp;
11
12        public Person(){}
13
14        @Id
15        @GeneratedValue(strategy = GenerationType.IDE
16        @Column(name = "person_id", nullable = false,
17        @Type(type = "int")
18        public int getId()

```

```
19     {
20         return this.id;
21     }
22
23     public void setId(int id)
24     {
25         this.id = id;
26     }
27
28     @Version
29     @Column(name = "timestamp", insertable = false)
30     @Generated(GenerationTime.ALWAYS)
31     public byte[] getTimestamp()
32     {
33         return this.timestamp;
34     }
35
36     public void setTimestamp(byte[] timestamp)
37     {
38         this.timestamp = timestamp;
39     }
40
41     @Column(name = "first_name", nullable = false)
42     public String getFirstName()
43     {
44         return this.firstName;
45     }
46
47     public void setFirstName(String fName)
48     {
49         this.firstName = fName;
50     }
51 }
52
```

Q7. What are the dependency jars required for a JPA application?

A7. Add relevant jar files via your Maven pom.xml file.

```
1  <!-- JPA and hibernate -->
2  <dependency>
3      <groupId>org.hibernate</groupId>
4      <artifactId>hibernate-core</artifactId>
5  </dependency>
6  <dependency>
7      <groupId>org.hibernate</groupId>
8      <artifactId>hibernate-entitymanager</artifactId>
9  </dependency>
10 <dependency>
11     <groupId>org.hibernate.javax.persistence</groupId>
12     <artifactId>hibernate-jpa-2.0-api</artifactId>
13 </dependency>
14
15 <!-- validator -->
16 <dependency>
17     <groupId>javax.validation</groupId>
18     <artifactId>validation-api</artifactId>
19 </dependency>
20
21 <dependency>
22     <groupId>org.hibernate</groupId>
```



```
23 <artifactId>hibernate-validator</artifactId>
24 </dependency>
25
```

Q8 What is difference between CrudRepository and JpaRepository interfaces in Spring Data?

A8. **JpaRepository** extends **PagingAndSortingRepository**, which in turn extends **CrudRepository**. Their main functions are:

- CrudRepository mainly provides CRUD (Create Read Update and Delete) functions.
- PagingAndSortingRepository provide methods to do pagination and sorting records.
- JpaRepository provides some JPA related method such as flushing the persistence context and delete records in a batch.

Q9. What steps are required for Spring CrudRepository to work with JPA?

A9.

Step 1: Add the jar dependency to your maven pom.xml file.

```
1 <dependency>
2   <groupId>org.springframework.data</groupId>
3   <artifactId>spring-data-jpa</artifactId>
4   <version>1.2.0-RELEASE</version>
5 </dependency>
6
```

Step 2: Define the JPA entity — that is your model class that maps to the table in the database.

```
1 //...
2 @Entity
3 @Table(name = "ReportStructure")
4 public class Node extends AbstractPersistable<Long>
5 {
6     private static final long serialVersionUID =
7
8     @ManyToOne
9     @JoinColumn(name = "ParentId", insertable =
10     private Node parent;
11
12     @OneToMany(cascade = CascadeType.ALL)
13     @JoinColumn(name = "ParentId", nullable = false)
```



```

14     private List<Node> children = new ArrayList<
15
16     @OneToOne(cascade = CascadeType.ALL)
17     @PrimaryKeyJoinColumn
18     private NodeAttributes attributes;
19
20     //....
21 }
22

```

Step 3: Define the CRUD repository by extending Spring's CrudRepository class. The CrudRepository gives you out of the box access to the following standard methods

- **delete(T entity)**, which deletes the entity given as a parameter.
- **findAll()** , which returns a list of entities.
- **findOne(ID id)**, which returns the entity using the id given a parameter as a search criteria.
- **save(T entity)** which saves the entity given as a parameter.

You can provide additional custom methods as shown below,

```

1  import org.springframework.data.jpa.repository.J
2  import org.springframework.data.jpa.repository.Q
3  import org.springframework.data.repository.CrudR
4
5  public interface NodeRepository extends CrudRepo
6  {
7      @Query("SELECT n from Node n JOIN n.key k WI
8          + "WHERE n.parent is null and n.isSo
9      List<Node> find(String clientId, Date evalDa
10
11      @Query("SELECT key from NodeKey key WHERE ke
12      List<NodeKey> fetch(String clientId);
13  }
14

```

Step 4:: The Spring config file to wire up JPA. This example uses HSQL.

```

1  <!-- Directory to scan for repository classes -->
2  <jpa:repositories
3      base-package="com.mydomain.model" />
4
5  <bean class="org.springframework.orm.jpa.JpaTran
6      id="transactionManager">
7      <property name="entityManagerFactory"
8          ref="entityManagerFactory" />
9      <property name="jpaDialect">

```

```
10     <bean class="org.springframework.orm.jpa.vendor
11     </property>
12 </bean>
13
14 <bean id="entityManagerFactory"
15     class="org.springframework.orm.jpa.LocalContainerEntityManagerFactoryBean"
16     <property name="dataSource" ref="dataSource" />
17     <property name="jpaVendorAdapter">
18         <bean class="org.springframework.orm.jpa.vendor
19             <property name="generateDdl" value="true"
20             <property name="database" value="HSQL" />
21         </bean>
22     </property>
23 </bean>
24
```

Step 5:: Use the NodeRepository for CRUD operations in the service layer.

```
1 public class ReportServiceImpl extends ReportService {
2
3     @Autowired
4     NodeRepository nodeRepository;
5
6     //...
7 }
```

Popular Posts

♦ 11 Spring boot interview questions & answers

825 views

♦ Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers

766 views

18 Java scenarios based interview Questions and Answers

400 views

001A: ♦ 7+ Java integration styles & patterns interview questions & answers

388 views

01b: ♦ 13 Spring basics Q8 – Q13 interview questions & answers

295 views

♦ 7 Java debugging interview questions & answers

293 views

01: ♦ 15 Ice breaker questions asked 90% of the time in Java job interviews with hints

285 views

♦ 10 ERD (Entity-Relationship Diagrams) Interview Questions and Answers

279 views

♦ Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers

239 views

001B: ♦ Java architecture & design concepts interview questions & answers

201 views

Bio

Latest Posts



Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via [Amazon.com](https://www.amazon.com) in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.**945+** paid members. [join my LinkedIn Group](#). [Reviews](#)



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via [Amazon.com](https://www.amazon.com) in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site.**945+** paid members. [join my LinkedIn Group](#). [Reviews](#)

001A: ♦ 7+ Java integration styles & patterns interview questions &

answers ›

Posted in Hibernate Job Interview Essentials, JPA, member-paid

Tags: Java/JEE FAQs, JEE FAQs

Empowers you to open more doors, and fast-track

Technical Know Hows

☀ [Java generics in no time](#) ☀ [Top 6 tips to transforming your thinking from OOP to FP](#) ☀ [How does a HashMap internally work? What is a hashing function?](#)
☀ [10+ Java String class interview Q&As](#) ☀ [Java auto un/boxing benefits & caveats](#) ☀ [Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect](#)

Non-Technical Know Hows

☀ [6 Aspects that can motivate you to fast-track your career & go places](#) ☀ [Are you reinventing yourself as a Java developer?](#) ☀ [8 tips to safeguard your Java career against offshoring](#) ☀ [My top 5 career mistakes](#)

Prepare to succeed

☀ [Turn readers of your Java CV go from “Blah blah” to “Wow”?](#) ☀ [How to prepare for Java job interviews?](#) ☀ [16 Technical Key Areas](#) ☀ [How to choose from multiple Java job offers?](#)

Select Category ▼

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.