

Industrial strength Java/JEE Career Companion to open more doors

[Home](#)
[Java FAQs](#)
[600+ Java Q&As](#)
[Career](#)
[Tutorials](#)
[Member](#)
[Why?](#)
[Can u Debug?](#)
[Java 8 ready?](#)
[Top X](#)
[Productivity Tools](#)
[Judging Experience?](#)

[Home](#) › [Interview](#) › [Core Java Interview Q&A](#) › [Java 7](#) › Java 7: Top 8 new features with examples

Java 7: Top 8 new features with examples

Posted on [November 9, 2014](#) by [Arulkumaran Kumaraswamipillai](#) — No

[Comments](#) ↓

0
Like
Share

Tweet

0
G+1
Share

There are several small new features and enhancements in Java 7. The major features and enhancements are in Java 8. Let's look at the Java 7 new features.

#1: string in switch statement:

```
1 public class Java7Feature1 {
2
3     private static String color = "BLUE";
4
5     private enum Color {
6         RED, GREEN
7     };
8
9     public static void main(String[] args) {
```

600+ Full Stack Java/JEE Interview Q&As ♥Free ♦FAQs

[open all](#) | [close all](#)

- [Ice Breaker Interview](#)
- [Core Java Interview C](#)
- [Java Overview \(4\)](#)
- [Data types \(6\)](#)
- [constructors-methc](#)
- [Reserved Key Wor](#)
- [Classes \(3\)](#)
- [Objects \(8\)](#)
- [OOP \(10\)](#)
- [GC \(2\)](#)
- [Generics \(5\)](#)
- [FP \(8\)](#)
- [IO \(7\)](#)
- [Multithreading \(12\)](#)
- [Algorithms \(5\)](#)
- [Annotations \(2\)](#)
- [Collection and Dat](#)
- [Differences Betwee](#)
- [Event Driven Progr](#)
- [Exceptions \(2\)](#)
- [Java 7 \(2\)](#)

```

10
11 // Pre Java 5
12 if (color.equals("RED")) {
13     System.out.println("Color is Red");
14 } else if (color.equals("GREEN")) {
15     System.out.println("Color is Green");
16 } else {
17     System.out.println("Color not found");
18 }
19
20 // Java 5 enum. try/catch is required for color
21 try {
22     switch (Color.valueOf(color)) {
23     case RED:
24         System.out.println("Color is Red");
25         break;
26     case GREEN:
27         System.out.println("Color is Green");
28     }
29 } catch (IllegalArgumentException e) {
30     System.out.println("Color not found");
31 }
32
33 // Java 7 String in switch statement for simpl
34 //JDK 7 switch performs better than if-else
35 //using types with enums is only useful when i
36 //the value for color could come from database
37 switch (color) {
38 case "RED":
39     System.out.println("Color is Red");
40     break;
41 case "GREEN":
42     System.out.println("Color is Green");
43     break;
44 default:
45     System.out.println("Color not found");
46 }
47 }
48
49 }
50
51
52

```

Output is:

```

1 Color not found
2 Color not found
3 Color not found
4

```

#2 Binary integral literals

```

1 public class Java7Feature2 {
2
3     public static void main(String[] args) {
4         // Pre Java 7

```

[Java 7 fork and j](#)
[Java 7: Top 8 ne](#)
[Java 8 \(24\)](#)
[JVM \(6\)](#)
[Reactive Programn](#)
[Swing & AWT \(2\)](#)
[JEE Interview Q&A \(3](#)
[Pressed for time? Jav](#)
[SQL, XML, UML, JSC](#)
[Hadoop & BigData Int](#)
[Java Architecture Inte](#)
[Scala Interview Q&As](#)
[Spring, Hibernate, & I](#)
[Testing & Profiling/Sa](#)
[Other Interview Q&A 1](#)
[Free Java Interview](#)

16 Technical Key Areas

open all | close all

- [Best Practice \(6\)](#)
- [Coding \(26\)](#)
- [Concurrency \(6\)](#)
- [Design Concepts \(7\)](#)
- [Design Patterns \(11\)](#)
- [Exception Handling \(3](#)
- [Java Debugging \(21\)](#)
- [Judging Experience I](#)
- [Low Latency \(7\)](#)
- [Memory Managemen](#)
- [Performance \(13\)](#)
- [QoS \(8\)](#)
- [Scalability \(4\)](#)
- [SDLC \(6\)](#)
- [Security \(13\)](#)
- [Transaction Managen](#)

```

5  int n = Integer.parseInt("10000000", 2);
6  System.out.println(n);
7
8  n = 1 << 7;
9  System.out.println(n);
10
11 // Java 7
12 n = 0b10000000; // 128 = 2^7
13 System.out.println(n);
14 }
15 }
16

```

Output:

```

1 128
2 128
3 128
4

```

#3: Underscores for better readability in numeric literals

```

1 public class Java7Feature3 {
2
3     public static void main(String[] args) {
4         //pre Java 7
5         int million = 1000000;
6         System.out.println(million);
7
8         //Java 7. More readable
9         million = 1_000_000;
10        System.out.println(million);
11
12        //consecutive underscores are allowed
13        int ten_million = 10__000_000;
14        System.out.println(ten_million);
15
16        //underscores can be used in other numeric types
17        double million_dollars_5_cents = 1_000_000.0_0;
18        System.out.println(million_dollars_5_cents);
19
20        //illegal to have underscores
21        //1. start or end a literal with an underscore
22        //2. have underscores before or after a decimal point
23    }
24 }
25

```

Output:

```

1 1000000
2 1000000

```

80+ step by step Java Tutorials

[open all](#) | [close all](#)

- [Setting up Tutorial \(6\)](#)
- [Tutorial - Diagnosis \(2\)](#)
- [Akka Tutorial \(9\)](#)
- [Core Java Tutorials \(2\)](#)
- [Hadoop & Spark Tuto](#)
- [JEE Tutorials \(19\)](#)
- [Scala Tutorials \(1\)](#)
- [Spring & Hibernate Ti](#)
- [Tools Tutorials \(19\)](#)
- [Other Tutorials \(45\)](#)

100+ Java pre-interview coding tests

[open all](#) | [close all](#)

- [Can you write code? \(](#)
- [♦ Complete the given](#)
- [Converting from A to I](#)
- [Designing your classe](#)
- [Java Data Structures](#)
- [Passing the unit tests](#)
- [What is wrong with th](#)
- [Writing Code Home A](#)
- [Written Test Core Jav](#)
- [Written Test JEE \(1\)](#)

How good are your?

[open all](#) | [close all](#)

- [Career Making Know-](#)
- [Job Hunting & Resum](#)

```

3 10000000
4 1000000.05
5

```

#4: AutoCloseable interface.

Java 5 introduced the *Closeable* interface and Java 7 has introduced the *AutoCloseable* interface to avoid the unsightly try/catch/finally(within finally try/catch) blocks to close a resource. It also prevents potential resource leaks due to not properly closing a resource. The *java.io.InputStream* and *java.io.OutputStream* now implements the *AutoCloseable* interface.



try-with-resources is one of the most useful additions in Java 7.

```

1 import java.io.BufferedReader;
2 import java.io.File;
3 import java.io.FileInputStream;
4 import java.io.IOException;
5 import java.io.InputStream;
6 import java.io.InputStreamReader;
7
8 public class Java7Feature4 {
9
10  public static void main(String[] args) {
11      // pre Java 7
12      BufferedReader br = null;
13
14      try {
15          File f = new File("c://temp/simple.txt");
16          InputStream is = new FileInputStream(f);
17          InputStreamReader isr = new InputStreamReader(is);
18          br = new BufferedReader(isr);
19
20          String read;
21
22          while ((read = br.readLine()) != null) {
23              System.out.println(read);
24          }
25      } catch (IOException ioe) {
26          ioe.printStackTrace();
27      } finally {
28          try {
29              if (br != null)
30                  br.close();
31          } catch (IOException ex) {

```

```
32     ex.printStackTrace();
33 }
34 }
35
36
37 // Java 7 -- more concise 11 lines as opposed
38 try (InputStream is = new FileInputStream(new
39     InputStreamReader isr = new InputStreamReader(
40     BufferedReader br2 = new BufferedReader(isr)
41
42     String read;
43
44     while ((read = br2.readLine()) != null) {
45         System.out.println(read);
46     }
47 }
48 }
49 catch (IOException ioe) {
50     ioe.printStackTrace();
51 }
52
53 }
54
55 }
56
```

The output is:

```
1 Big
2 brown fox
3 jumped over the fence
4 Big
5 brown fox
6 jumped over the fence
7
```

try can now have multiple statements in the parenthesis and each statement should create an object which implements the new java.lang.**AutoCloseable** interface. The **AutoCloseable** interface consists of just one method.

void close () throws Exception {}. Each *AutoCloseable* resource created in the try statement will be automatically closed! If an exception is thrown in the try block and another *Exception* is thrown while closing the resource, the first *Exception* is the one eventually thrown to the caller.

Think of the close() method as implicitly being called as the last line in the try block.

#5 Multi-catch to avoid code duplication

```
1 public class Java7Feature4 {
2
3     public static void main(String[] args) {
4
5         //pre Java 7
6         try {
7             someMethod();
8         } catch (CustomException1 ex1) {
9             ex1.printStackTrace();
10        } catch (CustomException2 ex2) {
11            ex2.printStackTrace();
12        }
13
14
15        //Java 7 -- 5 lines as opposed to 7 lines.
16        //no code duplication
17        try {
18            someMethod();
19        } catch (CustomException1|CustomException2 ex)
20            ex.printStackTrace();
21        }
22    }
23
24    public static void someMethod() throws CustomEx
25
26    }
27
28    public static class CustomException1 extends Ex
29        private static final long serialVersionUID = 1
30    }
31
32    public static class CustomException2 extends Ex
33        private static final long serialVersionUID = 1
34    }
35
36 }
37
```

Note that the pipe ‘|’ character is used as the delimiter.

#6 Improved type inference for generic instance creation

This is only a small change that makes generics declaration a little less verbose. As shown below, you can just use empty diamond “<>” in Java 7 on the RHS.

```
1 import java.util.Collections;
2 import java.util.HashMap;
3 import java.util.List;
4 import java.util.Map;
5
6 public class Java7Feature4 {
7
8     public static void main(String[] args) {
```

```

9      //Pre Java 7
10     getEmployeesWithManagersOld("a102");
11     //Java 7
12     getEmployeesWithManagersNew("a102");
13 }
14
15
16 public static Map<String, List<Employee>> getE
17     if(empCode == null){
18         return Collections.emptyMap();
19     }
20
21     //gives type safety warning. You need to add
22     Map<String, List<Employee>> mapEmployees = ne
23
24
25     return mapEmployees;
26 }
27
28
29 //Java 7
30 public static Map<String, List<Employee>> getE
31     if(empCode == null){
32         return Collections.emptyMap();
33     }
34
35     //no duplication of generic inference
36     Map<String, List<Employee>> mapEmployees = ne
37     //do something with mapEmployees
38
39     return mapEmployees;
40 }
41
42
43 static class Employee {}
44 }
45
46

```

#7: More new I/O APIs for the Java platform (NIO – 2.0)

Those who worked with Java IO may still remember the headaches that framework caused. It was never easy to work seamlessly across operating systems or multi-file systems. The NIO 2.0 has come forward with many enhancements. It's also introduced new classes to ease the life of a developer when working with multiple file systems with classes and interfaces such as **Path**, **Paths**, **FileSystem**, **FileSystems** and others.

Another very handy feature is the *WatchService* for file change notifications. It can monitor a directory for changes as demonstrated below.

```
1 import java.io.IOException;
2 import java.nio.file.FileSystems;
3 import java.nio.file.Files;
4 import java.nio.file.Path;
5 import java.nio.file.Paths;
6 import java.nio.file.StandardWatchEventKinds;
7 import java.nio.file.WatchEvent;
8 import java.nio.file.WatchEvent.Kind;
9 import java.nio.file.WatchKey;
10 import java.nio.file.WatchService;
11
12 public class Java7Feature7 {
13
14     public static void main(String[] args) throws I
15
16         // Java 7
17         Path path = Paths.get("c:\\Temp\\simple.txt");
18         System.out.println(path.getFileName());
19         System.out.println(path.getRoot());
20         System.out.println(path.getParent());
21
22         // Java 7 file change watch service
23         WatchService watchService = FileSystems.getDef
24
25         //register Temp folder with the watch service
26         path.getParent().register(watchService, Standa
27             StandardWatchEventKinds.ENTRY_MODIFY, Standa
28
29         //wait for incoming events
30         while (true) {
31             final WatchKey key = watchService.take();
32             for (WatchEvent<?> watchEvent : key.pollEvent
33                 final Kind<?> kind = watchEvent.kind();
34                 // Overflow event
35                 if (StandardWatchEventKinds.OVERFLOW == kind
36                     continue; // loop
37                 } else if (StandardWatchEventKinds.ENTRY_CRE
38                     || StandardWatchEventKinds.ENTRY_DELETE ==
39                     @SuppressWarnings("unchecked")
40                     final WatchEvent<Path> watchEventPath = (Wa
41                     final Path entry = watchEventPath.context()
42
43                     System.out.println(kind + "-->" + entry);
44
45             }
46         }
47
48         if (!key.reset()) {
49             break;
50         }
51     }
52 }
53
54 // deleting a file is as easy as.
55 Files.deleteIfExists(path); // Java 7 feature
56 }
57
58 }
59
60
```

The output will be something like:


```
1 simple.txt
2 c:\
3 c:\Temp
4 ENTRY_CREATE-->New Text Document.txt
5 ENTRY_DELETE-->New Text Document.txt
6 ENTRY_CREATE-->File1.txt
7 ENTRY_MODIFY-->File1.txt
8
9
```

#8: Fork and Join

Java 7 has incorporated the feature that would distribute the work across multiple cores and then join them to return the result set as a Fork and Join framework. The effective use of parallel cores in a Java program has always been a challenge. It's a divide-and-conquer algorithm where Fork-Join breaks the task at hand into mini-tasks until the mini-task is simple enough that it can be solved without further breakups. One important concept to note in this framework is that ideally no worker thread is idle. They implement a work-stealing algorithm in that idle workers "steal" the work from those workers who are busy.

The example below demonstrates this with a simple task of summing up 10 numbers. If the count of numbers to be added are greater than 5, it is forked into chunks of 5 to be processed by separate thread, and the forked sum are then joined to give the overall total of 10 numbers from 1 to 10, which is 55. The total of numbers 1 to 5 is 15, and 6 to 10 is 40.

```
1 import java.io.IOException;
2 import java.util.ArrayList;
3 import java.util.Arrays;
4 import java.util.List;
5 import java.util.concurrent.ForkJoinPool;
6 import java.util.concurrent.RecursiveTask;
7
8 public class Java7Feature8 {
9
10     static int[] numbers = { 1, 2, 3, 4, 5, 6, 7, 8
11
12     public static void main(String[] args) throws I
13         int numberOfCpuCores = Runtime.getRuntime()
14         ForkJoinPool forkJoinPool = new ForkJoinPoo
15         int sum = forkJoinPool.invoke(new ChunkingT
```

```
16     System.out.println(sum);
17 }
18
19 //inner class
20 static class SumCalculatorTask extends RecursiveTask<Integer> {
21     int[] numbers;
22
23     SumCalculatorTask(int[] numbers) {
24         this.numbers = numbers;
25     }
26
27     @Override
28     protected Integer compute() {
29         int sum = 0;
30         for (int i : numbers) {
31             sum += i;
32         }
33
34         System.out.println(Thread.currentThread().getName() + " sum is " + sum);
35
36         return sum;
37     }
38 }
39
40
41 //inner class
42 /**
43  *
44  * *chunking size is 5
45  */
46 static class ChunkingTask extends RecursiveTask<Integer> {
47
48     private static final int CHUNK_SIZE = 5;
49     int[] numbers;
50
51     ChunkingTask(int[] numbers) {
52         this.numbers = numbers;
53     }
54
55     @Override
56     protected Integer compute() {
57         int sum = 0;
58         List<RecursiveTask<Integer>> forks = new ArrayList<>();
59
60         //if the numbers size is > CHUNK_SIZE fork the task
61         if (numbers.length > CHUNK_SIZE) {
62             ChunkingTask chunk1 = new ChunkingTask(numbers, 0, numbers.length / 2);
63             ChunkingTask chunk2 = new ChunkingTask(numbers, numbers.length / 2, numbers.length);
64             forks.add(chunk1);
65             forks.add(chunk2);
66             chunk1.fork();
67             chunk2.fork();
68         }
69         //size is less than or equal to CHUNK_SIZE so compute it
70         else {
71             SumCalculatorTask sumCalculatorTask = new SumCalculatorTask(numbers);
72             forks.add(sumCalculatorTask);
73             sumCalculatorTask.fork();
74         }
75
76         // Combine the result from all the tasks
77         //join
78         for (RecursiveTask<Integer> task : forks) {
79             sum += task.join();
80         }
81     }
82 }
```

```
82     return sum;
83   }
84
85   }
86
87   }
88
```

Output is:

```
1 ForkJoinPool-1-worker-2 sum = 15
2 ForkJoinPool-1-worker-2 sum = 40
3 55
4
```

Java 8's *Arrays.parallelSort(...)* make use of this fork and join feature to sort an array in parallel.

Popular Posts

♦ [11 Spring boot interview questions & answers](#)

825 views

♦ [Q11-Q23: Top 50+ Core on Java OOP Interview Questions & Answers](#)

765 views

[18 Java scenarios based interview Questions and Answers](#)

399 views

001A: ♦ [7+ Java integration styles & patterns interview questions & answers](#)

388 views

01b: ♦ [13 Spring basics Q8 – Q13 interview questions & answers](#)

295 views

♦ [7 Java debugging interview questions & answers](#)

293 views

01: ♦ [15 Ice breaker questions asked 90% of the time in Java job interviews with hints](#)

285 views

♦ [10 ERD \(Entity-Relationship Diagrams\) Interview Questions and Answers](#)

279 views

♦ Q24-Q36: Top 50+ Core on Java classes, interfaces and generics interview questions & answers

239 views

001B: ♦ Java architecture & design concepts interview questions & answers

201 views

Bio

Latest Posts



Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site. **945+** paid members. [join my LinkedIn Group](#). [Reviews](#)



About Arulkumaran Kumaraswamipillai

Mechanical Eng to freelance Java developer in 3 yrs. Contracting since 2003, and attended 150+ Java job interviews, and often got 4 - 7 job offers to choose from. It pays to prepare. So, published Java interview Q&A books via Amazon.com in 2005, and sold 35,000+ copies. Books are outdated and replaced with this subscription based site. **945+** paid members. [join my LinkedIn Group](#). [Reviews](#)

◀ Java 8: Different ways to sort a collection of objects in pre and post

Java 8

SSL and truststore vs keystore for Java developers ▶

Posted in Java 7, member-paid

Tags: Novice FAQs, TopX

Leave a Reply

Logged in as geethika. [Log out?](#)

Comment

Empowers you to open more doors, and fast-track

Technical Know Hows

☀ [Java generics in no time](#) ☀ [Top 6 tips to transforming your thinking from OOP to FP](#) ☀ [How does a HashMap internally work? What is a hashing function?](#)

☀ [10+ Java String class interview Q&As](#) ☀ [Java auto un/boxing benefits & caveats](#) ☀ [Top 11 slacknesses that can come back and bite you as an experienced Java developer or architect](#)

Non-Technical Know Hows

☀ [6 Aspects that can motivate you to fast-track your career & go places](#) ☀ [Are you reinventing yourself as a Java developer?](#) ☀ [8 tips to safeguard your Java career against offshoring](#) ☀ [My top 5 career mistakes](#)

Prepare to succeed

☀ [Turn readers of your Java CV go from “Blah blah” to “Wow”?](#) ☀ [How to prepare for Java job interviews?](#) ☀ [16 Technical Key Areas](#) ☀ [How to choose from multiple Java job offers?](#)

© Disclaimer

The contents in this Java-Success are copy righted. The author has the right to correct or enhance the current content without any prior notice.

These are general advice only, and one needs to take his/her own circumstances into consideration. The author will not be held liable for any damages caused or alleged to be caused either directly or indirectly by these materials and resources. Any trademarked names or labels used in this blog remain the property of their respective trademark owners. No guarantees are made regarding the accuracy or usefulness of content, though I do make an effort to be accurate. Links to external sites do not imply endorsement of the linked-to sites.