

# Day 11: R Packages and Quanteda

Erin Rossiter

17 April, 2023

## (Class pre-requisites for Windows users)

1. Download the appropriate version of RTools for your version of R:  
<https://cran.r-project.org/bin/windows/Rtools/>
2. Install RTools by running the downloaded executable
3. Set the path to RTools in your system environment variables. To do this, right-click on “My Computer” > “Properties” > “Advanced system settings” > “Environment Variables”.

Under “System Variables”, find the “PATH” variable and click “Edit”. Add the path to the RTools bin folder (e.g., C:\Rtools\bin) to the list of paths.

Example: C:\\Program Files\\R\\R-4.2.2\\bin; C:\\Rtools;}

4. Restart your R session to ensure that the changes to the system environment variables take effect.

## Announcements

# Announcements

- PS09 due tomorrow
- Anything else?

# Announcements

- PS09 due tomorrow
- Anything else?

# Roadmap

# Roadmap

## Last unit:

- data cleaning and wrangling

## Final unit:

- advanced topics

## Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

## Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...



# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...



# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# Roadmap

Last unit:

- data cleaning and wrangling

Final unit:

- advanced topics

Today:

- R packages
- Basic text-as-data (Quanteda R package)
  - » Not any methods, just working in R
- Rcpp

Next time:

- Data viz
  - » Base R
  - » ggplot
  - » hopefully more fun stuff if time...

# R Packages

# What is an R package?

- a collection of (mainly) functions, but also data sets, help files, etc.
- a way to share code and data with other R users
  - » remember R is open-source language
  - » large and active community of R users **and developers** who create R packages
  - » R packages are why it is so impactful to learn R vs. another language
  - » usually, new stats methods in political science will make their way to R first

# What is an R package?

- a collection of (mainly) functions, but also data sets, help files, etc.
- a way to share code and data with other R users
  - » remember R is open-source language
  - » large and active community of R users **and developers** who create R packages
  - » R packages are why it is so impactful to learn R vs. another language
  - » usually, new stats methods in political science will make their way to R first

# What is an R package?

- a collection of (mainly) functions, but also data sets, help files, etc.
- a way to share code and data with other R users
  - » remember R is open-source language
  - » large and active community of R users **and developers** who create R packages
  - » R packages are why it is so impactful to learn R vs. another language
  - » usually, new stats methods in political science will make their way to R first

# What is an R package?

- a collection of (mainly) functions, but also data sets, help files, etc.
- a way to share code and data with other R users
  - » remember R is open-source language
  - » large and active community of R users **and developers** who create R packages
  - » R packages are why it is so impactful to learn R vs. another language
  - » usually, new stats methods in political science will make their way to R first

# What is an R package?

- a collection of (mainly) functions, but also data sets, help files, etc.
- a way to share code and data with other R users
  - » remember R is open-source language
  - » large and active community of R users **and developers** who create R packages
  - » R packages are why it is so impactful to learn R vs. another language
  - » usually, new stats methods in political science will make their way to R first



# What is an R package?

- a collection of (mainly) functions, but also data sets, help files, etc.
- a way to share code and data with other R users
  - » remember R is open-source language
  - » large and active community of R users **and developers** who create R packages
  - » R packages are why it is so impactful to learn R vs. another language
  - » usually, new stats methods in political science will make their way to R first

# Why make a package?

- You have a novel statistical method
- You want credit for something, perhaps citations even (see this paper)
- “Simple” way to share complex code/results/data.
- Coherent way to organize:
  - » Data
  - » Documentation/explanation
  - » Meta-data
  - » Execute complex code
- Free Hadley Wickham book if you want to make your own

# Why make a package?

- You have a novel statistical method
- You want credit for something, perhaps citations even (see this paper)
- “Simple” way to share complex code/results/data.
- Coherent way to organize:
  - » Data
  - » Documentation/explanation
  - » Meta-data
  - » Execute complex code
- Free Hadley Wickham book if you want to make your own

# Why make a package?

- You have a novel statistical method
- You want credit for something, perhaps citations even (see this paper)
- “Simple” way to share complex code/results/data.
- Coherent way to organize:
  - » Data
  - » Documentation/explanation
  - » Meta-data
  - » Execute complex code
- Free Hadley Wickham book if you want to make your own

# Why make a package?

- You have a novel statistical method
- You want credit for something, perhaps citations even (see this paper)
- “Simple” way to share complex code/results/data.
- Coherent way to organize:
  - » Data
  - » Documentation/explanation
  - » Meta-data
  - » Execute complex code
- Free Hadley Wickham book if you want to make your own

# Why make a package?

- You have a novel statistical method
- You want credit for something, perhaps citations even (see this paper)
- “Simple” way to share complex code/results/data.
- Coherent way to organize:
  - » Data
  - » Documentation/explanation
  - » Meta-data
  - » Execute complex code
- Free Hadley Wickham book if you want to make your own

Where to find/publish R packages

## Where to find/publish R packages

- CRAN
- Github



# CRAN

CRAN is the Comprehensive R Archive Network

- As of today, there are 19365 available packages! See [here](#)
- List by name

# CRAN

CRAN is the Comprehensive R Archive Network

- As of today, there are 19365 available packages! See [here](#)
- List by name

# CRAN

CRAN is the Comprehensive R Archive Network

- As of today, there are 19365 available packages! See [here](#)
- List by name

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN...
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - ... as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home

- CRAN is the primary repository for R packages
- But, some developers prefer to distribute their packages through GitHub
- Easier, quicker, less rules and hassle!
  - » Ex: Lots of dependencies that CRAN won't allow
- Or even kicked off CRAN...

2. Maybe they are still in development

- Version control
- Collaboration
- Distribution
- Documentation
- ... as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN...
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - ... as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN...
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - ... as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN...
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - ... as we know, all great on Github



# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN...
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - ... as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN. . .
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - . . . as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN. . .
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - . . . as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN. . .
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - . . . as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN. . .
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - . . . as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN. . .
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - . . . as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN. . .
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - . . . as we know, all great on Github

# GitHub

You might find R packages on Github. Why?

1. Maybe this is their final home
  - CRAN is the primary repository for R packages
  - But, some developers prefer to distribute their packages through GitHub
  - Easier, quicker, less rules and hassle!
    - » Ex: Lots of dependencies that CRAN won't allow
  - Or even kicked off CRAN. . .
2. Maybe they are still in development
  - Version control
  - Collaboration
  - Distribution
  - Documentation
  - . . . as we know, all great on Github



## Developing an R Package

# Package Structure

## An R package *must* contain:

- R functions ( .R files)
- Documentation ( .Rd files)
- Meta-data (NAMESPACE and DESCRIPTION)

## An R package *must* contain:

- R functions ( .R files)
- Documentation ( .Rd files)
- Meta-data (NAMESPACE and DESCRIPTION)

## An R package *must* contain:

- R functions ( .R files)
- Documentation ( .Rd files)
- Meta-data (NAMESPACE and DESCRIPTION)

## An R package *must* contain:

- R functions ( .R files)
- Documentation ( .Rd files)
- Meta-data (NAMESPACE and DESCRIPTION)

## An R package *can* contain:

- Datasets
- Demo files
- Class structures (and helper functions)
- Compiled code
- README
- More

## An R package *can* contain:

- Datasets
- Demo files
- Class structures (and helper functions)
- Compiled code
- README
- More



## An R package *can* contain:

- Datasets
- Demo files
- Class structures (and helper functions)
- Compiled code
- README
- More

## An R package *can* contain:

- Datasets
- Demo files
- Class structures (and helper functions)
- Compiled code
- README
- More

## An R package *can* contain:

- Datasets
- Demo files
- Class structures (and helper functions)
- Compiled code
- README
- More

## An R package *can* contain:

- Datasets
- Demo files
- Class structures (and helper functions)
- Compiled code
- README
- More

## Example: squaresPack

What is the necessary file structure to create an R package with these advanced statistical methods? (on board)

```
addSquares <- function(x, y){  
  return(list(square = (x^2 + y^2), x = x, y = y))  
}
```

```
subtractSquares <- function(x, y){  
  return(list(square = (x^2 - y^2), x = x, y = y))  
}
```

## In more detail

- Directory must have the name of the package
- DESCRIPTION file must have **exactly** that name. This contains required meta-data about the package (e.g., version number).
- NAMESPACE determined what functions or objects will be available in the global environment and sets up a package-specific namespace.
- The R directory contains \*.R files with your scripts/functions/etc.
- The man directory contains the \*.Rd help files.

## In more detail

- Directory must have the name of the package
- DESCRIPTION file must have **exactly** that name. This contains required meta-data about the package (e.g., version number).
- NAMESPACE determined what functions or objects will be available in the global environment and sets up a package-specific namespace.
- The R directory contains \*.R files with your scripts/functions/etc.
- The man directory contains the \*.Rd help files.

## In more detail

- Directory must have the name of the package
- DESCRIPTION file must have **exactly** that name. This contains required meta-data about the package (e.g., version number).
- NAMESPACE determined what functions or objects will be available in the global environment and sets up a package-specific namespace.
- The R directory contains \*.R files with your scripts/functions/etc.
- The man directory contains the \*.Rd help files.



## In more detail

- Directory must have the name of the package
- DESCRIPTION file must have **exactly** that name. This contains required meta-data about the package (e.g., version number).
- NAMESPACE determined what functions or objects will be available in the global environment and sets up a package-specific namespace.
- The R directory contains \*.R files with your scripts/functions/etc.
- The `man` directory contains the \*.Rd help files.

## In more detail

- Directory must have the name of the package
- DESCRIPTION file must have **exactly** that name. This contains required meta-data about the package (e.g., version number).
- NAMESPACE determined what functions or objects will be available in the global environment and sets up a package-specific namespace.
- The R directory contains \*.R files with your scripts/functions/etc.
- The man directory contains the \*.Rd help files.

## Folder: R

Put your R scripts in the R directory.

- The simplest convention is to include one R function in each file
- In many instances you will find that files contain multiple R functions, especially if there is some class system.

## Folder: R

Put your R scripts in the R directory.

- The simplest convention is to include one R function in each file
- In many instances you will find that files contain multiple R functions, especially if there is some class system.

## Folder: R

Put your R scripts in the R directory.

- The simplest convention is to include one R function in each file
- In many instances you will find that files contain multiple R functions, especially if there is some class system.

## Folder: `man`

- These are your help files!
- Written in markup language called “rd” (R documentation)

```
\name{addSquares}  
\alias{addSquares}  
\title{Adding squared values}  
\usage{  
  addSquares(x, y)  
}  
\usage{  
  addSquares(x, y)  
}  
\arguments{  
  \item{x}{A numeric object}  
  \item{y}{A numeric object with the same dimensionality as  
    \code{x}.}  
}  
\value{  
  A list with the elements  
  \item{squares}{The sum of the squared values}  
  \item{x}{The first object input}
```

## Folder: [man](#)

- These are your help files!
- Written in markup language called “rd” (R documentation)

```
\name{addSquares}
\alias{addSquares}
\title{Adding squared values}
\usage{
  addSquares(x, y)
}
\usage{
  addSquares(x, y)
}
\arguments{
  \item{x}{A numeric object}
  \item{y}{A numeric object with the same dimensionality as
    \code{x}.}
}
\value{
  A list with the elements
  \item{squares}{The sum of the squared values}
  \item{x}{The first object input}
```

## Folder: [man](#)

- These are your help files!
- Written in markup language called “rd” (R documentation)

```
\name{addSquares}
\alias{addSquares}
\title{Adding squared values}
\usage{
  addSquares(x, y)
}
\usage{
  addSquares(x, y)
}
\arguments{
  \item{x}{A numeric object}
  \item{y}{A numeric object with the same dimensionality as
    \code{x}.}
}
\value{
  A list with the elements
  \item{squares}{The sum of the squared values}
  \item{x}{The first object input}
```



## File: DESCRIPTION

### Contains:

- package name
- formal title
- current version number
- the date for the version release
- the name and contact information of of the author and maintainer
- dependencies
- list of the files in the R subdirectory

## File: DESCRIPTION

Contains:

- package name
- formal title
- current version number
- the date for the version release
- the name and contact information of of the author and maintainer
- dependencies
- list of the files in the R subdirectory

## File: DESCRIPTION

Contains:

- package name
- formal title
- current version number
- the date for the version release
- the name and contact information of the author and maintainer
- dependencies
- list of the files in the R subdirectory

## File: DESCRIPTION

Contains:

- package name
- formal title
- current version number
- the date for the version release
- the name and contact information of of the author and maintainer
- dependencies
- list of the files in the R subdirectory

## File: DESCRIPTION

Contains:

- package name
- formal title
- current version number
- the date for the version release
- the name and contact information of the author and maintainer
- dependencies
- list of the files in the R subdirectory

## File: DESCRIPTION

Contains:

- package name
- formal title
- current version number
- the date for the version release
- the name and contact information of of the author and maintainer
- dependencies
- list of the files in the R subdirectory

## File: DESCRIPTION

Contains:

- package name
- formal title
- current version number
- the date for the version release
- the name and contact information of the author and maintainer
- dependencies
- list of the files in the R subdirectory

## File: DESCRIPTION

Contains:

- package name
- formal title
- current version number
- the date for the version release
- the name and contact information of the author and maintainer
- dependencies
- list of the files in the R subdirectory



## Example:

```
Package: squaresPack
Title: Adding and subtracting squared values
Version: 0.1
Author: Jacob M. Montgomery
Maintainer: Jacob M. Montgomery <jacob.montgomery@wustl.edu>
Description: Find sum and difference of squared values
Depends:
  R (>= 3.0.0)
License: GPL (>= 2)
Suggests:
  devtools
Collate:
  `addSquares.R'
  `subtractSquares.R'
```

## File: NAMESPACE

This (can be) the most difficult part, and is aimed at setting up a package specific environment and controlling what functions users can see and/or use directly.

At a minimum, it needs to read in the functions, class definitions etc. that are “available” to R.

The contents of the NAMESPACE file for this package are:

```
export(addSquares)
export(subtractSquares)
```

## File: NAMESPACE

This (can be) the most difficult part, and is aimed at setting up a package specific environment and controlling what functions users can see and/or use directly.

At a minimum, it needs to read in the functions, class definitions etc. that are “available” to R.

The contents of the NAMESPACE file for this package are:

```
export(addSquares)  
export(subtractSquares)
```

## File: NAMESPACE

This (can be) the most difficult part, and is aimed at setting up a package specific environment and controlling what functions users can see and/or use directly.

At a minimum, it needs to read in the functions, class definitions etc. that are “available” to R.

The contents of the NAMESPACE file for this package are:

```
export(addSquares)  
export(subtractSquares)
```

## File: NAMESPACE

This (can be) the most difficult part, and is aimed at setting up a package specific environment and controlling what functions users can see and/or use directly.

At a minimum, it needs to read in the functions, class definitions etc. that are “available” to R.

The contents of the NAMESPACE file for this package are:

```
export(addSquares)
export(subtractSquares)
```

## Beyond scope for today

- Adding test files, see [here](#)
- Dependencies
- Adding data (its much like adding R functions)
- Final steps for submitting package to CRAN, meeting their rules, etc.
  - » See Hadley Wickham book linked at beginning

## Beyond scope for today

- Adding test files, see [here](#)
- Dependencies
- Adding data (its much like adding R functions)
- Final steps for submitting package to CRAN, meeting their rules, etc.
  - » See Hadley Wickham book linked at beginning

## Beyond scope for today

- Adding test files, see [here](#)
- Dependencies
- Adding data (its much like adding R functions)
- Final steps for submitting package to CRAN, meeting their rules, etc.
  - » See Hadley Wickham book linked at beginning



## Beyond scope for today

- Adding test files, see [here](#)
- Dependencies
- Adding data (its much like adding R functions)
- Final steps for submitting package to CRAN, meeting their rules, etc.
  - » See Hadley Wickham book linked at beginning

## Beyond scope for today

- Adding test files, see [here](#)
- Dependencies
- Adding data (its much like adding R functions)
- Final steps for submitting package to CRAN, meeting their rules, etc.
  - » See Hadley Wickham book linked at beginning

## Using R packages

# Downloading

# Downloading from CRAN

- We need to download and install the packages we want onto our local computers
- You'll ask R to download the package from a repository, probably CRAN or Github
  - » That's why we don't have all 19000+ package already at our disposal!

```
install.packages("A3")
```

# Downloading from CRAN

- We need to download and install the packages we want onto our local computers
- You'll ask R to download the package from a repository, probably CRAN or Github
  - » That's why we don't have all 19000+ package already at our disposal!

```
install.packages("A3")
```

# Downloading from CRAN

- We need to download and install the packages we want onto our local computers
- You'll ask R to download the package from a repository, probably CRAN or Github
  - » That's why we don't have all 19000+ package already at our disposal!

```
install.packages("A3")
```

# Downloading from CRAN

- We need to download and install the packages we want onto our local computers
- You'll ask R to download the package from a repository, probably CRAN or Github
  - » That's why we don't have all 19000+ package already at our disposal!

```
install.packages("A3")
```



# Downloading from Github

- We use the `install_github()` in the `devtools` package (yes, this is meta)
- The format is: `install_github("username/repo")`

```
# This package has functions that help install  
# other packages on GitHub!
```

```
install.packages("devtools")
```

```
# Load it (next topic in slides)
```

```
library(devtools)
```

```
# An Example
```

```
install_github("erossiter/blockclustr")
```

# Downloading from Github

- We use the `install_github()` in the `devtools` package (yes, this is meta)
- The format is: `install_github("username/repo")`

```
# This package has functions that help install  
# other packages on GitHub!
```

```
install.packages("devtools")
```

```
# Load it (next topic in slides)
```

```
library(devtools)
```

```
# An Example
```

```
install_github("erossiter/blockclustr")
```

# Downloading from Github

- We use the `install_github()` in the `devtools` package (yes, this is meta)
- The format is: `install_github("username/repo")`

```
# This package has functions that help install  
# other packages on GitHub!
```

```
install.packages("devtools")
```

```
# Load it (next topic in slides)
```

```
library(devtools)
```

```
# An Example
```

```
install_github("erossiter/blockclustr")
```

Loading

# Loading the package for use

- We download it, so entire package is now on our computer
- Now, we want to be able to use the functions (or anything else) in it!
- Loading the package is the same whether downloaded from CRAN or GitHub
- `library()` load everything in the package into memory

```
library(A3)
```

```
## Loading required package: xtable
```

```
## Loading required package: pbapply
```

```
library(blockclustr)
```

# Loading the package for use

- We download it, so entire package is now on our computer
- Now, we want to be able to use the functions (or anything else) in it!
- Loading the package is the same whether downloaded from CRAN or GitHub
- `library()` load everything in the package into memory

```
library(A3)
```

```
## Loading required package: xtable
```

```
## Loading required package: pbapply
```

```
library(blockclustr)
```

# Loading the package for use

- We download it, so entire package is now on our computer
- Now, we want to be able to use the functions (or anything else) in it!
- Loading the package is the same whether downloaded from CRAN or GitHub
- `library()` load everything in the package into memory

```
library(A3)
```

```
## Loading required package: xtable
```

```
## Loading required package: pbapply
```

```
library(blockclustr)
```

# Loading the package for use

- We download it, so entire package is now on our computer
- Now, we want to be able to use the functions (or anything else) in it!
- Loading the package is the same whether downloaded from CRAN or GitHub
- `library()` load everything in the package into memory

```
library(A3)
```

```
## Loading required package: xtable
```

```
## Loading required package: pbapply
```

```
library(blockclustr)
```



## Loading the package for use

- We download it, so entire package is now on our computer
- Now, we want to be able to use the functions (or anything else) in it!
- Loading the package is the same whether downloaded from CRAN or GitHub
- `library()` load everything in the package into memory

```
library(A3)
```

```
## Loading required package: xtable
```

```
## Loading required package: pbapply
```

```
library(blockclustr)
```

## Or access without loading

- Syntax is `'package::function()`
- Grabs function from the package
- Useful:
  - » to be very clear where function comes from
  - » if same function name in different packages
- Examples:

```
blockclustr::blockclustr()  
dplyr::left_join()  
rvest::read_html()
```

## Or access without loading

- Syntax is `'package::function()`
- Grabs function from the package
- Useful:
  - » to be very clear where function comes from
  - » if same function name in different packages
- Examples:

```
blockclustr::blockclustr()  
dplyr::left_join()  
rvest::read_html()
```

## Or access without loading

- Syntax is `'package::function()`
- Grabs function from the package
- Useful:
  - » to be very clear where function comes from
  - » if same function name in different packages
- Examples:

```
blockclustr::blockclustr()  
dplyr::left_join()  
rvest::read_html()
```

## Or access without loading

- Syntax is 'package::function()
- Grabs function from the package
- Useful:
  - » to be very clear where function comes from
  - » if same function name in different packages
- Examples:

```
blockclustr::blockclustr()  
dplyr::left_join()  
rvest::read_html()
```

## Or access without loading

- Syntax is 'package::function()
- Grabs function from the package
- Useful:
  - » to be very clear where function comes from
  - » if same function name in different packages
- Examples:

```
blockclustr::blockclustr()  
dplyr::left_join()  
rvest::read_html()
```

# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]

# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]



# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]

# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]

# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]

# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]

# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]

# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]

# Seeing the nuts and bolts

- Lots of people make R packages
- There are pros and cons of this. Thoughts?
  - » Some are better than others...
  - » Sometimes they are wrong. Sometimes they break.
- You might need to dig into the code itself
- On GitHub, it's easy
  - » Example: [<https://github.com/erossiter/blockclustr>]
- On CRAN, it's easy too, you just have to know where to look
  - » Example: [<https://cran.r-project.org/web/packages/stm/index.html>]

# Activity



quanteda: Text-as-data

# Representing text as numbers

- We usually have a **corpus of documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix (DTM)**
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » Document-term matrix (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words



# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# Representing text as numbers

- We usually have a **corpus** of **documents**
  - » Each document is made up of text!
- We need to represent the text in some quantitative way
  - » **Document-term matrix** (DTM)
  - » (Board)
- Usual simplifying assumptions:
  - » n-gram
    - usually 1-gram
  - » “bag of words”
    - order doesn't matter
  - » stemming
  - » remove punctuation, numbers, “stopwords,” most frequent or infrequent words

# When to do this vs. stringr?

- Representing text as a dataset is useful for subsequent, systematic analysis
  - » what proportion of documents talk about X?
  - » what are the main topics across the Corpus?
- What we did with stringr was aimed at data cleaning
  - » Lots of ways emails, names, address are in my dataset, I need to make variable systematic
  - » etc.
- Do not reinvent the wheel. Get your document into a DTM as soon as possible if you're going to do analyses with text.

# When to do this vs. stringr?

- Representing text as a dataset is useful for subsequent, systematic analysis
  - » what proportion of documents talk about X?
  - » what are the main topics across the Corpus?
- What we did with stringr was aimed at data cleaning
  - » Lots of ways emails, names, address are in my dataset, I need to make variable systematic
  - » etc.
- Do not reinvent the wheel. Get your document into a DTM as soon as possible if you're going to do analyses with text.



# When to do this vs. stringr?

- Representing text as a dataset is useful for subsequent, systematic analysis
  - » what proportion of documents talk about X?
  - » what are the main topics across the Corpus?
- What we did with stringr was aimed at data cleaning
  - » Lots of ways emails, names, address are in my dataset, I need to make variable systematic
  - » etc.
- Do not reinvent the wheel. Get your document into a DTM as soon as possible if you're going to do analyses with text.

# When to do this vs. stringr?

- Representing text as a dataset is useful for subsequent, systematic analysis
  - » what proportion of documents talk about X?
  - » what are the main topics across the Corpus?
- What we did with stringr was aimed at data cleaning
  - » Lots of ways emails, names, address are in my dataset, I need to make variable systematic
  - » etc.
- Do not reinvent the wheel. Get your document into a DTM as soon as possible if you're going to do analyses with text.

## When to do this vs. stringr?

- Representing text as a dataset is useful for subsequent, systematic analysis
  - » what proportion of documents talk about X?
  - » what are the main topics across the Corpus?
- What we did with stringr was aimed at data cleaning
  - » Lots of ways emails, names, address are in my dataset, I need to make variable systematic
  - » etc.
- Do not reinvent the wheel. Get your document into a DTM as soon as possible if you're going to do analyses with text.

## When to do this vs. stringr?

- Representing text as a dataset is useful for subsequent, systematic analysis
  - » what proportion of documents talk about X?
  - » what are the main topics across the Corpus?
- What we did with stringr was aimed at data cleaning
  - » Lots of ways emails, names, address are in my dataset, I need to make variable systematic
  - » etc.
- Do not reinvent the wheel. Get your document into a DTM as soon as possible if you're going to do analyses with text.

## When to do this vs. stringr?

- Representing text as a dataset is useful for subsequent, systematic analysis
  - » what proportion of documents talk about X?
  - » what are the main topics across the Corpus?
- What we did with stringr was aimed at data cleaning
  - » Lots of ways emails, names, address are in my dataset, I need to make variable systematic
  - » etc.
- Do not reinvent the wheel. Get your document into a DTM as soon as possible if you're going to do analyses with text.

## Example script

## Rcpp: Integrating R and C++

# Making R faster

- Rcpp is a way to integrate C++ code into R functions
- Why would we want to do this?
  - » C++ is much, much faster
- Deep down R is actually C
- R is a high level language designed to make **coding** faster and easier, but... as a consequence it can often execute slowly
- Hadley Wickham yet again has an amazing book on this



# Making R faster

- Rcpp is a way to integrate C++ code into R functions
- Why would we want to do this?
  - » C++ is much, much faster
- Deep down R is actually C
- R is a high level language designed to make **coding** faster and easier, but... as a consequence it can often execute slowly
- Hadley Wickham yet again has an amazing book on this

# Making R faster

- Rcpp is a way to integrate C++ code into R functions
- Why would we want to do this?
  - » C++ is much, much faster
- Deep down R is actually C
- R is a high level language designed to make **coding** faster and easier, but... as a consequence it can often execute slowly
- Hadley Wickham yet again has an amazing book on this

# Making R faster

- Rcpp is a way to integrate C++ code into R functions
- Why would we want to do this?
  - » C++ is much, much faster
- Deep down R is actually C
- R is a high level language designed to make **coding** faster and easier, but... as a consequence it can often execute slowly
- Hadley Wickham yet again has an amazing book on this

# Making R faster

- Rcpp is a way to integrate C++ code into R functions
- Why would we want to do this?
  - » C++ is much, much faster
- Deep down R is actually C
- R is a high level language designed to make **coding** faster and easier, but... as a consequence it can often execute slowly
- Hadley Wickham yet again has an amazing book on this

# Making R faster

- Rcpp is a way to integrate C++ code into R functions
- Why would we want to do this?
  - » C++ is much, much faster
- Deep down R is actually C
- R is a high level language designed to make **coding** faster and easier, but... as a consequence it can often execute slowly
- Hadley Wickham yet again has an amazing book on this

## At a high level

```
library(Rcpp)
cppFunction(
  'int addC(int x, int y, int z) {
    int sum = x + y + z;
    return sum;
  }')
addC(1,2,3)
```

## [1] 6

- You must declare the type for
  - » inputs
  - » outputs
  - » variables

## Compared to R...

In R things are quite different! What's different?

```
addR <- function(x, y, z){  
  return(x + y +z)  
}
```

## Exposure topic because...

- You need a C++ compiler to use Rcpp package
- You might have it, so feel free to try following along, but I won't debug in class