

Job Card – API Endpoints & Payloads

Reference for endpoints used by the Job Card module of the Candor Android app. Sectioned by screen / tab. Base path: /api/v1/production. All requests require Authorization: Bearer <token>.

1. Job Card List Screen

Activity: JobCardListActivity.java

GET	/api/v1/production/job-cards
	Fetch paginated list of job cards with optional filters. Query / Path Params: status, search, page, page_size, entity (all sent as query params) <i>Returns JobCardListResponse with paginated results.</i>

2. Job Card Detail – Header Actions

Activity: JobCardDetailActivity.java – loads detail and drives Start / Complete production.

GET	/api/v1/production/job-cards/{id}
	Fetch full job card detail (drives every tab). <i>Returns JobCardDetail.</i>
PUT	/api/v1/production/job-cards/{id}/start
	Mark production started (no body).
PUT	/api/v1/production/job-cards/{id}/complete
	Mark production completed (no body).

3. Overview Tab

Fragment: OverviewFragment.java

PUT	/api/v1/production/job-cards/{id}/assign
	Assign team leader and members to the job card. Payload: <pre>{ "team_leader": "", "team_members": ["", "", ...] }</pre>

4. Stage Chain Tab

Fragment: StageChainFragment.java

GET	/api/v1/production/orders/{orderId}/job-card-chain
	Fetch the chain of job cards for a production order (stage progression view). <i>Returns JSONArray of stages (rendered into chain UI).</i>

5. Materials Tab

Fragment: MaterialsFragment.java – QR scan receive, manual acknowledge, raise indents, dispatch to next stage.

GET	/api/v1/production/orders/{orderId}/job-card-chain
	Used here to compute what to dispatch & to which next stage.
POST	/api/v1/production/job-cards/{id}/receive-material
	Receive material via scanned QR box IDs. Payload: <pre>{ "box_ids": ["", "", ...] }</pre> <i>Response includes boxes_accepted count.</i>
POST	/api/v1/production/job-cards/{id}/acknowledge-material
	Manually acknowledge indent lines (used when no QR). Payload: <pre>{ "indent_lines": null, // null = acknowledge all "acknowledged_by": "" }</pre>
POST	/api/v1/production/indents/raise
	Raise an indent for a material that is short / unavailable. Payload: <pre>{ "material_sku_name": "", "item_category": "", "material_type": "RM PM", "required_qty_kg": 0.0, "uom": "kg", "job_card_id": "", "customer_name": "", "so_reference": "", "trigger_reason": "Insufficient stock", "entity": "" }</pre>
GET	/api/v1/production/job-cards/{id}/floor-stock-status
	Read current floor-stock balances for this job card.
POST	/api/v1/production/job-cards/{id}/dispatch-to-next?entity=<entity>
	Dispatch produced quantity to the next stage / job card. Query / Path Params: entity (query param, current entity from AuthManager) Payload: <pre>{ "qty_kg": 0.0 }</pre>
GET	/api/v1/production/job-cards/{id}/dispatch-log
	Fetch this job card's outbound dispatch log.

6. Output Accounting Tab

Fragment: OutputAccountingFragment.java – V2 output (FG, byproducts, balance materials, embedded QC).

GET	/api/v1/production/job-cards/{id}/output
	Fetch previously saved output (OutputV2Response).
POST	/api/v1/production/job-cards/{id}/output
	Save full V2 output payload (replaces legacy multi-call flow). Payload: <pre> { "fg_actual_kg": 0.0, "fg_actual_units": 0, "fg_expected_kg": 0.0, "fg_expected_units": 0, "rm_consumed_kg": 0.0, "process_loss_kg": 0.0, "byproducts": [{ "category": "", "qty_kg": 0.0, "uom": "kg", "remarks": "" }], "balance_materials": [{ "material_id": 0, "material_name": "", "balance_type": "left_over extra_given ...", "qty_kg": 0.0, "remarks": "" }], "qc": { "passed": true, "remarks": "", "corrective_action": "", "inspector": "" } }</pre>

7. Quality Tab

Fragment: QualityFragment.java – metal detection, weight checks, environment, QC inspection update (chained save).

POST	/api/v1/production/job-cards/{id}/metal-detection
	Record metal-detection / seal / weight gate / temperature checks. Payload: <pre> { "check_type": "", "fe_pass": true, "nfe_pass": true, "ss_pass": true, "failed_units": 0, "seal_check": true, "wt_check": true, "seal_failed_units": 0, "wt_failed_units": 0, "dough_temp_c": 0.0, "oven_temp_c": 0.0, "baking_temp_c": 0.0, "remarks": "" }</pre>

POST	/api/v1/production/job-cards/{id}/weight-checks
	Record packaging weight-check samples (target / tolerance / samples list). Payload: <pre>{ "target_wt_g": 0.0, "tolerance_g": 0.0, "accept_range_min": 0.0, "accept_range_max": 0.0, "samples": [{ "sample_number": 1, "net_weight": 0.0, "gross_weight": 0.0, "leak_test_pass": true }] }</pre>
POST	/api/v1/production/job-cards/{id}/environment
	Record environment parameters (temperature, humidity, etc.). Payload: <pre>{ "parameters": [{ "parameter_name": "", "value": "" }] }</pre>
PUT	/api/v1/production/qc/inspections/{inspectionId}
	Update / close out a QC inspection (called as the final step of the chained Quality save). Payload: <pre>{ "result": "pass fail", "findings": "", "corrective_action": "", "inspector_user": "" }</pre>
POST	/api/v1/production/job-cards/{id}/loss-reconciliation
	(Defined in service – loss reconciliation entries.) Payload: <pre>{ "entries": [{ "loss_category": "", "budgeted_loss_pct": 0.0, "budgeted_loss_kg": 0.0, "actual_loss_kg": 0.0, "remarks": "" }] }</pre>

8. Store Tab

Fragment: StoreFragment.java

Read-only view derived from the cached JobCardDetail (rmIndent / pmIndent lines). **No dedicated endpoints** are called from this tab.

9. Sign-offs Tab

Fragment: SignoffsFragment.java

PUT	/api/v1/production/job-cards/{id}/sign-off
	Record a sign-off (operator / supervisor / QC / etc.). Payload: <pre>{ "sign_off_type": "", "name": "" }</pre>

10. Remarks Tab

Fragment: RemarksFragment.java

POST	/api/v1/production/job-cards/{id}/remarks
	Append a remark to the job card. Payload: <pre>{ "remark_type": "", "content": "", "recorded_by": "" }</pre>

Appendix – Endpoint Index

All endpoints declared in JobCardService.java, in source order.

#	Method	Path
1	GET	/api/v1/production/job-cards
2	GET	/api/v1/production/job-cards/{id}
3	PUT	/api/v1/production/job-cards/{id}/start
4	PUT	/api/v1/production/job-cards/{id}/complete
5	PUT	/api/v1/production/job-cards/{id}/assign
6	POST	/api/v1/production/job-cards/{id}/output
7	GET	/api/v1/production/job-cards/{id}/output
8	PUT	/api/v1/production/job-cards/{id}/sign-off
9	POST	/api/v1/production/job-cards/{id}/remarks
10	POST	/api/v1/production/job-cards/{id}/acknowledge-material
11	POST	/api/v1/production/job-cards/{id}/receive-material
12	POST	/api/v1/production/indents/raise
13	POST	/api/v1/production/job-cards/{id}/metal-detection
14	POST	/api/v1/production/job-cards/{id}/weight-checks
15	POST	/api/v1/production/job-cards/{id}/environment
16	POST	/api/v1/production/job-cards/{id}/loss-reconciliation
17	GET	/api/v1/production/orders/{orderId}/job-card-chain
18	POST	/api/v1/production/job-cards/{id}/dispatch-to-next
19	GET	/api/v1/production/job-cards/{id}/dispatch-log
20	GET	/api/v1/production/job-cards/{id}/floor-stock-status
21	PUT	/api/v1/production/qc/inspections/{inspectionId}