```python
# Python test 5
# q1
D = [1000, 500, 200, 100, 50, 20, 10, 5]
amount = int(input("Enter amount : "))

note_1000 = amount // D[0]
print("Notes of 1000 :" , note_1000)
amt1 = amount % D[0]
print("Amount one :" , amt1)

note_500 = amt1 // D[1]
print("Notes of 500 :" , note_500)
amt2 = amt1 % D[1]
print("Amount two :" , amt2)

note_200 = amt2 // D[2]
print("Note of 200 :" , note_200)
amt3 = amt2 % D[2]
print("Amount three :" , amt3)

note_100 = amt3 // D[3]
print("Notes of 100 :" , note_100)
amt4 = amt3 % D[3]
print("Amount four :" , amt4)

note_50 = amt4 // D[4]
print("Notes of 50 :" , note_50)
amt5 = amt4 % D[4]
print("Amount five :",amt5)

note_20 = amt5 // D[5]
print("Notes of 20 :" , note_20)
amt6 = amt5 % D[5]
print("Amount six :",amt6)
```

```python
note_10 = amt6 // D[6]
print("Notes of 10 :" , note_10)
amt7 = amt6 % D[6]
print("Amount seven :",amt7)

note_5 = amt7 // D[7]
print("Notes of 5 :" , note_5)
amt8 = amt7 % D[7]
print("Amount seven :",amt8)
```

```
PS D:\Project\Python2025> & C:/Users/91848/AppData/Local/Programs/Python/Python311/python.exe d:/Projec
t/Python2025/Test5/t5_q1.py
Enter amount : 5880
Notes of 1000 : 5
Amount one : 880
Notes of 500 : 1
Amount two : 380
Note of 200 : 1
Amount three : 180
Notes of 100 : 1
Amount four : 80
Notes of 50 : 1
Amount five : 30
Notes of 20 : 1
Amount six : 10
Notes of 10 : 1
Amount seven : 0
Notes of 5 : 0
Amount seven : 0
PS D:\Project\Python2025>
```

```python
# q2
def find_missing_coin(coins):
    missing = 0
    for coin in coins:
        missing ^= coin
    return missing
n = 8
coins = [5, 7, 2, 7, 5, 2, 5]
print(n)
print(coins)
print(find_missing_coin(coins))
```

```
PROBLEMS   OUTPUT   DEBUG CONSOLE   TERMINAL   PORTS   GITLENS   AZURE
PS D:\Project\Python2025> & C:/Users/91848/AppData/Local/Programs/Python/Python311/python.exe d:/Project/Python2025/Test5/t5_q2.py
8
[5, 7, 2, 7, 5, 2, 5]
5
PS D:\Project\Python2025>
```

```python
# q3
Data = [
    [ 101, "Seema",45000 ] ,
    [ 340, "Rajani", 13000 ] ,
    [ 210, "Tannu", 14000 ] ,
    [ 320, "Suresh", 35000 ] ]

for i in range(len(Data)):
    for j in range(i,len(Data) - i - 1 ):
        if Data[j][2] > Data[j + 1] [2]:
            Data[j],Data[j + 1] = Data[j +
1],Data[j]

print(Data)
```

```
PROBLEMS   OUTPUT   DEBUG CONSOLE   TERMINAL   PORTS   GITLENS   AZURE
PS D:\Project\Python2025> & C:/Users/91848/AppData/Local/Programs/Python/Python311/python.exe d:/Project/Python2025/Test5/t5_q3.py
[[340, 'Rajani', 13000], [210, 'Tannu', 14000], [320, 'Suresh', 35000], [101, 'Seema', 45000]]
PS D:\Project\Python2025>
```

```python
# q4
list1 = [1,3,4,1,2,3,6,7,1,2,4]
print(list1)
md = dict()
```

```python
for element in list1:

    if( element in md ):
        md[element] += 1

    else:
        md[element] = 1

print(md)
```

```
PROBLEMS   OUTPUT   DEBUG CONSOLE   TERMINAL   PORTS   GITLENS   AZURE
PS D:\Project\Python2025> & C:/Users/91848/AppData/Local/Programs/Python/Python311/python.exe d:/Projec
t/Python2025/Test5/t5_q4.py
[1, 3, 4, 1, 2, 3, 6, 7, 1, 2, 4]
{1: 3, 3: 2, 4: 2, 2: 2, 6: 1, 7: 1}
PS D:\Project\Python2025>
```

```python
# q5

l1 = [1,2,3,4,5]
l2 = [1,2,6,7,8,9,70]
new_list = []
l3 = l1 + l2
for i in l3:
    if (i not in new_list):
        new_list.append((i))
print(new_list)
```

```
PROBLEMS   OUTPUT   DEBUG CONSOLE   TERMINAL   PORTS   GITLENS   AZURE
PS D:\Project\Python2025> & C:/Users/91848/AppData/Local/Programs/Python/Python311/python.exe d:/Projec
t/Python2025/Test5/t5_q5.py
[1, 2, 3, 4, 5, 6, 7, 8, 9, 70]
PS D:\Project\Python2025>
```