```python
# name of first file is vehicle.py
from abc import ABC, abstractmethod
# Abstract base class
class Vehicle(ABC):
    def __init__(self, num_persons=0):
        self.num_persons = num_persons
    @abstractmethod
    def calculate_toll(self):
        pass
# name of second file is twowheeler.py
from vehicle import Vehicle
# Two wheeler
class TwoWheeler(Vehicle):
    def __init__(self, num_persons=0):
        super().__init__(num_persons)

    def calculate_toll(self):
        base_toll = 20

        if self.num_persons > 2:
            extra = (self.num_persons - 2) * 10
            return base_toll + extra
        else:
            return base_toll

# name of third file is threewheeler.py
from vehicle import Vehicle
# Three wheeler
class ThreeWheeler(Vehicle):
    def __init__(self, num_persons=0):
        super().__init__(num_persons)

    def calculate_toll(self):
        base_toll = 30
```

```
        extra = 0
        if self.num_persons > 3:
            extra = (self.num_persons - 3) * 20
        return base_toll + extra

# name of fourth file is fourwheeler.py
from vehicle import Vehicle
# Four wheeler
class FourWheeler(Vehicle):
    def __init__(self, num_persons=0):
        super().__init__(num_persons)

    def calculate_toll(self):
        base_toll = 40
        extra = 0
        if self.num_persons > 4:
            extra = (self.num_persons - 4) * 40
        return base_toll + extra

# name of fifth file is heavyvehicle.py
from vehicle import Vehicle
# heavy vehicle
class HeavyVehicle(Vehicle):
    def __init__(self, num_persons=0):
        super().__init__(num_persons)

    def calculate_toll(self):
        base_toll = 60
        extra = 0
        if self.num_persons > 6:
            extra = (self.num_persons - 6) * 60
        return base_toll + extra

# name of main file is main.py
```

```python
# from vehicle import Vehicle
from twowheeler import TwoWheeler
from threewheeler import ThreeWheeler
from fourwheeler import FourWheeler
from heavyvehicle import HeavyVehicle

def main():
    while True:
        print("\n--- Toll Calculator Menu ---")
        print("1. Two Wheeler")
        print("2. Three Wheeler")
        print("3. Four Wheeler")
        print("4. Heavy Vehicle")
        print("5. Exit")

        ch = int(input("Enter your choice (1-5): "))

        if (ch == 5):
            print("Done. Thank You!!")
            break

        elif (ch < 1 or ch > 5):
            print("Invalid choice. Select from number 1 to 5.")
            break

        persons = int(input("Enter number of persons in vehicle: "))


        if (persons < 0):
            print("Number of persons can't be negative.")
```

```python
            break

        elif (ch == 1):
            vehicle = TwoWheeler(persons)
        elif (ch == 2):
            vehicle = ThreeWheeler(persons)
        elif (ch == 3):
            vehicle = FourWheeler(persons)
        elif (ch == 4):
            vehicle = HeavyVehicle(persons)

        toll = vehicle.calculate_toll()
        print("Total toll to be paid", "Rs.", toll)

if __name__ == "__main__":
    main()
```

output:

```
PROBLEMS   OUTPUT   DEBUG CONSOLE   TERMINAL   PORTS   GITLENS   AZURE   COMMENTS                    Python

PS D:\Project\Python2025> & C:/Users/91848/AppData/Local/Programs/Python/Python311/python.exe d:/Project/
Python2025/Test6/main.py

--- Toll Calculator Menu ---
1. Two Wheeler
2. Three Wheeler
3. Four Wheeler
4. Heavy Vehicle
5. Exit
Enter your choice (1-5): 1
Enter number of persons in vehicle: 3
Total toll to be paid Rs. 30

--- Toll Calculator Menu ---
1. Two Wheeler
2. Three Wheeler
3. Four Wheeler
4. Heavy Vehicle
5. Exit
Enter your choice (1-5):

Ln 37, Col 44   Spaces: 4   UTF-8   CRLF   Python   3.11.0   Go Live   Kite: ready
```