

Introduction

This document describes how the TEI standard was customized for the project *Lectures that Link*. The project focuses on building a data collection of Digital Humanities lecture series hosted by European institutions between 2014 and early 2025. The primary emphasis is on the lecture series themselves, the individual lectures within these series, and the speakers involved. Detailed descriptions of who these data were collected and encoded in TEI are provided in the following sections, with examples included in the running text.

Data Sources and Strategy for Data Selection and Capture

All data used in this project was exclusively sourced from publicly accessible websites, ensuring that only freely available information was included. Data behind authentication barriers, such as those requiring login credentials, was deliberately excluded from the collection process.

In addition to textual information about the lecture series found on individual websites, additional digital materials related to the events were incorporated into the project. These sources were accessed via hyperlinks found on the websites and include presentations, blog posts, related articles, and audiovisual content, such as videos.

While every effort has been made to ensure the dataset is comprehensive within the scope of the project, it does not claim to be exhaustive or definitive. Instead, it serves as a solid foundation for both the current and future analyses.

TEI Encoding of Lecture Series

Hierarchical Organization: Series, Terms, and Lectures

All lecture series are recorded in the <listEvent> element, which is located within <body>, a sub-element of <text>. To accurately reflect the inherent structure of lecture series, the XML is organized hierarchically. The term *lecture series* implies a three-tiered structure:

- The overarching series, representing the general lecture program.
- Individual editions or rounds of a series, typically aligned with academic semesters or other specific time periods.
- Individual lectures, which form the lowest hierarchical level, with most information.

To represent this hierarchy, the following approach is used:

Each lecture series is recorded within an `<event>` element, with the *type* attribute set to the value *lecture-series*. Additionally, the *where* attribute references the ID of the location where the series is hosted:

```
<event type="lecture-series"
  where="#rostock" xml:id="ls10">
  <eventName xml:lang="de">Digital Humanities im Fokus: Methoden, Anwen-
  dungen und
    Perspektiven</eventName>
  <eventName xml:lang="en">Digital Humanities in Focus: Methods, Applicati-
  ons, and
    Perspectives</eventName>
</event>
```

The `<event>` element contains an `<eventName>` sub-element, which records the original name of the series. The *xml:lang* attribute specifies the language of the lecture series name. If official translations exist, multiple `<eventName>` elements may be listed sequentially, as can be seen above.

Each lecture series consists of at least one, but usually multiple `<event>` elements, each representing an instance of the lecture series, for instance, an academic term in which the series took place. These `<event>` elements include a *type* attribute with the value *lecture-series-term*, as well as the attributes *from* and *to* indicating the term's duration (year and month):

```
<event from="2023-04" to="2024-07"
  type="lecture-series-term" xml:id="ls10_t1">
  <eventName xml:lang="de">Sommersemester 2023</eventName>
  <ptr target="https://web.archive.org/web/20241114133706/https://
  www.germanistik.uni-rostock.de/forschung/digital-humanities/rosdh/
  ringvorlesung/2023/"
  type="programme"/>
</event>
```

If a consolidated program overview is available for a given term, a `<ptr>` element is included after the `<eventName>` element. The *type* attribute of `<ptr>` is set to the value *programme* to indicate its purpose.

After these term-level `<event>` elements, individual lectures are recorded, as explained in the following sections.

Encoding Individual Lectures

A individual lecture is recorded as an `<event>` element with the attribute *type* (with the value *lecture*) and with the attribute *when*, which specifies the date of the event in the format year-month-day. The structure of the content within each `<event>` element remains consistent across all lectures. Therefore, it is described in the following subsections from top to bottom, using the example below:

```
<event type="lecture" when="2024-12-02"
  xml:id="ls10_t4_l7">
```

<eventName xml:lang="de">KI generiert Texte – Wie? und Warum? – Nachdenken eines

Informations- und Kommunikationswissenschaftlers</eventName>

<note type="abstract" xml:lang="de">

<p>Texte sind allgegenwärtig und es liegt nahe, Textproduktion zu automatisieren.

Texte können (über)lebenswichtig sein, daher ist ein Nachdenken darüber, wie Texte

funktionieren und was sie mit uns und wir mit ihnen machen, notwendig.

KI-generierte Texte verändern die Textwelt, ohne dass wir es notwendigerweise

bemerken. Die Perspektive der Sprach- und Kommunikationswissenschaft kann auf

Punkte hinweisen, worüber nachzudenken lohnen könnte.</p>

<p>Hier knüpft der Vortrag des Informatikers Clemens Cap an. Er schildert, wie große

Sprachmodelle wie beispielsweise ChatGPT heute aufgebaut sind. Daraus ergeben sich

unmittelbar die derzeitigen Fähigkeiten und Grenzen solcher Systeme. Der Kreis zum

Vortrag von Wolfgang Sucharowski schließt sich nun, wenn wir erkennen, dass seine

Beobachtungen keine Spekulationen sondern unmittelbare Konsequenzen aus der

Architektur solcher Systeme sind.</p>

</note>

<note type="keywords">

<term corresp="#german-studies #computer-science" type="discipline"/>

<term corresp="https://vocabs.dariah.eu/tadirah/commenting https://vocabs.dariah.eu/tadirah/machineLearning" type="topic"/>

</note>

<note type="realization">

<term type="speech">in person</term>

<term type="audience">hybrid</term>

</note>

<ptr target="https://web.archive.org/web/20241210104406/https://www.germanistik.uni-rostock.de/forschung/digital-humanities/rosdh/ringvorlesung/2024-25/n/ki-generiert-texte-wie-und-warum-nachdenken-eines-informations-und-kommunikationswissenschaftlers-202261/" type="programme"/>

<ptr target="https://doi.org/10.5281/zenodo.14525161" type="slides"/>

<listPerson>

<person corresp="#cap_clemens" role="speaker">

<name>

```

    <roleName type="title">Prof. Dr.</roleName>
  </name>
  <affiliation corresp="#uni-rostock"/>
</person>
<person corresp="#sucharowski_wolfgang"
  role="speaker">
  <name>
    <roleName type="title">Prof. Dr.</roleName>
  </name>
  <affiliation corresp="#uni-rostock"/>
</person>
</listPerson>
<org corresp="#uni-rostock"
  role="host-institution"/>
</event> [...]
<org corresp="#henny-krahmer_ulrike #alvares-freire_fernanda #renz_erik"
  role="organizer"/>

```

Titles and Abstracts

At the beginning of each entry, the lecture title is recorded using an `<eventName>` element. The language of the title is specified via the `xml:lang` attribute.

Directly below the title, the abstract of the lecture follows. This is captured within a `<note>` element, which is characterized by the `type` attribute set to the value `abstract`. Additionally, the `xml:lang` attribute specifies the language of the abstract.

```

<eventName xml:lang="de">KI generiert Texte - Wie? und Warum? - Nachdenken eines
Informations- und Kommunikationswissenschaftlers</eventName>
<note type="abstract" xml:lang="de">
  <p>Texte sind allgegenwärtig und es liegt nahe, Textproduktion zu automatisieren.
  Texte können (über)lebenswichtig sein, daher ist ein Nachdenken darüber, wie Texte
  funktionieren und was sie mit uns und wir mit ihnen machen, notwendig.
  KI-generierte Texte verändern die Textwelt, ohne dass wir es notwendigerweise
  bemerken. Die Perspektive der Sprach- und Kommunikationswissenschaft kann auf
  Punkte hinweisen, worüber nachzudenken lohnen könnte.</p>
  <p>Hier knüpft der Vortrag des Informatikers Clemens Cap an. Er schildert,
  wie große
  Sprachmodelle wie beispielsweise ChatGPT heute aufgebaut sind. Daraus ergeben sich
  unmittelbar die derzeitigen Fähigkeiten und Grenzen solcher Systeme. Der
  Kreis zum

```

Vortrag von Wolfgang Sucharowski schließt sich nun, wenn wir erkennen, dass seine

Beobachtungen keine Spekulationen, sondern unmittelbare Konsequenzen aus der

Architektur solcher Systeme sind.</p>

</note>

As the example above already shows, the abstract text itself is recorded within one or more <p> elements. If a list is included within the abstract, a <list> element is used, with individual list items represented by <item> elements.

If the abstract contains formatting elements such as bold, italics, or hyperlinks, these are not explicitly marked up.

If an abstract is available, it is recorded within the <note type="abstract"> tag. If no abstract is provided, the content of the note is set to "not found":

<note type="abstract" xml:lang="en">not found</note>

Keywords

Each recorded lecture is assigned keywords by the encoders to be able to analyze the distribution of disciplines, methods and topics across the lectures and lecture series. That is, the keywords are not collected from the websites of the lecture series but they are added by the editors of this data collection.

The keywords are stored inside of a <note> element, characterized by the attribute *type* with the value *keywords*. Within this <note> element, there are two <term> elements:

- One with <type="discipline">, specifying the academic discipline or disciplines covered by the talk.
- One with <type="topics-llm">, indicating the topics of the talk.

<note type="keywords">

<term corresp="#literary-studies"

type="discipline"/>

<term type="topics-llm">evolution, cultural change, computational methods, literature trends, causal mechanisms</term>

</note>

In case that there is more than one discipline, it is collected in the *corresp* attribute of the same <term> element. We opted for this (instead of using an individual <term> element for each keyword) to facilitate later processing of the data and for a more compact encoding of the information. For the disciplines, we use a pre-defined list that we created on our own. The topics were generated with a script calling an LLM.

Both discipline and topic assignments are based on the lecture content. This classification relies on the abstract and title of the lecture. Since every lecture has a title but not necessarily an abstract, classification is always possible. However, a longer title or the presence of an abstract allows for a more precise categorization.

Realization (Lecture Modality)

The lecture modality is recorded in the `<note type="realization">` tag, specifying whether the lecture was held in person, hybrid, or online. The `<note>` element contains two `<term>` sub-elements that define the modality separately for speakers and audience members. These `<term>` elements use the *type* attribute to distinguish between the modality of the speech and of the audience:

- `<term type="speech">`: Describes how the speakers delivered the lecture.
- `<term type="audience">`: Describes how the audience attended the lecture.

```
<note type="realization">  
  <term type="speech">in person</term>  
  <term type="audience">hybrid</term>  
</note>
```

The values for these elements are standardized to ensure consistency in data representation. The possible values are:

- *in person*: All participants (speakers or audience) were physically present at the lecture venue.
- *hybrid*: At least one participant (speaker or audience member) joined remotely, while others were present in person.
- *online*: All participants attended virtually; no one was physically present at the venue.

If a lecture was canceled, a fourth value, *canceled*, is used. In this case, as shown in the example below, the `<term type="audience">` tag is omitted since no audience attended:

canceled

Speakers, Titles, and Affiliation

The speakers of a lecture are recorded in a `<listPerson>` element. Each speaker is described using a `<person>` element with a *corresp* attribute that links to the corresponding person entry in the TEI header. The academic title (if provided) is stored within a `<roleName type="title">` element inside of the `<name>` element. The speaker's affiliation is captured within an `<affiliation>` element, referencing the corresponding institution, which is encoded in the TEI header. The information about the speakers, their affiliations, and the institutions is encoded in two places for the following reasons: on the one hand, we aim to have a centralized list of people and institutions in the TEI header, to which we can refer from individual events. On the other hand, the affiliations of people can change over time and the same is true for their titles. One person might not have a title at the moment of one event, but might have a title at another event later on, for instance, if someone completed his or her PhD. Therefore, information about the current affiliation of a speaker at the moment of the event and about the current title that a person has when the

event takes place is encoded directly inside of the individual event.

```
<listPerson>
  <person corresp="#cap_clemens"
    role="speaker">
    <name>
      <roleName type="title">Prof. Dr.</roleName>
    </name>
    <affiliation corresp="#uni-rostock"/>
  </person>
  <person corresp="#sucharowski_wolfgang"
    role="speaker">
    <name>
      <roleName type="title">Prof. Dr.</roleName>
    </name>
    <affiliation corresp="#uni-rostock"/>
  </person>
</listPerson>
```

The titles of the speaker(s) are recorded according to the information provided in the lecture program, supporting materials (slides, videos, or blog posts), or a short biography. Common academic titles include:

- Dr. / Dr.-Ing. / PhD
- PD (Priv.-Doz.)
- Asst. Prof. / Assoc. Prof. / Jun.-Prof. / Prof. (Univ.-Prof.)

These titles are standardized. For instance, "Univ.-Prof." is simplified to "Prof.", and variations in spelling (e.g., "PhD" and "Ph.D.") are standardized.

Academic degrees such as *Bakkalaureus Artium* / *Bachelor of Arts (B.A.)* and *Magister Artium* / *Master of Arts (M.A.)* are not recorded, as they are typically not included in the program. Similarly, if no title is available, the value *not found* is used:

```
<listPerson>
  <person corresp="#theise_antje"
    role="speaker">
    <name>
      <roleName type="title">not found</roleName>
    </name>
    <affiliation corresp="#ub-rostock"/>
  </person>
</listPerson>
```

Hosts and Organizers

Hosts are recorded at the end of the individual lecture entry to indicate which organizations were responsible for hosting the lecture, i.e., those that invited the speaker(s). The host institution is specified with an `<org>` element that includes the attribute *role* with the standardized value *host-institution*. The *corresp* attribute references the corresponding organization entry in the TEI

header. This value is recorded independently of the lecture modality (i.e., in presence, hybrid, or online).

```
<org corresp="#uni-rostock"
  role="host-institution"/>
```

As mentioned above, information about the hosting institutions concludes the section for an individual lecture. However, the final element within a lecture series term is the information about the organizers of the term. This information is stored within an `<org>` element with the attribute *role* and the standardized value *organizer*.

```
<org corresp="#henny-krahmer_ulrike #alvares-freire_fernanda #renz_erik"
  role="organizer"/>
```

Unlike host institutions, which are organizations, organizers are recorded as individual persons, as can be seen in the example above. It is possible for an organizer to also be a speaker in another lecture series or even in their own series.

Since organizational responsibility can change from term to term, it is considered appropriate to record this information at this level rather than for the entire series.

Creating IDs

The dataset assigns unique IDs to lecture series, lecture series terms, individual lectures, persons, organizations, and locations, which are consistently stored in the *xml:id* attribute. The following aspects must be considered when creating IDs:

- Lowercase only: All IDs are written exclusively in lowercase.
- No numbers: Numbers are not used in IDs.
- Latin script only: The Latin script is consistently applied.
- No diacritical marks: Diacritical marks (e.g., ä, ö, ü, â, ê, î) are completely removed or replaced with corresponding transliterations (e.g., ä → ae, ö → oe, è → e).

Additional considerations include:

- Standardized prefixes: Certain IDs, such as those for universities, always begin with a fixed prefix (e.g., *uni-* for universities, *fh-* for universities of applied sciences).
- Use of hyphens and underscores: Two types of separators are used in the dataset:
 - Underscores (`_`) are used exclusively for person IDs, separating the surname from the given name.
 - Hyphens (`-`) are used for organizations and locations to separate individual name components (e.g., multi-word city names). In person IDs, hyphens are used to connect multiple given names or multiple surnames.

Capturing Language

All collected information is recorded exclusively in the languages in which it appears on the respective websites. Each element of a lecture event that contains textual information in a certain language is marked with the attribute *xml:lang*, specifying the corresponding language value, such as *en* for English or *de* for German. No translations of content are produced.

The documentation of series, terms and lectures is mainly focused on English, Italian, German, Spanish, French and Portuguese, due to the language knowledge of the collaborators in this project. Other languages can be included, especially when it comes to recording the names of organizations or places. By default, these informations are documented in the language in which they originally emerged, which may differ from the respective national language.

In some cases, a title may include multiple languages, whether for stylistic reasons or because it contains a key term discussed in the lecture or an introductory quotation. In such instances, only the primary language of the title is recorded, while additional languages are not documented, as shown in the following example:

```
<eventName xml:lang="en">Le chemin de l'image in Renaissance Lyon: digital tools for the study of early modern illustrations</eventName>
<note type="abstract" xml:lang="en">
  <p>The talk will focus on the study of digital collections of early modern printed books and on the implementation of the Imagematching software in cooperation with the Visual Geometry Group of Department of Engineering Science at University of Oxford. In the research project The Early Modern Illustrated Book in Lyon (Equipex Biblissima/Ca' Foscari), the art historian Barbara Tramelli developed a new methodology for the study of book illustrations, using and implementing for her research Renaissance images two digital tools: [...]</p>
</note>
```

In such cases, the primary language of the element must be identified and recorded. In the example above, this would be English. The primary language can often be determined by identifying which part of the content conveys the core subject matter rather than serving a decorative or stylistic function. For titles, another useful indicator is the language of the accompanying abstract, if available.

Capturing Links

In order to ensure the long-term accessibility and reliability of information, we secure all relevant sources via links, which are then archived using the

Wayback Machine from the Internet Archive (<https://web.archive.org/>). This archiving process applies to all links, except for DOI links, which are permanent by definition and do not require additional archiving. However, links that lead to videos, such as those on YouTube, are not archived because archiving by the Wayback Machine is not possible in this case.

All links within the dataset are encoded using the <ptr> (pointer) element. Within this element, the *type* attribute is used to specify the exact role of the link, as seen in the following examples:

```
<ptr target="https://web.archive.org/web/20230609113732/https://
www.unive.it/data/33113/2/38661"
type="programme"/>
<ptr target="https://doi.org/10.5281/zenodo.7798685"
type="slides"/>
<ptr target="https://www.youtube.com/watch?v=itVMXEEKZFQ"
type="video"/>
<ptr target="https://doi.org/10.58079/o57z"
type="blogpost"/>
```

The values for the *type* attribute are as follows:

- *programme*: Refers to a complete programme for a semester or event series, or to a dedicated page for a specific lecture.
- *slides*: Points to presentation slides, such as PDFs or PowerPoint files.
- *video*: Links to a video recording of the lecture, including the presentation and possibly the discussion. These links are not archived.
- *blogpost*: Directs to a blog post discussing the lecture, potentially featuring parts of the presentation, speaker information, or related images.

It is important to highlight that we only capture links that directly originate from the lecture series' website. While further research to gather additional sources is possible, it has not been consistently carried out.

Capturing Organizations

Organizations involved in Digital Humanities lecture series are divided into two main roles: the affiliation of the (invited) speaker and the hosting venue.

In most cases, organizations are listed at the level of entire universities, research institutions, or cultural institutions. Specific departments or institutes within these organizations, where speakers may be affiliated, are not captured in the data. E.g. if an affiliation to the Institute of German Studies at the University of Rostock is mentioned in a program, only the University of Rostock is encoded.

Each organization is represented by a separate entry within the <particDesc> element, found under <listOrg>. The <org> sub-element defines the organization and is assigned a unique ID through the *xml:id* attribute. This ID is used throughout the dataset to ensure consistent referencing. Additionally, the *type* attribute within the <org> element is employed to specify the

organization's precise role. Available values for the *type* attribute include:

- *university*: for universities and universities of applied sciences
- *research_institution*: for private or public institutions that conduct research
- *company*: for companies or private sector organizations
- *glam*: for galleries, libraries, archives, museums; generally, all cultural and memory institutions
- *other*: we use this when none of the categories listed above apply, for example in the case of radio stations or newspapers.

As can be seen in the example below, the "Università di Bologna" is represented as an organization with the ID *uni-bologna*. The name of the organization is presented in the original language (Italian, in this case), and an external Wikidata identifier is included within the `<idno>` element.

```
<org type="university" xml:id="uni-bologna">
  <name xml:lang="it">Università di Bologna</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q131262</idno>
  <place corresp="#bologna"/>
</org>
```

Universities

As described above, all organizations, including all university entries, are assigned an ID. Unlike those of other organizations, university IDs always begin with *uni-* or *fh-* followed by a unique part, typically derived from the name or location of the institution. For example, the University of Rostock is captured as follows:

```
<org type="university" xml:id="uni-rostock">
  <name xml:lang="de">Universität Rostock</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q159895</idno>
  <place corresp="#rostock"/>
</org>
```

In order to maintain clarity and allow for future adjustments, the names of universities are standardized. For instance, "Julius-Maximilians-Universität Würzburg" is shortened to "Universität Würzburg", and the corresponding ID becomes *uni-wuerzburg*:

```
<org type="university"
xml:id="uni-wuerzburg">
  <name xml:lang="de">Universität Würzburg</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q161976</idno>
  <place corresp="#wuerzburg"/>
</org>
```

This simplification also reduces the need for updates when a university undergoes rebranding or changes its name, such as in the case of the recent shift in Münster from "Westfälische Wilhelms-Universität Münster" to "Universität Münster".

When multiple universities exist within the same city, additional distinctions

are added to the ID to avoid confusion. These distinctions are appended to the base ID formed by the university's type and location. For example, in London, where several institutions exist, their IDs are distinguished as follows:

```
<org type="university"
xml:id="uni-london-city">
  <name xml:lang="en">City, University of London</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q1094046</idno>
  <place corresp="#london"/>
</org>
<org type="university"
xml:id="uni-london-ucl">
  <name xml:lang="en">University College London</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q193196</idno>
  <place corresp="#london"/>
</org>
<org type="university"
xml:id="uni-london-kcl">
  <name xml:lang="en">King's College London</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q245247</idno>
  <place corresp="#london"/>
</org>
```

In contrast, Berlin presents another situation, as the German naming convention is that distinctions should precede the city name, resulting in IDs such as:

```
<org type="university"
xml:id="uni-fu-berlin">
  <name xml:lang="de">Freie Universität Berlin</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q153006</idno>
  <place corresp="#berlin"/>
</org>
<org type="university"
xml:id="uni-hu-berlin">
  <name xml:lang="de">Humboldt-Universität zu Berlin</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q152087</idno>
  <place corresp="#berlin"/>
</org>
<org type="university"
xml:id="uni-tu-berlin">
  <name xml:lang="de">Technische Universität Berlin</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q51985</idno>
  <place corresp="#berlin"/>
</org>
```

As with all organizations in the dataset, each university is assigned an external identifier, referenced through the `<idno>` element, which refers to the university's Wikidata entry.

Research Institutions

Research institutions are identified using the *type* attribute with the value *research_institution*. This category includes private and public research organizations that are not classified as universities.

```
<org type="research_institution"
  xml:id="research-mpi">
  <name xml:lang="de">Max-Planck-Institut für Wissenschaftsgeschichte</
name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q685399</idno>
  <place corresp="#berlin"/>
</org>
```

The structure follows the same pattern as universities, ensuring consistency across all organization types.

GLAM Institutions

GLAM organizations (Galleries, Libraries, Archives, and Museums) are identified using the *type* attribute with the value *glam*. The IDs for GLAM organizations are usually derived from existing abbreviations.

```
<org type="glam" xml:id="museum-snm">
  <name xml:lang="de">Schweizerisches Nationalmuseum (SNM)</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q2256718</idno>
  <place corresp="#zuerich"/>
</org>
```

To facilitate clear differentiation, prefixes such as *museum-*, *library-*, *gallery-*, and *archive-* are used in IDs when applicable. If an institution does not fit these categories, an existing abbreviation serves as the identifier:

```
<org type="glam" xml:id="spk">
  <name xml:lang="de">Stiftung Preußischer Kulturbesitz (SPK)</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q685171</idno>
  <place corresp="#berlin"/>
</org>
```

Companies

The *company* category includes both private and public organizations that are not primarily engaged in academic research. This encompasses commercial enterprises as well as organizations funded through grants or sponsorships, such as those providing infrastructure or research support.

Organizations in this category are identified using the *type* attribute with the value *company*. Similar to research institutions and GLAMs, company IDs are derived from their names and, where applicable, existing abbreviations.

```
<org type="company" xml:id="wordpress">
  <name xml:lang="en">WordPress Foundation</name>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q56787199</idno>
```

```

    <place corresp="#san-francisco"/>
  </org>
  <org type="company" xml:id="pagina">
    <name xml:lang="de">pagina Publikationstechnologien</name>
    <idno type="wikidata">https://www.wikidata.org/wiki/Q131538003</idno>
    <place corresp="#weil-der-stadt"/>
  </org>

```

Capturing Persons

Each speaker included in the dataset is represented by an individual entry within the `<listPerson>` element, specifically under `<particDesc>`.

To ensure consistent identification, every speaker is assigned a unique ID through the `xml:id` attribute. This identifier follows a standardized format, combining the speaker's surname and given name, separated by an underscore. In cases where a speaker has multiple given or family names, these are connected using hyphens. For example:

```

<person xml:id="maget-dominice_antoinette">
  <name>
    <forename>Antoinette</forename>
    <surname>Maget Dominicé</surname>
  </name>
  <gender>female</gender>
  <idno type="orcid">https://orcid.org/0000-0001-9056-4544</idno>
  <idno type="wikidata">https://www.wikidata.org/wiki/Q102211240</idno>
</person>

```

As shown above, each entry also records the speaker's social gender, represented by the `<gender>` element within the `<person>` element. The primary values for this element are *female* and *male*. The gender assignment is based primarily on the typical gender associations of given names. Additionally, where available, information from Wikidata and other external databases has been used to verify gender identity. If research indicates that a person does not fall within the binary gender spectrum, they are assigned the value *non-binary*. It should be noted that assigning gender based on name connotations is inherently prone to errors. While every effort has been made to ensure accuracy through external sources, there may still be instances where the assigned gender does not align with the individual's self-identification.

Each speaker entry includes a `<name>` element, which further contains `<forename>` and `<surname>` sub-elements. These store the full given name and surname of the individual without abbreviations or alterations.

Additionally, every speaker entry includes at least one, but typically two, `<idno>` elements. These elements reference external identifiers. One of these identifiers is the *orcid*, a researcher-specific identifier maintained by the speaker themselves, while the second is a *wikidata* ID. If a Wikidata entry does not already exist for a given speaker, a new record is created.

Capturing Locations

Each location in the dataset is represented by an individual entry within the `<listPlace>` element, specifically under `<settingDesc>`. There are three types of entries: for continents, for countries and for cities. This distinction is made using the *type* attribute, which takes either the value *continent*, *country* or *city*.

All location names are recorded in English or using the vernacular form if no English form is known, following the naming conventions in place at the time of data collection.

To ensure consistent identification, each location is assigned a unique ID using the *xml:id* attribute. In most cases, this ID matches the name of the city, country or continent. However, exceptions are made when a city shares the same name as the country it belongs to, such as Luxembourg City in Luxembourg. The same rule applies to city-states:

```
<place type="country" xml:id="singapore">
  <name>Singapore</name>
</place>
<place type="city" xml:id="singapore-city">
  <country corresp="#singapore"/>
  <name>Singapore</name>
  <idno type="tgn">http://vocab.getty.edu/page/tgn/7001488</idno>
</place>
```

Each city entry includes a `<name>` element that records the full name of the place without abbreviations or modifications. Additionally, every city entry contains a `<country>` element, which links the city to its corresponding country via the *ref* attribute.

Each city entry also includes an `<idno>` element. Using the *type* attribute, this element provides a reference to the Getty Thesaurus of Geographic Names (TGN), ensuring precise identification of the location.

```
<place type="city" xml:id="rostock">
  <country corresp="#germany"/>
  <name>Rostock</name>
  <idno type="tgn">http://vocab.getty.edu/page/tgn/7100449</idno>
</place>
```

For place names consisting of multiple words, hyphens are used to connect the words in the *xml:id* attribute:

```
<place type="city" xml:id="le-mans">
  <country ref="#france"/>
  <name>Le Mans</name>
  <idno type="tgn">http://vocab.getty.edu/page/tgn/7008494</idno>
</place>
```

TEI Specifications

Elements

<TEI>

<TEI> (TEI document) contains a single TEI-conformant document, combining a single TEI header with one or more members of the model.resource class. Multiple <TEI> elements may be combined within a <TEI> (or <teiCorpus>) element. [[4. Default Text Structure](#) [16.1. Varieties of Composite Text](#)]

Module

Attributes

textstructure

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.typed
 - *@type*
 - *@subtype*

version

specifies the version number of the TEI Guidelines against which this document is valid.
Status Optional
Datatype teidata.version

Note Major editions of the Guidelines have long been informally referred to by a name made up of the letter P (for Proposal) followed by a digit. The current release is one of the many releases of the fifth major edition of the Guidelines, known as P5. This attribute may be used to associate a TEI document with a specific release of the P5 Guidelines, in the absence of a more precise

association
 provided
 by the
source
 attribute
 on the
 associated
 <schema
 Spec>.

Contained by
May contain

Note

textstructure: TEI
 header: teiHeader
 textstructure: TEI text
 As with all elements in the TEI scheme (except <egXML>) this element is in the TEI namespace (see [5.7.2. Namespaces](#)). Thus, when it is used as the outermost element of a TEI document, it is necessary to specify the TEI namespace on it. This is customarily achieved by including `http://www.tei-c.org/ns/1.0` as the value of the XML namespace declaration (`xmlns`), without indicating a prefix, and then not using a prefix on TEI elements in the rest of the document. For example: `<TEI version="4.8.1" xml:lang="it" xmlns="http://www.tei-c.org/ns/1.0">.`

Example

```
<TEI version="3.3.0" xmlns="http://
www.tei-c.org/ns/1.0">
  <teiHeader>
    <fileDesc>
      <titleStmt>
        <title>The shortest TEI Document I
maginable</title>
      </titleStmt>
      <publicationStmt>
        <p>First published as part of TEI P
2, this is the P5
        version using a namespace.</p>
      </publicationStmt>
      <sourceDesc>
        <p>No source: this is an original wo
rk.</p>
      </sourceDesc>
```

Example

```
</fileDesc>
</teiHeader>
<text>
  <body>
    <p>This is about the shortest TEI document imaginable.</p>
  </body>
</text>
</TEI>
<TEI version="2.9.1" xmlns="http://www.tei-c.org/ns/1.0">
  <teiHeader>
    <fileDesc>
      <titleStmt>
        <title>A TEI Document containing four page images </title>
      </titleStmt>
      <publicationStmt>
        <p>Unpublished demonstration file.</p>
      </publicationStmt>
      <sourceDesc>
        <p>No source: this is an original work.</p>
      </sourceDesc>
    </fileDesc>
  </teiHeader>
  <facsimile>
    <graphic url="page1.png"/>
    <graphic url="page2.png"/>
    <graphic url="page3.png"/>
    <graphic url="page4.png"/>
  </facsimile>
</TEI>
```

Content model

```
<content>
  <sequence>
    <elementRef key="teiHeader"/>
    <alternate>
      <sequence>
        <classRef key="model.resource" maxOccurs="unbounded" minOccurs="1"/>
        <elementRef key="TEI" maxOccurs="unbounded" minOccurs="0"/>
      </sequence>
    </alternate>
  </sequence>
</content>
```

```

        maxOccurs="unbounded" minOccurs="1"/>
    </alternate>
</sequence>
</content>

```

Schema Declaration

```

element TEI
{
    tei_att.global.attributes,
    tei_att.typed.attributes,
    attribute version { text }?,
    ( tei_teiHeader, ( ( tei_model.resourc
e+, tei_TEI* ) | tei_TEI+ ) )
}

```

<affiliation>

<affiliation> (affiliation) contains an informal description of a person's present or past affiliation with some organization, for example an employer or sponsor. [[16.2.2. The Participant Description](#)]

Module

namesdates

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*

- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.editLike
 - *@evidence*
 - *@instant*
- att.naming
 - *@role*
 - *@nymRef*
 - att.canonical
 - *@key*
 - *@ref*
- att.typed
 - type
 - @subtype

type

characterizes the element in some sense, using any convenient classification scheme or typology.

Derived from att.typed

Status Optional

Datatype teidata.e
numerate
d

	Sample sponsor values include: recommend discredit pledged
Member of	model.addressLike
Contained by	model.persStateLike
	core: bibl date desc editor item name note p pubPlace publisher resp term title
	header: catDesc change licence
	namesdates: affiliation bloc country
	eventName forename gender
	nameLink person placeName
	roleName surname
May contain	core: date name note ptr term title
	header: idno
	namesdates: affiliation bloc country
	eventName forename nameLink
	placeName roleName surname
	character data
Note	If included, the name of an organization may be tagged using either the <name> element as above, or the more specific <orgName> element.
Example	<affiliation>Junior project officer for the US <name type="org">National Endowment for the Humanities</name> </affiliation>
Example	This example indicates that the person was affiliated with the Australian Journalists Association at some point between the dates listed. <affiliation notAfter="1960-01-01" notBefore="1957-02-28">Paid up member of the <orgName>Australian Journalists Association</orgName> </affiliation>
Example	This example indicates that the person was affiliated with Mount Holyoke

College throughout the entire span of the date range listed.

```
<affiliation from="1902-01-01"
to="1906-01-01">Was an assistant pr
ofessor at Mount Holyoke College.</
affiliation>
```

Content model

```
<content>
<macroRef key="macro.phraseSeq"/>
</content>
```

Schema Declaration

```
element affiliation
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.datable.attributes,
  tei_att.editLike.attributes,
  tei_att.naming.attributes,
  tei_att.typed.attribute.subtype,
  attribute type { text }?,
  tei_macro.phraseSeq
}
```

<availability>

<availability> (availability) supplies information about the availability of a text, for example any restrictions on its use or distribution, its copyright status, any licence applying to it, etc. [[2.2.4. Publication, Distribution, Licensing, etc.](#)]

Module

Attributes

```
header
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs
    • @copyOf
    • @next
    • @prev
    • @exclude
    • @select
  • att.global.rendition
    • @rend
```

	• <i>@style</i> • <i>@rendition</i> • att.global.responsibility • <i>@cert</i> • <i>@resp</i> • att.global.source • <i>@source</i> • att.declarable • <i>@default</i>
status	(status) supplies a code identifying the current availability of the text. Status Optional Datatype teidata.enumerated Legal values are: free (free) the text is freely available. unknown (unknown) the status of the text is unknown. restricted (restricted) the text

is
not
freel
y
avail
able.

Member of

Contained by

May contain

Note

Example

model.biblPart

model.publicationStmtPart.detail

core: bibl

header: publicationStmt

core: p

header: licence

A consistent format should be adopted

<availability status="restricted">

<p>Available for academic research p
urposes only.</p>

</availability>

<availability status="free">

<p>In the public domain</p>

</availability>

<availability status="restricted">

<p>Available under licence from the
publishers.</p>

</availability>

<availability>

<licence target="http://
opensource.org/licenses/MIT">

<p>The MIT License
applies to this document.</p>

<p>Copyright (C) 2011 by The Unive
rsity of Victoria</p>

<p>Permission is hereby granted, fre
e of charge, to any person obtaining a
copy

of this software and associated doc
umentation files (the "Software"), to de
al

in the Software without restriction,
including without limitation the rights
to use, copy, modify, merge, publish,
distribute, sublicense, and/or sell

copies of the Software, and to permi
t persons to whom the Software is
furnished to do so, subject to the fol
lowing conditions:</p>

<p>The above copyright notice and t
his permission notice shall be included

Example

in
all copies or substantial portions of
the Software.</p>
<p>THE SOFTWARE IS PROVIDED "
AS IS", WITHOUT WARRANTY OF ANY
KIND, EXPRESS OR
IMPLIED, INCLUDING BUT NOT LI
MITED TO THE WARRANTIES OF ME
RCHANTABILITY,
FITNESS FOR A PARTICULAR PUR
POSE AND NONINFRINGEMENT. IN
NO EVENT SHALL THE
AUTHORS OR COPYRIGHT HOLDE
RS BE LIABLE FOR ANY CLAIM, DAM
AGES OR OTHER
LIABILITY, WHETHER IN AN ACTI
ON OF CONTRACT, TORT OR OTHER
WISE, ARISING FROM,
OUT OF OR IN CONNECTION WIT
H THE SOFTWARE OR THE USE OR O
THER DEALINGS IN
THE SOFTWARE.</p>
</licence>
</availability>

Content model

```
<content>
  <alternate maxOccurs="unbounded"
    minOccurs="1">
    <classRef key="model.availabilityPar
t"/>
    <classRef key="model.pLike"/>
  </alternate>
</content>
```

Schema Declaration

```
element availability
{
  tei_att.global.attributes,
  tei_att.declarable.attributes,
  attribute status { "free" | "unknown"
| "restricted" }?,
  ( tei_model.availabilityPart | tei_mod
el.pLike )+
}
```

<bibl>

<bibl> (bibliographic citation) contains a loosely-structured bibliographic

citation of which the sub-components may or may not be explicitly tagged.

[[3.12.1. Methods of Encoding Bibliographic References and Lists of References](#) [2.2.7. The Source Description](#) [16.3.2. Declarable Elements](#)]

Module

Attributes

core

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
 - att.canonical
 - *@key*
 - *@ref*
 - att.cmc
 - *@generatedBy*
 - att.declarable
 - *@default*
 - att.docStatus
 - *@status*
 - att.sortable
 - *@sortKey*
 - att.typed
 - *@type*
 - *@subtype*

Member of

Contained by

model.biblLike model.biblPart

core: bibl desc item listBibl note p title

header: change licence sourceDesc

taxonomy

namesdates: event org person place

May contain

textstructure: body
core: bibl date editor name note ptr
pubPlace publisher respStmt term title
header: availability idno
namesdates: affiliation bloc country
eventName forename nameLink
placeName roleName surname
character data

Note

Contains *phrase-level* elements,
together with any combination of
elements from the model.biblPart class

Example

```
<bibl>Blain, Clements and Grundy: Fe  
minist Companion to Literature in Engl  
ish (Yale,  
1990)</bibl>
```

Example

```
<bibl>  
  <title level="a">The Interesting story  
of the Children in the Wood</title>. In  
<author>Victor E Neuberg</author>,  
<title>The Penny Histories</title>.  
<publisher>OUP</publisher>  
<date>1968</date>.  
</bibl>
```

Example

```
<bibl subtype="book_chapter" type=""  
article"  
xml:id="carlin_2003">  
  <author>  
    <name>  
      <surname>Carlin</surname>  
      (<forename>Claire</  
forename>)</name>  
    </author>,  
    <title level="a">The Staging of Impot  
ence : France's last  
congrès</title> dans  
<bibl type="monogr">  
  <title level="m">Theatrum mundi : s  
tudies in honor of Ronald W.  
Tobin</title>, éd.  
  <editor>  
    <name>  
      <forename>Claire</forename>  
      <surname>Carlin</surname>  
    </name>  
  </editor> et  
  <editor>  
    <name>
```

```

        <forename>Kathleen</forename>
        <surname>Wine</surname>
    </name>
</editor>,
    <pubPlace>Charlottesville, Va.</
pubPlace>,
    <publisher>Rookwood Press</
publisher>,
    <date when="2003">2003</date>.
</bibl>
</bibl>

```

Content model

```

<content>
<alternate maxOccurs="unbounded"
minOccurs="0">
    <textNode/>
    <classRef key="model.gLike"/>
    <classRef key="model.highlighted"/>
    <classRef key="model.pPart.data"/>
    <classRef key="model.pPart.edit"/>
    <classRef key="model.segLike"/>
    <classRef key="model.ptrLike"/>
    <classRef key="model.biblPart"/>
    <classRef key="model.global"/>
</alternate>
</content>

```

Schema Declaration

```

element bibl
{
    tei_att.global.attributes,
    tei_att.canonical.attributes,
    tei_att.cmc.attributes,
    tei_att.declarable.attributes,
    tei_att.docStatus.attributes,
    tei_att.sortable.attributes,
    tei_att.typed.attributes,
    (
        text
        | tei_model.gLike
        | tei_model.highlighted
        | tei_model.pPart.data
        | tei_model.pPart.edit
        | tei_model.segLike
        | tei_model.ptrLike
        | tei_model.biblPart
        | tei_model.global
    )*
}

```

}

<bloc>

<bloc> (bloc) contains the name of a geo-political unit consisting of two or more nation states or countries. [[14.2.3. Place Names](#)]

Module

namesdates

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*

	• <i>@to-iso</i> • att.dataable.w3c • <i>@when</i> • <i>@notBefore</i> • <i>@notAfter</i> • <i>@from</i> • <i>@to</i> • att.naming • <i>@role</i> • <i>@nymRef</i> • att.canonical • <i>@key</i> • <i>@ref</i> • att.typed • <i>@type</i> • <i>@subtype</i>
Member of	model.placeNamePart
Contained by	core: bibl date desc editor item name note p pubPlace publisher resp term title header: catDesc change licence namesdates: affiliation bloc country eventName forename gender nameLink org place placeName roleName surname
May contain	core: date name note ptr term title header: idno namesdates: affiliation bloc country eventName forename nameLink placeName roleName surname character data
Example	<bloc type="union">the European Uni on</bloc> <bloc type="continent">Africa</bloc>
Content model	<content> <macroRef key="macro.phraseSeq"/> </content>
Schema Declaration	element bloc { tei_att.global.attributes, tei_att.cmc.attributes, tei_att.dataable.attributes, tei_att.naming.attributes, tei_att.typed.attributes, tei_macro.phraseSeq

}

<body>

<body> (text body) contains the whole body of a single unitary text, excluding any front or back matter. [[4. Default Text Structure](#)]

Module

Attributes

textstructure

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.declaring
 - *@decls*

Contained by

May contain

textstructure: text

core: bibl desc list listBibl note p

namesdates: listEvent listOrg

listPerson listPlace

Example

<body>

<l>Nu scylun hergan hefaenricaes uard</l>

<l>metudæs maecti end his modgidanc</l>

<l>uerc uuldurfadur sue he uundra gi huaes</l>

<l>eci dryctin or astelidæ</l>

<l>he aerist scop aelda barnum</l>

<l>heben til hrofe haleg scepen.</l>

<l>tha middungeard moncynnæs uar

Content model

```
d</l>
<l>eci dryctin æfter tiadæ</l>
<l>firum foldu frea allmectig</l>
<trailer>primo cantauit Cædmon istu
d carmen.</trailer>
</body>

<content>
<sequence>
<classRef key="model.global"
maxOccurs="unbounded" minOccurs
="0"/>
<sequence minOccurs="0">
<classRef key="model.divTop"/>
<alternate maxOccurs="unbounded"
minOccurs="0">
<classRef key="model.global"/>
<classRef key="model.divTop"/>
</alternate>
</sequence>
<sequence minOccurs="0">
<classRef key="model.divGenLike"/
>
<alternate maxOccurs="unbounded"
minOccurs="0">
<classRef key="model.global"/>
<classRef key="model.divGenLike"/
>
</alternate>
</sequence>
<alternate>
<sequence maxOccurs="unbounded"
minOccurs="1">
<classRef key="model.divLike"/>
<alternate maxOccurs="unbounded"
"
minOccurs="0">
<classRef key="model.global"/>
<classRef key="model.divGenLike"/
>
</alternate>
</sequence>
<sequence maxOccurs="unbounded"
minOccurs="1">
<classRef key="model.div1Like"/>
<alternate maxOccurs="unbounded"
"
minOccurs="0">
```

```

        <classRef key="model.global"/>
        <classRef key="model.divGenLike"/>
    >
        </alternate>
    </sequence>
    <sequence>
        <sequence maxOccurs="unbounded"
"
            minOccurs="1">
                <alternate maxOccurs="1" minOcc
urs="1">
                    <elementRef key="schemaSpec"/>
                    <classRef key="model.common"/>
                </alternate>
                <classRef key="model.global"
maxOccurs="unbounded" minOccu
rs="0"/>
            </sequence>
            <alternate minOccurs="0">
                <sequence maxOccurs="unbounde
d"
                    minOccurs="1">
                        <classRef key="model.divLike"/>
                    <alternate maxOccurs="unbounde
d"
                        minOccurs="0">
                            <classRef key="model.global"/>
                            <classRef key="model.divGenLike
"/>
                        </alternate>
                    </sequence>
                <sequence maxOccurs="unbounde
d"
                    minOccurs="1">
                        <classRef key="model.div1Like"/>
                    <alternate maxOccurs="unbounde
d"
                        minOccurs="0">
                            <classRef key="model.global"/>
                            <classRef key="model.divGenLike
"/>
                        </alternate>
                    </sequence>
                </alternate>
            </sequence>
        <sequence maxOccurs="unbounded"
minOccurs="0">

```

```

    <classRef key="model.divBottom"/>
    <classRef key="model.global"
      maxOccurs="unbounded" minOccurs="0"/>
  </sequence>
</sequence>
</content>

```

Schema Declaration

```

element body
{
  tei_att.global.attributes,
  tei_att.declaring.attributes,
  (
    tei_model.global*,
    ( ( tei_model.divTop, ( tei_model.global | tei_model.divTop )* )? ),
    (
      ( tei_model.divGenLike, ( tei_model.global | tei_model.divGenLike )* )?
    ),
    (
      (
        ( tei_model.divLike, ( tei_model.global | tei_model.divGenLike )* )+
      )
      | (
        (
          tei_model.div1Like,
          ( tei_model.global | tei_model.divGenLike )*
        )+
      )
      | (
        ( ( ( schemaSpec | tei_model.common ), tei_model.global* )+ ),
        (
          (
            (
              tei_model.divLike,
              ( tei_model.global | tei_model.divGenLike )*
            )+
          )
          | (
            (
              tei_model.div1Like,
              ( tei_model.global | tei_model

```

```

del.divGenLike )*
        )+
    )
    )?
)
),
( ( tei_model.divBottom, tei_model.
global* )*)
)
}

```

<catDesc>

<catDesc> (category description) describes some category within a taxonomy or text typology, either in the form of a brief prose description or in terms of the situational parameters used by the TEI formal <textDesc>.

[\[2.3.7. The Classification Declaration\]](#)

Module

header

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
 - att.canonical
 - *@key*
 - *@ref*

Contained by

May contain

header: category

core: date name ptr term title

header: idno

Example Example

```
namesdates: affiliation bloc country
eventName forename nameLink
placeName roleName surname
character data
<catDesc>Prose reportage</catDesc>
<catDesc>
  <textDesc n="novel">
    <channel mode="w">print; part issu
es</channel>
    <constitution type="single"/>
    <derivation type="original"/>
    <domain type="art"/>
    <factuality type="fiction"/>
    <interaction type="none"/>
    <preparedness type="prepared"/>
    <purpose degree="high" type="enter
tain"/>
    <purpose degree="medium" type="in
form"/>
  </textDesc>
</catDesc>
```

Content model

```
<content>
  <alternate maxOccurs="unbounded"
minOccurs="0">
    <textNode/>
    <classRef key="model.limitedPhrase"
/>
    <classRef key="model.catDescPart"/
>
  </alternate>
</content>
```

Schema Declaration

```
element catDesc
{
  tei_att.global.attributes,
  tei_att.canonical.attributes,
  ( text | tei_model.limitedPhrase | tei_
model.catDescPart )*
}
```

<category>

<category> (category) contains an individual descriptive category, possibly nested within a superordinate category, within a user-defined taxonomy.

[\[2.3.7. The Classification Declaration\]](#)

Module

header

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.datcat
 - *@datcat*
 - *@valueDatcat*
 - *@targetDatcat*

Contained by
May contain

Example

Example

Example

```
header: category taxonomy
core: desc
header: catDesc category
<category xml:id="b1">
  <catDesc>Prose reportage</
catDesc>
</category>
<category xml:id="b2">
  <catDesc>Prose </catDesc>
  <category xml:id="b11">
    <catDesc>journalism</catDesc>
  </category>
  <category xml:id="b12">
    <catDesc>fiction</catDesc>
  </category>
</category>
<category xml:id="LIT">
  <catDesc xml:lang="pl">literatura pi
ękna</catDesc>
  <catDesc xml:lang="en">fiction</
```

Content model

```
catDesc>
  <category xml:id="LPROSE">
    <catDesc xml:lang="pl">proza</
catDesc>
  <catDesc xml:lang="en">prose</
catDesc>
  </category>
  <category xml:id="LPOETRY">
    <catDesc xml:lang="pl">poezja</
catDesc>
  <catDesc xml:lang="en">poetry</
catDesc>
  </category>
  <category xml:id="LDRAMA">
    <catDesc xml:lang="pl">dramat</
catDesc>
  <catDesc xml:lang="en">drama</
catDesc>
  </category>
</category>

<content>
  <sequence>
    <alternate>
      <elementRef key="catDesc"
        maxOccurs="unbounded" minOccurs="1"/>
      <alternate maxOccurs="unbounded"
        minOccurs="0">
        <classRef key="model.descLike"/>
        <elementRef key="equiv"/>
        <elementRef key="gloss"/>
      </alternate>
    </alternate>
    <elementRef key="category"
      maxOccurs="unbounded" minOccurs="0"/>
  </sequence>
</content>
```

Schema Declaration

```
element category
{
  tei_att.global.attributes,
  tei_att.datcat.attributes,
  (
    ( tei_catDesc+ | ( tei_model.descLike | equiv | gloss )* ),

```

```

        tei_category*
    )
}

```

<change>

<change> (change) documents a change or set of changes made during the production of a source document, or during the revision of an electronic file. [\[2.6. The Revision Description 2.4.1. Creation 12.7. Identifying Changes and Revisions\]](#)

Module

Attributes

header

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.ascribed
 - *@who*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso

- *@when-iso*
- *@notBefore-iso*
- *@notAfter-iso*
- *@from-iso*
- *@to-iso*
- att.dataable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.docStatus
 - *@status*
- att.typed
 - *@type*
 - *@subtype*

target (target) points to one or more elements that belong to this change.

Status Optional
Datatype 1-∞
 occurrences of teidata.pointer separated by whitespace

Contained by
May contain

header: listChange revisionDesc
 core: bibl date desc list listBibl name
 note p ptr term title
 header: idno
 namesdates: affiliation bloc country
 eventName forename listEvent listOrg
 listPerson listPlace nameLink
 placeName roleName surname
 character data

Note

The *who* attribute may be used to point to any other element, but will typically specify a <respStmt> or <person> element elsewhere in the header, identifying the person responsible for the change and their role in making it.

It is recommended that changes be

recorded with the most recent first. The *status* attribute may be used to indicate the status of a document following the change documented.

Example

```
<titleStmt>
  <title> ... </title>
  <editor xml:id="LDB">Lou Burnard</
editor>
  <respStmt xml:id="BZ">
    <resp>copy editing</resp>
    <name>Brett Zamir</name>
  </respStmt>
</titleStmt>
<!-- ... -->
<revisionDesc status="published">
  <change status="public" when="2008-02-02"
    who="#BZ">Finished chapter 23</
change>
  <change status="draft" when="2008-01-02"
    who="#BZ">Finished chapter 2</
change>
  <change n="P2.2" when="1991-12-21"
    who="#LDB">Added examples to sec
tion 3</change>
  <change when="1991-11-11" who="#
MSM">Deleted chapter 10</change>
</revisionDesc>
<profileDesc>
  <creation>
    <listChange>
      <change xml:id="DRAFT1">First dr
aft in pencil</change>
      <change notBefore="1880-12-09"
xml:id="DRAFT2">First revision, m
ostly
        using green ink</change>
      <change notBefore="1881-02-13"
xml:id="DRAFT3">Final corrections
as
        supplied to printer.</change>
    </listChange>
  </creation>
</profileDesc>
```

Example

Content model

```

<content>
  <macroRef key="macro.specialPara"/>
</content>

```

Schema Declaration

```

element change
{
  tei_att.global.attributes,
  tei_att.ascribed.attributes,
  tei_att.dataable.attributes,
  tei_att.docStatus.attributes,
  tei_att.typed.attributes,
  attribute target { list { + } }?,
  tei_macro.specialPara
}

```

<classDecl>

<classDecl> (classification declarations) contains one or more taxonomies defining any classificatory codes used elsewhere in the text. [[2.3.7. The Classification Declaration](#) [2.3. The Encoding Description](#)]

Module

header

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*

Member of

model.encodingDescPart

Contained by
May contain
Example

```
header: encodingDesc
header: taxonomy
<classDecl>
  <taxonomy xml:id="LCSH">
    <bibl>Library of Congress Subject H
eadings</bibl>
  </taxonomy>
</classDecl>
<!-- ... -->
<textClass>
  <keywords scheme="#LCSH">
    <term>Political science</term>
    <term>United States — Politics and
government —
  Revolution, 1775-1783</term>
  </keywords>
</textClass>
```

Content model

```
<content>
  <elementRef key="taxonomy"
    maxOccurs="unbounded" minOccurs
="1"/>
</content>
```

Schema Declaration

```
element classDecl { tei_att.global.attri
butes, tei_taxonomy+ }
```

<country>

<country> (country) contains the name of a geo-political unit, such as a nation, country, colony, or commonwealth, larger than or administratively superior to a region and smaller than a bloc. [[14.2.3. Place Names](#)]

Module

Attributes

```
namesdates
  • att.global
    • @xml:id
    • @n
    • @xml:lang
    • @xml:base
    • @xml:space
    • att.global.linking
      • @corresp
      • @synch
      • @sameAs
      • @copyOf
      • @next
      • @prev
      • @exclude
```

- *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.naming
 - *@role*
 - *@nymRef*
 - att.canonical
 - *@key*
 - *@ref*
- att.typed
 - *@type*
 - *@subtype*

**Member of
Contained by**

model.placeNamePart
core: bibl date desc editor item name
note p pubPlace publisher resp term
title
header: catDesc change licence

May contain

namesdates: affiliation bloc country
eventName forename gender
nameLink org place placeName
roleName surname
core: date name note ptr term title
header: idno

Note

namesdates: affiliation bloc country
eventName forename nameLink
placeName roleName surname
character data
The recommended source for codes to
represent coded country names is ISO
3166.

Example

```
<country key="DK">Denmark</country>
```

Content model

```
<content>  
  <macroRef key="macro.phraseSeq"/>  
</content>
```

Schema Declaration

```
element country  
{  
  tei_att.global.attributes,  
  tei_att.cmc.attributes,  
  tei_att.dataable.attributes,  
  tei_att.naming.attributes,  
  tei_att.typed.attributes,  
  tei_macro.phraseSeq  
}
```

<date>

<date> (date) contains a date in any format. [[3.6.4. Dates and Times](#) [2.2.4. Publication, Distribution, Licensing, etc.](#) [2.6. The Revision Description](#) [3.12.2.4. Imprint, Size of a Document, and Reprint Information](#) [16.2.3. The Setting Description](#) [14.4. Dates](#)]

Module**Attributes**

```
core  
  • att.global  
    • @xml:id  
    • @n  
    • @xml:lang  
    • @xml:base  
    • @xml:space  
    • att.global.linking  
      • @corresp  
      • @synch  
      • @sameAs
```

- *@copyOf*
- *@next*
- *@prev*
- *@exclude*
- *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.calendarSystem
 - *@calendar*
- att.canonical
 - *@key*
 - *@ref*
- att.cmc
 - *@generatedBy*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.dimensions
 - *@unit*
 - *@quantity*
 - *@extent*
 - *@precision*

- *@scope*
- att.ranging
 - *@atLeast*
 - *@atMost*
 - *@min*
 - *@max*
 - *@confidence*
- att.editLike
 - *@evidence*
 - *@instant*
- att.typed
 - *@type*
 - *@subtype*

Member of

Contained by

model.dateLike
 model.publicationStmtPart.detail
 core: bibl date desc editor item name
 note p pubPlace publisher resp term
 title
 header: catDesc change licence
 publicationStmt
 namesdates: affiliation bloc country
 eventName forename gender
 nameLink placeName roleName
 surname

May contain

core: date name note ptr term title
 header: idno
 namesdates: affiliation bloc country
 eventName forename nameLink
 placeName roleName surname
 character data

Example

<date when="1980-02">early Februar
 y 1980</date>

Example

Given on the <date when="1977-06-
 12">Twelfth Day
 of June in the Year of Our Lord One Th
 ousand Nine Hundred and Seventy-
 seven of the Republic
 the Two Hundredth and first and of th
 e University the Eighty-Sixth.</date>

Example

<date when="1990-09">September 19
 90</date>

Content model

<content>
 <alternate maxOccurs="unbounded"
 minOccurs="0">
 <textNode/>
 <classRef key="model.gLike"/>
 <classRef key="model.phrase"/>


```

    <classRef key="model.global"/>
  </alternate>
</content>

```

Schema Declaration

```

element date
{
  tei_att.global.attributes,
  tei_att.calendarSystem.attributes,
  tei_att.canonical.attributes,
  tei_att.cmc.attributes,
  tei_att.dataable.attributes,
  tei_att.dimensions.attributes,
  tei_att.editLike.attributes,
  tei_att.typed.attributes,
  ( text | tei_model.gLike | tei_model.p
hrase | tei_model.global )*
}

```

<desc>

<desc> (description) contains a short description of the purpose, function, or use of its parent element, or when the parent is a documentation element, describes or defines the object being documented. [[23.4.1. Description of Components](#)]

Module

Attributes

- core
 - att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*

	• att.global.source • @source • att.cmc • @generatedBy • att.typed • type • @subtype
type	characterizes the element in some sense, using any convenient classification scheme or typology. Derived from att.typed Status Optional Datatype teidata.enumerated Suggested values include: deprecated information) This element describes why or how its parent element is being deprecated,

typically including recommendations for alternative encoding.

```
<dataSpec ident="
teidata.point"
module="tei"
validUntil="2050-
02-25">
  <desc type="depr
ecationInfo"
versionDate="201
8-09-14"
xml:lang="en">S
everal standards b
odies, including NI
ST in the USA,
  strongly recomm
end against ending
the representation
of a number
  with a decimal po
int. So instead of <
q>3.</q> use eithe
r <q>3</q>
  or <q>3.0</
q>.</desc>
<!-- ... -->
</dataSpec>
```

**Member of
Contained by**

model.descLike model.labelLike
core: desc item list listBibl note p title
header: category change licence
listChange taxonomy
namesdates: event listEvent listOrg
listPerson listPlace org place
textstructure: body
core: bibl date desc list listBibl name
ptr term title
header: idno

May contain

	namesdates: affiliation bloc country eventName forename listEvent listOrg listPerson listPlace nameLink placeName roleName surname character data
Note	When used in a specification element such as <elementSpec>, TEI convention requires that this be expressed as a finite clause, beginning with an active verb.
Example	Example of a <desc> element inside a documentation element. <dataSpec ident="teidata.point" module="tei"> <desc versionDate="2010-10-17" xml:lang="en">defines the data type used to express a point in cartesian space.</desc> <content> <dataRef name="token" restriction="(-?[0-9]+(\.[0-9]+)?,-?[0-9]+(\.[0-9]+)?)"> </content> <!-- ... --> </dataSpec>
Example	Example of a <desc> element in a non-documentation element. <place xml:id="KERG2"> <placeName>Kerguelen Islands</placeName> <!-- ... --> <terrain> <desc>antarctic tundra</desc> </terrain> <!-- ... --> </place>
Schematron	A <desc> with a <i>type</i> of <i>deprecationInfo</i> should only occur when its parent element is being deprecated. Furthermore, it should always occur in an element that is being deprecated when <desc> is a valid child of that element. <sch:rule context="tei:desc[@type eq 'deprecationInfo']"> <sch:assert test="../@validUntil">Information about a deprecation should

only be present in a specification element that is being deprecated: that is, only an element that has a @validUntil attribute should have a child <desc type="deprecationInfo">.</sch:assert> </sch:rule>

Content model

```
<content>
  <macroRef key="macro.limitedContent"/>
</content>
```

Schema Declaration

```
element desc
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.typed.attribute.subtype,
  attribute type { "deprecationInfo" }?,
  tei_macro.limitedContent
}
```

<editor>

<editor> contains a secondary statement of responsibility for a bibliographic item, for example the name of an individual, institution or organization, (or of several such) acting as editor, compiler, translator, etc. [[3.12.2.2. Titles, Authors, and Editors](#)]

Module

Attributes

```
core
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs
    • @copyOf
    • @next
    • @prev
    • @exclude
    • @select
  • att.global.rendition
    • @rend
    • @style
```

- *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.naming
 - *@role*
 - *@nymRef*
 - att.canonical
 - *@key*
 - *@ref*

**Member of
Contained by**

May contain

Note

model.respLike

core: bibl

header: titleStmt

core: date name note ptr term title

header: idno

namesdates: affiliation bloc country

eventName forename nameLink

placeName roleName surname

character data

A consistent format should be adopted.

Particularly where cataloguing is likely to be based on the content of the header, it is advisable to use generally

recognized authority lists for the exact form of personal names.

Example

```
<editor role="Technical_Editor">Ron
Van den Branden</editor>
<editor role="Editor-in-Chief">John W
alsh</editor>
<editor role="Managing_Editor">Ann
e Baillot</editor>
```

Content model

```
<content>
  <macroRef key="macro.phraseSeq"/>
</content>
```

Schema Declaration

```
element editor
{
  tei_att.global.attributes,
  tei_att.dataable.attributes,
  tei_att.naming.attributes,
  tei_macro.phraseSeq
}
```

<encodingDesc>

<encodingDesc> (encoding description) documents the relationship between an electronic text and the source or sources from which it was derived. [[2.3. The Encoding Description 2.1.1. The TEI Header and Its Components](#)]

Module

header

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility

Member of
Contained by
May contain

Example

Content model

Schema Declaration

- *@cert*
- *@resp*
- att.global.source
- *@source*

model.teiHeaderPart

header: teiHeader

core: p

header: classDecl

<encodingDesc>

<p>Basic encoding, capturing lexical information only. All hyphenation, punctuation, and variant spellings normalized. No formatting or layout information preserved.</p>
 </encodingDesc>

<content>

<alternate maxOccurs="unbounded" minOccurs="1">

<classRef key="model.encodingDescPart"/>

<classRef key="model.pLike"/>

</alternate>

</content>

element encodingDesc

{

tei_att.global.attributes,

(tei_model.encodingDescPart | tei_model.pLike)+

}

<event>

<event> (event) contains data relating to anything of significance that happens in time. [[14.3.1. Basic Principles](#)]

Module

Attributes

namesdates

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*

- *@sameAs*
- *@copyOf*
- *@next*
- *@prev*
- *@exclude*
- *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.editLike
 - *@evidence*
 - *@instant*
- att.locatable
 - *@where*
- att.naming
 - *@role*
 - *@nymRef*
- att.canonical
 - *@key*
 - *@ref*

Member of
Contained by

May contain

Example

- att.sortable
 - *@sortKey*
- att.typed
 - *@type*
 - *@subtype*

model.eventLike

namesdates: event listEvent org

person place

core: bibl desc listBibl note p ptr

header: idno

namesdates: event eventName

listEvent listPerson listPlace org

person place

<listEvent>

<event when="1618-05-23" where="#Prague"

xml:id="SecondDefPrague">

<eventName>1618 Defenestration of Prague</eventName>

<idno>https://www.wikidata.org/wiki/Q13365740</idno>

<listPerson type="defenstrated">

<person>

<persName>Jaroslav Bořita z Marti nic</persName>

<idno type="GND">https://d-nb.info/gnd/116810998</idno>

</person>

<person>

<persName>Vilém Slavata z Chlumu a Košumberka</persName>

<idno type="GND">https://d-nb.info/gnd/1018376615</idno>

</person>

<person>

<persName>Filip Fabricius</persName>

<idno type="GND">https://d-nb.info/gnd/133946118</idno>

</person>

</listPerson>

<place xml:id="Prague">

<placeName>Prague</placeName>

</place>

</event>

<event from="1618" to="1648"

xml:id="ThirtyYearsWar">

<eventName>Thirty Years' War</

```

eventName>
  <idno>https://www.wikidata.org/
wiki/Q2487</idno>
  <event when="1643-03-19" where="
#Rocroi"
    xml:id="BattleofRocroi">
      <eventName>Battle of Rocroi</
eventName>
      <idno type="Wikidata">https://
www.wikidata.org/wiki/Q728480</
idno>
      <idno type="GND">https://d-
nb.info/gnd/4202901-6</idno>
      <place xml:id="Rocroi">
        <placeName>Rocroi</placeName>
        <location>
          <geo decls="#WGS">49.926111 4.
522222</geo>
        </location>
      </place>
    </event>
  </event>
</listEvent>
<person>
  <event type="mat" when="1972-10-
12">
    <label>matriculation</label>
  </event>
  <event type="grad" when="1975-06-
23">
    <label>graduation</label>
  </event>
</person>

```

Example

Content model

```

<content>
  <sequence>
    <elementRef key="idno"
      maxOccurs="unbounded" minOccurs
="0"/>
    <classRef key="model.headLike"
      maxOccurs="unbounded" minOccurs
="0"/>
    <alternate>
      <classRef key="model.pLike"
        maxOccurs="unbounded" minOccur
s="1"/>
      <classRef key="model.labelLike"
        maxOccurs="unbounded" minOccur

```

```

s="1"/>
  <elementRef key="eventName"
    maxOccurs="unbounded" minOccurs="1"/>
s="1"/>
</alternate>
<alternate maxOccurs="unbounded"
  minOccurs="0">
  <classRef key="model.noteLike"/>
  <classRef key="model.biblLike"/>
  <elementRef key="linkGrp"/>
  <elementRef key="link"/>
  <elementRef key="idno"/>
  <elementRef key="ptr"/>
</alternate>
<classRef key="model.eventLike"
  maxOccurs="unbounded" minOccurs="0"/>
<alternate maxOccurs="unbounded"
  minOccurs="0">
  <classRef key="model.personLike"
    maxOccurs="1" minOccurs="1"/>
  <elementRef key="listPerson"
    maxOccurs="1" minOccurs="1"/>
</alternate>
<alternate maxOccurs="unbounded"
  minOccurs="0">
  <classRef key="model.placeLike"
    maxOccurs="1" minOccurs="1"/>
  <elementRef key="listPlace"
    maxOccurs="1" minOccurs="1"/>
</alternate>
<classRef key="model.objectLike"
  maxOccurs="unbounded" minOccurs="0"/>
<alternate maxOccurs="unbounded"
  minOccurs="0">
  <elementRef key="relation" maxOccurs="1"
    minOccurs="1"/>
  <elementRef key="listRelation"
    maxOccurs="1" minOccurs="1"/>
</alternate>
</sequence>
</content>

```

Schema Declaration

```

element event
{

```

```

    tei_att.global.attributes,
    tei_att.dataable.attributes,
    tei_att.editLike.attributes,
    tei_att.locatable.attributes,
    tei_att.naming.attributes,
    tei_att.sortable.attributes,
    tei_att.typed.attributes,
    (
        tei_idno*,
        tei_model.headLike*,
        ( tei_model.pLike+ | tei_model.labe
lLike+ | tei_eventName+ ),
        (
            tei_model.noteLike
            | tei_model.biblLike
            | linkGrp
            | link
            | tei_idno
            | tei_ptr
        )*,
        tei_model.eventLike*,
        ( tei_model.personLike | tei_listPers
on )*,
        ( tei_model.placeLike | tei_listPlace
)*,
        tei_model.objectLike*,
        ( relation | listRelation )*
    )
}

```

<eventName>

<eventName> (name of an event) contains a proper noun or noun phrase used to refer to an event. [[14.2.4. Event Names](#)]

Module

namesdates

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*

- *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.editLike
 - *@evidence*
 - *@instant*
- att.personal
 - *@full*
 - *@sort*
- att.naming
 - *@role*
 - *@nymRef*
 - att.canonical
 - *@key*
 - *@ref*
- att.typed
 - *@type*
 - *@subtype*

**Member of
Contained by**

model.nameLike
core: bibl date desc editor item name
note p pubPlace publisher resp term
title
header: catDesc change licence
namesdates: affiliation bloc country
event eventName forename gender
nameLink org placeName roleName
surname

May contain

core: date name note ptr term title
header: idno
namesdates: affiliation bloc country
eventName forename nameLink
placeName roleName surname
character data

Example

```
<listEvent>
  <event from="1939-09-01" to="1945-09-02">
    <eventName xml:lang="de">Zweiter
Weltkrieg</eventName>
    <eventName xml:lang="en">World W
ar II</eventName>
    <idno type="GND">https://d-
nb.info/gnd/4079167-1</idno>
    <idno type="Wikidata">https://
www.wikidata.org/wiki/Q362</idno>
    <event from="1939-09-01" to="1939-10-06"
xml:id="UeberfallAufPolen">
      <eventName xml:lang="de">Überfal
l auf Polen</eventName>
      <eventName xml:lang="en">Invasio
n of Poland</eventName>
      <idno type="GND">https://d-
nb.info/gnd/4175002-0</idno>
      <idno type="LOC">https://
id.loc.gov/authorities/sh85148341</
idno>
      <listPlace type="affected">
        <place>
          <placeName xml:lang="pl">Gdańs
k</placeName>
          <location>
            <geo>54.350556 18.652778</
geo>
          </location>
        </place>
      </listPlace>
    </event>
  </listEvent>
```

```

</event>
<event from="1941-06-22" to="1945-05-09">
  <eventName xml:lang="de">Deutscher-Sowjetischer Krieg</eventName>
  <eventName xml:lang="ru">Великая Отечественная война</eventName>
  <idno type="GND">https://d-nb.info/gnd/4076906-9</idno>
  <idno type="Wikidata">https://www.wikidata.org/wiki/Q189266</idno>
</event>
</event>
</listEvent>

```

Example

```

<p>On <date when="1719-03-19">Monday</date>, <rs type="person">she</rs> was writing about the <eventName ref="#SecondDefPrague">1618 Defenestration of Prague</eventName> which initiated the <rs ref="#ThirtyYearsWar" type="event">long war</rs>.</p>

```

Example

```

<event from="2019-09-16" to="2019-09-20"
  xml:id="tei2019graz">
  <eventName type="full">TEI 2019: What is text, really? TEI and beyond</eventName>
  <eventName type="short">TEI 2019</eventName>
  <note> The abstract leading to the <gi>eventName</gi> element is available at <ref target="https://gams.uni-graz.at/o:tei2019.141">https://gams.uni-graz.at/o:tei2019.141</ref>.
    Other related documents are available through <ref target="https://gams.uni-graz.at/tei2019">https://gams.uni-graz.at/tei2019</ref>, as well as in the
    <ref target="https://zenodo.org/communities/tei2019">TEI 2019 Zenodo community</ref>.
  </note>
  <listPerson type="LocalOrganizers">
    <person>

```



```

    <persName>
      <surname>Raunig</surname>
      <forename>Elisabeth</forename>
    </persName>
  </person>
  <person>
    <persName>
      <surname>Scholger</surname>
      <forename>Martina</forename>
    </persName>
  </person>
  <person>
    <persName>
      <surname>Scholger</surname>
      <forename>Walter</forename>
    </persName>
  </person>
  <person>
    <persName>
      <surname>Steiner</surname>
      <forename>Elisabeth</forename>
    </persName>
  </person>
  <person>
    <persName>
      <surname>Vogeler</surname>
      <forename>Georg</forename>
    </persName>
  </person>
</listPerson>
<place xml:lang="de">
  <placeName>Universität Graz</
placeName>
  <location>
    <address>
      <addrLine>ReSoWi Gebäude</
addrLine>
      <addrLine>Universitätsstraße 15</
addrLine>
      <postCode>8010</postCode>
      <settlement>Graz</settlement>
      <country>Österreich</country>
    </address>
    <geo>15.451651587656 47.0782151
12534</geo>
  </location>
</place>
</listRelation>

```

```

    <relation active="#tei2019graz"
      name="P31_is_instance_of" passive=
"#AnnualTEIConference"
      ref="https://www.wikidata.org/wiki/
Property:P31" type="CRM"/>
  </listRelation>
</event>

```

Content model

```

<content>
  <macroRef key="macro.phraseSeq"/>
</content>

```

Schema Declaration

```

element eventName
{
  tei_att.global.attributes,
  tei_att.dataable.attributes,
  tei_att.editLike.attributes,
  tei_att.personal.attributes,
  tei_att.typed.attributes,
  tei_macro.phraseSeq
}

```

<fileDesc>

<fileDesc> (file description) contains a full bibliographic description of an electronic file. [[2.2. The File Description](#) [2.1.1. The TEI Header and Its Components](#)]

Module

Attributes

```

header
  • att.global
    • @xml:id
    • @n
    • @xml:lang
    • @xml:base
    • @xml:space
    • att.global.linking
      • @corresp
      • @synch
      • @sameAs
      • @copyOf
      • @next
      • @prev
      • @exclude
      • @select
    • att.global.rendition
      • @rend
      • @style
      • @rendition

```

- att.global.responsibility
 - @cert
 - @resp
- att.global.source
 - @source

Contained by
May contain

Note

header: *teiHeader*
header: *publicationStmt sourceDesc titleStmt*

The major source of information for those seeking to create a catalogue entry or bibliographic citation for an electronic file. As such, it provides a title and statements of responsibility together with details of the publication or distribution of the file, of any series to which it belongs, and detailed bibliographic notes for matters not addressed elsewhere in the header. It also contains a full bibliographic description for the source or sources from which the electronic text was derived.

Example

```
<fileDesc>
  <titleStmt>
    <title>The shortest possible TEI document</title>
  </titleStmt>
  <publicationStmt>
    <p>Distributed as part of TEI P5</p>
  </publicationStmt>
  <sourceDesc>
    <p>No print source exists: this is an original digital text</p>
  </sourceDesc>
</fileDesc>
```

Content model

```
<content>
  <sequence>
    <sequence>
      <elementRef key="titleStmt"/>
      <elementRef key="editionStmt" minOccurs="0"/>
      <elementRef key="extent" minOccurs="0"/>
      <elementRef key="publicationStmt"/>
    >
```

```

        <elementRef key="seriesStmt"
            maxOccurs="unbounded" minOccurs="0"/>
        <elementRef key="notesStmt"
            minOccurs="0"/>
    </sequence>
    <elementRef key="sourceDesc"
        maxOccurs="unbounded" minOccurs="1"/>
</sequence>
</content>

```

Schema Declaration

```

element fileDesc
{
    tei_att.global.attributes,
    (
        (
            tei_titleStmt,
            editionStmt?,
            extent?,
            tei_publicationStmt,
            seriesStmt*,
            notesStmt?
        ),
        tei_sourceDesc+
    )
}

```

<forename>

<forename> (forename) contains a forename, given or baptismal name.
[\[14.2.1. Personal Names\]](#)

Module

Attributes

```

namesdates
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs
    • @copyOf
    • @next
    • @prev
    • @exclude

```

- *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.personal
 - *@full*
 - *@sort*
- att.naming
 - *@role*
 - *@nymRef*
 - att.canonical
 - *@key*
 - *@ref*
- att.typed
 - *@type*
 - *@subtype*

**Member of
Contained by**

model.persNamePart
 core: bibl date desc editor item name
 note p pubPlace publisher resp term
 title
 header: catDesc change licence
 namesdates: affiliation bloc country
 eventName forename gender
 nameLink org placeName roleName
 surname

May contain

core: date name note ptr term title
 header: idno
 namesdates: affiliation bloc country
 eventName forename nameLink
 placeName roleName surname
 character data

Example

```
<persName>
  <roleName>Ex-President</
roleName>
  <forename>George</forename>
  <surname>Bush</surname>
</persName>
```

Content model

```
<content>
  <macroRef key="macro.phraseSeq"/>
```

</content>

Schema Declaration

```
element forename
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.personal.attributes,
  tei_att.typed.attributes,
  tei_macro.phraseSeq
}
```

<gender>

<gender> (gender) specifies the gender identity of a person, persona, or character. [[14.3.2.1. Personal Characteristics](#)]

Module

namesdates

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*

	• <i>@to-custom</i> • <i>@datingPoint</i> • <i>@datingMethod</i> • att.datable.iso • <i>@when-iso</i> • <i>@notBefore-iso</i> • <i>@notAfter-iso</i> • <i>@from-iso</i> • <i>@to-iso</i> • att.datable.w3c • <i>@when</i> • <i>@notBefore</i> • <i>@notAfter</i> • <i>@from</i> • <i>@to</i> • att.editLike • <i>@evidence</i> • <i>@instant</i> • att.typed • <i>@type</i> • <i>@subtype</i>
value	supplies a coded value for gender identity. Status Optional Datatype 1-∞ occurrences of teidata .gender separated by whitespace Note Values for this attribute may be locally defined by a project, or they may refer to an external standard.

Member of
Contained by
May contain

model.persStateLike
namesdates: person
core: date name note ptr term title
header: idno
namesdates: affiliation bloc country
eventName forename nameLink
placeName roleName surname
character data

Note

As with other culturally-constructed traits such as age and sex, the way in which this concept is described in different cultural contexts varies. The normalizing attributes are provided only as an optional means of simplifying that variety for purposes of interoperability or project-internal taxonomies for consistency, and should not be used where that is inappropriate or unhelpful. The content of the element may be used to describe the intended concept in more detail.

Example

```
<gender value="W">woman</gender>
```

Example

```
<gender value="NB">non-binary</gender>
```

Content model

```
<content>  
  <macroRef key="macro.phraseSeq"/>  
</content>
```

Schema Declaration

```
element gender  
{  
  tei_att.global.attributes,  
  tei_att.dataable.attributes,  
  tei_att.editLike.attributes,  
  tei_att.typed.attributes,  
  attribute value { list { + } }?,  
  tei_macro.phraseSeq  
}
```

<idno>

<idno> (identifier) supplies any form of identifier used to identify some object, such as a bibliographic item, a person, a title, an organization, etc. in a standardized way. [[14.3.1. Basic Principles](#) [2.2.4. Publication, Distribution, Licensing, etc.](#) [2.2.5. The Series Statement](#) [3.12.2.4. Imprint, Size of a](#)

[Document, and Reprint Information\]](#)

Module

Attributes

header

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*

	• <i>@from</i> • <i>@to</i>
	• att.sortable • <i>@sortKey</i> • att.typed • type • @subtype
type	categorizes the identifier, for example as an ISBN, Social Security number, etc. Derived from att.typed Status Optional Datatype teidata.enumerated Suggested values include: ISBN International Standard Book Number: a 13- or (if assigned prior to 2007) 10-digit identifying number assigned by the publi

shin
g
indu
stry
to a
publi
shed
book
or
simil
ar
item,
regis
tere
d
with
the
[Inter
natio
nal
ISB
N
Agen
cy.](#)

ISSN

Inter
natio
nal
Stan
dard
Seri
al
Num
ber:
an
eight
-digit
num
ber
to
uniq
uely
ident
ify a
seria
l
publi
catio

n.

DOI

Digital
al
Object
Identifier
: a
unique
string of
letters
and
numbers
assigned
to an
electronic
document

.

URI

Uniform
Resource
Identifier
: a
string of
characters
to
uniquely
identify a
resource,
following

the
synt
ax of
[RFC
3986](#)

VIAF

A
data
num
ber
in
the
Virtu
al
Inter
net
Auth
ority
File
assign
ed
to
link
diffe
rent
nam
es in
catal
ogs
arou
nd
the
worl
d for
the
same
entit
y.

ESTC

Engli
sh
Shor
t-
Title
Cata
logu

e
num
ber:
an
ident
ifyin
g
num
ber
assig
ned
to a
docu
ment
in
Engli
sh
print
ed in
the
Briti
sh
Isles
or
Nort
h
Ame
rica
befo
re
1801

.
OCLC
OCL
C
cont
rol
num
ber
(reco
rd
num
ber)
for
the
unio
n
catal

og
reco
rd in
Worl
dCat
, a
unio
n
catal
og
for
mem
ber
libra
ries
in
the
Onli
ne
Com
pute
r
Libr
ary
Cent
er
glob
al
coop
erati
ve.

Member of

Contained by

May contain

Note

model.nameLike model.personPart
model.publicationStmtPart.detail
core: bibl date desc editor item name
note p pubPlace publisher resp term
title
header: catDesc change idno licence
publicationStmt
namesdates: affiliation bloc country
event eventName forename gender
nameLink org person place placeName
roleName surname
header: idno
character data
<idno> should be used for labels
which identify an object or concept in
a formal cataloguing system such as a
database or an RDF store, or in a

distributed system such as the World Wide Web. Some suggested values for *type* on `<idno>` are *ISBN*, *ISSN*, *DOI*, and *URI*.

Example

```
<idno type="ISBN">978-1-906964-22-1</idno>
<idno type="ISSN">0143-3385</idno>
<idno type="DOI">10.1000/123</idno>
<idno type="URI">http://www.worldcat.org/oclc/185922478</idno>
<idno type="URI">http://authority.nzetc.org/463/</idno>
<idno type="LT">Thomason Tract E.5 37(17)</idno>
<idno type="Wing">C695</idno>
<idno type="oldCat">
  <g ref="#sym"/>345
</idno>
```

In the last case, the identifier includes a non-Unicode character which is defined elsewhere by means of a `<glyph>` or `<char>` element referenced here as `#sym`.

Content model

```
<content>
  <alternate maxOccurs="unbounded" minOccurs="0">
    <textNode/>
    <classRef key="model.gLike"/>
    <elementRef key="idno"/>
  </alternate>
</content>
```

Schema Declaration

```
element idno
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.dataable.attributes,
  tei_att.sortable.attributes,
  tei_att.typed.attribute.subtype,
  attribute type
  {
    "ISBN" | "ISSN" | "DOI" | "URI" | "V
```



```
IAF" | "ESTC" | "OCLC"
}?,
( text | tei_model.gLike | tei_idno )*
}
```

<item>

<item> (item) contains one component of a list. [[3.8. Lists 2.6. The Revision Description](#)]

Module

Attributes

```
core
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs
    • @copyOf
    • @next
    • @prev
    • @exclude
    • @select
  • att.global.rendition
    • @rend
    • @style
    • @rendition
  • att.global.responsibility
    • @cert
    • @resp
  • att.global.source
    • @source
• att.sortable
  • @sortKey
```

Contained by

May contain

```
core: list
core: bibl date desc list listBibl name
note p ptr term title
header: idno
namesdates: affiliation bloc country
eventName forename listEvent listOrg
listPerson listPlace nameLink
placeName roleName surname
character data
May contain simple prose or a
sequence of chunks.
```

Note

Whatever string of characters is used

to label a list item in the copy text may be used as the value of the global *n* attribute, but it is not required that numbering be recorded explicitly. In ordered lists, the *n* attribute on the `<item>` element is by definition synonymous with the use of the `<label>` element to record the enumerator of the list item. In glossary lists, however, the term being defined should be given with the `<label>` element, not *n*.

Example

```
<list rend="numbered">
  <head>Here begin the chapter headings of Book IV</head>
  <item n="4.1">The death of Queen Clotild.</item>
  <item n="4.2">How King Lothar wanted to appropriate one third of the Church revenues.</item>
  <item n="4.3">The wives and children of Lothar.</item>
  <item n="4.4">The Counts of the Bretons.</item>
  <item n="4.5">Saint Gall the Bishop.</item>
  <item n="4.6">The priest Cato.</item>
  <item> ...</item>
</list>
```

Content model

```
<content>
  <macroRef key="macro.specialPara"/>
</content>
```

Schema Declaration

```
element item
{
  tei_att.global.attributes,
  tei_att.sortable.attributes,
  tei_macro.specialPara
}
```

<licence>

<licence> contains information about a licence or other legal agreement applicable to the text. [[2.2.4. Publication, Distribution, Licensing, etc.](#)]

Module Attributes

header

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.pointing

**Member of
Contained by
May contain**

- *@targetLang*
- *@target*
- *@evaluate*

model.availabilityPart
header: availability
core: bibl date desc list listBibl name
note p ptr term title
header: idno
namesdates: affiliation bloc country
eventName forename listEvent listOrg
listPerson listPlace nameLink
placeName roleName surname
character data

Note

A <licence> element should be supplied for each licence agreement applicable to the text in question. The *target* attribute may be used to reference a full version of the licence. The *when*, *notBefore*, *notAfter*, *from* or *to* attributes may be used in combination to indicate the date or dates of applicability of the licence.

Example

```
<licence target="http://
www.nzetc.org/tm/scholarly/tei-
NZETC-Help.html#licensing"> Licence
: Creative Commons Attribution-Share
Alike 3.0 New Zealand Licence
</licence>
```

Example

```
<availability>
  <licence notBefore="2013-01-01"
    target="http://creativecommons.org/
licenses/by/3.0/">
    <p>The Creative Commons Attributio
n 3.0 Unported (CC BY 3.0) Licence
    applies to this document.</p>
    <p>The licence was added on Januar
y 1, 2013.</p>
  </licence>
</availability>
```

Content model

```
<content>
  <macroRef key="macro.specialPara"/
>
</content>
```

Schema Declaration

element licence

```

{
  tei_att.global.attributes,
  tei_att.dataable.attributes,
  tei_att.pointing.attributes,
  tei_macro.specialPara
}

```

<list>

<list> (list) contains any sequence of items organized as a list. [[3.8. Lists](#)]

Module

core

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.sortable
 - *@sortKey*
- att.typed
 - type
 - @subtype

type

(type) describes the nature of the items in the list.
Derived from att.typed
Status Optional

Datatype	teidata.e numerate d
Suggest	gloss
ed	(glos s)
values	s)
include:	each list item gloss es some term or conc ept, whic h is give n by a <lab el> elem ent prec edin g the list item.
	index
	(inde x) each list item is an entr y in an inde x such as the alph abeti

cal
topic
al
inde
x at
the
back
of a
print
volu
me.

instructions

(instr
ructi
ons)
each
list
item
is a
step
in a
sequ
ence
of
instr
uctio
ns,
as in
a
recip
e.

litany

(lita
ny)
each
list
item
is
one
of a
sequ
ence
of
petit
ions,
supp

lications
or
invocations,
typically
in a religious
ritual.

syllogism

(syllogism)
each list item
is part of an argument consisting of two or more propositions and a final conclusion derived from them

Note

Previous

versions of these Guidelines recommend the use of *type* on <list> to encode the rendering or appearance of a list (whether it was bulleted, numbered, etc.). The current recommendation is to use the *rend* or *style* attributes for these aspects of a list, while using *type* for the more appropriate task of characterizing the nature of the content of a list. The formal syntax of

the
element
declarati
ons
allows
<label>
tags to be
omitted
from lists
tagged
<list
type="gl
oss">;
this is
however
a
semantic
error.

**Member of
Contained by**

model.listLike
core: desc item note p title
header: change licence revisionDesc
sourceDesc

**May contain
Note**

textstructure: body
core: desc item note
May contain an optional heading
followed by a series of items, or a
series of label and item pairs, the
latter being optionally preceded by one
or two specialized headings.

Example

```
<list rend="numbered">
  <item>a butcher</item>
  <item>a baker</item>
  <item>a candlestick maker, with
  <list rend="bulleted">
    <item>rings on his fingers</item>
    <item>bells on his toes</item>
  </list>
</item>
</list>
```

Example

```
<list rend="bulleted" type="syllogism"
>
  <item>All Cretans are liars.</item>
  <item>Epimenides is a Cretan.</
item>
  <item>ERGO Epimenides is a liar.</
item>
</list>
```

Example

```
<list rend="simple" type="litany">
  <item>God save us from drought.</
item>
  <item>God save us from pestilence.</
item>
  <item>God save us from wickedness i
n high places.</item>
  <item>Praise be to God.</item>
</list>
```

Example

The following example treats the short numbered clauses of Anglo-Saxon legal codes as lists of items. The text is from an ordinance of King Athelstan (924–939):

```
<div1 type="section">
  <head>Athelstan's Ordinance</
head>
  <list rend="numbered">
    <item n="1">Concerning thieves. Fir
st, that no thief is to be spared who is c
aught with
      the stolen goods, [if he is] over twel
ve years and [if the value of the goods i
s] over
      eightpence.
    <list rend="numbered">
      <item n="1.1">And if anyone does s
pare one, he is to pay for the thief with
his
      wergild — and the thief is to be n
o nearer a settlement on that account
      — or to
      clear himself by an oath of that a
mount.</item>
      <item n="1.2">If, however, he [the t
hief] wishes to defend himself or to esc
ape, he is
      not to be spared [whether younge
r or older than twelve].</item>
      <item n="1.3">If a thief is put into
prison, he is to be in prison 40 days, an
d he may
      then be redeemed with 120 shilli
ngs; and the kindred are to stand suret
y for him
      that he will desist for ever.</
item>
      <item n="1.4">And if he steals afte
```

r that, they are to pay for him with his wergild,

or to bring him back there.</

item>

<item n="1.5">And if he steals after that, they are to pay for him with his wergild,

whether to the king or to him to whom it rightly belongs; and everyone of those who

supported him is to pay 120 shillings to the king as a fine.</item>

</list>

</item>

<item n="2">Concerning lordless men. And we pronounced about these lordless men, from whom

no justice can be obtained, that one should order their kindred to fetch back such a

person to justice and to find him a lord in public meeting.

<list rend="numbered">

<item n="2.1">And if they then will not, or cannot, produce him on that appointed day,

he is then to be a fugitive afterwards, and he who encounters him is to strike him

down as a thief.</item>

<item n="2.2">And he who harbours him after that, is to pay for him with his wergild

or to clear himself by an oath of that amount.</item>

</list>

</item>

<item n="3">Concerning the refusal of justice. The lord who refuses justice and upholds

his guilty man, so that the king is appealed to, is to repay the value of the goods and

120 shillings to the king; and he who appeals to the king before he demands justice as

often as he ought, is to pay the same fine as the other would have done, if

he had
 refused him justice.
 <list rend="numbered">
 <item n="3.1">And the lord who is
 an accessory to a theft by his slave, and
 it becomes
 known about him, is to forfeit the
 slave and be liable to his wergild on th
 e first
 occasionp if he does it more often
 , he is to be liable to pay all that he ow
 ns.</item>
 <item n="3.2">And likewise any of
 the king's treasurers or of our reeves,
 who has been
 an accessory of thieves who have
 committed theft, is to liable to the sam
 e.</item>
</list>
</item>
 <item n="4">Concerning treachery t
 o a lord. And we have pronounced conc
 erning treachery to
 a lord, that he [who is accused] is to
 forfeit his life if he cannot deny it or is
 afterwards convicted at the three-
 fold ordeal.</item>
</list>
</div1>

Note that nested lists have been used
 so the tagging mirrors the structure
 indicated by the two-level numbering
 of the clauses. The clauses could have
 been treated as a one-level list with
 irregular numbering, if desired.

Example

<p>These decrees, most blessed Pope
 Hadrian, we propounded in the public
 council ... and they
 confirmed them in our hand in your st
 ead with the sign of the Holy Cross, an
 d afterwards
 inscribed with a careful pen on the pa
 per of this page, affixing thus the sign
 of the Holy
 Cross.
 <list rend="simple">
 <item>I, Eanbald, by the grace of Go
 d archbishop of the holy church of York

, have
 subscribed to the pious and catholic
 validity of this document with the sign
 of the Holy
 Cross.</item>
 <item>I, Ælfwold, king of the people
 across the Humber, consenting have su
 bscribed with
 the sign of the Holy Cross.</item>
 <item>I, Tilberht, prelate of the chur
 ch of Hexham, rejoicing have subscribe
 d with the
 sign of the Holy Cross.</item>
 <item>I, Higbald, bishop of the churc
 h of Lindisfarne, obeying have subscrib
 ed with the
 sign of the Holy Cross.</item>
 <item>I, Ethelbert, bishop of Candid
 a Casa, suppliant, have subscribed wit
 h the sign of
 the Holy Cross.</item>
 <item>I, Ealdwulf, bishop of the churc
 h of Mayo, have subscribed with devo
 ut will.</item>
 <item>I, Æthelwine, bishop, have su
 bscribed through delegates.</item>
 <item>I, Sicga, patrician, have subsc
 ribed with serene mind with the sign of
 the Holy
 Cross.</item>
 </list>

Schematron

</p>
 <sch:rule context="tei:list[@type='glo
 ss']">
 <sch:assert test="tei:label">The
 content of a "gloss" list should include
 a sequence of one or more pairs of a
 label element followed by an item
 element</sch:assert> </sch:rule>

Content model

<content>
 <sequence>
 <alternate maxOccurs="unbounded"
 minOccurs="0">
 <classRef key="model.divTop"/>
 <classRef key="model.global"/>
 <elementRef key="desc"
 maxOccurs="unbounded" minOccurs="1">

```

s="0"/>
</alternate>
<alternate>
  <sequence maxOccurs="unbounded"
    minOccurs="1">
    <elementRef key="item"/>
    <classRef key="model.global"
      maxOccurs="unbounded" minOccur
s="0"/>
    </sequence>
  <sequence>
    <elementRef key="headLabel"
      minOccurs="0"/>
    <elementRef key="headItem"
      minOccurs="0"/>
    <sequence maxOccurs="unbounded
"
      minOccurs="1">
      <elementRef key="label"/>
      <classRef key="model.global"
        maxOccurs="unbounded" minOccu
rs="0"/>
      <elementRef key="item"/>
      <classRef key="model.global"
        maxOccurs="unbounded" minOccu
rs="0"/>
      </sequence>
    </sequence>
  </alternate>
  <sequence maxOccurs="unbounded"
    minOccurs="0">
    <classRef key="model.divBottom"/>
    <classRef key="model.global"
      maxOccurs="unbounded" minOccur
s="0"/>
    </sequence>
  </sequence>
</content>

```

Schema Declaration

```

element list
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.sortable.attributes,
  tei_att.typed.attribute.subtype,
  attribute type
}

```

```

        "gloss" | "index" | "instructions" | "li
tany" | "syllogism"
    }?,
    (
        ( tei_model.divTop | tei_model.glob
al | tei_desc* )*,
        (
            ( ( tei_item, tei_model.global* )+ )
            | (
                headLabel?,
                headItem?,
                ( ( label, tei_model.global*, tei_i
tem, tei_model.global* )+ )
            )
        ),
        ( ( tei_model.divBottom, tei_model.
global* )*)
    )
}

```

<listBibl>

<listBibl> (citation list) contains a list of bibliographic citations of any kind.

[\[3.12.1. Methods of Encoding Bibliographic References and Lists of References\]](#) [2.2.7. The Source Description](#) [16.3.2. Declarable Elements\]](#)

Module

core

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*

	• att.global.source • @source • att.cmc • @generatedBy • att.declarable • @default • att.sortable • @sortKey • att.typed • @type • @subtype
Member of	model.biblLike
Contained by	core: desc item listBibl note p title header: change licence sourceDesc taxonomy namesdates: event org person place textstructure: body
May contain	core: bibl desc listBibl
Example	<pre> <listBibl> <head>Works consulted</head> <bibl>Blain, Clements and Grundy: F eminist Companion to Literature in English (Yale, 1990) </bibl> <biblStruct> <analytic> <title>The Interesting story of the C hildren in the Wood</title> </analytic> <monogr> <title>The Penny Histories</title> <author>Victor E Neuberg</ author> <imprint> <publisher>OUP</publisher> <date>1968</date> </imprint> </monogr> </biblStruct> </listBibl> </pre>
Content model	<pre> <content> <sequence> <classRef key="model.headLike" maxOccurs="unbounded" minOccurs ="0"/> <elementRef key="desc" </pre>

```

        maxOccurs="unbounded" minOccurs
="0"/>
        <alternate maxOccurs="unbounded"
minOccurs="0">
            <classRef key="model.milestoneLike
"
                maxOccurs="1" minOccurs="1"/>
            <elementRef key="relation" maxOcc
urs="1"
                minOccurs="1"/>
            <elementRef key="listRelation"
                maxOccurs="1" minOccurs="1"/>
        </alternate>
        <sequence maxOccurs="unbounded"
minOccurs="1">
            <classRef key="model.biblLike"
                maxOccurs="unbounded" minOccur
s="1"/>
            <alternate maxOccurs="unbounded"
minOccurs="0">
                <classRef key="model.milestoneLik
e"
                    maxOccurs="1" minOccurs="1"/>
                <elementRef key="relation"
                    maxOccurs="1" minOccurs="1"/>
                <elementRef key="listRelation"
                    maxOccurs="1" minOccurs="1"/>
            </alternate>
        </sequence>
    </sequence>
</content>

```

Schema Declaration

```

element listBibl
{
    tei_att.global.attributes,
    tei_att.cmc.attributes,
    tei_att.declarable.attributes,
    tei_att.sortable.attributes,
    tei_att.typed.attributes,
    (
        tei_model.headLike*,
        tei_desc*,
        ( tei_model.milestoneLike | relation
| listRelation )*,
        (
            (
                tei_model.biblLike+,

```

```

        ( tei_model.milestoneLike | rela
tion | listRelation )*
    )+
)
}

```

<listChange>

<listChange> groups a number of change descriptions associated with either the creation of a source text or the revision of an encoded text. [[2.6. The Revision Description](#) [12.7. Identifying Changes and Revisions](#)]

Module

header

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.sortable
 - *@sortKey*
- att.typed
 - *@type*
 - *@subtype*

ordered

indicates whether the ordering of its child <change> elements is to be considered significant or not.

	Status Optional Datatype teidata.truthValue Default true
Contained by	header: listChange revisionDesc
May contain	core: desc
Note	header: change listChange When this element appears within the <creation> element it documents the set of revision campaigns or stages identified during the evolution of the original text. When it appears within the <revisionDesc> element, it documents only changes made during the evolution of the encoded representation of that text.
Example	<pre> <revisionDesc> <listChange> <change when="1991-11-11" who="#LB"> deleted chapter 10 </change> <change when="1991-11-02" who="#MSM"> completed first draft </change> </listChange> </revisionDesc> </pre>
Example	<pre> <profileDesc> <creation> <listChange ordered="true"> <change xml:id="CHG-1">First stage, written in ink by a writer</change> <change xml:id="CHG-2">Second stage, written in Goethe's hand using pencil</change> <change xml:id="CHG-3">Fixation of the revised passages and further revisions by Goethe using ink</change> <change xml:id="CHG-4">Addition of another stanza in a different hand, probably at a later stage</change> </listChange> </creation> </profileDesc> </pre>
Content model	<pre> <content> <sequence> </pre>

```

<elementRef key="desc"
  maxOccurs="unbounded" minOccurs
="0"/>
<alternate maxOccurs="unbounded"
  minOccurs="1">
  <elementRef key="listChange"/>
  <elementRef key="change"/>
</alternate>
</sequence>
</content>

```

Schema Declaration

```

element listChange
{
  tei_att.global.attributes,
  tei_att.sortable.attributes,
  tei_att.typed.attributes,
  attribute ordered { text }?,
  ( tei_desc*, ( tei_listChange | tei_cha
nge )+ )
}

```

<listEvent>

<listEvent> (list of events) contains a list of descriptions, each of which provides information about an identifiable event. [[14.3.1. Basic Principles](#)]

Module

namesdates

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*

- *@resp*
- att.global.source
- *@source*
- att.cmc
- *@generatedBy*
- att.declarable
- *@default*
- att.sortable
- *@sortKey*
- att.typed
- *@type*
- *@subtype*

**Member of
Contained by**

May contain

Example

model.eventLike model.listLike
 core: desc item note p title
 header: change licence sourceDesc
 namesdates: event listEvent org
 person place
 textstructure: body
 core: desc
 namesdates: event listEvent
 <listEvent>
 <head>Battles of the American Civil
 War: Kentucky</head>
 <event when="1861-09-19" xml:id="e
 vent01">
 <label>Barbourville</label>
 <desc>The Battle of Barbourville was
 one of the early engagements of
 the American Civil War. It occurred
 September 19, 1861, in Knox
 County, Kentucky during the campai
 gn known as the Kentucky Confederate
 Offensive. The battle is considered t
 he first Confederate victory in
 the commonwealth, and threw a sca
 re into Federal commanders, who
 rushed troops to central Kentucky i
 n an effort to repel the invasion,
 which was finally thwarted at the <
 ref target="#event02">Battle of
 Camp Wildcat</ref> in October.</
 desc>
 </event>
 <event when="1861-10-21" xml:id="e
 vent02">
 <label>Camp Wild Cat</label>
 <desc>The Battle of Camp Wildcat (a
 lso known as Wildcat Mountain and Ca

mp

Wild Cat) was one of the early engagements of the American Civil

War. It occurred October 21, 1861, in northern Laurel County, Kentucky

during the campaign known as the Kentucky Confederate Offensive. The

battle is considered one of the very first Union victories, and marked

the first engagement of troops in the commonwealth of Kentucky.</desc>

</event>

<event from="1864-06-11" to="1864-06-12"

xml:id="event03">

<label>Cynthiana</label>

<desc>The Battle of Cynthiana (or Kellar's Bridge) was an engagement

during the American Civil War that was fought on June 11 and 12, 1864,

in Harrison County, Kentucky, near the town of Cynthiana. A part of

Confederate Brigadier General John Hunt Morgan's 1864 Raid into

Kentucky, the battle resulted in a victory by Union forces over the

raiders and saved the town from capture.</desc>

</event>

</listEvent>

Content model

<content>

<sequence>

<classRef key="model.headLike" maxOccurs="unbounded" minOccurs="0"/>

<elementRef key="desc" maxOccurs="unbounded" minOccurs="0"/>

<alternate maxOccurs="unbounded" minOccurs="0">

<elementRef key="relation" maxOccurs="1"

minOccurs="1"/>

<elementRef key="listRelation"

maxOccurs="1" minOccurs="1"/>

</alternate>

<sequence maxOccurs="unbounded"

```

minOccurs="1">
  <classRef key="model.eventLike"
    maxOccurs="unbounded" minOccurs="1"/>
  <alternate maxOccurs="unbounded"
    minOccurs="0">
    <elementRef key="relation"
      maxOccurs="1" minOccurs="1"/>
    <elementRef key="listRelation"
      maxOccurs="1" minOccurs="1"/>
  </alternate>
</sequence>
</sequence>
</content>

```

Schema Declaration

```

element listEvent
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.declarable.attributes,
  tei_att.sortable.attributes,
  tei_att.typed.attributes,
  (
    tei_model.headLike*,
    tei_desc*,
    ( relation | listRelation )*,
    ( ( tei_model.eventLike+, ( relation
| listRelation )* )+ )
  )
}

```

<listOrg>

<listOrg> (list of organizations) contains a list of elements, each of which provides information about an identifiable organization. [[14.2.2. Organizational Names](#)]

Module

Attributes

```

namesdates
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs

```


- *@copyOf*
- *@next*
- *@prev*
- *@exclude*
- *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.declarable
 - *@default*
- att.sortable
 - *@sortKey*
- att.typed
 - *@type*
 - *@subtype*

**Member of
Contained by**

May contain

Note

Example

model.listLike model.orgPart
 core: desc item note p title
 corpus: particDesc
 header: change licence sourceDesc
 namesdates: listOrg org
 textstructure: body

core: desc
 namesdates: listOrg org
 The type attribute may be used to distinguish lists of organizations of a particular type if convenient.

```
<listOrg>
  <head>Libyans</head>
  <org>
    <orgName>Adyrmachidae</
orgName>
    <desc>These people have, in most po
ints, the same customs as the Egyptian
s, but
      use the costume of the Libyans. The
ir women wear on each leg a ring mad
e of
      bronze [...]</desc>
  </org>
```

```

<org>
  <orgName>Nasamonians</
orgName>
  <desc>In summer they leave their flo
cks and herds upon the sea-shore, and
go up
  the country to a place called Augila,
where they gather the dates from the
  palms [...]</desc>
</org>
<org>
  <orgName>Garamantians</
orgName>
  <desc>[...] avoid all society or interc
ourse with their fellow-men, have no
  weapon of war, and do not know ho
w to defend themselves. [...]</desc>
<!-- ... -->
</org>
</listOrg>

```

Content model

```

<content>
  <sequence>
    <classRef key="model.headLike"
      maxOccurs="unbounded" minOccurs
="0"/>
    <elementRef key="desc"
      maxOccurs="unbounded" minOccurs
="0"/>
    <alternate maxOccurs="unbounded"
      minOccurs="0">
      <elementRef key="relation" maxOcc
urs="1"
        minOccurs="1"/>
      <elementRef key="listRelation"
        maxOccurs="1" minOccurs="1"/>
    </alternate>
    <sequence maxOccurs="unbounded"
      minOccurs="1">
      <alternate maxOccurs="unbounded"
        minOccurs="1">
        <elementRef key="org" maxOccurs
="1"
          minOccurs="1"/>
        <elementRef key="listOrg" maxOcc
urs="1"
          minOccurs="1"/>
      </alternate>

```

```

<alternate maxOccurs="unbounded"
minOccurs="0">
  <elementRef key="relation"
    maxOccurs="1" minOccurs="1"/>
  <elementRef key="listRelation"
    maxOccurs="1" minOccurs="1"/>
</alternate>
</sequence>
</sequence>
</content>

```

Schema Declaration

```

element listOrg
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.declarable.attributes,
  tei_att.sortable.attributes,
  tei_att.typed.attributes,
  (
    tei_model.headLike*,
    tei_desc*,
    ( relation | listRelation )*,
    ( ( ( tei_org | tei_listOrg )+, ( relatio
n | listRelation )* )+ )
  )
}

```

<listPerson>

<listPerson> (list of persons) contains a list of descriptions, each of which provides information about an identifiable person or a group of people, for example the participants in a language interaction, or the people referred to in a historical source. [[14.3.2. The Person Element](#) [16.2. Contextual Information](#) [2.4. The Profile Description](#) [16.3.2. Declarable Elements](#)]

Module

namesdates

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*

	• <i>@prev</i> • <i>@exclude</i> • <i>@select</i> • att.global.rendition • <i>@rend</i> • <i>@style</i> • <i>@rendition</i> • att.global.responsibility • <i>@cert</i> • <i>@resp</i> • att.global.source • <i>@source</i> • att.cmc • <i>@generatedBy</i> • att.declarable • <i>@default</i> • att.sortable • <i>@sortKey</i> • att.typed • <i>@type</i> • <i>@subtype</i>
Member of	model.listLike model.orgPart
Contained by	core: desc item note p title
	corpus: particDesc
	header: change licence sourceDesc
	namesdates: event listPerson org
	textstructure: body
May contain	core: desc
	namesdates: listPerson org person
Note	The <i>type</i> attribute may be used to distinguish lists of people of a particular type if convenient.
Example	<pre> <listPerson type="respondents"> <personGrp xml:id="PXXX"/> <person age="mid" sex="2" xml:id="P1234"/> <person age="mid" sex="1" xml:id="P4332"/> <listRelation> <relation mutual="#P1234 #P4332" name="spouse" type="personal"/> </listRelation> </listPerson> </pre>
Content model	<pre> <content> <sequence> <classRef key="model.headLike" </pre>

```

    maxOccurs="unbounded" minOccurs
="0"/>
    <elementRef key="desc"
    maxOccurs="unbounded" minOccurs
="0"/>
    <alternate maxOccurs="unbounded"
    minOccurs="0">
    <elementRef key="relation" maxOcc
urs="1"
    minOccurs="1"/>
    <elementRef key="listRelation"
    maxOccurs="1" minOccurs="1"/>
    </alternate>
    <sequence maxOccurs="unbounded"
    minOccurs="1">
    <alternate maxOccurs="unbounded"
    minOccurs="1">
    <classRef key="model.personLike"
    maxOccurs="1" minOccurs="1"/>
    <elementRef key="listPerson"
    maxOccurs="1" minOccurs="1"/>
    </alternate>
    <alternate maxOccurs="unbounded"
    minOccurs="0">
    <elementRef key="relation"
    maxOccurs="1" minOccurs="1"/>
    <elementRef key="listRelation"
    maxOccurs="1" minOccurs="1"/>
    </alternate>
    </sequence>
</sequence>
</content>

```

Schema Declaration

```

element listPerson
{
    tei_att.global.attributes,
    tei_att.cmc.attributes,
    tei_att.declarable.attributes,
    tei_att.sortable.attributes,
    tei_att.typed.attributes,
    (
        tei_model.headLike*,
        tei_desc*,
        ( relation | listRelation )*,
        (
            ( tei_model.personLike | tei_list

```

```

Person )+,
      ( relation | listRelation )*
    )+
  )
}

```

<listPlace>

<listPlace> (list of places) contains a list of places, optionally followed by a list of relationships (other than containment) defined amongst them. [[2.2.7. The Source Description 14.3.4. Places](#)]

Module

namesdates

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.declarable
 - *@default*
- att.sortable
 - *@sortKey*
- att.typed
 - *@type*
 - *@subtype*

Member of Contained by

model.listLike model.orgPart
core: desc item note p title

May contain

Example

Content model

corpus: settingDesc
header: change licence sourceDesc
namesdates: event listPlace org place
textstructure: body

core: desc
namesdates: listPlace place
<listPlace type="offshoreIslands">
 <place>
 <placeName>La roche qui pleure</
placeName>
 </place>
 <place>
 <placeName>Ile aux cerfs</
placeName>
 </place>
</listPlace>

<content>
 <sequence>
 <classRef key="model.headLike"
 maxOccurs="unbounded" minOccurs
="0"/>
 <elementRef key="desc"
 maxOccurs="unbounded" minOccurs
="0"/>
 <alternate maxOccurs="unbounded"
 minOccurs="0">
 <elementRef key="relation" maxOcc
urs="1"
 minOccurs="1"/>
 <elementRef key="listRelation"
 maxOccurs="1" minOccurs="1"/>
 </alternate>
 <sequence maxOccurs="unbounded"
 minOccurs="1">
 <alternate maxOccurs="unbounded"
 minOccurs="1">
 <classRef key="model.placeLike"
 maxOccurs="1" minOccurs="1"/>
 <elementRef key="listPlace"
 maxOccurs="1" minOccurs="1"/>
 </alternate>
 <alternate maxOccurs="unbounded"
 minOccurs="0">
 <elementRef key="relation"
 maxOccurs="1" minOccurs="1"/>
 <elementRef key="listRelation"
 maxOccurs="1" minOccurs="1"/>

```

    </alternate>
  </sequence>
</sequence>
</content>

```

Schema Declaration

```

element listPlace
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.declarable.attributes,
  tei_att.sortable.attributes,
  tei_att.typed.attributes,
  (
    tei_model.headLike*,
    tei_desc*,
    ( relation | listRelation )*,
    (
      (
        ( tei_model.placeLike | tei_listPl
ace )+,
        ( relation | listRelation )*
      )+
    )
  )
}

```

<name>

<name> (name, proper noun) contains a proper noun or noun phrase. [[3.6.1. Referring Strings](#)]

Module

Attributes

- core
 - att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition

- *@rend*
- *@style*
- *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.editLike
 - *@evidence*
 - *@instant*
- att.personal
 - *@full*
 - *@sort*
 - att.naming
 - *@role*
 - *@nymRef*
 - att.canonical
 - *@key*
 - *@ref*
- att.typed
 - *@type*
 - *@subtype*

model.nameLike.agent

Member of

Contained by

model.personPart
core: bibl date desc editor item name
note p pubPlace publisher resp
respStmt term title
header: catDesc change licence
namesdates: affiliation bloc country
eventName forename gender
nameLink org person place placeName
roleName surname

May contain

core: date name note ptr term title
header: idno
namesdates: affiliation bloc country
eventName forename nameLink
placeName roleName surname
character data

Note

Proper nouns referring to people, places, and organizations may be tagged instead with <persName>, <placeName>, or <orgName>, when the TEI module for names and dates is included.

Example

```
<name type="person">Thomas Hoccle  
ve</name>  
<name type="place">Villingaholt</  
name>  
<name type="org">Vetus Latina Instit  
ut</name>  
<name ref="#HOC001" type="person"  
>Occleve</name>
```

Content model

```
<content>  
  <macroRef key="macro.phraseSeq"/>  
</content>
```

Schema Declaration

```
element name  
{  
  tei_att.global.attributes,  
  tei_att.cmc.attributes,  
  tei_att.datable.attributes,  
  tei_att.editLike.attributes,  
  tei_att.personal.attributes,  
  tei_att.typed.attributes,  
  tei_macro.phraseSeq  
}
```

<nameLink>

<nameLink> (name link) contains a connecting phrase or link used within a name but not regarded as part of it, such as *van der* or *of*. [[14.2.1. Personal Names](#)]

Module

Attributes

namesdates

- att.global
 - @xml:id
 - @n
 - @xml:lang
 - @xml:base
 - @xml:space
 - att.global.linking
 - @corresp
 - @synch
 - @sameAs
 - @copyOf
 - @next
 - @prev
 - @exclude
 - @select
 - att.global.rendition
 - @rend
 - @style
 - @rendition
 - att.global.responsibility
 - @cert
 - @resp
 - att.global.source
 - @source
- att.cmc
 - @generatedBy
- att.typed
 - @type
 - @subtype

model.persNamePart

core: bibl date desc editor item name
note p pubPlace publisher resp term
title

header: catDesc change licence

namesdates: affiliation bloc country

eventName forename gender

nameLink org placeName roleName
surname

core: date name note ptr term title

header: idno

namesdates: affiliation bloc country

eventName forename nameLink

Member of

Contained by

May contain

Example

```
placeName roleName surname
character data
<persName>
  <forename>Frederick</forename>
  <nameLink>van der</nameLink>
  <surname>Tronck</surname>
</persName>
```

Example

```
<persName>
  <forename>Alfred</forename>
  <nameLink>de</nameLink>
  <surname>Musset</surname>
</persName>
```

Content model

```
<content>
  <macroRef key="macro.phraseSeq"/>
</content>
```

Schema Declaration

```
element nameLink
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.typed.attributes,
  tei_macro.phraseSeq
}
```

<note>

<note> (note) contains a note or annotation. [[3.9.1. Notes and Simple Annotation](#) [2.2.6. The Notes Statement](#) [3.12.2.8. Notes and Statement of Language](#) [10.3.5.4. Notes within Entries](#)]

Module

core

Attributes

- att.global
 - @xml:id
 - @n
 - @xml:lang
 - @xml:base
 - @xml:space
- att.global.linking
 - @corresp
 - @synch
 - @sameAs
 - @copyOf
 - @next
 - @prev
 - @exclude
 - @select
- att.global.rendition

- *@rend*
- *@style*
- *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.anchoring
 - *@anchored*
 - *@targetEnd*
- att.cmc
 - *@generatedBy*
- att.placement
 - *@place*
- att.pointing
 - *@targetLang*
 - *@target*
 - *@evaluate*
- att.typed
 - *@type*
 - *@subtype*
- att.written
 - *@hand*

**Member of
Contained by**

model.noteLike
 core: bibl date editor item list name
 note p pubPlace publisher resp
 respStmt term title
 header: change licence
 namesdates: affiliation bloc country
 event eventName forename gender
 nameLink org person place placeName
 roleName surname
 textstructure: body text
 core: bibl date desc list listBibl name
 note p ptr term title
 header: idno
 namesdates: affiliation bloc country
 eventName forename listEvent listOrg
 listPerson listPlace nameLink
 placeName roleName surname
 character data

May contain

Example

In the following example, the translator has supplied a footnote containing an explanation of the term translated as "painterly":
 And yet it is not only
 in the great line of Italian renaissance

art, but even in the painterly <note place="bottom" resp="#MDMH" type="gloss">
 <term xml:lang="de">Malerisch</term>. This word has, in the German, two distinct meanings, one objective, a quality residing in the object, the other subjective, a mode of apprehension and creation. To avoid confusion, they have been distinguished in English as <mentioned>picturesque</mentioned> and <mentioned>painterly</mentioned> respectively.
 </note> style of the Dutch genre painters of the seventeenth century that drapery has this psychological significance.

<!-- elsewhere in the document -->
 <respStmt xml:id="MDMH">
 <resp>translation from German to English</resp>
 <name>Hottinger, Marie Donald Mackie</name>
 </respStmt>

For this example to be valid, the code MDMH must be defined elsewhere, for example by means of a responsibility statement in the associated TEI header.

The global *n* attribute may be used to supply the symbol or number used to mark the note's point of attachment in the source text, as in the following example:

Mevorakh b. Saadya's mother, the matriarch of the family during the second half of the eleventh century, <note anchored="true" n="126"> The alleged mention of Judah Nagid's mother in a letter from 1071 is, in fact, a reference to Judah's children; cf. above, nn. 111 and

Example

d 54. </note> is well known from Geniza documents published by Jacob Mann. However, if notes are numbered in sequence and their numbering can be reconstructed automatically by processing software, it may well be considered unnecessary to record the note numbers.

Content model

```
<content>
  <macroRef key="macro.specialPara"/>
</content>
```

Schema Declaration

```
element note
{
  tei_att.global.attributes,
  tei_att.anchoring.attributes,
  tei_att.cmc.attributes,
  tei_att.placement.attributes,
  tei_att.pointing.attributes,
  tei_att.typed.attributes,
  tei_att.written.attributes,
  tei_macro.specialPara
}
```

<org>

<org> (organization) provides information about an identifiable organization such as a business, a tribe, or any other grouping of people. [[14.3.3. Organizational Data](#)]

Module

Attributes

```
namesdates
  • att.global
    • @xml:id
    • @n
    • @xml:lang
    • @xml:base
    • @xml:space
    • att.global.linking
      • @corresp
      • @synch
      • @sameAs
      • @copyOf
      • @next
      • @prev
      • @exclude
```

	• <i>@select</i> • att.global.rendition • <i>@rend</i> • <i>@style</i> • <i>@rendition</i> • att.global.responsibility • <i>@cert</i> • <i>@resp</i> • att.global.source • <i>@source</i> • att.editLike • <i>@evidence</i> • <i>@instant</i> • att.sortable • <i>@sortKey</i> • att.typed • <i>@type</i> • <i>@subtype</i>
role	specifies a primary role or classification for the organization. Status Optional Datatype 1–∞ occurrences of teidata .enumerated separated by whitespace Note Values for this attribute may be locally defined by a project, using arbitrary keywords such as <i>artist</i>, <i>employer</i>,

familyGroup, or politicalParty, each of which should be associated with a definition. Such local definitions will typically be provided by a <desc> for each <valItem> element in the schema specification of the project's customization.

**Member of
Contained by**

model.personLike
corpus: particDesc
namesdates: event listOrg listPerson
org

May contain

core: bibl desc listBibl name note p ptr
header: idno
namesdates: bloc country event
eventName forename listEvent listOrg
listPerson listPlace nameLink org
person place placeName roleName
surname

Example

```
<org xml:id="JAMs">
  <orgName>Justified Ancients of Mummu</orgName>
  <desc>An underground anarchist collective spearheaded by
  <persName>Hagbard Celine</
```

```

persName>, who fight the Illuminati
  from a golden submarine, the <name
>Leif Ericson</name>
</desc>
<bibl>
  <author>Robert Shea</author>
  <author>Robert Anton Wilson</
author>
  <title>The Illuminatus! Trilogy</
title>
</bibl>
</org>

```

Content model

```

<content>
  <sequence>
    <classRef key="model.headLike"
      maxOccurs="unbounded" minOccurs
="0"/>
    <alternate>
      <classRef key="model.pLike"
        maxOccurs="unbounded" minOccurs
="0"/>
      <alternate maxOccurs="unbounded"
minOccurs="0">
        <classRef key="model.labelLike"/>
        <classRef key="model.nameLike"/>
        <classRef key="model.placeLike"/>
        <classRef key="model.orgPart"/>
        <classRef key="model.milestoneLik
e"/>
      </alternate>
    </alternate>
    <alternate maxOccurs="unbounded"
minOccurs="0">
      <classRef key="model.noteLike"/>
      <classRef key="model.biblLike"/>
      <elementRef key="linkGrp"/>
      <elementRef key="link"/>
      <elementRef key="ptr"/>
    </alternate>
    <classRef key="model.personLike"
      maxOccurs="unbounded" minOccurs
="0"/>
  </sequence>
</content>

```

Schema Declaration

element org

```

{
  tei_att.global.attributes,
  tei_att.editLike.attributes,
  tei_att.sortable.attributes,
  tei_att.typed.attributes,
  attribute role { list { + } }?,
  (
    tei_model.headLike*,
    (
      tei_model.pLike*
      | (
        tei_model.labelLike
        | tei_model.nameLike
        | tei_model.placeLike
        | tei_model.orgPart
        | tei_model.milestoneLike
      )*
    ),
    ( tei_model.noteLike | tei_model.bibliLike | linkGrp | link | tei_ptr )*,
    tei_model.personLike*
  )
}

```

<p>

<p> (paragraph) marks paragraphs in prose. [[3.1. Paragraphs](#) [7.2.5. Speech Contents](#)]

Module

Attributes

- core
 - att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*

	• att.global.responsibility • <i>@cert</i> • <i>@resp</i> • att.global.source • <i>@source</i> • att.cmc • <i>@generatedBy</i> • att.declaring • <i>@decls</i> • att.fragmentable • <i>@part</i> • att.written • <i>@hand</i>
Member of Contained by	model.pLike core: item note corpus: particDesc settingDesc header: availability change encodingDesc licence publicationStmt sourceDesc namesdates: event org person place textstructure: body core: bibl date desc list listBibl name note ptr term title header: idno namesdates: affiliation bloc country eventName forename listEvent listOrg listPerson listPlace nameLink placeName roleName surname character data
May contain	
Example	<p>Hallgerd was outside. <q>There is blood on your axe,</q> she said. <q>What have you done?</q> </p> <p> <q>I have now arranged that you can be married a second time,</q> replied Thjostolf. </p> <p> <q>Then you must mean that Thorvald is dead,</q> she said. </p> <p> <q>Yes,</q> said Thjostolf. <q>And now you must think up some plan for me.</q> </p>

Schematron

```
<sch:rule context="tei:p">
  <sch:report test="(ancestor::tei:ab or
  ancestor::tei:p) and
  not( ancestor::tei:floatingText |
  parent::tei:exemplum | parent::tei:item
  | parent::tei:note | parent::tei:q |
  parent::tei:quote | parent::tei:remarks |
  parent::tei:said | parent::tei:sp |
  parent::tei:stage | parent::tei:cell |
  parent::tei:figure )"> Abstract model
  violation: Paragraphs may not occur
  inside other paragraphs or ab
  elements. </sch:report> </sch:rule>
```

Schematron

```
<sch:rule context="tei:l//tei:p">
  <sch:assert test="ancestor::tei:floatin
  gText | parent::tei:figure |
  parent::tei:note"> Abstract model
  violation: Metrical lines may not
  contain higher-level structural
  elements such as div, p, or ab, unless p
  is a child of figure or note, or is a
  descendant of floatingText.
  </sch:assert> </sch:rule>
```

Content model

```
<content>
  <macroRef key="macro.paraContent"/
  >
</content>
```

Schema Declaration

```
element p
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.declaring.attributes,
  tei_att.fragmentable.attributes,
  tei_att.written.attributes,
  tei_macro.paraContent
}
```

<particDesc>

<particDesc> (participation description) describes the identifiable speakers, voices, or other participants in any kind of text or other persons named or otherwise referred to in a text, edition, or metadata. [[16.2. Contextual Information](#)]

Module

corpus

Attributes

- att.global

- *@xml:id*
- *@n*
- *@xml:lang*
- *@xml:base*
- *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.declarable
 - *@default*

**Member of
Contained by
May contain**

Note

model.profileDescPart
header: profileDesc
core: p
namesdates: listOrg listPerson org
person
May contain a prose description
organized as paragraphs, or a
structured list of persons and person
groups, with an optional formal
specification of any relationships
amongst them.

Example

```
<particDesc>
<listPerson>
  <person age="mid" sex="2" xml:id="
P-1234">
    <p>Female informant, well-
educated, born in
      Shropshire UK, 12 Jan 1950, of un
known occupation. Speaks French flue
ntly.
      Socio-Economic status B2.</p>
  </person>
```

```

<person sex="1" xml:id="P-4332">
  <persName>
    <surname>Hancock</surname>
    <forename>Antony</forename>
    <forename>Aloysius</forename>
    <forename>St John</forename>
  </persName>
  <residence notAfter="1959">
    <address>
      <street>Railway Cuttings</street>
      <settlement>East Cheam</
settlement>
    </address>
  </residence>
  <occupation>comedian</
occupation>
</person>
<listRelation>
  <relation mutual="#P-1234 #P-
4332"
    name="spouse" type="personal"/>
</listRelation>
</listPerson>
</particDesc>

```

This example shows both a very simple person description, and a very detailed one, using some of the more specialized elements from the module for Names and Dates.

Content model

```

<content>
  <alternate>
    <classRef key="model.pLike"
      maxOccurs="unbounded" minOccurs
="1"/>
    <alternate maxOccurs="unbounded"
      minOccurs="1">
      <classRef key="model.personLike"/
>
    <elementRef key="listPerson"/>
    <elementRef key="listOrg"/>
  </alternate>
</alternate>
</content>

```

Schema Declaration

```

element particDesc
{

```

```

    tei_att.global.attributes,
    tei_att.declarable.attributes,
    (
        tei_model.pLike+
        | ( tei_model.personLike | tei_listPers
on | tei_listOrg )+
    )
}

```

<person>

<person> (person) provides information about an identifiable individual, for example a participant in a language interaction, or a person referred to in a historical source. [[14.3.2. The Person Element](#) [16.2.2. The Participant Description](#)]

Module

Attributes

namesdates

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
 - att.editLike
 - *@evidence*
 - *@instant*
 - att.sortable
 - *@sortKey*

role

specifies a primary
role or
classification for

the person.

Status Optional

Datatype 1-∞

occurrences
of teidata
.enumerated
separated by
whitespace

Note

Values for this attribute may be locally defined by a project, using arbitrary keywords such as *artist*, *employer*, *author*, *relative*, or *servant*, each of which should be associated with a definition. Such local definitions will typically be provided by a <valList> element in the

	project schema specificat ion.
sex	specifies the sex of the person. Status Optional Datatype 1-∞ occurren ces of teidata .sex separate d by whitespa ce Note Values for this attribute may be defined locally by a project, or they may refer to an external standard.
gender	specifies the gender of the person. Status Optional Datatype 1-∞ occurren ces of teidata .gender separate d by whitespa ce Note Values for this attribute may be defined locally by

	a project, or they may refer to an external standard.
age	specifies an age group for the person. Status Optional Datatype teidata.enumerated Note Values for this attribute may be locally defined by a project, using arbitrary keywords such as <i>infant</i>, <i>child</i>, <i>teen</i>, <i>adult</i>, or <i>senior</i>, each of which should be associated with a definition. Such local definitions will typically be provided by a <valList> element

in the
project
schema
specificat
ion.

**Member of
Contained by**

May contain

Note

Example

Example

Example

model.personLike
corpus: particDesc
namesdates: event listPerson org
core: bibl listBibl name note p ptr
header: idno
namesdates: affiliation event gender
listEvent

May contain either a prose description organized as paragraphs, or a sequence of more specific demographic elements drawn from the model.personPart class.

```
<person age="adult" sex="F">
  <p>Female respondent, well-
  educated, born in Shropshire UK, 12 Ja
  n 1950, of unknown occupation. Speak
  s French fluently. Socio-Economic
  status B2.</p>
</person>
```

```
<person age="immortal" role="god"
  sex="intersex">
  <persName>Hermaphroditos</
  persName>
  <persName xml:lang="grc">Ἑρμαφρό
  διτος</persName>
</person>
```

```
<person role="poet" sex="M" xml:id=
"Ovi01">
  <persName xml:lang="en">Ovid</
  persName>
  <persName xml:lang="la">Publius Ov
  idius Naso</persName>
  <birth when="-0044-03-20"> 20 Marc
  h 43 BC <placeName>
    <settlement type="city">Sulmona</
    settlement>
    <country key="IT">Italy</country>
  </placeName>
  </birth>
  <death notAfter="0018" notBefore="
  0017">17 or 18 AD <placeName>
    <settlement type="city">Tomis (Con
```

```

stanta)</settlement>
  <country key="RO">Romania</
country>
  </placeName>
</death>
</person>

```

Example

The following exemplifies an adaptation of the vCard standard to indicate an unknown gender for a fictional character.

```

<person gender="U" xml:id="ariel">
  <persName>Ariel</persName>
  <note>Character in <title level="m">
The Tempest</title>.</note>
</person>

```

Content model

```

<content>
  <alternate>
    <classRef key="model.pLike"
      maxOccurs="unbounded" minOccurs
="1"/>
    <alternate maxOccurs="unbounded"
      minOccurs="0">
      <classRef key="model.personPart"/>
      <classRef key="model.global"/>
      <elementRef key="ptr"/>
    </alternate>
  </alternate>
</content>

```

Schema Declaration

```

element person
{
  tei_att.global.attributes,
  tei_att.editLike.attributes,
  tei_att.sortable.attributes,
  attribute role { list { + } }?,
  attribute sex { list { + } }?,
  attribute gender { list { + } }?,
  attribute age { text }?,
  (
    tei_model.pLike+
    | ( tei_model.personPart | tei_model.
global | tei_ptr )*
  )
}

```

<place>

<place> (place) contains data about a geographic location. [[14.3.4. Places](#)]

Module

namesdates

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.editLike
 - *@evidence*
 - *@instant*
- att.sortable
 - *@sortKey*
- att.typed
 - *@type*
 - *@subtype*

Member of

model.placeLike

Contained by

corpus: settingDesc

May contain

namesdates: event listPlace org place
core: bibl desc listBibl name note p ptr
header: idno
namesdates: bloc country event
listEvent listPlace place placeName
<place>
 <country>Lithuania</country>
 <country xml:lang="lt">Lietuva</country>
</place>

Example

Content model

```
<settlement>Vilnius</settlement>
</place>
<place>
  <settlement>Kaunas</settlement>
</place>
</place>

<content>
  <sequence>
    <classRef key="model.headLike"
      maxOccurs="unbounded" minOccurs="0"/>
    <alternate>
      <classRef key="model.pLike"
        maxOccurs="unbounded" minOccurs="0"/>
      <alternate maxOccurs="unbounded"
        minOccurs="0">
        <classRef key="model.labelLike"/>
        <classRef key="model.placeStateLike"/>
        <classRef key="model.eventLike"/>
        <elementRef key="name"/>
      </alternate>
    </alternate>
    <alternate maxOccurs="unbounded"
      minOccurs="0">
      <classRef key="model.noteLike"/>
      <classRef key="model.biblLike"/>
      <elementRef key="idno"/>
      <elementRef key="ptr"/>
      <elementRef key="linkGrp"/>
      <elementRef key="link"/>
    </alternate>
    <alternate maxOccurs="unbounded"
      minOccurs="0">
      <classRef key="model.placeLike"/>
      <elementRef key="listPlace"/>
    </alternate>
  </sequence>
</content>
```

Schema Declaration

```
element place
{
  tei_att.global.attributes,
  tei_att.editLike.attributes,
  tei_att.sortable.attributes,
```

```

tei_att.typed.attributes,
(
  tei_model.headLike*,
  (
    tei_model.pLike*
    | (
      tei_model.labelLike
      | tei_model.placeStateLike
      | tei_model.eventLike
      | tei_name
    )*
  ),
  (
    tei_model.noteLike
    | tei_model.biblLike
    | tei_idno
    | tei_ptr
    | linkGrp
    | link
  )*,
  ( tei_model.placeLike | tei_listPlace
)*
)
}

```

<placeName>

<placeName> (place name) contains an absolute or relative place name.
[\[14.2.3. Place Names\]](#)

Module

Attributes

- namesdates
- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*

- *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*
 - *@from-iso*
 - *@to-iso*
 - att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*
- att.editLike
 - *@evidence*
 - *@instant*
- att.personal
 - *@full*
 - *@sort*
- att.naming
 - *@role*
 - *@nymRef*
 - att.canonical
 - *@key*
 - *@ref*
- att.typed
 - *@type*
 - *@subtype*

Member of
Contained by

model.placeNamePart
core: bibl date desc editor item name
note p pubPlace publisher resp term

	title header: catDesc change licence namesdates: affiliation bloc country eventName forename gender nameLink org place placeName roleName surname core: date name note ptr term title header: idno namesdates: affiliation bloc country eventName forename nameLink placeName roleName surname character data
May contain	
Example	<placeName> <settlement>Rochester</settlement> <region>New York</region> </placeName>
Example	<placeName> <geogName>Arrochar Alps</ geogName> <region>Argylshire</region> </placeName>
Example	<placeName> <measure>10 miles</measure> <offset>Northeast of</offset> <settlement>Attica</settlement> </placeName>
Content model	<content> <macroRef key="macro.phraseSeq"/> </content>
Schema Declaration	element placeName { tei_att.global.attributes, tei_att.cmc.attributes, tei_att.dataable.attributes, tei_att.editLike.attributes, tei_att.personal.attributes, tei_att.typed.attributes, tei_macro.phraseSeq }
<profileDesc>	
<profileDesc> (text-profile description) provides a detailed description of non-bibliographic aspects of a text, specifically the languages and sublanguages used, the situation in which it was produced, the participants	

and their setting. [[2.4. The Profile Description 2.1.1. The TEI Header and Its Components](#)]

Module

Attributes

header

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*

Member of
Contained by
May contain
Note

model.teiHeaderPart

header: *teiHeader*

corpus: *particDesc settingDesc*

Although the content model permits it, it is rarely meaningful to supply multiple occurrences for any of the child elements of *<profileDesc>* unless these are documenting multiple texts.

Example

```
<profileDesc>
  <langUsage>
    <language ident="fr">French</
language>
  </langUsage>
  <textDesc n="novel">
    <channel mode="w">print; part issu
es</channel>
    <constitution type="single"/>
    <derivation type="original"/>
    <domain type="art"/>
    <factuality type="fiction"/>
```

```

    <interaction type="none"/>
    <preparedness type="prepared"/>
    <purpose degree="high" type="enter
tain"/>
    <purpose degree="medium" type="in
form"/>
  </textDesc>
  <settingDesc>
    <setting>
      <name>Paris, France</name>
      <time>Late 19th century</time>
    </setting>
  </settingDesc>
</profileDesc>

```

Content model

```

<content>
  <classRef key="model.profileDescPart
"
    maxOccurs="unbounded" minOccurs
="0"/>
</content>

```

Schema Declaration

```

element profileDesc { tei_att.global.att
ributes, tei_model.profileDescPart* }

```

<ptr>

<ptr> (pointer) defines a pointer to another location. [[3.7. Simple Links and Cross-References](#) [17.1. Links](#)]

Module

Attributes

```

core
  • att.global
    • @xml:id
    • @n
    • @xml:lang
    • @xml:base
    • @xml:space
    • att.global.linking
      • @corresp
      • @synch
      • @sameAs
      • @copyOf
      • @next
      • @prev
      • @exclude
      • @select
    • att.global.rendition
      • @rend

```

	• <i>@style</i> • <i>@rendition</i> • att.global.responsibility • <i>@cert</i> • <i>@resp</i> • att.global.source • <i>@source</i> • att.cReferencing • <i>@cRef</i> • att.cmc • <i>@generatedBy</i> • att.declaring • <i>@decls</i> • att.internetMedia • <i>@mimeType</i> • att.pointing • <i>@targetLang</i> • <i>@target</i> • <i>@evaluate</i> • att.typed • <i>@type</i> • <i>@subtype</i>
Member of	model.ptrLike
Contained by	core: bibl date desc editor item name note p pubPlace publisher resp term title header: catDesc change licence publicationStmnt namesdates: affiliation bloc country event eventName forename gender nameLink org person place placeName roleName surname
May contain	Empty element
Note	The <i>target</i> and <i>cRef</i> attributes are mutually exclusive.
Example	<pre><ptr target="#p143 #p144"/> <ptr target="http://www.tei-c.org"/> <ptr cRef="1.3.4"/></pre>
Schematron	<pre><sch:rule context="tei:ptr"> <sch:report test="@target and @cRef">Only one of the attributes @target and @cRef may be supplied on <sch:name/>.</sch:report> </sch:rule></pre>
Content model	<pre><content> <empty/></pre>

</content>

Schema Declaration

```
element ptr
{
  tei_att.global.attributes,
  tei_att.cReferencing.attributes,
  tei_att.cmc.attributes,
  tei_att.declaring.attributes,
  tei_att.internetMedia.attributes,
  tei_att.pointing.attributes,
  tei_att.typed.attributes,
  empty
}
```

<pubPlace>

<pubPlace> (publication place) contains the name of the place where a bibliographic item was published. [[3.12.2.4. Imprint, Size of a Document, and Reprint Information](#)]

Module

Attributes

```
core
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs
    • @copyOf
    • @next
    • @prev
    • @exclude
    • @select
  • att.global.rendition
    • @rend
    • @style
    • @rendition
  • att.global.responsibility
    • @cert
    • @resp
  • att.global.source
    • @source
• att.naming
  • @role
  • @nymRef
```

	• att.canonical • @key • @ref
Member of	model.imprintPart
Contained by	model.publicationStmtPart.detail
May contain	core: bibl header: publicationStmt core: date name note ptr term title header: idno namesdates: affiliation bloc country eventName forename nameLink placeName roleName surname character data
Example	<pre> <publicationStmt> <publisher>Oxford University Press</ publisher> <pubPlace>Oxford</pubPlace> <date>1989</date> </publicationStmt> </pre>
Content model	<pre> <content> <macroRef key="macro.phraseSeq"/> </content> </pre>
Schema Declaration	<pre> element pubPlace { tei_att.global.attributes, tei_att.naming.attributes, tei_macro.phraseSeq } </pre>
<publicationStmt>	
<publicationStmt> (publication statement) groups information concerning the publication or distribution of an electronic or other text. [2.2.4. Publication, Distribution, Licensing, etc. 2.2. The File Description]	
Module	header
Attributes	• att.global • @xml:id • @n • @xml:lang • @xml:base • @xml:space • att.global.linking • @corresp • @synch • @sameAs

- *@copyOf*
- *@next*
- *@prev*
- *@exclude*
- *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*

Contained by
May contain

Note

header: fileDesc

core: date p ptr pubPlace publisher

header: availability idno

Where a publication statement contains several members of the model.publicationStmtPart.agency or model.publicationStmtPart.detail classes rather than one or more paragraphs or anonymous blocks, care should be taken to ensure that the repeated elements are presented in a meaningful order. It is a conformance requirement that elements supplying information about publication place, address, identifier, availability, and date be given following the name of the publisher, distributor, or authority concerned, and preferably in that order.

Example

```
<publicationStmt>
  <publisher>C. Muquardt </
publisher>
  <pubPlace>Bruxelles & Leipzig<
/pubPlace>
  <date when="1846"/>
</publicationStmt>
```

Example

```
<publicationStmt>
  <publisher>Chadwyck Healey</
publisher>
  <pubPlace>Cambridge</pubPlace>
  <availability>
    <p>Available under licence only</p>
  </availability>
```


Example

```
<date when="1992">1992</date>
</publicationStmt>
<publicationStmt>
  <publisher>Zea Books</publisher>
  <pubPlace>Lincoln, NE</pubPlace>
  <date>2017</date>
  <availability>
    <p>This is an open access work licen
sed under a Creative Commons Attribu
tion 4.0 International license.</p>
  </availability>
  <ptr target="http://
digitalcommons.unl.edu/zeabook/55"/>
</publicationStmt>
```

Content model

```
<content>
  <alternate>
    <sequence maxOccurs="unbounded"
      minOccurs="1">
      <classRef key="model.publicationSt
mtPart.agency"/>
      <classRef key="model.publicationSt
mtPart.detail"
        maxOccurs="unbounded" minOccur
s="0"/>
    </sequence>
    <classRef key="model.pLike"
      maxOccurs="unbounded" minOccurs
="1"/>
  </alternate>
</content>
```

Schema Declaration

```
element publicationStmt
{
  tei_att.global.attributes,
  (
    (
      (
        tei_model.publicationStmtPart.
agency,
        tei_model.publicationStmtPart.
detail*
      )+
    )
    | tei_model.pLike+
  )
}
```

<publisher>

<publisher> (publisher) provides the name of the organization responsible for the publication or distribution of a bibliographic item. [[3.12.2.4. Imprint, Size of a Document, and Reprint Information](#) [2.2.4. Publication, Distribution, Licensing, etc.](#)]

Module

Attributes

core

- att.global
 - @xml:id
 - @n
 - @xml:lang
 - @xml:base
 - @xml:space
- att.global.linking
 - @corresp
 - @synch
 - @sameAs
 - @copyOf
 - @next
 - @prev
 - @exclude
 - @select
- att.global.rendition
 - @rend
 - @style
 - @rendition
- att.global.responsibility
 - @cert
 - @resp
- att.global.source
 - @source
- att.canonical
 - @key
 - @ref

Member of

Contained by

May contain

model.imprintPart

model.publicationStmtPart.agency

core: bibl

header: publicationStmt

core: date name note ptr term title

header: idno

namesdates: affiliation bloc country

eventName forename nameLink

placeName roleName surname

character data

Note

Use the full form of the name by which a company is usually referred to, rather than any abbreviation of it which may appear on a title page

Example

```
<imprint>
  <pubPlace>Oxford</pubPlace>
  <publisher>Clarendon Press</
publisher>
  <date>1987</date>
</imprint>
```

Content model

```
<content>
  <macroRef key="macro.phraseSeq"/>
</content>
```

Schema Declaration

```
element publisher
{
  tei_att.global.attributes,
  tei_att.canonical.attributes,
  tei_macro.phraseSeq
}
```

<resp>

<resp> (responsibility) contains a phrase describing the nature of a person's intellectual responsibility, or an organization's role in the production or distribution of a work. [[3.12.2.2. Titles, Authors, and Editors](#) [2.2.1. The Title Statement](#) [2.2.2. The Edition Statement](#) [2.2.5. The Series Statement](#)]

Module

core

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*

- att.global.source
 - @source
- att.canonical
 - @key
 - @ref
- att.datable
 - @period
 - att.datable.custom
 - @when-custom
 - @notBefore-custom
 - @notAfter-custom
 - @from-custom
 - @to-custom
 - @datingPoint
 - @datingMethod
 - att.datable.iso
 - @when-iso
 - @notBefore-iso
 - @notAfter-iso
 - @from-iso
 - @to-iso
 - att.datable.w3c
 - @when
 - @notBefore
 - @notAfter
 - @from
 - @to

Contained by
May contain

core: respStmt
core: date name note ptr term title
header: idno
namesdates: affiliation bloc country
eventName forename nameLink
placeName roleName surname
character data

Note

The attribute *ref*, inherited from the class att.canonical may be used to indicate the kind of responsibility in a normalized form by referring directly to a standardized list of responsibility types, such as that maintained by a naming authority, for example the list maintained at <http://www.loc.gov/marc/relators/relacode.html> for bibliographic usage.

Example

```
<respStmt>
  <resp ref="http://id.loc.gov/
  vocabulary/relators/
```

```
com.html">compiler</resp>
  <name>Edward Child</name>
</respStmt>
```

Content model

```
<content>
  <macroRef key="macro.phraseSeq.limited"/>
</content>
```

Schema Declaration

```
element resp
{
  tei_att.global.attributes,
  tei_att.canonical.attributes,
  tei_att.dataable.attributes,
  tei_macro.phraseSeq.limited
}
```

<respStmt>

<respStmt> (statement of responsibility) supplies a statement of responsibility for the intellectual content of a text, edition, recording, or series, where the specialized elements for authors, editors, etc. do not suffice or do not apply. May also be used to encode information about individuals or organizations which have played a role in the production or distribution of a bibliographic work. [[3.12.2.2. Titles, Authors, and Editors](#) [2.2.1. The Title Statement](#) [2.2.2. The Edition Statement](#) [2.2.5. The Series Statement](#)]

Module

core

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility

**Member of
Contained by**

**May contain
Example**

Example

Content model

- *@cert*
- *@resp*
- att.global.source
- *@source*
- att.canonical
- *@key*
- *@ref*

model.respLike
core: bibl
header: titleStmt
core: name note resp
<respStmt>
 <resp>transcribed from original ms</resp>
 <persName>Claus Huitfeldt</persName>
</respStmt>
<respStmt>
 <resp>converted to XML encoding</resp>
 <name>Alan Morrison</name>
</respStmt>

<content>
 <sequence>
 <alternate>
 <sequence>
 <elementRef key="resp"
 maxOccurs="unbounded" minOccurs="1"/>
 <classRef key="model.nameLike.agent"
 maxOccurs="unbounded" minOccurs="1"/>
 </sequence>
 <sequence>
 <classRef key="model.nameLike.agent"
 maxOccurs="unbounded" minOccurs="1"/>
 <elementRef key="resp"
 maxOccurs="unbounded" minOccurs="1"/>
 </sequence>
 </alternate>
 <elementRef key="note"
 maxOccurs="unbounded" minOccurs="1"/>
 </sequence>

```
="0"/>
</sequence>
</content>
```

Schema Declaration

```
element respStmt
{
  tei_att.global.attributes,
  tei_att.canonical.attributes,
  (
    (
      ( tei_resp+, tei_model.nameLike.
agent+ )
      | ( tei_model.nameLike.agent+, tei
_resp+ )
    ),
    tei_note*
  )
}
```

<revisionDesc>

<revisionDesc> (revision description) summarizes the revision history for a file. [[2.6. The Revision Description 2.1.1. The TEI Header and Its Components](#)]

Module

Attributes

- header
- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source

Contained by
May contain

Note

Example

Content model

Schema Declaration

<roleName>

<roleName> (role name) contains a name component which indicates that the referent has a particular role or position in society, such as an official title or rank. [[14.2.1. Personal Names](#)]

- @source
- att.docStatus
- @status

header: teiHeader

core: list

header: change listChange

If present on this element, the *status* attribute should indicate the current status of the document. The same attribute may appear on any <change> to record the status at the time of that change. Conventionally <change> elements should be given in reverse date order, with the most recent change at the start of the list.

```
<revisionDesc status="embargoed">  
  <change when="1991-11-11" who="#  
LB"> deleted chapter 10 </change>  
</revisionDesc>
```

```
<content>  
  <alternate>  
    <elementRef key="list"  
      maxOccurs="unbounded" minOccurs  
="1"/>  
    <elementRef key="listChange"  
      maxOccurs="unbounded" minOccurs  
="1"/>  
    <elementRef key="change"  
      maxOccurs="unbounded" minOccurs  
="1"/>  
  </alternate>  
</content>
```

```
element revisionDesc  
{  
  tei_att.global.attributes,  
  tei_att.docStatus.attributes,  
  ( tei_list+ | tei_listChange+ | tei_cha  
nge+ )  
}
```


Module Attributes

Member of Contained by

namesdates

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.cmc
 - *@generatedBy*
- att.personal
 - *@full*
 - *@sort*
- att.naming
 - *@role*
 - *@nymRef*
 - att.canonical
 - *@key*
 - *@ref*
- att.typed
 - *@type*
 - *@subtype*

model.persNamePart

core: bibl date desc editor item name
note p pubPlace publisher resp term
title

header: catDesc change licence

namesdates: affiliation bloc country

eventName forename gender

nameLink org placeName roleName

May contain

surname
core: date name note ptr term title
header: idno
namesdates: affiliation bloc country
eventName forename nameLink
placeName roleName surname
character data

Note

A <roleName> may be distinguished from an <addName> by virtue of the fact that, like a title, it typically exists independently of its holder.

Example

```
<persName>
  <forename>William</forename>
  <surname>Poulteny</surname>
  <roleName>Earl of Bath</
roleName>
</persName>
```

Example

```
<p>The <roleName role="solicitor_ge
neral">S.G.</roleName> is the only n
ational public official,
including the Supreme Court justices,
required by statute to be "learned in th
e law."</p>
```

Example

```
<p>
  <persName ref="#NJF">
    <roleName role="solicitor_general">
Solicitor General</roleName> Noel J.
Francisco</persName>,
representing the administration, asser
ted in rebuttal that there was nothing t
o disavow (...)
<persName ref="#NJF">Francisco</
persName> had violated the scrupulou
s standard of candor about the facts an
d
the law that <roleName role="solicito
r_general">S.G.s</roleName>, in Rep
ublican and Democratic administration
s
alike, have repeatedly said they must
honor.
</p>
```

Content model

```
<content>
  <macroRef key="macro.phraseSeq"/>
</content>
```

Schema Declaration

```
element roleName
{
  tei_att.global.attributes,
  tei_att.cmc.attributes,
  tei_att.personal.attributes,
  tei_att.typed.attributes,
  tei_macro.phraseSeq
}
```

<settingDesc>

<settingDesc> (setting description) describes the setting or settings within which a language interaction takes place, or other places otherwise referred to in a text, edition, or metadata. [[16.2. Contextual Information 2.4. The Profile Description](#)]

Module

Attributes

```
corpus
  • att.global
    • @xml:id
    • @n
    • @xml:lang
    • @xml:base
    • @xml:space
    • att.global.linking
      • @corresp
      • @synch
      • @sameAs
      • @copyOf
      • @next
      • @prev
      • @exclude
      • @select
    • att.global.rendition
      • @rend
      • @style
      • @rendition
    • att.global.responsibility
      • @cert
      • @resp
    • att.global.source
      • @source
    • att.declarable
      • @default
```

Member of
Contained by
May contain

Note

```
model.profileDescPart
header: profileDesc
core: p
namesdates: listPlace place
May contain a prose description
```

organized as paragraphs, or a series of <setting> elements. If used to record not settings of language interactions, but other places mentioned in the text, then <place> optionally grouped by <listPlace> inside <standOff> should be preferred.

Example

```
<settingDesc>
  <p>Texts recorded in the
    Canadian Parliament building in Otta
    wa, between April and November 1988
  </p>
</settingDesc>
```

Content model

```
<content>
  <alternate>
    <classRef key="model.pLike"
      maxOccurs="unbounded" minOccurs
      ="1"/>
    <alternate maxOccurs="unbounded"
      minOccurs="1">
      <elementRef key="setting"/>
      <classRef key="model.placeLike"/>
      <elementRef key="listPlace"/>
    </alternate>
  </alternate>
</content>
```

Schema Declaration

```
element settingDesc
{
  tei_att.global.attributes,
  tei_att.declarable.attributes,
  ( tei_model.pLike+ | ( setting | tei_mo
del.placeLike | tei_listPlace )+ )
}
```

<sourceDesc>

<sourceDesc> (source description) describes the source(s) from which an electronic text was derived or generated, typically a bibliographic description in the case of a digitized text, or a phrase such as 'born digital' for a text which has no previous existence. [[2.2.7. The Source Description](#)]

Module

Attributes

header

- att.global
 - @xml:id
 - @n
 - @xml:lang

- *@xml:base*
- *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*
- att.declarable
 - *@default*

Contained by
May contain

Example

header: fileDesc
core: bibl list listBibl p
namesdates: listEvent listOrg
listPerson listPlace
<sourceDesc>
 <bibl>
 <title level="a">The Interesting stor
y of the Children in the Wood</title>. I
n
 <author>Victor E Neuberg</author>,
 <title>The Penny Histories</title>.
 <publisher>OUP</publisher>
 <date>1968</date>. </bibl>
 </sourceDesc>
<sourceDesc>
 <p>Born digital: no previous source e
xists.</p>
</sourceDesc>

Example

Content model

<content>
 <alternate>
 <classRef key="model.pLike"
 maxOccurs="unbounded" minOccurs
="1"/>
 <alternate maxOccurs="unbounded"
 minOccurs="1">

```

        <classRef key="model.biblLike"/>
        <classRef key="model.sourceDescPart"/>
        <classRef key="model.listLike"/>
    </alternate>
</alternate>
</content>

```

Schema Declaration

```

element sourceDesc
{
    tei_att.global.attributes,
    tei_att.declarable.attributes,
    (
        tei_model.pLike+
        | ( tei_model.biblLike | tei_model.sourceDescPart | tei_model.listLike )+
    )
}

```

<surname>

<surname> (surname) contains a family (inherited) name, as opposed to a given, baptismal, or nick name. [[14.2.1. Personal Names](#)]

Module

Attributes

```

namesdates
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs
    • @copyOf
    • @next
    • @prev
    • @exclude
    • @select
  • att.global.rendition
    • @rend
    • @style
    • @rendition
  • att.global.responsibility
    • @cert
    • @resp
  • att.global.source

```

	• <i>@source</i> • att.cmc • <i>@generatedBy</i> • att.personal • <i>@full</i> • <i>@sort</i> • att.naming • <i>@role</i> • <i>@nymRef</i> • att.canonical • <i>@key</i> • <i>@ref</i> • att.typed • <i>@type</i> • <i>@subtype</i>
Member of	model.persNamePart
Contained by	core: bibl date desc editor item name note p pubPlace publisher resp term title
	header: catDesc change licence namesdates: affiliation bloc country eventName forename gender nameLink org placeName roleName surname
May contain	core: date name note ptr term title header: idno namesdates: affiliation bloc country eventName forename nameLink placeName roleName surname character data
Example	<surname type="combine">St John St evas</surname>
Content model	<content> <macroRef key="macro.phraseSeq"/> </content>
Schema Declaration	element surname { tei_att.global.attributes, tei_att.cmc.attributes, tei_att.personal.attributes, tei_att.typed.attributes, tei_macro.phraseSeq }

<taxonomy>

<taxonomy> (taxonomy) defines a typology either implicitly, by means of a bibliographic citation, or explicitly by a structured taxonomy. [[2.3.7. The Classification Declaration](#)]

Module

Attributes

header

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.datcat
 - *@datcat*
 - *@valueDatcat*
 - *@targetDatcat*

Contained by May contain

Note

Example

header: classDecl taxonomy

core: bibl desc listBibl

header: category taxonomy

Nested taxonomies are common in many fields, so the <taxonomy> element can be nested.

```
<taxonomy xml:id="tax.b">
  <bibl>Brown Corpus</bibl>
  <category xml:id="tax.b.a">
    <catDesc>Press Reportage</
catDesc>
    <category xml:id="tax.b.a1">
      <catDesc>Daily</catDesc>
```



```

</category>
<category xml:id="tax.b.a2">
  <catDesc>Sunday</catDesc>
</category>
<category xml:id="tax.b.a3">
  <catDesc>National</catDesc>
</category>
<category xml:id="tax.b.a4">
  <catDesc>Provincial</catDesc>
</category>
<category xml:id="tax.b.a5">
  <catDesc>Political</catDesc>
</category>
<category xml:id="tax.b.a6">
  <catDesc>Sports</catDesc>
</category>
</category>
<category xml:id="tax.b.d">
  <catDesc>Religion</catDesc>
  <category xml:id="tax.b.d1">
    <catDesc>Books</catDesc>
  </category>
  <category xml:id="tax.b.d2">
    <catDesc>Periodicals and tracts</
catDesc>
  </category>
</category>
</taxonomy>
<taxonomy>
  <category xml:id="literature">
    <catDesc>Literature</catDesc>
    <category xml:id="poetry">
      <catDesc>Poetry</catDesc>
      <category xml:id="sonnet">
        <catDesc>Sonnet</catDesc>
        <category xml:id="shakesSonnet">
          <catDesc>Shakespearean Sonnet</
catDesc>
        </category>
      </category>
      <category xml:id="petraSonnet">
        <catDesc>Petrarchan Sonnet</
catDesc>
      </category>
    </category>
  </category>
  <category xml:id="haiku">
    <catDesc>Haiku</catDesc>
  </category>
</category>

```

Example

```

<category xml:id="drama">
  <catDesc>Drama</catDesc>
</category>
</category>
<category xml:id="meter">
  <catDesc>Metrical Categories</
catDesc>
  <category xml:id="feet">
    <catDesc>Metrical Feet</catDesc>
    <category xml:id="iambic">
      <catDesc>Iambic</catDesc>
    </category>
    <category xml:id="trochaic">
      <catDesc>trochaic</catDesc>
    </category>
  </category>
  <category xml:id="feetNumber">
    <catDesc>Number of feet</
catDesc>
    <category xml:id="pentameter">
      <catDesc>>Pentameter</catDesc>
    </category>
    <category xml:id="tetrameter">
      <catDesc>>Tetrameter</catDesc>
    </category>
  </category>
</taxonomy>
<!-- elsewhere in document -->
<lg ana="#shakesSonnet #iambic #pe
ntameter">
  <l>Shall I compare thee to a summer'
s day</l>
<!-- ... -->
</lg>

```

Content model

```

<content>
  <alternate>
    <alternate>
      <alternate maxOccurs="unbounded"
minOccurs="1">
        <elementRef key="category"/>
        <elementRef key="taxonomy"/>
      </alternate>
    <sequence>
      <alternate maxOccurs="unbounded
"
minOccurs="1">

```

```

        <classRef key="model.descLike"
            maxOccurs="1" minOccurs="1"/>
        <elementRef key="equiv" maxOccurs="1"
            minOccurs="1"/>
        <elementRef key="gloss" maxOccurs="1"
            minOccurs="1"/>
    </alternate>
    <alternate maxOccurs="unbounded"
        minOccurs="0">
        <elementRef key="category"/>
        <elementRef key="taxonomy"/>
    </alternate>
</sequence>
</alternate>
<sequence>
    <classRef key="model.biblLike"/>
    <alternate maxOccurs="unbounded"
        minOccurs="0">
        <elementRef key="category"/>
        <elementRef key="taxonomy"/>
    </alternate>
</sequence>
</alternate>
</content>

```

Schema Declaration

```

element taxonomy
{
    tei_att.global.attributes,
    tei_att.datcat.attributes,
    (
        (
            ( tei_category | tei_taxonomy )+
            | (
                ( tei_model.descLike | equiv | gloss )+,
                ( tei_category | tei_taxonomy )*
            )
        )
        | ( tei_model.biblLike, ( tei_category
            | tei_taxonomy )* )
    )
}

```

<teiHeader>

<teiHeader> (TEI header) supplies descriptive and declarative metadata associated with a digital resource or set of resources. [[2.1.1. The TEI Header and Its Components](#) [16.1. Varieties of Composite Text](#)]

Module

header

Attributes

- att.global
 - @xml:id
 - @n
 - @xml:lang
 - @xml:base
 - @xml:space
- att.global.linking
 - @corresp
 - @synch
 - @sameAs
 - @copyOf
 - @next
 - @prev
 - @exclude
 - @select
- att.global.rendition
 - @rend
 - @style
 - @rendition
- att.global.responsibility
 - @cert
 - @resp
- att.global.source
 - @source

Contained by
May contain

textstructure: TEI
header: encodingDesc fileDesc
profileDesc revisionDesc
One of the few elements
unconditionally required in any TEI
document.

Note

Example

```
<teiHeader>
<fileDesc>
  <titleStmt>
    <title>Shakespeare: the first folio (1
623) in electronic form</title>
    <author>Shakespeare, William (156
4-1616)</author>
    <respStmt>
      <resp>Originally prepared by</
resp>
      <name>Trevor Howard-Hill</
```

name>
 </respStmt>
 <resp>Revised and edited by</
 resp>
 <name>Christine Avern-Carr</
 name>
 </respStmt>
 </titleStmt>
 <publicationStmt>
 <distributor>Oxford Text Archive</
 distributor>
 <address>
 <addrLine>13 Banbury Road, Oxford
 OX2 6NN, UK</addrLine>
 </address>
 <idno type="OTA">119</idno>
 <availability>
 <p>Freely available on a non-
 commercial basis.</p>
 </availability>
 <date when="1968">1968</date>
 </publicationStmt>
 <sourceDesc>
 <bibl>The first folio of Shakespeare,
 prepared by Charlton Hinman (The No
 rton Facsimile,
 1968)</bibl>
 </sourceDesc>
 </fileDesc>
 <encodingDesc>
 <projectDesc>
 <p>Originally prepared for use in th
 e production of a series of old-spelling
 concordances in 1968, this text wa
 s extensively checked and revised for u
 se during the
 editing of the new Oxford Shakesp
 eare (Wells and Taylor, 1989).</p>
 </projectDesc>
 <editorialDecl>
 <correction>
 <p>Turned letters are silently corre
 cted.</p>
 </correction>
 <normalization>
 <p>Original spelling and typograph
 y is retained, except that long s and lig

```

atured
    forms are not encoded.</p>
</normalization>
</editorialDecl>
<refsDecl xml:id="ASLREF">
  <cRefPattern matchPattern="(S+) ([
^.]+)\.(\.*)"
    replacementPattern="#xpath(//
div1[@n='$1']/div2/[@n='$2']//
lb[@n='$3'])">
    <p>A reference is created by assem
bling the following, in the reverse orde
r as that
        listed here: <list>
            <item>the <att>n</att> value of t
he preceding <gi>lb</gi>
            </item>
            <item>a period</item>
            <item>the <att>n</att> value of t
he ancestor <gi>div2</gi>
            </item>
            <item>a space</item>
            <item>the <att>n</att> value of t
he parent <gi>div1</gi>
            </item>
        </list>
    </p>
  </cRefPattern>
</refsDecl>
</encodingDesc>
<revisionDesc>
  <list>
    <item>
      <date when="1989-04-12">12 Apr
89</date> Last checked by CAC</
item>
    <item>
      <date when="1989-03-01">1 Mar 8
9</date> LB made new file</item>
    </list>
  </revisionDesc>
</teiHeader>

<content>
  <sequence>
    <elementRef key="fileDesc"/>
    <classRef key="model.teiHeaderPart
"

```

Content model

```

        maxOccurs="unbounded" minOccurs
        ="0"/>
        <elementRef key="revisionDesc"
        minOccurs="0"/>
    </sequence>
</content>

```

Schema Declaration

```

element teiHeader
{
    tei_att.global.attributes,
    ( tei_fileDesc, tei_model.teiHeaderPa
rt*, tei_revisionDesc? )
}

```

<term>

<term> (term) contains a single-word, multi-word, or symbolic designation which is regarded as a technical term. [[3.4.1. Terms and Glosses](#)]

Module

Attributes

```

core
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs
    • @copyOf
    • @next
    • @prev
    • @exclude
    • @select
  • att.global.rendition
    • @rend
    • @style
    • @rendition
  • att.global.responsibility
    • @cert
    • @resp
  • att.global.source
    • @source
• att.cReferencing
  • @cRef
• att.canonical
  • @key

```

- *@ref*
- att.cmc
 - *@generatedBy*
- att.declaring
 - *@decls*
- att.pointing
 - *@targetLang*
 - *@target*
 - *@evaluate*
- att.sortable
 - *@sortKey*
- att.typed
 - *@type*
 - *@subtype*

**Member of
Contained by**

model.emphLike
 core: bibl date desc editor item name
 note p pubPlace publisher resp term
 title
 header: catDesc change licence
 namesdates: affiliation bloc country
 eventName forename gender
 nameLink placeName roleName
 surname

May contain

core: date name note ptr term title
 header: idno
 namesdates: affiliation bloc country
 eventName forename nameLink
 placeName roleName surname
 character data

Note

When this element appears within an <index> element, it is understood to supply the form under which an index entry is to be made for that location. Elsewhere, it is understood simply to indicate that its content is to be regarded as a technical or specialised term. It may be associated with a <gloss> element by means of its *ref* attribute; alternatively a <gloss> element may point to a <term> element by means of its *target* attribute.

In formal terminological work, there is frequently discussion over whether terms must be atomic or may include multi-word lexical items, symbolic designations, or phraseological units.

The <term> element may be used to mark any of these. No position is taken on the philosophical issue of what a term can be; the looser definition simply allows the <term> element to be used by practitioners of any persuasion.

As with other members of the att.canonical class, instances of this element occurring in a text may be associated with a canonical definition, either by means of a URI (using the *ref* attribute), or by means of some system-specific code value (using the *key* attribute). Because the mutually exclusive *target* and *cRef* attributes overlap with the function of the *ref* attribute, they are deprecated and may be removed at a subsequent release.

Example

A computational device that infers structure

from grammatical strings of words is known as a <term>parser</term>, and much of the history

of NLP over the last 20 years has been occupied with the design of parsers.

Example

We may define <term rend="sc" xml:id="TDPV1">discoursal point of view</term> as

<gloss target="#TDPV1">the relationship, expressed

through discourse structure, between the implied author or some other addresser, and the

fiction.</gloss>

Example

We may define <term ref="#TDPV2" rend="sc">discoursal point of view</term> as

<gloss xml:id="TDPV2">the relationship, expressed

through discourse structure, between the implied author or some other addresser, and the

fiction.</gloss>

Example

We discuss Leech's concept of <term ref="myGlossary.xml#TDPV2" rend="sc">discoursal point of view</term> bel

Content model

ow.

```
<content>
  <macroRef key="macro.phraseSeq"/>
</content>
```

Schema Declaration

```
element term
{
  tei_att.global.attributes,
  tei_att.cReferencing.attributes,
  tei_att.canonical.attributes,
  tei_att.cmc.attributes,
  tei_att.declaring.attributes,
  tei_att.pointing.attributes,
  tei_att.sortable.attributes,
  tei_att.typed.attributes,
  tei_macro.phraseSeq
}
```

<text>

<text> (text) contains a single text of any kind, whether unitary or composite, for example a poem or drama, a collection of essays, a novel, a dictionary, or a corpus sample. [[4. Default Text Structure 16.1. Varieties of Composite Text](#)]

Module

Attributes

```
textstructure
• att.global
  • @xml:id
  • @n
  • @xml:lang
  • @xml:base
  • @xml:space
  • att.global.linking
    • @corresp
    • @synch
    • @sameAs
    • @copyOf
    • @next
    • @prev
    • @exclude
    • @select
  • att.global.rendition
    • @rend
    • @style
    • @rendition
  • att.global.responsibility
    • @cert
    • @resp
```

	• att.global.source • <i>@source</i> • att.declaring • <i>@decls</i> • att.typed • <i>@type</i> • <i>@subtype</i> • att.written • <i>@hand</i>
Member of	model.resource
Contained by	textstructure: TEI
May contain	core: note
Note	textstructure: body This element should not be used to represent a text which is inserted at an arbitrary point within the structure of another, for example as in an embedded or quoted narrative; the <floatingText> is provided for this purpose.
Example	<pre> <text> <front> <docTitle> <titlePart>Autumn Haze</titlePart> </docTitle> </front> <body> <l>Is it a dragonfly or a maple leaf</l> <l>That settles softly down upon the water?</l> </body> </text> </pre>
Example	The body of a text may be replaced by a group of nested texts, as in the following schematic: <pre> <text> <front> <!-- front matter for the whole group --> </front> <group> <text> <!-- first text --> </text> <text> <!-- second text --> </pre>

Content model

```
</text>
</group>
</text>

<content>
  <sequence>
    <classRef key="model.global"
      maxOccurs="unbounded" minOccurs
="0"/>
    <sequence minOccurs="0">
      <elementRef key="front"/>
      <classRef key="model.global"
        maxOccurs="unbounded" minOccur
s="0"/>
    </sequence>
    <alternate>
      <elementRef key="body"/>
      <elementRef key="group"/>
    </alternate>
    <classRef key="model.global"
      maxOccurs="unbounded" minOccurs
="0"/>
    <sequence minOccurs="0">
      <elementRef key="back"/>
      <classRef key="model.global"
        maxOccurs="unbounded" minOccur
s="0"/>
    </sequence>
  </sequence>
</content>
```

Schema Declaration

```
element text
{
  tei_att.global.attributes,
  tei_att.declaring.attributes,
  tei_att.typed.attributes,
  tei_att.written.attributes,
  (
    tei_model.global*,
    ( ( front, tei_model.global* )? ),
    ( tei_body | group ),
    tei_model.global*,
    ( ( back, tei_model.global* )? )
  )
}
```

<title>

<title> (title) contains a title for any kind of work. [[3.12.2.2. Titles, Authors, and Editors](#) [2.2.1. The Title Statement](#) [2.2.5. The Series Statement](#)]

Module

core

Attributes

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
 - att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
 - att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
 - att.global.responsibility
 - *@cert*
 - *@resp*
 - att.global.source
 - *@source*
- att.canonical
 - *@key*
 - *@ref*
- att.cmc
 - *@generatedBy*
- att.datable
 - *@period*
 - att.datable.custom
 - *@when-custom*
 - *@notBefore-custom*
 - *@notAfter-custom*
 - *@from-custom*
 - *@to-custom*
 - *@datingPoint*
 - *@datingMethod*
 - att.datable.iso
 - *@when-iso*
 - *@notBefore-iso*
 - *@notAfter-iso*

	• <i>@from-iso</i> • <i>@to-iso</i>
	• att.dataable.w3c • <i>@when</i> • <i>@notBefore</i> • <i>@notAfter</i> • <i>@from</i> • <i>@to</i>
	• att.typed • type • @subtype
type	classifies the title according to some convenient typology. Derived from att.typed Status Optional Datatype teidata.e numerate d Sample main values include: main title sub (sub ordi nate) subti tle, title of part alt (alte rnat e) alter nate title, often in anot her lang uage , by

which the work is also known

short

abbreviated form of title

desc

(descriptive) descriptive phrase of the work functioning as a title

Note

This attribute is provided for convenience in analysing titles and processing them according to their type; where such

specialized processing is not necessary, there is no need for such analysis, and the entire title, including subtitles and any parallel titles, may be enclosed within a single <title> element.

level

indicates the bibliographic level for a title, that is, whether it identifies an article, book, journal, series, or unpublished material.

Status Optional
Datatype teidata.enumerated

Legal values are: a (analytic) the title applies to an analytic item,

such
as
an
artic
le,
poe
m,
or
othe
r
work
publi
shed
as
part
of a
large
r
item.

m

(mon
ogra
phic)
the
title
appli
es to
a
mon
ogra
ph
such
as a
book
or
othe
r
item
consi
dere
d to
be a
disti
nct
publi
catio
n,
inclu

ding
singl
e
volu
mes
of
multi
-
volu
me
work
s

j

(jour
nal)
the
title
appli
es to
any
seria
l or
perio
dical
publi
catio
n
such
as a
jour
nal,
mag
azin
e, or
news
pape
r

s

(seri
es)
the
title
appli
es to
a
serie
s of

other
wise
e
disti
nct
publi
cation
ns
such
as a
colle
ction

u

(unp
ublis
hed)
the
title
appli
es to
any
unpu
blish
ed
mate
rial
(incl
udin
g
thes
es
and
disse
rtati
ons
unle
ss
publi
shed
by a
com
merc
ial
pres
s)

Note

The level
of a title
is

sometime
 s implied
 by its
 context:
 for
 example,
 a title
 appearin
 g directly
 within an
 <analytic
 >
 element
 is *ipso*
facto of
 level 'a',
 and one
 appearin
 g within
 a
 <series>
 element
 of level
 's'. For
 this
 reason,
 the *level*
 attribute
 is not
 required
 in
 contexts
 where its
 value can
 be
 unambig
 uously
 inferred.
 Where it
 is
 supplied
 in such
 contexts,
 its value
 should
 not
 contradic
 t the

	value implied by its parent element.
Member of Contained by	model.emphLike core: bibl date desc editor item name note p pubPlace publisher resp term title header: catDesc change licence titleStmt namesdates: affiliation bloc country eventName forename gender nameLink placeName roleName surname
May contain	core: bibl date desc list listBibl name note ptr term title header: idno namesdates: affiliation bloc country eventName forename listEvent listOrg listPerson listPlace nameLink placeName roleName surname character data
Note	The attributes <i>key</i> and <i>ref</i> , inherited from the class att.canonical may be used to indicate the canonical form for the title; the former, by supplying (for example) the identifier of a record in some external library system; the latter by pointing to an XML element somewhere containing the canonical form of the title.
Example	<title>Information Technology and the Research Process: Proceedings of a conference held at Cranfield Institute of Technology, UK, 18-21 July 1989</title>
Example	<title>Hardy's Tess of the D'Urbervilles: a machine readable edition</title>
Example	<title type="full"> <title type="main">Synthèse</title> <title type="sub">an international journal for epistemology, methodology and history of science</title>

Content model

</title>

<content>

<macroRef key="macro.paraContent"/>

</content>

Schema Declaration

element title

```
{
  tei_att.global.attributes,
  tei_att.canonical.attributes,
  tei_att.cmc.attributes,
  tei_att.datable.attributes,
  tei_att.typed.attribute.subtype,
  attribute type { text }?,
  attribute level { "a" | "m" | "j" | "s" | "u" }?,
  tei_macro.paraContent
}
```

<titleStmt>

<titleStmt> (title statement) groups information about the title of a work and those responsible for its content. [[2.2.1. The Title Statement](#) [2.2. The File Description](#)]

Module

Attributes

header

- att.global
 - *@xml:id*
 - *@n*
 - *@xml:lang*
 - *@xml:base*
 - *@xml:space*
- att.global.linking
 - *@corresp*
 - *@synch*
 - *@sameAs*
 - *@copyOf*
 - *@next*
 - *@prev*
 - *@exclude*
 - *@select*
- att.global.rendition
 - *@rend*
 - *@style*
 - *@rendition*
- att.global.responsibility
 - *@cert*

Contained by
May contain
Example

- *@resp*
- att.global.source
- *@source*

header: fileDesc
 core: editor respStmt title
 <titleStmt>
 <title>Capgrave's Life of St. John Norbert: a machine-readable transcription</title>
 <respStmt>
 <resp>compiled by</resp>
 <name>P.J. Lucas</name>
 </respStmt>
 </titleStmt>

Content model

<content>
 <sequence>
 <elementRef key="title" maxOccurs="unbounded" minOccurs="1"/>
 <classRef key="model.respLike" maxOccurs="unbounded" minOccurs="0"/>
 </sequence>
 </content>

Schema Declaration

```
element titleStmt
{
  tei_att.global.attributes,
  ( tei_title+, tei_model.respLike* )
}
```

Model classes

model.addressLike

model.addressLike groups elements used to represent a postal or email address. [[1. The TEI Infrastructure](#)]

Module

tei

Used by

model.pPart.data

Members

affiliation

model.attributable

model.attributable groups elements that contain a word or phrase that can be attributed to a source. [[3.3.3. Quotation](#) [4.3.2. Floating Texts](#)]

Module

tei

Used by	macro.phraseSeq model.inter
Members	<i>model.quoteLike</i>

model.availabilityPart

model.availabilityPart groups elements such as licences and paragraphs of text which may appear as part of an availability statement. [[2.2.4. Publication, Distribution, Licensing, etc.](#)]

Module	tei
Used by	availability
Members	<i>licence</i>

model.biblLike

model.biblLike groups elements containing a bibliographic description. [[3.12. Bibliographic Citations and References](#)]

Module	tei
Used by	event listBibl model.inter model.personPart org place sourceDesc taxonomy
Members	<i>bibl listBibl</i>

model.biblPart

model.biblPart groups elements which represent components of a bibliographic description. [[3.12. Bibliographic Citations and References](#)]

Module	tei
Used by	bibl
Members	<i>model.imprintPart[pubPlace publisher]</i> <i>model.respLike[editor respStmt]</i> <i>availability bibl</i>

model.common

model.common groups common chunk- and inter-level elements. [[1.3. The TEI Class System](#)]

Module	tei
Used by	body
Members	<i>model.cmc model.divPart[model.lLike model.pLike[p]]</i> <i>model.inter[model.attributable[model. quoteLike] model.biblLike[bibl listBibl]</i> <i>model.egLike model.labelLike[desc]</i> <i>model.listLike[list listEvent listOrg listPerson listPlace] model.oddDecl model.stageLike]</i>

Note	This class defines the set of chunk- and inter-level elements; it is used in many content models, including those for textual divisions.
-------------	--

model.dateLike

model.dateLike groups elements containing temporal expressions. [[3.6.4. Dates and Times](#) [14.4. Dates](#)]

Module	tei
Used by	model.pPart.data
Members	<i>date</i>

model.descLike

model.descLike groups elements which contain a description of their function.

Module	tei
Used by	category taxonomy
Members	<i>desc</i>

model.divBottom

model.divBottom groups elements appearing at the end of a text division. [[4.2. Elements Common to All Divisions](#)]

Module	tei
Used by	body list
Members	<i>model.divBottomPart</i> <i>model.divWrapper</i>

model.divPart

model.divPart groups paragraph-level elements appearing directly within divisions. [[1.3. The TEI Class System](#)]

Module	tei
Used by	macro.specialPara model.common
Members	<i>model.lLike</i> <i>model.pLike</i> [<i>p</i>]
Note	Note that this element class does not include members of the model.inter class, which can appear either within or between paragraph-level items.

model.divTop

model.divTop groups elements appearing at the beginning of a text division. [[4.2. Elements Common to All Divisions](#)]

Module	tei
Used by	body list
Members	<i>model.divTopPart</i> [<i>model.headLike</i>] <i>model.divWrapper</i>

model.divTopPart

model.divTopPart groups elements which can occur only at the beginning of a text division. [[4.6. Title Pages](#)]

Module	tei
Used by	model.divTop
Members	<i>model.headLike</i>

model.emphLike

model.emphLike groups phrase-level elements which are typographically distinct and to which a specific function can be attributed. [[3.3. Highlighting and Quotation](#)]

Module	tei
Used by	model.highlighted model.limitedPhrase
Members	<i>term title</i>

model.encodingDescPart

model.encodingDescPart groups elements which may be used inside <encodingDesc> and appear multiple times.

Module	tei
Used by	encodingDesc
Members	<i>classDecl</i>

model.eventLike

model.eventLike groups elements which describe events.

Module	tei
Used by	event listEvent model.orgPart model.personPart place
Members	<i>event listEvent</i>

model.global

model.global groups elements which may appear at any point within a TEI text. [[1.3. The TEI Class System](#)]

Module	tei
Used by	bibl body date list macro.phraseSeq macro.phraseSeq.limited macro.specialPara model.paraPart person text
Members	<i>model.global.edit model.global.meta model.milestoneLike model.noteLike[note]</i>

model.highlighted

model.highlighted groups phrase-level elements which are typographically distinct. [[3.3. Highlighting and Quotation](#)]

Module	tei
Used by	bibl model.phrase
Members	<i>model.emphLike[term title] model.hiLike</i>

model.imprintPart

model.imprintPart groups the bibliographic elements which occur inside imprints. [[3.12. Bibliographic Citations and References](#)]

Module	tei
Used by	model.biblPart
Members	<i>pubPlace publisher</i>

model.inter

model.inter groups elements which can appear either within or between paragraph-like elements. [[1.3. The TEI Class System](#)]

Module	tei
Used by	macro.limitedContent macro.specialPara model.common model.paraPart
Members	<i>model.attributable[model.quoteLike] model.biblLike[bibl listBibl] model.egLike model.labelLike[desc] model.listLike[list listEvent listOrg listPerson listPlace] model.oddDecl model.stageLike</i>

model.labelLike

model.labelLike groups elements used to gloss or explain other parts of a document.

Module	tei
Used by	event model.inter org place
Members	<i>desc</i>

model.limitedPhrase

model.limitedPhrase groups phrase-level elements excluding those elements primarily intended for transcription of existing sources. [[1.3. The TEI Class System](#)]

Module	tei
Used by	catDesc macro.limitedContent macro.phraseSeq.limited
Members	<i>model.emphLike[term title] model.hiLike model.pPart.data[model.addressLike[a ffiliation] model.dateLike[date] model.measureLike model.nameLike[model.nameLike.agen t[name] model.offsetLike model.persNamePart[forename nameLink roleName surname] model.placeStateLike[model.placeNam</i>

*ePart[bloc country placeName]]
 eventName idno]]
 model.pPart.editorial
 model.pPart.msdesc [model.phrase.xml](#)
 model.ptrLike[ptr]*

model.listLike

model.listLike groups list-like elements. [[3.8. Lists](#)]

Module *tei*
Used by *model.inter sourceDesc*
Members *list listEvent listOrg listPerson
 listPlace*

model.nameLike

model.nameLike groups elements which name or refer to a person, place, or organization.

Module *tei*
Used by *model.pPart.data org*
Members *model.nameLike.agent[name]
 model.offsetLike
 model.persNamePart[forename
 nameLink roleName surname]
 model.placeStateLike[model.placeNam
 ePart[bloc country placeName]]
 eventName idno*

Note A superset of the naming elements that may appear in datelines, addresses, statements of responsibility, etc.

model.nameLike.agent

model.nameLike.agent groups elements which contain names of individuals or corporate bodies. [[3.6. Names, Numbers, Dates, Abbreviations, and Addresses](#)]

Module *tei*
Used by *model.nameLike respStmt*
Members *name*
Note This class is used in the content model of elements which reference names of people or organizations.

model.noteLike

model.noteLike groups globally-available note-like elements. [[3.9. Notes, Annotation, and Indexing](#)]

Module *tei*
Used by *event model.global org place*

Members

note

model.orgPart

model.orgPart groups elements which form part of the description of an organization.

Module

tei

Used by

org

Members

*model.eventLike[event listEvent]
listOrg listPerson listPlace*

model.pLike

model.pLike groups paragraph-like elements.

Module

tei

Used by

*availability encodingDesc event
model.divPart org particDesc person
place publicationStmnt settingDesc
sourceDesc*

Members

p

model.pPart.data

model.pPart.data groups phrase-level elements containing names, dates, numbers, measures, and similar data. [[3.6. Names, Numbers, Dates, Abbreviations, and Addresses](#)]

Module

tei

Used by

Members

*bibl model.limitedPhrase model.phrase
model.addressLike[affiliation]
model.dateLike[date]
model.measureLike
model.nameLike[model.nameLike.agent[name]
model.offsetLike
model.persNamePart[forename
nameLink roleName surname]
model.placeStateLike[model.placeNamePart[bloc country placeName]]
eventName idno]*

model.pPart.edit

model.pPart.edit groups phrase-level elements for simple editorial correction and transcription. [[3.5. Simple Editorial Changes](#)]

Module

tei

Used by

bibl model.phrase

Members

*model.pPart.editorial
model.pPart.transcriptional*

model.paraPart

model.paraPart groups elements that may appear in paragraphs and similar elements. [[3.1. Paragraphs](#)]

Module

Used by

Members

tei
macro.paraContent
model.gLike
model.global[model.global.edit
model.global.meta
model.milestoneLike
model.noteLike[note]]
model.inter[model.attributable[model.
quoteLike] model.biblLike[bibl listBibl]
model.egLike model.labelLike[desc]
model.listLike[list listEvent listOrg
listPerson listPlace] model.oddDecl
model.stageLike] model.lLike
model.phrase[model.graphicLike
model.highlighted[model.emphLike[ter
m title] model.hiLike] model.lPart
model.pPart.data[model.addressLike[a
ffiliation] model.dateLike[date]
model.measureLike
model.nameLike[model.nameLike.agen
t[name] model.offsetLike
model.persNamePart[forename
nameLink roleName surname]
model.placeStateLike[model.placeNam
ePart[bloc country placeName]]
eventName idno]]
model.pPart.edit[model.pPart.editorial
model.pPart.transcriptional]
model.pPart.msdesc [model.phrase.xml](#)
model.ptrLike[ptr] model.segLike
model.specDescLike]

model.persNamePart

model.persNamePart groups elements which form part of a personal name. [[14.2.1. Personal Names](#)]

Module

Used by

Members

namesdates
model.nameLike
forename nameLink roleName
surname

model.persStateLike

model.persStateLike groups elements describing changeable characteristics of a person which have a definite duration, for example occupation, residence,

or name.

Module

Used by

Members

Note

tei

model.personPart

affiliation gender

These characteristics of an individual are typically a consequence of their own action or that of others.

model.personLike

model.personLike groups elements which provide information about people and their relationships.

Module

Used by

Members

tei

event listPerson org particDesc

org person

model.personPart

model.personPart groups elements which form part of the description of a person. [[16.2.2. The Participant Description](#)]

Module

Used by

Members

tei

person

model.biblLike[bibl listBibl]

model.eventLike[event listEvent]

model.persStateLike[affiliation

gender] idno name

model.phrase

model.phrase groups elements which can occur at the level of individual words or phrases. [[1.3. The TEI Class System](#)]

Module

Used by

Members

tei

date macro.phraseSeq

macro.specialPara model.paraPart

model.graphicLike

model.highlighted[model.emphLike[term title] model.hiLike] model.lPart

model.pPart.data[model.addressLike[affiliation] model.dateLike[date]

model.measureLike

model.nameLike[model.nameLike.agent[name] model.offsetLike

model.persNamePart[forename nameLink roleName surname]

model.placeStateLike[model.placeNamePart[bloc country placeName]]

eventName idno]]

model.pPart.edit[model.pPart.editorial

model.pPart.transcriptional]

*model.pPart.msdesc [model.phrase.xml](#)
model.ptrLike[ptr] model.segLike
model.specDescLike*

Note

This class of elements can occur within paragraphs, list items, lines of verse, etc.

model.placeLike

model.placeLike groups elements used to provide information about places and their relationships.

Module	tei
Used by	event listPlace org place settingDesc
Members	<i>place</i>

model.placeNamePart

model.placeNamePart groups elements which form part of a place name. [[14.2.3. Place Names](#)]

Module	tei
Used by	model.placeStateLike
Members	<i>bloc country placeName</i>

model.placeStateLike

model.placeStateLike groups elements which describe changing states of a place.

Module	tei
Used by	model.nameLike place
Members	<i>model.placeNamePart[bloc country placeName]</i>

model.profileDescPart

model.profileDescPart groups elements which may be used inside <profileDesc> and appear multiple times.

Module	tei
Used by	profileDesc
Members	<i>particDesc settingDesc</i>

model.ptrLike

model.ptrLike groups elements used for purposes of location and reference. [[3.7. Simple Links and Cross-References](#)]

Module	tei
Used by	bibl model.limitedPhrase model.phrase model.publicationStmtPart.detail
Members	<i>ptr</i>

model.publicationStmtPart.agency

model.publicationStmtPart.agency groups the child elements of a <publicationStmt> element of the TEI header that indicate an authorising agent. [[2.2.4. Publication, Distribution, Licensing, etc.](#)]

Module	tei
Used by	publicationStmt
Members	<i>publisher</i>
Note	The 'agency' child elements, while not required, are required if one of the 'detail' child elements is to be used. It is not valid to have a 'detail' child element without a preceding 'agency' child element. See also model.publicationStmtPart.detail.

model.publicationStmtPart.detail

model.publicationStmtPart.detail groups the agency-specific child elements of the <publicationStmt> element of the TEI header. [[2.2.4. Publication, Distribution, Licensing, etc.](#)]

Module	tei
Used by	publicationStmt
Members	<i>model.ptrLike[ptr] availability date idno pubPlace</i>
Note	A 'detail' child element may not occur unless an 'agency' child element precedes it. See also model.publicationStmtPart.agency.

model.resource

model.resource groups separate elements which constitute the content of a digital resource, as opposed to its metadata. [[1.3. The TEI Class System](#)]

Module	tei
Used by	TEI
Members	<i>text</i>

model.respLike

model.respLike groups elements which are used to indicate intellectual or other significant responsibility, for example within a bibliographic element.

Module	tei
Used by	model.biblPart titleStmt
Members	<i>editor respStmt</i>

model.teiHeaderPart

model.teiHeaderPart groups high level elements which may appear more than once in a TEI header.

Module	tei
Used by	teiHeader
Members	<i>encodingDesc profileDesc</i>

Attribute classes

att.anchoring

att.anchoring (anchoring) provides attributes for use on annotations, e.g. notes and groups of notes describing the existence and position of an anchor for annotations.

Module	tei	
Members	<i>note</i>	
Attributes	anchored	(anchored) indicates whether the copy text shows the exact place of reference for the note. Status Optional Datatype teidata.truthValue Default true Note In modern texts, notes are usually anchored by means of explicit footnote or endnote symbols. An explicit indicatio n of the phrase or line annotated may however

be used
 instead
 (e.g.
 'page
 218, lines
 3-4'). The
anchored
 attribute
 indicates
 whether
 any
 explicit
 location
 is given,
 whether
 by
 symbol or
 by prose
 cross-
 reference
 . The
 value
true
 indicates
 that such
 an
 explicit
 location
 is
 indicated
 in the
 copy text;
 the value
false
 indicates
 that the
 copy text
 does not
 indicate a
 specific
 place of
 attachme
 nt for the
 note. If
 the
 specific
 symbols
 used in

	the copy text at the location the note is anchored are to be recorded, use the <i>n</i> attribute.
targetEnd	(target end) points to the end of the span to which the note is attached, if the note is not embedded in the text at that point. Status Optional Datatype 1-∞ occurrences of teidata.pointer separated by whitespace Note This attribute is retained for backwards compatibility; it may be removed at a subsequent release of the Guidelines. The recomme

ended way
of
pointing
to a span
of
elements
is by
means of
the range
function
of
XPointer,
as
further
described
in
[17.2.4.6.
range\(\)](#).

Example

```
<p>(…) tamen reuerendos dominos ar  
chiepiscopum et canonicos Leopoliense  
s  
necnon episcopum in duplicibus Quatu  
ortemporibus<anchor xml:id="A55234  
"/> totaliter expediui...</p>  
<!-- elsewhere in the document -->  
<noteGrp targetEnd="#A55234">  
  <note xml:lang="en"> Quatuor Temp  
ora, so called dry fast days.  
  </note>  
  <note xml:lang="pl"> Quatuor Tempo  
ra, tzw. Suche dni postne.  
  </note>  
</noteGrp>
```

att.ascribed

att.ascribed provides attributes for elements representing speech or action that can be ascribed to a specific individual. [[3.3.3. Quotation 8.3. Elements Unique to Spoken Texts](#)]

Module

Members

Attributes

tei

change

who

indicates the
person, or group of
people, to whom
the element
content is ascribed.

Status Optional

Datatype 1-∞

occurrences
of teidata
.pointer
separated by
whitespace

In the following example from Hamlet, speeches (<sp>) in the body of the play are linked to <role> elements in the <castList> using the *who* attribute.

```
<castItem type="role">  
  <role xml:id="Bernardo">Bernardo</role>  
</castItem>  
<castItem type="role">  
  <role xml:id="Francisco">Francisco</role>  
  <roleDesc>a soldier</roleDesc>  
</castItem>  
<!-- ... -->  
<sp who="#Bernardo">  
  <speaker>Bernardo</speaker>  
  <l n="1">Who's there?</l>  
</sp>  
<sp who="#Francisco">  
  <speaker>Francisco</speaker>  
  <l n="2">Nay, answer me: stand, and unfold yourself.</l>  
</sp>
```

Note	For transcribed speech, this will typically identify a participant or participant group; in other contexts, it will point to any identified <person> element.
-------------	---

att.cReferencing

att.cReferencing provides attributes that may be used to supply a *canonical reference* as a means of identifying the target of a pointer.

Module	tei
Members	<i>ptr term</i>
Attributes	cRef

(canonical reference) specifies the destination of the pointer by supplying a canonical reference expressed using the scheme defined in a <refsDecl> element in the TEI header.

Status	Optional
Datatype	teidata.text

Note	The value of <i>cRef</i> should be constructed so that
-------------	--

when the algorithm for the resolution of canonical references (described in section [17.2.5. Canonical References](#)) is applied to it the result is a valid URI reference to the intended target.

The `<refsDecl>` to use may be indicated with the *decls* attribute.

Currently these Guidelines only provide for a single canonical reference to be encoded on any given `<ptr>`

element.

att.calendarSystem

att.calendarSystem provides attributes for indicating calendar systems to which a date belongs. [[3.6.4. Dates and Times](#) [14.4. Dates](#)]

Module

tei

Members

date

Attributes

calendar

indicates one or more systems or calendars to which the date represented by the content of this element belongs.

Status Optional

Datatype 1-∞

occurrences of teidata.pointer separated by whitespace

Schematron <sch:rule context=

"tei:*[@calendar]">

<sch:assert test="string-length(normalize-space(.)) gt 0">
@calendar

indicates one or more systems or calendars to which the date represent

ed by the
content
of this
element
belongs,
but this
<sch:na
me/>
element
has no
textual
content.<
/sch:asse
rt>
</sch:rul
e>

He was born on <d
ate calendar="#gr
egorian">Feb. 22,
1732</date> (<dat
e calendar="#julia
n"
when="1732-02-
22">Feb. 11, 1731/
32,
O.S.</date>).

He was born on <
date calendar="#g
regorian #julian"
when="1732-02-
22">Feb. 22, 1732
(Feb. 11, 1731/32,
O.S.)</date>.

Note Note that
the
calendar
attribute
declares
the
calendar
system
used to
interpret
the
textual
content

of an element, as it appears on an original source. It does *not* modify the interpretation of the normalization attributes provided by att.databl e.w3c, att.databl e.iso, or att.databl e.custom. Attribute s from those first two classes are always interpreted as Gregorian or proleptic Gregorian dates, as per the respective standards on which they are based. The calender

system used to interpret the last (att.datable.custom) may be specified with *datingMethod*.

att.canonical

att.canonical provides attributes that can be used to associate a representation such as a name or title with canonical information about the object being named or referenced. [[14.1.1. Linking Names and Their Referents](#)]

Module

Members

Attributes

tei

att.naming[att.personal[eventName forename name placeName roleName surname] affiliation bloc country editor event pubPlace] bibl catDesc date publisher resp respStmt term title key

provides an externally-defined means of identifying the entity (or entities) being named, using a coded value of some kind.

Status Optional
Datatype teidata.text

```
<author>
  <name key="Hugo, Victor (1802-1885)"
    ref="http://www.idref.fr/026927608">Victor Hugo</name>
</author>
```

Note The value may be a unique identifier

from a database, or any other externally-defined string identifying the referent. No particular syntax is proposed for the values of the *key* attribute, since its form will depend entirely on practice within a given project.

ref

(reference)
provides an explicit means of locating a full definition or identity for the entity being named by means of one or more URIs.

Status Optional
Datatype 1-∞ occurrences of teidata.pointer separated by whitespace

<name ref="http://

```
viaf.org/viaf/
109557338"
type="person">Seamus Heaney</
name>
```

Note The value must point directly to one or more XML elements or other resources by means of one or more URIs, separated by whitespace. If more than one is supplied the implication is that the name identifies several distinct entities.

Example

In this contrived example, a canonical reference to the same organisation is provided in four different ways.

```
<author n="1">
  <name ref="http://
nzetc.victoria.ac.nz/tm/scholarly/name-
427308.html"
type="organisation">New Zealand Pa
liament, Legislative Council</name>
</author>
```

```
<author n="2">
```

```

<name ref="nzvn:427308"
  type="organisation">New Zealand Pa
liament, Legislative Council</name>
</author>

```

```

<author n="3">
  <name ref="./
named_entities.xml#o427308"
  type="organisation">New Zealand Pa
liament, Legislative Council</name>
</author>

```

```

<author n="4">
  <name key="name-427308"
  type="organisation">New Zealand Pa
liament, Legislative Council</name>
</author>

```

The first presumes the availability of an internet connection and a processor that can resolve a URI (most can). The second requires, in addition, a `<prefixDef>` that declares how the `nzvm` prefix should be interpreted. The third does not require an internet connection, but does require that a file named `named_entities.xml` be in the same directory as the TEI document. The fourth requires that an entire external system for key resolution be available.

Note

The *key* attribute is more flexible and general-purpose, but its use in interchange requires that documentation about how the key is to be resolved be sent to the recipient of the TEI document. In contrast values of the *ref* attribute are resolved using the widely accepted protocols for a URI, and thus less documentation, if any, is likely required by the recipient in data interchange.

These guidelines provide no semantic basis or suggested precedence when both *key* and *ref* are provided. For this reason simultaneous use of both is not recommended unless documentation

explaining the use is provided, probably in an ODD customizaiton, for interchange.

att.cmc

att.cmc (computer-mediated communication) provides attributes categorizing how the element content was created in a CMC environment.

Module

tei

Members

*affiliation bibl bloc country date desc
forename idno list listBibl listEvent
listOrg listPerson listPlace name
nameLink note p placeName ptr
roleName surname term title*

Attributes

generatedBy (generated by)
categorizes how
the content of an
element was
generated in a
CMC environment.

Status Optional

Datatype teidata.e
numerate
d

Schematron <sch:rule
context=
"tei:*[@g
enerated
By]">
<sch:ass
ert test="
ancestor-
or-
self::tei:p
ost">The
@generat
edBy
attribute
is for use
within a
<post>
element.
</sch:ass
ert>
</sch:rul
e>

**Suggested human
ed** the

values	cont
include:	ent
	was
	'natu
	rally'
	type
	d or
	spok
	en
	by a
	hum
	an
	user
	template
	the
	cont
	ent
	was
	gene
	rate
	d
	after
	a
	hum
	an
	user
	activ
	ated
	a
	temp
	late
	for
	its
	inser
	tion
	system
	the
	cont
	ent
	was
	gene
	rate
	d by
	the
	syste
	m,
	i.e.

the
CMC
envir
onm
ent

bot

the
cont
ent
was
gene
rate
d by
a
bot,
i.e. a
non-
hum
an
agen
t,
typic
ally
one
that
is
not
part
of
the
CMC
envir
onm
ent
itself

**unspeci
fied**

the
cont
ent
was
gene
rate
d by
an
unkn
own

or
unsp
ecifi
ed
proc
ess

automatic system
message in chat:
user moves on to
another chatroom
<post generatedBy
="system"
rend="color:blue"
type="event"
who="#system">
<p>
 <name corresp="A02"
 type="nickname"
 >McMike</name>
geht
 in einen anderen
Raum: <name type
="roomname">Kre
uzfahrt</name>
</p>
</post>
automatic system
message in chat:
user enters a
chatroom
<post generatedBy
="system"
type="event">
<p>
 <name corresp="A08"
 type="nickname"
 >c_bo</name> bet
ritt
 den Raum. </p>
</post>
automatic system
message in chat:
user changes his
font color
<post generatedBy
="system"

```

rend="color:red"
type="event">
<p>
  <name corresp="
  #A08"
    type="nickname"
  >c_bo</name> hat
  die
    Farbe gewechselt
  .
</p>
</post>
An automatic
signature of user
including an
automatic
timestamp
(Wikipedia
discussion,
anonymized). The
specification of
generatedBy at the
inner element
<signed> is meant
to override the
specification at the
outer element
<post>. This is
generally possible
when the outer
generatedBy value
is "human".
<post generatedBy
="human"
indentLevel="2"
synch="#t003944
07"
type="standard"
who="#WU00005
582">
  <p> Kurze Nachfr
age: Die Hieros für
den Goldnamen sta
mmen
    auch von Beckera
th gem. Literatur ?
  Grüße —</p>
  <signed generated

```

```

By="template"
  rend="inline">
  <gap reason="signatureContent"/>
  <time generatedBy="template">18:50, 22. Okt. 2008 (CEST)</time>
</signed>
</post>
Wikipedia talk
page: user
signature
<post generatedBy="human"
  type="written">
<!-- ... main content of posting ... -->
  <signed generatedBy="template">
    <gap reason="signatureContent"/>
    <time generatedBy="template">12:01, 12. Jun. 2009 (CEST)</time>
  </signed>
</post>

```

att.dateable

att.dateable provides attributes for normalization of elements that contain dates, times, or dateable events. [[3.6.4. Dates and Times](#) [14.4. Dates](#)]

Module

tei

Members

*affiliation bloc change country date
editor event eventName gender idno
licence name placeName resp title*

Attributes

- att.dateable.custom
 - @when-custom
 - @notBefore-custom
 - @notAfter-custom
 - @from-custom
 - @to-custom
 - @datingPoint
 - @datingMethod
- att.dateable.iso
 - @when-iso
 - @notBefore-iso

- *@notAfter-iso*
- *@from-iso*
- *@to-iso*
- att.datable.w3c
 - *@when*
 - *@notBefore*
 - *@notAfter*
 - *@from*
 - *@to*

period supplies pointers to one or more definitions of named periods of time (typically <category>s, <date>s, or <event>s) within which the datable item is understood to have occurred.

Status Optional
Datatype 1-∞

occurrences of teidata.pointer separated by whitespace

Note

This ‘superclass’ provides attributes that can be used to provide normalized values of temporal information. By default, the attributes from the att.datable.w3c class are provided. If the module for names & dates is loaded, this class also provides attributes from the att.datable.iso and att.datable.custom classes. In general, the possible values of attributes restricted to the W3C datatypes form a subset of those values available via the ISO 8601 standard. However, the greater expressiveness of the ISO datatypes may not be needed, and there exists much greater software support for the W3C datatypes.

att.datable.custom

att.datable.custom provides attributes for normalization of elements that contain datable events to a custom dating system (i.e. other than the Gregorian used by W3 and ISO). [[14.4. Dates](#)]

Module

namesdates

Members

*att.datable[affiliation bloc change
country date editor event eventName
gender idno licence name placeName
resp title]*

Attributes

when-custom

supplies the value of a date or time in some custom standard form.

Status Optional

Datatype 1-∞

occurrences of teidata .word separated by whitespace

The following are examples of custom date or time formats that are *not* valid ISO or W3C format normalizations, normalized to a different dating system

<p>Alhazen died in Cairo on the
<date when="1040-03-06"
when-
custom="431-06-12"> 12th day of Jumada t-Tania, 430 AH

</date>.</p>

<p>The current world will end at the
<date when="2012-12-21"

when-
custom="13.0.0.0.
0">end of B'ak'tun
13</date>.</p>
<p>The Battle of
Meggidu
(<date when-
custom="Thutmose
_III:23">23rd year
of reign of Thutmos
e III</date>).</p>
<p>Esidorus bixit i
n pace annos LXX p
lus minus sub
<date when-
custom="Ind:4-10-
11">die XI mensis
Octobris indictione
IIII</date>
</p>
Not all custom date
formulations will
have Gregorian
equivalents. The
when-custom
attribute and other
custom dating are
not constrained to
a datatype by the
TEI, but individual
projects are
recommended to
regularize and
document their
dating formats.
notBefore-custom specifies the
earliest possible
date for the event
in some custom
standard form.
Status Optional
Datatype 1-∞
occurren
ces
of teidata
.word
separate
d by

	whitespace
notAfter-custom	specifies the latest possible date for the event in some custom standard form. Status Optional Datatype 1-∞ occurrences of teidata.word separated by whitespace
from-custom	indicates the starting point of the period in some custom standard form. Status Optional Datatype 1-∞ occurrences of teidata.word separated by whitespace <event datingMethod="#julian" from-custom="1666-09-02" to-custom="1666-09-05" xml:id="FIRE1"> <head>The Great Fire of London</head> <p>The Great Fire of London burned through a large part

	of the city of London.</p> </event>
to-custom	indicates the ending point of the period in some custom standard form. Status Optional Datatype 1-∞ occurrences of teidata.word separated by whitespace
datingPoint	supplies a pointer to some location defining a named point in time with reference to which the datable item is understood to have occurred. Status Optional Datatype teidata.pointer
datingMethod	supplies a pointer to a <calendar> element or other means of interpreting the values of the custom dating attributes. Status Optional Datatype teidata.pointer Containing the Originall, Antiquity, In creafe, Moderne eftate, and defcription of that Citie, w ritten in the yeare <date calendar="#"

```

julian"
  datingMethod="#julian"
  when-
  custom="1598">1598</date>. by Iohn Stow

```

Citizen of London. In this example, the *calendar* attribute points to a <calendar> element for the Julian calendar, specifying that the text content of the <date> element is a Julian date, and the *datingMethod* attribute also points to the Julian calendar to indicate that the content of the *when-custom* attribute value is Julian too.

```

<date datingMethod="#creationOfWorld"
  when="1382-06-28"
  when-
  custom="6890-06-20"> μηνὶ Ἰουνίου
εἰς <num>κ</num>
<num> ἔτους <num>
>ζω</num>
</date>

```

In this example, a date is given in a Mediaeval text measured ‘from the creation of the world’, which is normalized (in *when*) to the Gregorian date, but

is also normalized (in *when-custom*) to a machine-actionable, numeric version of the date from the Creation.

Note Note that the *datingMethod* attribute (unlike *calendar* defined in att.datable) defines the calendar or dating system to which the date described by the parent element is normalized (i.e. in the *when-custom* or other *X-custom* attributes), *not* the calendar of the original date in the element.

att.datable.iso

att.datable.iso provides attributes for normalization of elements that contain

datable events using the ISO 8601:2004 standard. [[3.6.4. Dates and Times](#)
[14.4. Dates](#)]

Module

Members

namesdates

att.datable[affiliation bloc change

country date editor event eventName

gender idno licence name placeName

resp title]

Attributes

when-iso

supplies the value
of a date or time in
a standard form.

Status Optional

Datatype teidata.te
mporal.is
o

The following are
examples of ISO
date, time, and
date & time
formats that are
not valid W3C
format
normalizations.

<date when-
iso="1996-09-
24T07:25+00">Se
pt. 24th, 1996 at 3:
25 in the morning<
/date>

<date when-
iso="1996-09-
24T03:25-
04">Sept. 24th, 19
96 at 3:25 in the m
orning</date>

<time when-
iso="1999-01-
04T20:42-05">4 Ja
n 1999 at 8:42 pm
</time>

<time when-
iso="1999-W01-
1T20,70-05">4 Jan
1999 at 8:42 pm</
time>

<date when-
iso="2006-05-
18T10:03">a few

minutes after ten i
n the morning on T
hu 18 May</date>
<time when-
iso="03:00">3 A.M
</time>
<time when-
iso="14">around t
wo</time>
<time when-
iso="15,5">half pa
st three</time>
All of the examples
of the *when*
attribute in the
att.dataable.w3c
class are also valid
with respect to this
attribute.
He likes to be punc
tual. I said <q>
<time when-
iso="12">around n
oon</time>
</q>, and he show
ed up at <time whe
n-
iso="12:00:00">12
O'clock</time> on
the dot.
The second
occurrence of
<time> could have
been encoded with
the *when* attribute,
as 12:00:00 is a
valid time with
respect to the W3C
XML Schema Part
2: Datatypes
Second Edition
specification. The
first occurrence
could not.
notBefore-iso specifies the
earliest possible
date for the event
in standard form,

notBefore-iso

	e.g. yyyy-mm-dd. Status Optional Datatype teidata.temporal.iso
notAfter-iso	specifies the latest possible date for the event in standard form, e.g. yyyy-mm-dd. Status Optional Datatype teidata.temporal.iso
from-iso	indicates the starting point of the period in standard form. Status Optional Datatype teidata.temporal.iso
to-iso	indicates the ending point of the period in standard form. Status Optional Datatype teidata.temporal.iso

Note

The value of these attributes should be a normalized representation of the date, time, or combined date & time intended, in any of the standard formats specified by ISO 8601:2004, using the Gregorian calendar.

If both *when-iso* and *dur-iso* are specified, the values should be interpreted as indicating a span of time by its starting time (or date) and duration. That is,

```
<date dur-iso="P8D" when-iso="2007-06-01"/>
```

indicates the same time period as

```
<date when-iso="2007-06-01/P8D"/>
```

In providing a 'regularized' form, no

claim is made that the form in the source text is incorrect; the regularized form is simply that chosen as the main form for purposes of unifying variant forms under a single heading.

att.dateable.w3c

att.dateable.w3c provides attributes for normalization of elements that contain dateable events conforming to the W3C XML Schema Part 2: Datatypes Second Edition. [[3.6.4. Dates and Times](#) [14.4. Dates](#)]

Module

tei

Members

att.dateable[affiliation bloc change country date editor event eventName gender idno licence name placeName resp title]

Attributes

when

supplies the value of the date or time in a standard form, e.g. yyyy-mm-dd.

Status Optional

Datatype tei:dateable.w3c

Examples of W3C date, time, and date & time formats.

<p>

<date when="1945-10-24">24 Oct 45</date>

<date when="1996-09-

24T07:25:00Z">September 24th, 1996 at 3:25 in the morning</date>

<time when="1999-01-04T20:42:00-05:00">Jan 4 1999 at 8 pm</time>

<time when="14:12:38">fourteen twelve and 38 seconds</time>

<date when="196

2-10">October of 1
 962</date>
 <date when="--06-
 12">June 12th</
 date>
 <date when="---
 01">the first of the
 month</date>
 <date when="--
 08">August</
 date>
 <date when="200
 6">MMVI</date>
 <date when="005
 6">AD 56</date>
 <date when="-
 0056">56 BC</
 date>
 </p>
 This list begins in
 the year 1632, mor
 e precisely on Trini
 ty Sunday, i.e. the
 Sunday after
 Pentecost, in that
 year the
 <date calendar="#
 julian"
 when="1632-06-
 06">27th of May (o
 ld style)</date>.
 <opener>
 <dateline>
 <placeName>Dor
 chester, Village,</
 placeName>
 <date when="182
 8-03-02">March 2
 d. 1828.</date>
 </dateline>
 <salute>To
 Mrs. Cornell,</
 salute> Sunday <ti
 me when="12:00:0
 0">noon.</time>
 </opener>
 specifies the
 earliest possible

notBefore

	date for the event in standard form, e.g. yyyy-mm-dd. Status Optional Datatype teidata.temporal.w3c
notAfter	specifies the latest possible date for the event in standard form, e.g. yyyy-mm-dd. Status Optional Datatype teidata.temporal.w3c
from	indicates the starting point of the period in standard form, e.g. yyyy-mm-dd. Status Optional Datatype teidata.temporal.w3c
to	indicates the ending point of the period in standard form, e.g. yyyy-mm-dd. Status Optional Datatype teidata.temporal.w3c

Schematron

```
<sch:rule context="tei:*[@when]">
<sch:report role="nonfatal"
test="@notBefore|@notAfter|@from|
@to">The @when attribute cannot be
used with any other att.dataable.w3c
attributes.</sch:report> </sch:rule>
```

Schematron

```
<sch:rule context="tei:*[@from]">
<sch:report role="nonfatal"
test="@notBefore">The @from and
@notBefore attributes cannot be used
together.</sch:report> </sch:rule>
```

Schematron

```
<sch:rule context="tei:*[@to]">
<sch:report role="nonfatal"
```

Example

```
test="@notAfter">The @to and
@notAfter attributes cannot be used
together.</sch:report> </sch:rule>
<date from="1863-05-28" to="1863-
06-01">28 May through 1 June 1863</
date>
```

Note

The value of these attributes should be a normalized representation of the date, time, or combined date & time intended, in any of the standard formats specified by XML Schema Part 2: Datatypes Second Edition, using the Gregorian calendar.

The most commonly-encountered format for the date portion of a temporal attribute is yyyy-mm-dd, but yyyy, --mm, ---dd, yyyy-mm, or --mm-dd may also be used. For the time part, the form hh:mm:ss is used.

Note that this format does not currently permit use of the value 0000 to represent the year 1 BCE; instead the value -0001 should be used.

att.datcat

att.datcat provides attributes that are used to align XML elements or attributes with the appropriate Data Categories (DCs) defined by an external taxonomy, in this way establishing the identity of information containers and values, and providing means of interpreting them. [[10.5.2. Lexical View 19.3. Other Atomic Feature Values](#)]

Module

tei

Members

category taxonomy

Attributes

datcat

provides a pointer to a definition of, and/or general information about, (a) an information container (element or attribute) or (b) a value of an information container (element content or attribute value), by referencing an external taxonomy

	or ontology. If <i>valueDatcat</i> is present in the immediate context, this attribute takes on role (a), while <i>valueDatcat</i> performs role (b). Status Optional Datatype 1-∞ occurrences of teidata .pointer separated by whitespace
valueDatcat	provides a definition of, and/or general information about a value of an information container (element content or attribute value), by reference to an external taxonomy or ontology. Used especially where a contrast with <i>datcat</i> is needed. Status Optional Datatype 1-∞ occurrences of teidata .pointer separated by whitespace
targetDatcat	provides a definition of, and/or general information about,

information structure of an object referenced or modeled by the containing element, by reference to an external taxonomy or ontology. This attribute has the characteristics of the *datcat* attribute, except that it addresses not its containing element, but an object that is being referenced or modeled by its containing element.

Status Optional
Datatype 1-∞ occurrences of teidata.pointer separated by whitespace

Example

The example below presents the TEI encoding of the [name-value pair](#) <part of speech, common noun>, where the name (key) 'part of speech' is abbreviated as 'POS', and the value, 'common noun' is symbolized by 'NN'. The entire name-value pair is encoded by means of the element <f>. In TEI XML, that element acts as the container, labeled with the *name* attribute. Its contents may be complex or simple. In the case at hand, the content is the symbol 'NN'. The *datcat* attribute relates the feature *name* (i.e., the key) to the data category 'part of speech', while the attribute *valueDatcat* relates the feature *value*

to the data category *common noun*. Both these data categories should be defined in an external and preferably open reference taxonomy or ontology.

```
<fs>
  <f datcat="http://hdl.handle.net/
11459/CCR_C-396_5a972b93-2294-
ab5c-a541-7c344c5f26c3"
  name="POS">
    <symbol value="NN"
      valueDatcat="http://hdl.handle.net/
11459/CCR_C-1256_7ec6083c-23d4-
224d-6f94-eebbe6861545"/>
    </f>
  <!-- ... -->
</fs>
```

'NN' is the symbol for common noun used e.g. in the [CLAWS-7 tagset](#) defined by the University Centre for Computer Corpus Research on Language at the University of Lancaster. The very same data category used for tagging an early version of the British National Corpus, and coming from the [BNC Basic \(C5\) tagset](#), uses the symbol 'NN0' (rather than 'NN'). Making these values semantically interoperable would be extremely difficult without a human expert if they were not anchored in a single point of an established reference taxonomy of morphosyntactic data categories. In the case at hand, the string 'http://hdl.handle.net/11459/CCR_C-1256_7ec6083c-23d4-224d-6f94-eebbe6861545' is both a persistent identifier of the data category in question, as well as a pointer to a shared definition of *common noun*. While the symbols 'NN', 'NN0', and many others (often coming from languages other than English) are implicitly members of the container category 'part of speech', it is sometimes useful not to rely on such an implicit relationship but rather use an explicit identifier for that data

category, to distinguish it from other morphosyntactic data categories, such as gender, tense, etc. For that purpose, the above example uses the *datcat* attribute to reference a definition of *part of speech*. The reference taxonomy in this example is the [CLARIN Concept Registry](#). If the feature structure markup exemplified above is to be repeated many times in a single document, it is much more efficient to gather the persistent identifiers in a single place and to only reference them, implicitly or directly, from feature structure markup. The following example is much more concise than the one above and relies on the concepts of feature structure declaration and feature value library, discussed in chapter FS.

```
<fs>
  <f fVal="#commonNoun" name="POS"
"/>
<!-- ... -->
</fs>
```

The assumption here is that the relevant feature values are collected in a place that the annotation document in question has access to — preferably, a single document per linguistic resource, for example an `<fsdDecl>` that is XIncluded as a sibling of `<text>` or a child of `<encodingDesc>`; a `<taxonomy>` available resource-wide (e.g., in a shared header) is also an option. The example below presents an `<fvLib>` element that collects the relevant feature values (most of them omitted). At the same time, this example shows one way of encoding a *tagset*, i.e., an established inventory of values of (in the case at hand) morphosyntactic categories.

```
<fvLib n="POS values">
  <symbol datcat="http://
hdl.handle.net/11459/CCR_C-
396_5a972b93-2294-ab5c-a541-
7c344c5f26c3"
```

```

    value="NN" xml:id="commonNoun"/
  >
  <symbol datcat="http://
hdl.handle.net/11459/CCR_C-
1371_fbebd9ec-a7f4-9a36-d6e9-
88ee16b944ae"
    value="NP" xml:id="properNoun"/>
  <!-- ... -->
</fvLib>

```

Note that these Guidelines do not prescribe a specific choice between *datcat* and *valueDatcat* in such cases. The former is the generic way of referencing a data category, whereas the latter is more specific, in that it references a data category that represents a value. The choice between them comes into play where a single element — or a tight element complex, such as the `<f>/<symbol>` complex illustrated above — make it necessary or useful to distinguish between the container data category and its value.

Example

In the context of dictionaries designed with semantic interoperability in mind, the following example ensures that the `<pos>` element is interpreted as the same information container as in the case of the example of `<f name="POS">` above.

```

<gramGrp>
  <pos datcat="http://hdl.handle.net/
11459/CCR_C-396_5a972b93-2294-
ab5c-a541-7c344c5f26c3"
    valueDatcat="http://hdl.handle.net/
11459/CCR_C-1256_7ec6083c-23d4-
224d-6f94-eebbe6861545">NN</pos>
</gramGrp>

```

Efficiency of this type of interoperable markup demands that the references to the particular data categories should best be provided in a single place within the dictionary (or a single place within the project), rather than being repeated inside every entry. For the container elements, this can be achieved at the level of `<tagUsage>`,

although here, the *valueDatcat* attribute should be used, because it is not the <tagUsage> element that is associated with the relevant data category, but rather the element <pos> (or <case>, etc.) that is described by <tagUsage>:

```

<tagsDecl partial="true">
<!-- ... -->
  <namespace name="http://www.tei-
c.org/ns/1.0">
    <tagUsage gi="pos"
      targetDatcat="http://
hdl.handle.net/11459/CCR_C-
396_5a972b93-2294-ab5c-a541-
7c344c5f26c3">Contains the part of sp
eech.</tagUsage>
    <tagUsage gi="case"
      targetDatcat="http://
hdl.handle.net/11459/CCR_C-
1840_9f4e319c-f233-6c90-9117-
7270e215f039">Contains information
about the grammatical case that the de
scribed form is inflected for.</
tagUsage>
<!-- ... -->
  </namespace>
</tagsDecl>

```

Another possibility is to shorten the URIs by means of the <prefixDef> mechanism, as illustrated below:

```

<listPrefixDef>
  <prefixDef ident="ccr" matchPattern
="pos"
  replacementPattern="http://
hdl.handle.net/11459/CCR_C-
396_5a972b93-2294-ab5c-a541-
7c344c5f26c3"/>
  <prefixDef ident="ccr" matchPattern
="adj"
  replacementPattern="http://
hdl.handle.net/11459/CCR_C-
1230_23653c21-fca1-edf8-fd7c-
3df2d6499157"/>
</listPrefixDef>
<!-- ... -->
<entry>
<!--...-->

```

```

<form>
  <orth>isotope</orth>
</form>
<gramGrp>
  <pos datcat="ccr:pos"
    valueDatcat="ccr:adj">adj</pos>
</gramGrp>
<!--...-->
</entry>

```

This mechanism creates implications that are not always wanted, among others, in the case at hand, suggesting that the identifiers ‘pos’ and ‘adj’ belong to a namespace associated with the CLARIN Concept Repository (CCR), whereas that is solely a shorthand mechanism whose scope is the current resource. Documenting this clearly in the header of the dictionary is therefore advised. Yet another possibility is to associate the information about the relationship between a TEI markup element and the data category that it is intended to model already at the level of modeling the dictionary resource, that is, at the level of the ODD, in the <equiv> element that is a child of <elementSpec> or <attDef>.

Example

The <taxonomy> element is a handy tool for encoding taxonomies that are later referenced by att.datcat attributes, but it can also act as an intermediary device, for example holding a fragment of an external taxonomy (or ‘flattening’ an external ontology) that is relevant to the project or document at hand. (It is also imaginable that, for the purpose of the project at hand, the local <taxonomy> element combines vocabularies that originate from more than one external taxonomy or ontology.) In such cases, the <taxonomy> creates a local layer of indirection: the att.datcat attributes internal to the resource may reference the <category> elements stored in the header (as well as the <taxonomy>

element itself), whereas these same <category> and <taxonomy> elements use att.datcat attributes to reference the original taxonomy or ontology.

```

<encodingDesc>
<!-- ... -->
  <classDecl>
<!-- ... -->
    <taxonomy datcat="https://
universaldependencies.org/u/dep/
index.html"
      xml:id="UD-SYN">
      <desc>
        <term>UD syntactic relations</
term>
      </desc>
      <category valueDatcat="https://
universaldependencies.org/u/dep/
acl.html"
        xml:id="acl">
        <catDesc>
          <term>acl</term>: Clausal modifi
er of noun (adjectival clause)</
catDesc>
        </category>
        <category valueDatcat="https://
universaldependencies.org/u/dep/acl-
relcl.html"
          xml:id="acl_relcl">
          <catDesc>
            <term>acl:relcl</term>: relative cl
ause modifier</catDesc>
          </category>
          <category valueDatcat="https://
universaldependencies.org/u/dep/
advcl.html"
            xml:id="advcl">
            <catDesc>
              <term>advcl</term>: Adverbial cl
ause modifier</catDesc>
            </category>
          </category>
        </taxonomy>
      </classDecl>
    </encodingDesc>

```

The above fragment was excerpted from the GB subset of the [ParlaMint](#).

Example

[project](#) in April 2023, and enriched with att.datcat attributes for the purpose of illustrating the mechanism described here. Note that, in the ideal case, the values of att.datcat attributes should be persistent identifiers, and that the addressing scheme of Universal Dependencies is treated here as persistent for the sake of illustration. Note also that the contrast between *datcat* used on <taxonomy> on the one hand, and the *valueDatcat* used on <category> on the other, is not mandatory: both kinds of relations could be encoded by means of the generic *datcat* attribute, but using the former for the container and the latter for the content is more user-friendly. The *targetDatcat* attribute is designed to be used in, e.g., feature structure declarations, and is analogous to the *targetLang* attribute of the att.pointing class, in that it describes the object that is being referenced, rather than the referencing object.

```
<fDecl name="POS"
  targetDatcat="http://hdl.handle.net/
11459/CCR_C-396_5a972b93-2294-
ab5c-a541-7c344c5f26c3">
  <fDescr>part of speech (morphosynta
ctic category)</fDescr>
  <vRange>
    <vAlt>
      <symbol datcat="http://
hdl.handle.net/11459/CCR_C-
1256_7ec6083c-23d4-224d-6f94-
eecbe6861545"
        value="NN"/>
      <symbol datcat="http://
hdl.handle.net/11459/CCR_C-
1371_fbebd9ec-a7f4-9a36-d6e9-
88ee16b944ae"
        value="NP"/>
    <!-- ... -->
  </vAlt>
</vRange>
</fDecl>
```

Above, the <fDecl> uses *targetDatcat*,

because if it were to use *datcat*, it would be asserting that it is an instance of the container data category *part of speech*, whereas it is not — it models a container (<f>) that encodes a part of speech. Note also that it is the <f> that is modeled above, not its values, which are used as direct references to data categories; hence the use of *datcat* in the <symbol> element.

Example

The att.datcat attributes can be used for any sort of taxonomies. The example below illustrates their usefulness for describing usage domain labels in dictionaries on the example of the *Dicionário da Língua Portuguesa* by António de Morais Silva, retro-digitised in the [MORDigital project](#).

```
<!-- in the dictionary header -->
<encodingDesc>
  <classDecl>
    <taxonomy xml:id="domains">
<!--...-->
      <category xml:id="domain.medical_
and_health_sciences">
        <catDesc xml:lang="en">Medical a
nd Health Sciences</catDesc>
        <catDesc xml:lang="pt">Ciências
Médicas e da Saúde</catDesc>
        <category valueDatcat="https://
vocabs.rossio.fcsh.unl.pt/pub/
morais_domains/pt/page/0025"
xml:id="domain.medical_and_healt
h_sciences.medicine">
          <catDesc xml:lang="en">
            <term>Medicine</term>
            <gloss>
<!--...-->
              </gloss>
            </catDesc>
            <catDesc xml:lang="pt">
              <term>Medicina</term>
              <gloss>
<!--...-->
                </gloss>
```

```

        </catDesc>
        </category>
    </category>
<!--...-->
    </taxonomy>
</classDecl>
</encodingDesc>
<!--

```

inside an <entry> element: -->

```

<usg type="domain"
  valueDatcat="#domain.medical_and_
health_sciences.medicine">Med.</
usg>

```

In the Morais dictionary, the relevant domain labels are in the header, getting referenced inside the dictionary, from <usg> elements. The vocabulary used for dictionary-internal labelling is in turn anchored in the [MorDigital controlled vocabulary service](#) of the NOVA University of Lisbon – School of Social Sciences and Humanities (NOVA FCSH).

The TEI Abstract Model can be expressed as a hierarchy of attribute-value matrices (AVMs) of various types and of various levels of complexity, nested or grouped in various ways. At the most abstract level, an AVM consists of an information container and the value (contents) of that container.

A simple example of an XML serialization of such structures is, on the one hand, the opening and closing tags that delimit and name the container, and, on the other, the content enclosed by the two tags that constitutes the value. An analogous example is an attribute name and the value of that attribute.

In a TEI XML example of two equivalent serializations expressing the name-value pair <part-of-speech,common-noun>, namely <pos>commonNoun</pos> and pos="common-noun", one would

Note

classify the element `<pos>` and the attribute *pos* as containers (mapping onto the first member of the relevant name-value pair), while the character data content of `<pos>` or the value of *pos* would be seen as mapping onto the second member of the pair.

The `att.datcat` class provides means of addressing the containers and their values, while at the same time providing a way to interpret them in the context of external taxonomies or ontologies. Aligning e.g. both the `<pos>` element and the *pos* attribute with the same value of an external reference point (i.e., an entry in an agreed taxonomy) affirms the identity of the concept serialised by both the element container and the attribute container, and optionally provides a definition of that concept (in the case at hand, the concept *part of speech*).

The value of the `att.datcat` attributes should be a PID (persistent identifier) that points to a specific — and, ideally, shared — taxonomy or ontology. Among the resources that can, to a lesser or greater extent, be used as inventories of (more or less) standardized linguistic categories are the GOLD ontology, [CLARIN CCR](#), [OLiA](#), or [TermWeb's DatCatInfo](#), and also the [Universal Dependencies](#) inventory, on the assumption that its URIs are going to persist. It is imaginable that a project may choose to address a local taxonomy store instead, but this risks losing the advantage of interchangeability with other projects.

Historically, *datcat* and *valueDatcat* originate from the (now obsolete) ISO 12620:2009 standard, describing the data model and procedures for a Data Category Registry (DCR). The current version of that standard, ISO 12620-1,

does not standardize the serialization of pointers, merely mentioning the TEI att.datcat as an example.

Note that no constraint prevents the occurrence of a combination of att.datcat attributes: the <fDecl> element, which is a natural bearer of the *targetDatcat* attribute, is an instance of a specific modeling element, and, in principle, could be semantically fixed by an appropriate reference taxonomy of modeling devices.

att.declarable

att.declarable provides attributes for those elements in the TEI header which may be independently selected by means of the special purpose *decls* attribute. [[16.3. Associating Contextual Information with a Text](#)]

Module

tei

Members

availability bibl listBibl listEvent listOrg listPerson listPlace particDesc settingDesc sourceDesc

Attributes

default

indicates whether or not this element is selected by default when its parent is selected.

Status Optional

Datatype teidata.truthValue

Legal values are: **true**

This element is selected if its parent is selected

false

This element

can only be selected explicitly, unless it is the only one of its kind, in which case it is selected if its parent is selected. [Default]

Note

The rules governing the association of declarable elements with individual parts of a TEI text are fully defined in chapter [16.3. Associating Contextual Information with a Text](#). Only one element of a particular type may have a *default* attribute with a value of *true*.

att.declaring

att.declaring provides attributes for elements which may be independently associated with a particular declarable element within the header, thus overriding the inherited default for that element. [[16.3. Associating Contextual Information with a Text](#)]

Module

tei

Members

body p ptr term text

Attributes

decls (declarations)
identifies one or more *declarable*

elements within the header, which are understood to apply to the element bearing this attribute and its content.

Status Optional
Datatype 1-∞ occurrences of teidata.pointer separated by whitespace

Note

The rules governing the association of declarable elements with individual parts of a TEI text are fully defined in chapter [16.3. Associating Contextual Information with a Text](#).

att.dimensions

att.dimensions provides attributes for describing the size of physical objects.

Module

Members

Attributes

tei
date

- att.ranging
 - @atLeast
 - @atMost
 - @min
 - @max
 - @confidence

unit

names the unit used for the measurement

Status Optional
Datatype teidata.enumerated

Suggested values include: **cm** (centimetres)
mm (millimetres)

	es)
	in (inch es)
	line lines of text
	char (cha racte rs) char acter s of text
quantity	specifies the length in the units specified Status Optional Datatype teidata.n umeric
extent	indicates the size of the object concerned using a project-specific vocabulary combining quantity and units in a single string of words. Status Optional Datatype teidata.te xt <gap extent="5 wo rds"/> <height extent="h alf the page"/> characterizes the precision of the values specified by the other attributes. Status Optional Datatype teidata.ce rtainty
precision	where the
scope	

measurement summarizes more than one observation, specifies the applicability of this measurement.

Status Optional
Datatype teidata.enumerated

Sample values include: all measurement applies to all instances.

most measurement applies to most of the instances inspected.

range measurement applies to only the specified range of instances.

nces.

att.docStatus

att.docStatus provides attributes for use on metadata elements describing the status of a document.

Module

Members

Attributes

tei

bibl change revisionDesc

status

describes the status of a document either currently or, when associated with a dated element, at the time indicated.

Status Optional

Datatype teidata.enumerated

Sample values approved

include:

candidate

cleared

deprecated

draft

[Default]

embargoed

expired

frozen

galley

proposed

published

**recomm
endation**

**submitte
d**

**unfinish
ed**

**withdra
wn**

Example

```
<revisionDesc status="published">  
  <change status="published"  
    when="2010-10-21"/>  
  <change status="cleared" when="201  
0-10-02"/>  
  <change status="embargoed"  
    when="2010-08-02"/>  
  <change status="frozen" when="201  
0-05-01"  
    who="#MSM"/>  
  <change status="draft" when="2010-  
03-01"  
    who="#LB"/>  
</revisionDesc>
```

att.editLike

att.editLike provides attributes describing the nature of an encoded scholarly intervention or interpretation of any kind. [[3.5. Simple Editorial Changes](#) [11.3.1. Origination](#) [14.3.2. The Person Element](#) [12.3.1.1. Core Elements for Transcriptional Work](#)]

Module

Members

Attributes

tei

affiliation date event eventName

gender name org person place

placeName

evidence

indicates the
nature of the
evidence
supporting the
reliability or
accuracy of the
intervention or
interpretation.

Status Optional

Datatype 1-∞
occurren

ces
of teidata
.enumera
ted
separate
d by
whitespa
ce

Suggest internal
ed ther
values e is
include: inter
nal
evid
ence
to
supp
ort
the
inter
venti
on.

external
ther
e is
exter
nal
evid
ence
to
supp
ort
the
inter
venti
on.

conjectu
re the
inter
venti
on or
inter
pret
ation
has
been

made by the editor, catalogue, or scholar on the basis of their expertise.

instant indicates whether this is an instant revision or not.
Status Optional
Datatype teidata.x TruthValue
Default false

Note

The members of this attribute class are typically used to represent any kind of editorial intervention in a text, for example a correction or interpretation, or to date or localize manuscripts etc.

Each pointer on the *source* (if present) corresponding to a witness or witness group should reference a bibliographic citation such as a <witness>, <msDesc>, or <bibl> element, or another external bibliographic citation, documenting the source concerned.

att.fragmentable

att.fragmentable provides attributes for representing fragmentation of a structural element, typically as a consequence of some overlapping hierarchy.

Module tei
Members *p*
Attributes part specifies whether or not its parent element is fragmented in

some way, typically
by some other
overlapping
structure: for
example a speech
which is divided
between two or
more verse
stanzas, a
paragraph which is
split across a page
division, a verse
line which is
divided between
two speakers.

Status Optional
Datatype teidata.e
numerate
d

Legal Y
values (yes)
are: the
elem
ent
is
frag
ment
ed in
some
(uns
peci
fied)
resp
ect

N (no)
the
elem
ent
is
not
frag
ment
ed,
or no
clai
m is

made as to its completeness
[Default]

I (initial) this is the initial part of a fragmented element

M (medial) this is a medial part of a fragmented element

F (final) this is the final part of a fragment

ed
elem
ent

Note

The values *I*, *M*, or *F* should be used only where it is clear how the element may be reconstituted.

att.global

att.global provides attributes common to all elements in the TEI encoding scheme. [[1.3.1.1. Global Attributes](#)]

Module

Members

tei

TEI affiliation availability bibl bloc body catDesc category change classDecl country date desc editor encodingDesc event eventName fileDesc forename gender idno item licence list listBibl listChange listEvent listOrg listPerson listPlace name nameLink note org p particDesc person place placeName profileDesc ptr pubPlace publicationStmt publisher resp respStmt revisionDesc roleName settingDesc sourceDesc surname taxonomy teiHeader term text title titleStmt

Attributes

- att.global.linking
 - @corresp
 - @synch
 - @sameAs
 - @copyOf
 - @next
 - @prev
 - @exclude
 - @select
- att.global.rendition
 - @rend
 - @style
 - @rendition

- att.global.responsibility
 - *@cert*
 - *@resp*
- att.global.source
 - *@source*

xml:id (identifier)
 provides a unique identifier for the element bearing the attribute.
Status Optional
Datatype ID
Note The *xml:id* attribute may be used to specify a canonical reference for an element; see section [3.11. Reference Systems](#).

n (number) gives a number (or other label) for an element, which is not necessarily unique within the document.
Status Optional
Datatype teidata.text
Note The value of this attribute is always understood to be a single token, even if it

contains space or other punctuation characters, and need not be composed of numbers only. It is typically used to specify the numbering of chapters, sections, list items, etc.; it may also be used in the specification of a standard reference system for the text.

xml:lang

(language) indicates the language of the element content using a 'tag' generated according to [BCP 47](#).

Status Optional
Datatype teidata.language
 <p> ... The consequences of this rapid depopul

ation were the loss
of the last
<foreign xml:lang=
"rap">ariki</
foreign> or chief
(Routledge 1920:2
05,210) and their c
onnections to
ancestral territoria
l organization.</p>

Note The
xml:lang
value will
be
inherited
from the
immediat
ely
enclosing
element,
or from
its
parent,
and so on
up the
documen
t
hierarchy
. It is
generally
good
practice
to specify
xml:lang
at the
highest
appropria
te level,
noticing
that a
different
default
may be
needed
for the
<teiHead
er> from
that

needed
for the
associated
resource
element
or
elements,
and that
a single
TEI
document
may
contain
texts in
many
languages.

Only
attributes
with free
text
values
(rare in
these
guidelines)
will be
in the
scope of
xml:lang.

The
authoritative
list
of
registered
language
subtags
is
maintained
by
IANA and
is
available
at
<https://www.iana.org>

[rg/assignments/language-subtag-registry](https://www.w3.org/assignments/language-subtag-registry).

For a good general overview of the construction of language tags, see <https://www.w3.org/International/articles/language-tags/>, and for a practical step-by-step guide, see <https://www.w3.org/International/questions/qa-choosing-language-tags.en.php>.

The value used must conform with BCP 47. If the value is a private use code (i.e.,

starts with x- or contains -x-), a <language> element with a matching value for its *ident* attribute should be supplied in the TEI header to document this value. Such documentation may also optionally be supplied for non-private-use codes, though these must remain consistent with their (IETF)Internet Engineering Task Force definitions.

xml:base

provides a base URI reference with

which applications can resolve relative URI references into absolute URI references.

Status Optional
Datatype teidata.pointer

```
<div type="bibl">
  <head>Selections
from <title level="
m">The Collected
Letters of Robert S
outhey. Part 1: 179
1-1797</title>
</head>
<listBibl xml:base
="https://romantic-
circles.org/sites/
default/files/
imported/editions/
southey_letters/
XML/">
  <bibl>
    <ref target="lett
erEEd.26.3.xml">
      <title>Robert S
outhey to Grosveno
r Charles Bedford<
/title>, <date when
="1792-04-03">3 A
pril 1792</date>.
    </ref>
  </bibl>
  <bibl>
    <ref target="lett
erEEd.26.57.xml">
      <title>Robert S
outhey to Anna Se
ward</title>, <dat
e when="1793-09-
18">18 September
1793</date>.
    </ref>
  </bibl>
  <bibl>
    <ref target="lett
erEEd.26.85.xml">
```

	<title>Robert S outhey to Robert L ovell</title>, <dat e from="1794-04- 05" to="1794-04- 06">5-6 April, 179 4</date>. </ref> </bibl> </listBibl> </div>
xml:space	signals an intention about how white space should be managed by applications. Status Optional Datatype teidata.e numerate d Legal default values sign are: als that the appli catio n's defa ult whit e- spac e proc essin g mod es are acce ptabl e preserve indic ates

the
inten
t
that
appli
catio
ns
pres
erve
all
whit
e
spac
e

Note The [XML specification](#) provides further guidance on the use of this attribute. Note that many parsers may not handle xml:space correctly.

att.global.linking

att.global.linking provides a set of attributes for hypertextual linking. [[17. Linking, Segmentation, and Alignment](#)]

Module

linking

Members

*att.global[TEI affiliation availability
bibl bloc body catDesc category
change classDecl country date desc
editor encodingDesc event eventName
fileDesc forename gender idno item
licence list listBibl listChange listEvent
listOrg listPerson listPlace name
nameLink note org p particDesc
person place placeName profileDesc
ptr pubPlace publicationStmt*

Attributes

*publisher resp respStmt revisionDesc
 roleName settingDesc sourceDesc
 surname taxonomy teiHeader term
 text title titleStmt]*
 corresp (corresponds)
 points to elements
 that correspond to
 the current
 element in some
 way.
Status Optional
Datatype 1-∞
 occurrences
 of teidata
 .pointer
 separate
 d by
 whitespace
 ce
 <group>
 <text xml:id="t1-
 g1-t1"
 xml:lang="mi">
 <body xml:id="t1-
 g1-t1-body1">
 <div type="chapt
 er">
 <head>He Wha
 kamaramatanga m
 o te Ture Hoko, Rii
 hi hoki, i nga When
 ua Maori, 1876.</
 head>
 <p>...</p>
 </div>
 </body>
 </text>
 <text xml:id="t1-
 g1-t2"
 xml:lang="en">
 <body corresp=""
 #t1-g1-t1-body1"
 xml:id="t1-g1-t2-
 body1">
 <div type="chapt
 er">
 <head>An Act t

o regulate the Sale,
Letting, and Dispos
al of Native Lands,
1876.</head>

<p>...</p>

</div>

</body>

</text>

</group>

In this example a
<group> contains
two <text>s, each
containing the
same document in
a different
language. The
correspondence is
indicated using
corresp. The
language is
indicated using
xml:lang, whose
value is inherited;
both the tag with
the *corresp* and the
tag pointed to by
the *corresp* inherit
the value from
their immediate
parent.

<!-- In a placeogra
phy called "places.
xml" --><place cor
resp="people.xml#
LOND2 people.xml
#GENI1"

xml:id="LOND1">
<placeName>Lon
don</placeName>
<desc>The city of
London...</desc>
</place>

<!-- In a literary pe
rsonography called
"people.xml" -->
<person corresp=""
places.xml#LOND1

```

#GENI1"
xml:id="LOND2">
  <persName type=
"lit">London</
persName>
  <note>
    <p>Allegorical ch
aracter representin
g the city of <place
Name ref="places.
xml#LOND1">Lon
don</
placeName>.</p>
  </note>
</person>
<person corresp="
places.xml#LOND1
#LOND2"
xml:id="GENI1">
  <persName type=
"lit">London's Gen
ius</persName>
  <note>
    <p>Personificatio
n of London's geniu
s. Appears as an
    allegorical char
acter in mayoral sh
ows.
    </p>
  </note>
</person>

```

In this example, a <place> element containing information about the city of London is linked with two <person> elements in a literary personography. This correspondence represents a slightly looser relationship than the one in the

	preceding example; there is no sense in which an allegorical character could be substituted for the physical city, or vice versa, but there is obviously a correspondence between them. (synchronous) points to elements that are synchronous with the current element.
synch	Status Optional Datatype $1-\infty$ occurrences of teidata .pointer separated by whitespace
sameAs	points to an element that is the same as the current element. Status Optional Datatype teidata.p ointer
copyOf	points to an element of which the current element is a copy. Status Optional Datatype teidata.p ointer Note Any content of the current element should be

	ignored. Its true content is that of the element being pointed at.
next	points to the next element of a virtual aggregate of which the current element is part. Status Optional Datatype teidata.p ointer Note It is recomme nded that the element indicated be of the same type as the element bearing this attribute.
prev	(previous) points to the previous element of a virtual aggregate of which the current element is part. Status Optional Datatype teidata.p ointer Note It is recomme nded that the element indicated be of the

	same type as the element bearing this attribute.
exclude	points to elements that are in exclusive alternation with the current element. Status Optional Datatype 1-∞ occurrences of teidata .pointer separated by whitespace
select	selects one or more alternants; if one alternant is selected, the ambiguity or uncertainty is marked as resolved. If more than one alternant is selected, the degree of ambiguity or uncertainty is marked as reduced by the number of alternants not selected. Status Optional Datatype 1-∞ occurrences of teidata .pointer separate

	d by whitespace
Note	This attribute should be placed on an element which is superordinate to all of the alternants from which the selection is being made.

att.global.rendition

att.global.rendition provides rendering attributes common to all elements in the TEI encoding scheme. [[1.3.1.1.3. Rendition Indicators](#)]

Module

Members

tei
att.global[TEI affiliation availability
 bibl bloc body catDesc category
 change classDecl country date desc
 editor encodingDesc event eventName
 fileDesc forename gender idno item
 licence list listBibl listChange listEvent
 listOrg listPerson listPlace name
 nameLink note org p particDesc
 person place placeName profileDesc
 ptr pubPlace publicationStmt
 publisher resp respStmt revisionDesc
 roleName settingDesc sourceDesc
 surname taxonomy teiHeader term
 text title titleStmt]

Attributes

rend	(rendition) indicates how the element in question was rendered or presented in the source text.
Status	Optional
Datatype	1-∞

occurrences
of teidata
.word
separated by
whitespace

```
<head rend="align  
(center) case(allcaps)">  
  <lb/>To The <lb/  
>Duchesse <lb/>of  
<lb/>Newcastle,  
<lb/>On Her <lb/>  
  <hi rend="case(mixed)">New Blazing  
-World</hi>.  
</head>
```

Note These Guidelines make no binding recommendations for the values of the *rend* attribute; the characteristics of visual presentation vary too much from text to text and the decision to record or ignore individual characteristics varies too much

from project to project. Some potentially useful conventions are noted from time to time at appropriate points in the Guidelines. The values of the *rend* attribute are a set of sequence - indeterminate individual tokens separated by whitespace.

style

contains an expression in some formal style definition language which defines the rendering or presentation used for this element in the source text.

Status Optional
Datatype teidata.text

```
<head style="text-align: center; font-variant: small-caps">
```

```

<lb/>To The <lb/
>Duchesse <lb/>of
<lb/>Newcastle, <
lb/>On Her
<lb/>
<hi style="font-
variant: normal">N
ew Blazing-
World</hi>.
</head>

```

Note Unlike the attribute values of *rend*, which uses whitespace as a separator, the *style* attribute may contain whitespace. This attribute is intended for recording inline stylistic information concerning the source, not any particular output. The formal language in which values for

this attribute are expressed may be specified using the <styleDef Decl> element in the TEI header.

If *style* and *rendition* are both present on an element, then *style* overrides or complements *rendition*. *style* should not be used in conjunction with *rend*, because the latter does not employ a formal style definition language.

rendition

points to a description of the rendering or presentation used for this element in

the source text.

Status Optional

Datatype 1-∞

occurrences
of teidata
.pointer
separated by
whitespace

```
<head rendition="#ac #sc">
  <lb/>To The <lb/>
>Duchesse <lb/>of
<lb/>Newcastle, <
lb/>On Her
<lb/>
  <hi rendition="#normal">New Blazing-World</hi>.
</head>
<!-- elsewhere... -->
<rendition scheme="css"
  xml:id="sc">font-variant: small-caps</rendition>
<rendition scheme="css"
  xml:id="normal">font-variant: normal</rendition>
<rendition scheme="css"
  xml:id="ac">text-align: center</rendition>
```

Note The *rendition* attribute is used in a very similar way to the *class* attribute

defined
for
XHTML
but with
the
important
distinction that its
function
is to
describe
the
appearance
of the
source
text, not
necessarily
to
determine
how
that text
should be
presented
on
screen or
paper.

If
rendition
is used to
refer to a
style
definition
in a
formal
language
like CSS,
it is
recommended that
it not be
used in
conjunction
with
rend.
Where
both

rendition
and *rend*
are
supplied,
the latter
is
understo
od to
override
or
complem
ent the
former.

Each URI
provided
should
indicate a
<renditio
n>
element
defining
the
intended
rendition
in terms
of some
appropria
te style
language,
as
indicated
by the
scheme
attribute.

att.global.responsibility

att.global.responsibility provides attributes indicating the agent responsible for some aspect of the text, the markup or something asserted by the markup, and the degree of certainty associated with it. [[1.3.1.1.4. Sources, certainty, and responsibility](#) [3.5. Simple Editorial Changes](#) [12.3.2.2. Hand, Responsibility, and Certainty Attributes](#) [18.3. Spans and Interpretations](#) [14.1.1. Linking Names and Their Referents](#)]

Module

tei

Members

att.global[*TEI affiliation availability*
bibl bloc body catDesc category
change classDecl country date desc

*editor encodingDesc event eventName
 fileDesc forename gender idno item
 licence list listBibl listChange listEvent
 listOrg listPerson listPlace name
 nameLink note org p particDesc
 person place placeName profileDesc
 ptr pubPlace publicationStmt
 publisher resp respStmt revisionDesc
 roleName settingDesc sourceDesc
 surname taxonomy teiHeader term
 text title titleStmt]*

Attributes

cert	(certainty) signifies the degree of certainty associated with the intervention or interpretation. Status Optional Datatype teidata.pr
resp	obCert (responsible party) indicates the agency responsible for the intervention or interpretation, for example an editor or transcriber. Status Optional Datatype 1-∞ occurrences of teidata.pointer separated by whitespace Note To reduce the ambiguity of a <i>resp</i> pointing directly to a person or

organization, we
 recommend that
resp be
 used to
 point not
 to an
 agent
 (<person
 > or
 <org>)
 but to a
 <respSt
 mt>,
 <author
 >,
 <editor>
 or similar
 element
 which
 clarifies
 the exact
 role
 played by
 the
 agent.
 Pointing
 to
 multiple
 <respSt
 mt>s
 allows
 the
 encoder
 to specify
 clearly
 each of
 the roles
 played in
 part of a
 TEI file
 (creating,
 transcribi
 ng,
 encoding,
 editing,
 proofing

etc.).

Example

Blessed are the
<choice>
 <sic>cheesemakers</sic>
 <corr cert="high" resp="#editor">pe
acemakers</corr>
</choice>: for they shall be called the
children of God.

Example

```
<!-- in the <text> ... --><lg>
<!-- ... -->
<l>Punkes, Panders, bafe extortionizi
ng
  sla<choice>
  <sic>n</sic>
  <corr resp="#JENS1_transcriber">u
</corr>
  </choice>es,</l>
<!-- ... -->
</lg>
<!-- in the <teiHeader> ... -->
<!-- ... -->
<respStmt xml:id="JENS1_transcriber
">
  <resp when="2014">Transcriber</
resp>
  <name>Janelle Jenstad</name>
</respStmt>
```

att.global.source

att.global.source provides attributes used by elements to point to an external source. [[1.3.1.1.4. Sources, certainty, and responsibility](#) [3.3.3. Quotation](#) [8.3.4. Writing](#)]

Module

Members

tei
att.global[TEI affiliation availability
bibl bloc body catDesc category
change classDecl country date desc
editor encodingDesc event eventName
fileDesc forename gender idno item
licence list listBibl listChange listEvent
listOrg listPerson listPlace name
nameLink note org p particDesc
person place placeName profileDesc
ptr pubPlace publicationStmt
publisher resp respStmt revisionDesc
roleName settingDesc sourceDesc
surname taxonomy teiHeader term

Attributes

<i>text title titleStmt]</i>	
source	specifies the source from which some aspect of this element is drawn.
Status	Optional
Datatype	1-∞ occurrences of teidata.pointer separated by whitespace
Schematron	<pre><sch:rule context="tei:*[@source]"> <sch:let name="srcs" value="tokenize(normalize-space(@source),' ')/> <sch:report test=" (self::tei:classRef self::tei:ataRef self::tei:elementRef self::tei:macroRef self::tei:moduleRef self::tei:schemaSpec) and \$srcs[2]" > When</pre>

used on a
 schema
 descripti
 on
 element
 (like
 <sch:valu
 e-of selec
 t="name(
 .)"/>), the
 @source
 attribute
 should
 have only
 1 value.
 (This one
 has
 <sch:valu
 e-of selec
 t="count(
 \$srcs)"/>
 .)
 </sch:rep
 ort>
 </sch:rul
 e>

Note

The
source
 attribute
 points to
 an
 external
 source.
 When
 used on
 an
 element
 describin
 g a
 schema
 compone
 nt
 (<classR
 ef>,
 <dataRef
 >,
 <element
 Ref>,

<macroRef>, <moduleRef>, or <schemaSpec>), it identifies the source from which declarations for the components should be obtained.

On other elements it provides a pointer to the bibliographical source from which a quotation or citation is drawn.

In either case, the location may be provided using any form of URI, for example an absolute URI, a relative

URI, a private scheme URI of the form `tei:x.y.z`, where `x.y.z` indicates the version number, e.g. `tei:4.3.2` for TEI P5 release 4.3.2 or (as a special case) `tei:current` for whatever is the latest release, or a private scheme URI that is expanded to an absolute URI as documented in a `<prefixDef>`.

When used on elements describing schema components,

source
should
have only
one
value;
when
used on
other
elements
multiple
values
are
permitted
.

Example

```
<p>
<!-- ... --> As Willard McCarty (<bibl x
ml:id="mcc_2012">2012, p.2</bibl>)
tells us, <quote source="#mcc_2012"
>'Collaboration' is a problematic and s
hould be a contested
    term.</quote>
<!-- ... -->
</p>
```

Example

```
<p>
<!-- ... -->
    <quote source="#chicago_15_ed">Gr
ammatical theories are in flux, and the
more we learn, the
    less we seem to know.</quote>
<!-- ... -->
</p>
<!-- ... -->
<bibl xml:id="chicago_15_ed">
    <title level="m">The Chicago Manual
of Style</title>,
    <edition>15th edition</edition>. <pu
bPlace>Chicago</pubPlace>: <publis
her>University of
    Chicago Press</publisher> (<date>
2003</date>), <biblScope unit="page
">p.147</biblScope>.
```

Example

```
</bibl>
<elementRef key="p" source="tei:2.0.
1"/>
Include in the schema an element
named <p> available from the TEI P5
```

Example

2.0.1 release.

```
<schemaSpec ident="myODD"
  source="mycompiledODD.xml">
  <!-- further declarations specifying the
  components required -->
</schemaSpec>
```

Create a schema using components
taken from the file
mycompiledODD.xml.

att.internetMedia

att.internetMedia provides attributes for specifying the type of a computer resource using a standard taxonomy.

Module

tei

Members

ptr

Attributes

mimeType

(MIME media type)
specifies the
applicable
multimedia
internet mail
extension (MIME)
media type.

Status Optional

Datatype 1-∞

occurren
ces
of teidata
.word
separate
d by
whitespa
ce

Example

In this example *mimeType* is used to indicate that the URL points to a TEI XML file encoded in UTF-8.

```
<ref mimeType="application/tei+xml;
charset=UTF-8"
target="https://
raw.githubusercontent.com/TEIC/TEI/
dev/P5/Source/guidelines-en.xml"/>
```

Note

This attribute class provides an attribute for describing a computer resource, typically available over the internet, using a value taken from a standard taxonomy. At present only a single taxonomy is supported, the Multipurpose Internet Mail Extensions

(MIME) Media Type system. This typology of media types is defined by the Internet Engineering Task Force in [RFC 2046](#). The [list of types](#) is maintained by the Internet Assigned Numbers Authority (IANA). The *mimeType* attribute must have a value taken from this list.

att.locatable

att.locatable provides attributes for referencing locations by pointing to entries in a canonical list of places. [[2.3.9. The Unit Declaration 14.3.4.3. States, Traits, and Events](#)]

Module	tei	
Members	<i>event</i>	
Attributes	<i>where</i>	indicates one or more locations by pointing to a <place> element or other canonical description. Status Optional Datatype 1-∞ occurrences of teidata.pointer separated by whitespace

att.naming

att.naming provides attributes common to elements which refer to named persons, places, organizations etc. [[3.6.1. Referring Strings 14.3.7. Names and Nyms](#)]

Module	tei	
Members	<i>att.personal[eventName forename name placeName roleName surname] affiliation bloc country editor event pubPlace</i>	
Attributes	• <i>att.canonical</i> • <i>@key</i> • <i>@ref</i>	
	<i>role</i>	may be used to specify further

	information about the entity referenced by this name in the form of a set of whitespace-separated values, for example the occupation of a person, or the status of a place.
	Status Optional
	Datatype 1-∞
	occurrences of teidata.enumerated separated by whitespace
nymRef	(reference to the canonical name) provides a means of locating the canonical form (<i>nym</i>) of the names associated with the object named by the element bearing it.
	Status Optional
	Datatype 1-∞
	occurrences of teidata.pointer separated by whitespace
	Note The value must point directly to one or

more XML elements by means of one or more URIs, separated by whitespace. If more than one is supplied, the implication is that the name is associated with several distinct canonical names.

att.personal

att.personal (attributes for components of names usually, but not necessarily, personal names) common attributes for those elements which form part of a name usually, but not necessarily, a personal name. [[14.2.1. Personal Names](#)]

Module

Members

Attributes

tei

eventName forename name

placeName roleName surname

- att.naming
 - *@role*
 - *@nymRef*
- att.canonical
 - *@key*
 - *@ref*

full

indicates whether the name component is given in full, as an abbreviation or simply as an initial.

Status Optional

Datatype	teidata.e numerate d
Legal values are:	yes (yes) the nam e com pone nt is spell ed out in full. <i>[Def ault]</i> abb (abb revia ted) the nam e com pone nt is give n in an abbr eviat ed form . init (initi al lette r) the nam e com pone nt is

indicated only by one initial.

sort

(sort) specifies the sort order of the name component in relation to others within the name.
Status Optional
Datatype teidata.count

att.placement

att.placement provides attributes for describing where on the source page or object a textual element appears. [[3.5.3. Additions, Deletions, and Omissions](#) [12.3.1.4. Additions and Deletions](#)]

Module

tei

Members

note

Attributes

place

specifies where this item is placed.
Status Recommended
Datatype 1-∞ occurrences of teidata.enumerated separated by whitespace

Suggested values include: top at the top of the page
bottom at the foot

of
the
page
margin
in
the
mar
gin
(left,
right
, or
both
)

opposite
on
the
oppo
site,
i.e.
facin
g,
page

overleaf
on
the
othe
r
side
of
the
leaf

above
abov
e the
line

right
to
the
right
, e.g.
to
the
right
of a
verti
cal
line

of
text,
or to
the
right
of a
figur
e

below
belo
w
the
line

left
to
the
left,
e.g.
to
the
left
of a
verti
cal
line
of
text,
or to
the
left
of a
figur
e

end
at
the
end
of
e.g.
chap
ter
or
volu
me.

inline
withi
n the

body
of
the
text.
inspace
in a
pred
efined
space,
for
example
left
by
an
earlier
scribe.

```
<add place="margin">[An addition written in the margin]
</add>
<add place="bottom opposite">[An addition written at the
foot of the current
page and also on the
facing page]</
add>
<note place="bottom">Ibid, p.7</
note>
```

att.pointing

att.pointing provides a set of attributes used by all elements which point to other elements by means of one or more URI references. [[1.3.1.1.2. Language Indicators 3.7. Simple Links and Cross-References](#)]

Module	tei	
Members	<i>licence note ptr term</i>	
Attributes	targetLang	specifies the language of the content to be found at the destination

referenced by
target, using a
 'language tag'
 generated
 according to [BCP
 47](#).

Status Optional
Datatype teidata.la
 nguage

**Schemat
 ron** <sch:rule
 context=
 "tei:*[not
 (self::tei:s
 chemaSp
 ec)]
 [@target
 Lang]">
 <sch:ass
 ert test="
 @target"
 >@target
 Lang
 should
 only be
 used on
 <sch:na
 me/> if
 @target
 is
 specified.
 </sch:ass
 ert>
 </sch:rul
 e>

<linkGrp xml:id="p
 ol-swh_aln_2.1-
 linkGrp">
 <ptr target="pol/
 UDHR/
 text.xml#pol_txt_1-
 head"
 targetLang="pl"
 type="tuv"
 xml:id="pol-
 sw_h_aln_2.1.1-
 ptr"/>
 <ptr target="sw_h/
 UDHR/

```

text.xml#swh_txt_1
-head"
  targetLang="sw"
  type="tuv"
  xml:id="pol-
swh_aln_2.1.2-
ptr"/>
</linkGrp>

```

In the example above, the <linkGrp> combines pointers at parallel fragments of the *Universal Declaration of Human Rights*: one of them is in Polish, the other in Swahili.

Note The value must conform to BCP 47. If the value is a private use code (i.e., starts with x- or contains -x-), a <language> element with a matching value for its *ident* attribute should be supplied in the TEI header to document this

value.
Such
documen
tation
may also
optionally
be
supplied
for non-
private-
use
codes,
though
these
must
remain
consisten
t with
their
(IETF)Int
ernet
Engineeri
ng Task
Force
definition
s.

target

specifies the
destination of the
reference by
supplying one or
more URI
References.

Status Optional

Datatype 1-∞
occurren
ces
of teidata
.pointer
separate
d by
whitespa
ce

Note One or
more
syntactic
ally valid
URI

reference
s,
separate
d by
whitespa
ce.
Because
whitespa
ce is used
to
separate
URIs, no
whitespa
ce is
permitted
inside a
single
URI. If a
whitespa
ce
character
is
required
in a URI,
it should
be
escaped
with the
normal
mechanis
m, e.g.
TEI
%20Cons
ortium.

evaluate

(evaluate) specifies
the intended
meaning when the
target of a pointer
is itself a pointer.

Status Optional
Datatype teidata.e
numerate
d

Legal **all**
values if the
are: elem
ent

point
ed to
is
itself
a
point
er,
then
the
targ
et of
that
point
er
will
be
take
n,
and
so
on,
until
an
elem
ent
is
foun
d
whic
h is
not a
point
er.

one

if the
elem
ent
point
ed to
is
itself
a
point
er,
then
its
targ
et

(whether a pointer or not) is taken as the target of this pointer.

none

no further evaluation of targets is carried out beyond that needed to find the element specified in the pointer's target.

Note

If no value is given, the

application
 program
 is
 responsible for
 deciding
 (possibly
 on the
 basis of
 user
 input)
 how far
 to trace a
 chain of
 pointers.

att.ranging

att.ranging provides attributes for describing numerical ranges.

Module

tei

Members

att.dimensions[date]

Attributes

atLeast

gives a minimum
 estimated value for
 the approximate
 measurement.

Status Optional

Datatype teidata.n
 umeric

atMost

gives a maximum
 estimated value for
 the approximate
 measurement.

Status Optional

Datatype teidata.n
 umeric

min

where the
 measurement
 summarizes more
 than one
 observation or a
 range, supplies the
 minimum value
 observed.

Status Optional

Datatype teidata.n
 umeric

max

where the

measurement
summarizes more
than one
observation or a
range, supplies the
maximum value
observed.

Status Optional
Datatype teidata.n
umeric

confidence specifies the
degree of
statistical
confidence
(between zero and
one) that a value
falls within the
range specified by
min and *max*, or
the proportion of
observed values
that fall within that
range.

Status Optional
Datatype teidata.pr
obability

Example

The MS. was lost in transmission by mail from
<del rend="overstrike">
 <gap atLeast="1" atMost="2"
 extent="one or two letters" reason="illegible" unit="chars"/>

Philadelphia to the Graphic office, New York.

Example

Americares has been supporting the health sector in Eastern Europe since 1986,
and since 1992 has provided <measure atLeast="120000000"
 commodity="currency" unit="USD">
more
than \$120m</measure> in aid to Ukrainians.

att.sortable

att.sortable provides attributes for elements in lists or groups that are sortable, but whose sorting key cannot be derived mechanically from the element content. [[10.1. Dictionary Body and Overall Structure](#)]

Module

tei

Members

*bibl event idno item list listBibl
listChange listEvent listOrg listPerson
listPlace org person place term*

Attributes

sortKey

supplies the sort key for this element in an index, list or group which contains it.

Status Optional

Datatype teidata.word

David's other principal backer, Josiah ha-Kohen <index indexName="NAME">

<term sortKey="Azarya_Josiah_Kohen">Josiah ha-Kohen b. Azarya</term></index> b. Azarya, son of one of the last gaons of Sura was David's own first cousin.

Note The sort key is used to determine the sequence and grouping of entries in an index. It provides a sequence of characters which,

when
sorted
with the
other
values,
will
produced
the
desired
order;
specifics
of sort
key
construct
ion are
applicatio
n-
dependen
t

Dictionar
y order
often
differs
from the
collation
sequence
of
machine-
readable
character
sets; in
English-
language
dictionari
es, an
entry for
4-H will
often
appear
alphabeti
zed
under
'fourh',
and
McCoy
may be
alphabeti

zed
under
'maccoy',
while A1,
A4, and
A5 may
all
appear in
numeric
order
'alphabet
ized'
between
'a-' and
'AA'. The
sort key
is
required
if the
orthogra
phy of
the
dictionar
y entry
does not
suffice to
determin
e its
location.

att.typed

att.typed provides attributes that can be used to classify or subclassify elements in any way. [[1.3.1. Attribute Classes](#) [18.1.1. Words and Above](#) [3.6.1. Referring Strings](#) [3.7. Simple Links and Cross-References](#) [3.6.5. Abbreviations and Their Expansions](#) [3.13.1. Core Tags for Verse](#) [7.2.5. Speech Contents](#) [4.1.1. Un-numbered Divisions](#) [4.1.2. Numbered Divisions](#) [4.2.1. Headings and Trailers](#) [4.4. Virtual Divisions](#) [14.3.2.3. Personal Relationships](#) [12.3.1.1. Core Elements for Transcriptional Work](#) [17.1.1. Pointers and Links](#) [17.3. Blocks, Segments, and Anchors](#) [13.2. Linking the Apparatus to the Text](#) [23.5.1.2. Defining Content Models: RELAX NG](#) [8.3. Elements Unique to Spoken Texts](#) [24.3.1.3. Modification of Attribute and Attribute Value Lists](#)]

Module

tei

Members

*TEI affiliation bibl bloc change country
date desc event eventName forename
gender idno list listBibl listChange
listEvent listOrg listPerson listPlace
name nameLink note org place*

Attributes

<i>placeName ptr roleName surname</i>	
<i>term text title</i>	
<i>type</i>	characterizes the element in some sense, using any convenient classification scheme or typology. Status Optional Datatype teidata.e numerate d <pre><div type="verse"> > <head>Night in T arras</head> <lg type="stanza"> > <l>At evening tra mping on the hot w hite road</l> <l>...</l> </lg> <lg type="stanza"> > <l>A wind sprang up from nowhere a s the sky</l> <l>...</l> </lg> </div></pre>
Note	The <i>type</i> attribute is present on a number of elements, not all of which are members of att.typed, usually because these elements

	restrict the possible values for the attribute in a specific way.
subtype	(subtype) provides a sub-categorization of the element, if needed. Status Optional Datatype teidata.enumerated Note The <i>subtype</i> attribute may be used to provide any sub-classification for the element additional to that provided by its <i>type</i> attribute.

Schematron

Note

```
<sch:rule context="tei:*[@subtype]">
<sch:assert test="@type">The
<sch:name/> element should not be
categorized in detail with @subtype
unless also categorized in general with
@type</sch:assert> </sch:rule>
```

When appropriate, values from an established typology should be used. Alternatively a typology may be defined in the associated TEI header. If values are to be taken from a project-specific list, this should be defined

using the <valList> element in the project-specific schema description, as described in [24.3.1.3. Modification of Attribute and Attribute Value Lists](#) .

att.written

att.written provides attributes to indicate the hand in which the content of an element was written in the source being transcribed. [[1.3.1. Attribute Classes](#)]

Module

tei

Members

note p text

Attributes

hand

points to a
<handNote>
element describing
the hand
considered
responsible for the
content of the
element concerned.

Status Optional
Datatype teidata.p
ointer

Macros

macro.limitedContent

macro.limitedContent (paragraph content) defines the content of prose elements that are not used for transcription of extant materials. [[1.3. The TEI Class System](#)]

Module

tei

Used by

desc

Content model

```
<content>
  <alternate maxOccurs="unbounded"
    minOccurs="0">
    <textNode/>
    <classRef key="model.limitedPhrase"
  />
    <classRef key="model.inter"/>
  </alternate>
</content>
```

Declaration

```
tei_macro.limitedContent =
  ( text | tei_model.limitedPhrase | tei_
model.inter )*
```

macro.paraContent

macro.paraContent (paragraph content) defines the content of paragraphs and similar elements. [[1.3. The TEI Class System](#)]

Module tei
Used by p title
Content model

```
<content>
  <alternate maxOccurs="unbounded"
    minOccurs="0">
    <textNode/>
    <classRef key="model.paraPart"/>
  </alternate>
</content>
```

Declaration

```
tei_macro.paraContent = ( text | tei_model.paraPart )*
```

macro.phraseSeq

macro.phraseSeq (phrase sequence) defines a sequence of character data and phrase-level elements. [[1.4.1. Standard Content Models](#)]

Module tei
Used by affiliation bloc country editor
eventName forename gender name
nameLink placeName pubPlace
publisher roleName surname term

Content model

```
<content>
  <alternate maxOccurs="unbounded"
    minOccurs="0">
    <textNode/>
    <classRef key="model.gLike"/>
    <classRef key="model.attributable"/>
  >
  <classRef key="model.phrase"/>
  <classRef key="model.global"/>
</alternate>
</content>
```

Declaration

```
tei_macro.phraseSeq =
(
  text
  | tei_model.gLike
  | tei_model.attributable
  | tei_model.phrase
)
```

| tei_model.global
)*

macro.phraseSeq.limited

macro.phraseSeq.limited (limited phrase sequence) defines a sequence of character data and those phrase-level elements that are not typically used for transcribing extant documents. [[1.4.1. Standard Content Models](#)]

Module tei
Used by resp
Content model

```
<content>
  <alternate maxOccurs="unbounded"
    minOccurs="0">
    <textNode/>
    <classRef key="model.limitedPhrase"
  />
    <classRef key="model.global"/>
  </alternate>
</content>
```

Declaration

```
tei_macro.phraseSeq.limited =
  ( text | tei_model.limitedPhrase | tei_
    model.global )*
```

macro.specialPara

macro.specialPara ('special' paragraph content) defines the content model of elements such as notes or list items, which either contain a series of component-level elements or else have the same structure as a paragraph, containing a series of phrase-level and inter-level elements. [[1.3. The TEI Class System](#)]

Module tei
Used by change item licence note
Content model

```
<content>
  <alternate maxOccurs="unbounded"
    minOccurs="0">
    <textNode/>
    <classRef key="model.gLike"/>
    <classRef key="model.phrase"/>
    <classRef key="model.inter"/>
    <classRef key="model.divPart"/>
    <classRef key="model.global"/>
  </alternate>
</content>
```

Declaration

```

tei_macro.specialPara =
(
    text
    | tei_model.gLike
    | tei_model.phrase
    | tei_model.inter
    | tei_model.divPart
    | tei_model.global
)*

```

Datatypes

teidata.certainty

teidata.certainty defines the range of attribute values expressing a degree of certainty.

Module

tei

Used by

teidata.probCert

Content model

```

<content>
  <valList type="closed">
    <valItem ident="high"/>
    <valItem ident="medium"/>
    <valItem ident="low"/>
    <valItem ident="unknown"/>
  </valList>
</content>

```

Declaration

```

tei_teidata.certainty = "high" | "medium" | "low" | "unknown"

```

Note

Certainty may be expressed by one of the predefined symbolic values *high*, *medium*, or *low*. The value *unknown* should be used in cases where the encoder does not wish to assert an opinion about the matter.

teidata.count

teidata.count defines the range of attribute values used for a non-negative integer value used as a count.

Module

tei

Used by

Content model

```

<content>
  <dataRef name="nonNegativeInteger"/>

```

</content>

Declaration

tei_teidata.count = xsd:nonNegativeInteger

Note

Any positive integer value or zero is permitted

teidata.duration.iso

teidata.duration.iso defines the range of attribute values available for representation of a duration in time using ISO 8601 standard formats.

Module

tei

Used by

Content model

```
<content>
  <dataRef name="token"
    restriction="[0-9.,DHMPRSTWYZ/;+\\-]+"/>
</content>
```

Declaration

tei_teidata.duration.iso = token { pattern = "[0-9.,DHMPRSTWYZ/;+\\-]+" }

Example

<time dur-iso="PT0,75H">three-quarters of an hour</time>

Example

<date dur-iso="P1,5D">a day and a half</date>

Example

<date dur-iso="P14D">a fortnight</date>

Example

<time dur-iso="PT0.02S">20 ms</time>

Note

A duration is expressed as a sequence of number-letter pairs, preceded by the letter P; the letter gives the unit and may be Y (year), M (month), D (day), H (hour), M (minute), or S (second), in that order. The numbers are all unsigned integers, except for the last, which may have a decimal component (using either . or , as the decimal point; the latter is preferred). If any number is 0, then that number-letter pair may be omitted. If any of the H (hour), M (minute), or S (second) number-letter pairs are present, then the separator T must precede the first 'time' number-letter pair.

For complete details, see ISO 8601 *Data elements and interchange formats — Information interchange — Representation of dates and times*.

teidata.duration.w3c

teidata.duration.w3c defines the range of attribute values available for representation of a duration in time using W3C datatypes.

Module `tei`

Used by

Content model

```
<content>
  <dataRef name="duration"/>
</content>
```

Declaration

```
tei_teidata.duration.w3c = xsd:duration
```

Example

```
<time dur="PT45M">forty-five minutes</time>
```

Example

```
<date dur="P1DT12H">a day and a half</date>
```

Example

```
<date dur="P7D">a week</date>
```

Example

```
<time dur="PT0.02S">20 ms</time>
```

Note

A duration is expressed as a sequence of number-letter pairs, preceded by the letter P; the letter gives the unit and may be Y (year), M (month), D (day), H (hour), M (minute), or S (second), in that order. The numbers are all unsigned integers, except for the S number, which may have a decimal component (using . as the decimal point). If any number is 0, then that number-letter pair may be omitted. If any of the H (hour), M (minute), or S (second) number-letter pairs are present, then the separator T must precede the first 'time' number-letter pair.

For complete details, see the [W3C specification](#).

teidata.enumerated

teidata.enumerated defines the range of attribute values expressed as a

single XML name taken from a list of documented possibilities.

Module `tei`
Used by `teidata.gender teidata.sexElement:`
Content model

```
<content>  
  <dataRef key="teidata.word"/>  
</content>
```

Declaration

Note

`tei_teidata.enumerated = teidata.word`
Attributes using this datatype must contain a single 'word' which contains only letters, digits, punctuation characters, or symbols: thus it cannot include whitespace.

Typically, the list of documented possibilities will be provided (or exemplified) by a value list in the associated attribute specification, expressed with a `<valList>` element.

teidata.gender

teidata.gender defines the range of attribute values used to represent the gender of a person, persona, or character.

Module `tei`
Used by `Element:`
Content model

```
<content>  
  <dataRef key="teidata.enumerated"/>  
>  
</content>
```

Declaration

Note

`tei_teidata.gender = teidata.enumerated`

Values for attributes using this datatype may be defined locally by a project, or they may refer to an external standard.

Values for this datatype should not be used to encode morphological gender (cf. `<gen>`, *msd* as defined in [att.linguistic](#), and [10.3.1. Information on Written and Spoken Forms](#)).

teidata.language

teidata.language defines the range of attribute values used to identify a particular combination of human language and writing system. [[6.1. Language Identification](#)]

Module

tei

Used by

Content model

```
<content>
  <alternate>
    <dataRef name="language"/>
    <valList>
      <valItem ident=""/>
    </valList>
  </alternate>
</content>
```

Declaration

```
tei teidata.language = xsd:language | (
  "" )
```

Note

The values for this attribute are language ‘tags’ as defined in [BCP 47](#). Currently BCP 47 comprises RFC 5646 and RFC 4647; over time, other IETF documents may succeed these as the best current practice.

A ‘language tag’, per BCP 47, is assembled from a sequence of components or *subtags* separated by the hyphen character (-, U+002D). The tag is made of the following subtags, in the following order. Every subtag except the first is optional. If present, each occurs only once, except the fourth and fifth components (variant and extension), which are repeatable.

language

The IANA-registered code for the language. This is almost always the same as the ISO 639 2-letter language code if there is one. The list of available registered language subtags can be found at <https://www.iana.org/assignments/language-subtag-registry>. It is recommended that this code be written in lower case.

script

The ISO 15924 code for the script. These codes consist of 4 letters, and it is recommended they be written with an initial capital, the other three letters in lower case. The canonical list of codes is maintained by the Unicode Consortium, and is available at <https://unicode.org/iso15924/iso15924-codes.html>. The IETF recommends this code be omitted unless it is necessary to make a distinction you need.

region

Either an ISO 3166 country code or a UN M.49 region code that is registered with IANA (not all such codes are registered, e.g. UN codes for economic groupings or codes for countries for which there is already an ISO 3166 2-letter code are not registered). The former consist of 2 letters, and it is recommended they be written in upper case; the list of codes can be searched or browsed at <https://www.iso.org/obp/ui/#search/code/>. The latter consist of 3 digits; the list of codes can be found at <http://unstats.un.org/unsd/methods/m49/m49.htm>.

variant

An IANA-registered variation. These codes 'are used to indicate additional, well-recognized variations that define a language or its dialects that are not covered by other available subtags'.

extension

An extension has the format of a single letter followed by a hyphen followed by additional subtags. There are currently only two extensions in use. Extension T

indicates that the content was transformed. For example *en-t-it* could be used for content in English that was translated from Italian. Extension T is described in the informational [RFC 6497](#). Extension U can be used to embed a variety of locale attributes. It is described in the informational [RFC 6067](#).

private use

An extension that uses the initial subtag of the single letter x (i.e., starts with x-) has no meaning except as negotiated among the parties involved. These should be used with great care, since they interfere with the interoperability that use of RFC 4646 is intended to promote. In order for a document that makes use of these subtags to be TEI-conformant, a corresponding <language> element must be present in the TEI header.

There are two exceptions to the above format. First, there are language tags in the [IANA registry](#) that do not match the above syntax, but are present because they have been ‘grandfathered’ from previous specifications.

Second, an entire language tag can consist of only a private use subtag. These tags start with x-, and do not need to follow any further rules established by the IETF and endorsed by these Guidelines. Like all language tags that make use of private use subtags, the language in question must be documented in a corresponding <language> element in the TEI header.

Examples include

sn

Shona

zh-TW

Taiwanese

zh-Hant-HK

Chinese written in traditional script as used in Hong Kong

en-SL

English as spoken in Sierra Leone

pl

Polish

es-MX

Spanish as spoken in Mexico

es-419

Spanish as spoken in Latin America

The W3C Internationalization Activity has published a useful introduction to BCP 47, [Language tags in HTML and XML](#).

teidata.name

teidata.name defines the range of attribute values expressed as an XML Name.

Module

tei

Used by

Content model

```
<content>
  <dataRef name="Name"/>
</content>
```

Declaration

Note

tei_teidata.name = xsd:Name
Attributes using this datatype must contain a single word which follows the rules defining a legal XML name (see <https://www.w3.org/TR/REC-xml/#dt-name>): for example they cannot include whitespace or begin with digits.

teidata.numeric

teidata.numeric defines the range of attribute values used for numeric values.

Module

tei

Used by

Content model

```

<content>
  <alternate>
    <dataRef name="double"/>
    <dataRef name="token"
      restriction="(\-?[\d]+\^-?[\d]+)"/>
    <dataRef name="decimal"/>
  </alternate>
</content>

```

Declaration

```

tei_teidata.numeric =
  xsd:double | token { pattern = "(\\-?[\\d]+\\^-?[\\d]+)" } | xsd:decimal

```

Note

Any numeric value, represented as a decimal number, in floating point format, or as a ratio.

To represent a floating point number, expressed in scientific notation, 'E notation', a variant of 'exponential notation', may be used. In this format, the value is expressed as two numbers separated by the letter E. The first number, the significand (sometimes called the mantissa) is given in decimal format, while the second is an integer. The value is obtained by multiplying the mantissa by 10 the number of times indicated by the integer. Thus the value represented in decimal notation as 1000.0 might be represented in scientific notation as 10E3.

A value expressed as a ratio is represented by two integer values separated by a solidus (/) character. Thus, the value represented in decimal notation as 0.5 might be represented as a ratio by the string 1/2.

teidata.outputMeasurement

teidata.outputMeasurement defines a range of values for use in specifying the size of an object that is intended for display.

Module

tei

Used by

Content model

```

<content>

```

```

<dataRef name="token"
  restriction="[\-+]?d+(\.\d+)?(%|cm|
mm|in|pt|pc|px|em|ex|ch|rem|vw|vh|
vmin|vmax)"/>
</content>

```

Declaration

```

tei_teidata.outputMeasurement =
  token
  {
    pattern = "[\-+]?d+(\.\d+)?(%|cm|
mm|in|pt|pc|px|em|ex|ch|rem|vw|vh|
vmin|vmax)"
  }

```

Example

```

<figure>
  <head>The TEI Logo</head>
  <figDesc>Stylized yellow angle brack
ets with the letters <mentioned>TEI</
mentioned> in
  between and <mentioned>text enco
ding initiative</mentioned> underneat
h, all on a white
  background.</figDesc>
  <graphic height="600px"
  url="http://www.tei-c.org/logos/TEI-
600.jpg" width="600px"/>
</figure>

```

Note

These values map directly onto the values used by XSL-FO and CSS. For definitions of the units see those specifications; at the time of this writing the most complete list is in the [CSS3 working draft](#).

teidata.pattern

teidata.pattern defines attribute values which are expressed as a regular expression.

Module

tei

Used by

Content model

```

<content>
  <dataRef name="token"/>
</content>

```

Declaration

```

tei_teidata.pattern = token

```

Note

[Wikipedia](#)

This TEI datatype is mapped to the XSD token datatype, and may therefore contain any string of characters. However, it is recommended that the value used conform to the particular flavour of regular expression syntax supported by XSD Schema.

teidata.pointer

teidata.pointer defines the range of attribute values used to provide a single URI, absolute or relative, pointing to some other resource, either within the current document or elsewhere.

Module

tei

Used by

Element:

Content model

```
<content>
  <dataRef name="anyURI" restriction
    ="\S+"/>
</content>
```

Declaration

```
tei_teidata.pointer = xsd:anyURI { pattern = "\S+" }
```

Note

The range of syntactically valid values is defined by [RFC 3986](#) *Uniform Resource Identifier (URI): Generic Syntax*. Note that the values themselves are encoded using [RFC 3987](#) *Internationalized Resource Identifiers (IRIs) mapping to URIs*. For example, <https://secure.wikimedia.org/wikipedia/en/wiki/%> is encoded as <https://secure.wikimedia.org/wikipedia/en/wiki/%25> while <http://-موقع.وزارة-> is encoded as <http://xn--4gbrim.xn----rmckbbajlc6dj7bxne2c.xn--wgbh1c/>

teidata.probCert

teidata.probCert defines a range of attribute values which can be expressed either as a numeric probability or as a coded certainty value.

Module

tei

Used by

Content model

```

<content>
  <alternate>
    <dataRef key="teidata.probability"/>
    <dataRef key="teidata.certainty"/>
  </alternate>
</content>

```

Declaration

```

tei_teidata.probCert = teidata.probabili
ty | teidata.certainty

```

teidata.probability

teidata.probability defines the range of attribute values expressing a probability.

Module

tei

Used by

teidata.probCert

Content model

```

<content>
  <dataRef name="double">
    <dataFacet name="minInclusive" val
ue="0"/>
    <dataFacet name="maxInclusive" val
ue="1"/>
  </dataRef>
</content>

```

Declaration

Note

```

tei_teidata.probability = xsd:double
Probability is expressed as a real
number between 0 and 1; 0
representing certainly false and 1
representing certainly true.

```

teidata.replacement

teidata.replacement defines attribute values which contain a replacement template.

Module

tei

Used by

Content model

```

<content>
  <textNode/>
</content>

```

Declaration

```

tei_teidata.replacement = text

```

teidata.sex

teidata.sex defines the range of attribute values used to identify the sex of an organism.

Module

tei

Used by

Element:

Content model

```
<content>
  <dataRef key="teidata.enumerated"/>
>
</content>
```

Declaration

Note

tei_teidata.sex = teidata.enumerated
Values for attributes using this datatype may be defined locally by a project, or they may refer to an external standard.

teidata.temporal.iso

teidata.temporal.iso defines the range of attribute values expressing a temporal expression such as a date, a time, or a combination of them, that conform to the international standard *Data elements and interchange formats - Information interchange - Representation of dates and times*.

Module

tei

Used by

Content model

```
<content>
  <alternate>
    <dataRef name="date"/>
    <dataRef name="gYear"/>
    <dataRef name="gMonth"/>
    <dataRef name="gDay"/>
    <dataRef name="gYearMonth"/>
    <dataRef name="gMonthDay"/>
    <dataRef name="time"/>
    <dataRef name="dateTime"/>
    <dataRef name="token"
      restriction="[0-9.,DHMPRSTWYZ/
+\\-]+"/>
  </alternate>
</content>
```

Declaration

```
tei_teidata.temporal.iso =
  xsd:date
| xsd:gYear
```



```
| xsd:gMonth
| xsd:gDay
| xsd:gYearMonth
| xsd:gMonthDay
| xsd:time
| xsd:dateTime
| token { pattern = "[0-9.,DHMPRSTWYZ/[:-]+]" }
```

Note

If it is likely that the value used is to be compared with another, then a time zone indicator should always be included, and only the `dateTime` representation should be used.

For all representations for which ISO 8601:2004 describes both a *basic* and an *extended* format, these Guidelines recommend use of the extended format.

teidata.temporal.w3c

teidata.temporal.w3c defines the range of attribute values expressing a temporal expression such as a date, a time, or a combination of them, that conform to the W3C XML Schema Part 2: Datatypes Second Edition specification.

Module

tei

Used by

Content model

```
<content>
  <alternate>
    <dataRef name="date"/>
    <dataRef name="gYear"/>
    <dataRef name="gMonth"/>
    <dataRef name="gDay"/>
    <dataRef name="gYearMonth"/>
    <dataRef name="gMonthDay"/>
    <dataRef name="time"/>
    <dataRef name="dateTime"/>
  </alternate>
</content>
```

Declaration

```
tei_teidata.temporal.w3c =
  xsd:date
  | xsd:gYear
  | xsd:gMonth
  | xsd:gDay
```

| xsd:gYearMonth
| xsd:gMonthDay
| xsd:time
| xsd:dateTime

Note

If it is likely that the value used is to be compared with another, then a time zone indicator should always be included, and only the dateTime representation should be used.

teidata.text

teidata.text defines the range of attribute values used to express some kind of identifying string as a single sequence of Unicode characters possibly including whitespace.

Module

tei

Used by

Content model

```
<content>  
  <dataRef name="string"/>  
</content>
```

Declaration

Note

tei_teidata.text = string
Attributes using this datatype must contain a single 'token' in which whitespace and other punctuation characters are permitted.

teidata.truthValue

teidata.truthValue defines the range of attribute values used to express a truth value.

Module

tei

Used by

Element:

Content model

```
<content>  
  <dataRef name="boolean"/>  
</content>
```

Declaration

Note

tei_teidata.truthValue = xsd:boolean
The possible values of this datatype are *1* or *true*, or *0* or *false*.

This datatype applies only for cases where uncertainty is inappropriate; if the attribute concerned may have a

value other than true or false, e.g. *unknown*, or *inapplicable*, it should have the extended version of this datatype: teidata.xTruthValue.

teidata.version

teidata.version defines the range of attribute values which may be used to specify a TEI or Unicode version number.

Module tei
Used by Element:
Content model

```
<content>
  <dataRef name="token"
    restriction="[\d]+(\.[\d]+){0,2}"/>
</content>
```

Declaration

```
tei teidata.version = token { pattern =
  "[\d]+(\.[\d]+){0,2}" }
```

Note

The value of this attribute follows the pattern specified by the Unicode consortium for its version number (<https://unicode.org/versions/>). A version number contains digits and fullstop characters only. The first number supplied identifies the major version number. A second and third number, for minor and sub-minor version numbers, may also be supplied.

teidata.versionNumber

teidata.versionNumber defines the range of attribute values used for version numbers.

Module tei
Used by
Content model

```
<content>
  <dataRef name="token"
    restriction="[\d]+[a-z]*[\d]*(\.[\d]+[a-
z]*[\d]*){0,3}"/>
</content>
```

Declaration

```
tei teidata.versionNumber =
  token { pattern = "[\d]+[a-z]*[\d]*(\.
```

`[\\d]+[a-z]*[\\d]*){0,3}" }`

teidata.word

teidata.word defines the range of attribute values expressed as a single word or token.

Module

tei

Used by

teidata.enumerated

Content model

```
<content>
  <dataRef name="token"
    restriction="[^\\p{C}\\p{Z}]+"/>
</content>
```

Declaration

```
tei_teidata.word = token { pattern = "[
^\\p{C}\\p{Z}]+"
```

Note

Attributes using this datatype must contain a single 'word' which contains only letters, digits, punctuation characters, or symbols: thus it cannot include whitespace.

teidata.xTruthValue

teidata.xTruthValue (extended truth value) defines the range of attribute values used to express a truth value which may be unknown.

Module

tei

Used by

Content model

```
<content>
  <alternate>
    <dataRef name="boolean"/>
    <valList>
      <valItem ident="unknown"/>
      <valItem ident="inapplicable"/>
    </valList>
  </alternate>
</content>
```

Declaration

```
tei_teidata.xTruthValue = xsd:boolean |
( "unknown" | "inapplicable" )
```

Note

In cases where where uncertainty is inappropriate, use the datatype `teidata.TruthValue`.

teidata.xpath

teidata.xpath defines attribute values which contain an XPath expression.

Module `tei`

Used by

Content model

```
<content>  
  <textNode/>  
</content>
```

Declaration

```
tei_teidata.xpath = text
```

Note

Any XPath expression using the syntax defined in [6.2.](#)

When writing programs that evaluate XPath expressions, programmers should be mindful of the possibility of malicious code injection attacks. For further information about XPath injection attacks, see the [article at OWASP](#).