

	1	2	3	4	5	6	7	8	9	10	11	12																
A																												
B	FEED DIAMETER: FEED AREA: ENTRY M/S:	 11.3 99.6 27.6	 13.2 136.1 20.2	 14.2 158.6 17.5	 16.1 204.6 13.6	 17.3 235.6 11.8	 19.5 300.0 9.26	 21.0 346.0 7.99	 22.0 380.0 7.28	 25.7 520.0 5.33	 29.0 661.0 4.19	 31.1 760.0 3.64	 32.5 828.0 3.34															
C	PASS: WIDTH ON FACE: HEIGHT: PARTING: AREA: REDUCTION %:	DV_9.0RM 16.72 6.80 1.00 78.50 21.1	DV_9.5RM 15.22 8.02 1.00 84.88 14.7	DV_10.0RM 19.14 7.32 1.20 99.75 26.7	DV_10.5RM 19.19 8.14 1.20 107.85 20.7	DV_11.0RM 19.68 8.56 1.20 120.00 24.3	DV_11.5RM 18.27 9.64 1.20 126.85 20.0	DV_12.0RM 18.91 10.42 1.20 136.14 14.2	DV_12.5RM 22.35 9.92 1.20 155.96 23.8	DV_13.0RM 23.11 10.64 1.20 166.27 18.7	DV_13.5RM 25.16 10.72 1.20 183.39 22.2	DV_14.0RM 24.16 11.72 1.20 192.51 18.3	DV_14.5RM 21.44 12.98 1.20 198.55 15.7	DV_15.0RM 28.22 11.96 1.40 230.06 23.2	DV_15.5RM 27.25 12.92 1.40 240.11 20.0	DV_16.0RM 29.31 12.94 1.40 262.06 24.3	DV_17.0RM 27.27 14.81 1.75 283.16 18.2	DV_18.0RM 27.46 16.10 1.40 313.11 17.6	DV_19.0RM 32.66 15.92 1.40 371.45 28.6	DV_20.0RM 33.26 17.20 2.00 404.02 22.3	DV_21.0RM 34.51 18.70 2.00 435.41 16.3	DV_22.0RM 37.96 18.86 1.40 498.31 24.6	DV_23.0RM 39.13 20.28 1.40 534.00 19.2	DV_24.0RM 39.25 21.12 2.10 586.24 22.9	DV_25.0RM 40.56 22.16 1.40 633.27 23.5	DV_26.0RM 41.49 23.50 1.40 671.90 18.9	DV_27.0RM 42.46 25.00 1.40 709.56 14.3	
D	PASS: WIDTH ON FACE: HEIGHT: PARTING: AREA: REDUCTION %:	9.0 9.61 9.12 1.00 65.33 16.8	9.5 10.15 9.64 1.00 73.00 14.0	10.0 10.67 10.14 1.20 80.75 19.2	10.5 11.20 10.64 1.20 88.91 17.6	11.0 11.74 11.16 1.20 97.82 18.4	11.5 12.28 11.66 1.20 106.84 15.8	12.0 12.80 12.16 1.20 116.13 14.6	12.5 13.34 12.68 1.20 126.28 19.0	13.0 13.88 13.18 1.20 136.43 18.0	13.5 14.39 13.68 1.20 146.98 19.8	14.0 14.95 14.20 1.20 158.37 17.8	14.5 15.46 14.70 1.20 169.72 14.4	15.0 15.90 15.22 1.40 181.94 21.0	15.5 16.53 15.72 1.40 194.09 19.2	16.0 17.07 16.22 1.40 206.63 21.2	17.0 18.13 17.24 1.38 233.43 17.6	18.0 19.23 18.26 1.40 261.87 16.3	19.0 20.31 19.26 1.40 291.34 21.6	20.0 21.41 20.28 1.40 323.02 20.1	21.0 22.51 21.28 1.38 355.66 18.3	22.0 23.58 22.30 1.40 390.57 21.6	23.0 24.68 23.32 1.40 427.12 20.0	24.0 25.78 24.34 1.40 465.30 20.6	25.0 26.86 25.34 1.40 504.32 20.4	26.0 27.95 26.36 1.40 545.73 18.7	27.0 27.96 27.38 1.40 588.79 17.0	
E	COLD SIZE (MM)	9.00	9.50	10.0	10.5	11.0	11.5	12.0	12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	17.0	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0	27.0	
F	PASS: WIDTH ON FACE: HEIGHT: PARTING: AREA: REDUCTION %:																											
G	PASS: WIDTH ON FACE: HEIGHT: PARTING: AREA: REDUCTION %:																											
H	FINISHED SIZE:	9.00	9.50	10.0	10.5	11.0	11.5	12.0	12.5	13.0	13.5	14.0	14.5	15.0	15.5	16.0	17.0	18.0	19.0	20.0	21.0	22.0	23.0	24.0	25.0	26.0	27.0	
I	FINISHING M/S: MPH @ 100% EFF. (PER STRAND)	42.4 75.0	37.9 75.0	34.3 75.0	31.1 75.0	28.3 75.0	25.9 75.0	23.8 75.0	21.9 75.0	20.3 75.0	18.8 75.0	17.5 75.0	16.3 75.0	15.2 75.0	14.3 75.0	1												