

# Docker Storage

Shreyas Dhareshwar

Micro Focus

13<sup>th</sup> October 2018


# Agenda

- *Brush-up on Docker basics*
- *Linux Volumes*
- *AUFS and Default Docker File System*
- *Types of Docker mount*
  - *Volumes*
  - *Bind mounts*
  - *Tempfs*
- *Hands-on*

# Brush-up on Docker basics

- `docker run hello-world`, `docker pull` and `docker images`
- `docker run ubuntu bash`
- `docker run -idt ubuntu bash` , install `vi` and `docker commit`
- `docker exec -it «container_id»`
- `docker run --name web -d -p 3000:80 nginx`
- `docker run --name web1 -d -p 3100:80 --mount type=volume,source=nginx-vol,destination=/usr/share/nginx/html nginx`
- `docker run --name web2 -d -p 3200:80 -v /root/Public:/usr/share/nginx/html nginx`
- `docker rm -f $(docker ps -qa)`

# Linux Volumes





# Storage Drivers (AUFS, overlay, etc)




1. Create a container: `docker run --name web -d -p 3000:80 nginx`
2. Connect to container and explore file system (`/usr/share/nginx/html`)
3. Check physical file system on host (`/var/lib/docker/`)
4. Create file on container
5. Find the file on the host
6. Check volume diff of the container
7. Kill and remove the container

What happens to the container's file system?

# AUFS





# Default Docker file system




1. “Writable container layer”
2. No static path from outside the container
3. No container, no data
4. Tightly coupled with host machine
5. Union FS - slower performance

# Types of Docker mount







# Volumes



- Created and managed by Docker
  - Explicitly (`docker volume create`)
  - Implicitly (during container creation)
- Can be Named or Anonymous
- Supports volume drivers
- Cleanup possible (`docker volume prune`)




# Volumes – Use cases




- Persistency across container lifecycle
- Sharing data across containers (say across 2 nginx's)
- Decoupled host-container file system architecture
- Storing data outside the host (central storage or cloud)
- Backup and restore


# Bind mounts



- Created by docker if needed
- Maintained by host
- Can have security implications
- Performant
- Needs specific dir structure on host




# Bind mounts – Use cases




- Sharing config from host
- DevOps build lifecycle – *target* folder into container
- Persistency across container lifecycle
- Sharing data across containers (say across 2 nginx's)


# Tempfs



- Only in memory!
- Great for storing sensitive data
- Extremely fast
- No cleanup needed




# Tempfs – Use cases



- I/O sensitive projects
- Standalone containers with need to store runtime info

# Reference material



- <https://docs.docker.com/storage/>

Thank You.