

#### M.S. Ramaiah Institute of Technology (Autonomous Institute, Affiliated to VTU) Department of Computer Science and Engineering

Course Name: Operating Systems: CS51

Credits: 3:1:0

Term: September – December 2020

Faculty: Chandkrika Prasad Vandana S Sardar



### Process Concept

The contents in this presentation are selected from Operating Systems Concepts – 9<sup>th</sup> Edition, Silberschatz, Galvin and Gagne @2013



### Operations on Processes

System must provide mechanisms for:

- Process creation
- Process termination
- And so on as detailed next



#### **Process Creation**

- Parent process create children processes, which, in turn create other processes, forming a tree of processes
- Generally, process identified and managed via a process identifier (pid)
- Resource sharing options
  - Parent and children share all resources
  - Children share subset of parent's resources
  - Parent and child share no resources
- Execution options
  - Parent and children execute concurrently
  - Parent waits until children terminate



System call fork() is used to create processes.

The purpose of fork() is to create a new process, which becomes the child process of the caller.

After a new child process is created, both processes will execute the next instruction following the fork() system call.

Therefore, we have to distinguish the parent from the child. This can be done by testing the returned value of fork():

If fork() returns a negative value, the creation of a child process was unsuccessful.

fork() returns a zero to the newly created child process.

fork() returns a positive value, the process ID of the child process, to the parent. The returned process ID is of type pid\_t defined in sys/types.h



```
#include <stdio.h>
#include <stdlib.h>
#include <unistd.h>
  int main(int argc, char *argv[]) {
     printf("hello world (pid:%d) \n", (int) getpid());
    int rc = fork();
    if (rc < 0) {
     // fork failed
      fprintf(stderr, "fork failed\n");
   exit(1);
   } else if (rc == 0) {
    // child (new process)
    printf("hello, I am child (pid:%d)\n", (int) getpid
    } else {
      // parent goes down this path (main)
      printf("hello, I am parent of %d (pid:%d) \n",
17
              rc, (int) getpid());
     return 0;
200
21
```



```
prompt> ./p1
hello world (pid:29146)
hello, I am parent of 29147 (pid:29146)
hello, I am child (pid:29147)
prompt>
```




```
#include <stdio.h>
#include <stdlib.h>
3 #include <unistd.h>
4 #include <sys/wait.h>
5
6 int main(int argc, char *argv[]) {
    printf("hello world (pid:%d)\n", (int) getpid());
   int rc = fork();
    if (rc < 0) { // fork failed; exit
      fprintf(stderr, "fork failed\n");
    exit(1);
   } else if (rc == 0) { // child (new process)
      printf("hello, I am child (pid:%d)\n", (int) getpid());
13
     } else { // parent goes down this path (main)
      int rc_wait = wait(NULL);
      printf("hello, I am parent of %d (rc_wait:%d) (pid:%d) \n",
              rc, rc_wait, (int) getpid());
17
18
     return 0;
20
```




```
prompt> ./p2
hello world (pid:29266)
hello, I am child (pid:29267)
hello, I am parent of 29267 (rc_wait:29267) (pid:29266)
prompt>
```












```
Parent
                                          Child
                                              pid = 0
                                 main()
main()
           pid = 3456
                                   pid=fork();
 pid=fork();
                                    if (pid == 0)
   if (pid == 0)
                                       ChildProcess();
      ChildProcess();
   else
                                    else
                                       ParentProcess();
      ParentProcess();
                                 void ChildProcess()
      ChildProcess()
void
   . . . . .
                                 void ParentProcess()
void ParentProcess()
   . . . . .
```








```
Parent
                                             Child
  main()
                                    main()
             pid = 3456
                                                  pid = 0
     pid=fork();
                                       pid=fork();
     if (pid == 0)
                                        if (pid == 0)
        ChildProcess();
                                           ChildProcess();
     else
                                       else
        ParentProcess();
                                           ParentProcess();
  void ChildProcess()
                                   void ChildProcess()
                                        . . . . .
     . . . . .
void ParentProcess()
                                    void ParentProcess()
     . . . . .
                                        . . . . .
```



#### Process Creation (Cont.)

- Address space
  - Child duplicate of parent
  - Child has a program loaded into it
- UNIX examples
  - fork () system call creates new process
  - exec() system call used after a fork() to replace the process' memory space with a new program





#### C Program Forking Separate Process

```
#include <sys/types.h>
#include <stdio.h>
#include <unistd.h>
int main()
pid_t pid;
   /* fork a child process */
   pid = fork();
   if (pid < 0) { /* error occurred */
     fprintf(stderr, "Fork Failed");
     return 1;
   else if (pid == 0) { /* child process */
      execlp("/bin/ls", "ls", NULL);
   else { /* parent process */
      /* parent will wait for the child to complete */
      wait(NULL);
     printf("Child Complete");
   return 0;
```



# Output??

```
#include <stdio.h>
#include <sys/types.h>
#include <unistd.h>
int main()
  // make two process which run same
  // program after this instruction
  fork();
  printf("Hello world!\n");
  return 0;
```

Hello world! Hello world!



# Output??

```
#include <stdio.h>
#include <sys/types.h>
int main()
  fork();
  fork();
  fork();
  printf("hello\n");
  return 0;
```

hello
hello
hello
hello
hello
hello
hello
hello



## Explanation of output



## Explanation of output

The main process: P0

Processes created by the 1st fork: P1

Processes created by the 2nd fork: P2, P3

Processes created by the 3rd fork: P4, P5, P6, P7

```
P0
/ | \
P1 P4 P2
/ \
P3 P6 P5
/
P7
```



### Output??

```
include <stdio.h>
#include <sys/types.h>
#include <unistd.h>
void forkexample()
if (fork() == 0) // child process because return value zero
    printf("Hello from Child!\n");
   // parent process because return value non-zero.
  else
    printf("Hello from Parent!\n");
int main()
  forkexample();
  return 0;
```



### Output??

```
#include <stdio.h>
#include <sys/types.h>
#include <unistd.h>
void forkexample()
  int x = 1;
  if (fork() == 0)
     printf("Child has x = %d\n", ++x);
  else
     printf("Parent has x = %d\n", --x);
int main()
  forkexample();
  return 0;
```

```
Parent has x = 0

Child has x = 2

(or)

Child has x = 2

Parent has x = 0
```



#### **Process Termination**

- Process executes last statement and then asks the operating system to delete it using the exit() system call.
  - Returns status data from child to parent (via wait())
  - Process's resources are deallocated by operating system
- Parent may terminate the execution of children processes using the **abort()** system call. Some reasons for doing so:
  - Child has exceeded allocated resources
  - Task assigned to child is no longer required
  - The parent is exiting and the operating systems does not allow a child to continue if its parent terminates



#### **Process Termination**

- Some operating systems do not allow child to exists if its parent has terminated. If a process terminates, then all its children must also be terminated.
  - cascading termination. All children, grandchildren, etc. are terminated.
  - The termination is initiated by the operating system.
- The parent process may wait for termination of a child process by using the wait() system call. The call returns status information and the pid of the terminated process


```
pid = wait(&status);
```

- If no parent waiting (did not invoke wait()) process is a zombie
- If parent terminated without invoking wait, process is an orphan



#### Interprocess Communication

- Processes within a system may be *independent* or *cooperating*
- Cooperating process can affect or be affected by other processes, including sharing data
- Reasons for cooperating processes:
  - Information sharing
  - Computation speedup
  - Modularity
  - Convenience
- Cooperating processes need interprocess communication (IPC)
- Two models of IPC
  - Shared memory
  - Message passing





#### Cooperating Processes

- *Independent* process cannot affect or be affected by the execution of another process
- *Cooperating* process can affect or be affected by the execution of another process
- Advantages of process cooperation
  - Information sharing
  - Computation speed-up
  - Modularity
  - Convenience



#### Producer-Consumer Problem

Paradigm for cooperating processes, *producer* process produces information that is consumed by a *consumer* process

- unbounded-buffer places no practical limit on the size of the buffer
- bounded-buffer assumes that there is a fixed buffer size



#### Bounded-Buffer — Shared-Memory Solution

Solution is correct, but can only use BUFFER\_SIZE-1 elements



#### Bounded-Buffer — Producer

#### Bounded Buffer – Consumer



#### Interprocess Communication — Shared Memory

- An area of memory shared among the processes that wish to communicate
- The communication is under the control of the users processes not the operating system.
- Major issues is to provide mechanism that will allow the user processes to synchronize their actions when they access shared memory.
- Synchronization is discussed in great details in Chapter 5.



#### Interprocess Communication – Message Passing

- Mechanism for processes to communicate and to synchronize their actions
- Message system processes communicate with each other without resorting to shared variables
- IPC facility provides two operations:
  - **send**(*message*)
  - receive(message)
- The *message* size is either fixed or variable



#### Message Passing (Cont.)

- If processes P and Q wish to communicate, they need to:
  - Establish a *communication link* between them
  - Exchange messages via send/receive
- Implementation issues:
  - How are links established?
  - Can a link be associated with more than two processes?
  - How many links can there be between every pair of communicating processes?
  - What is the capacity of a link?
  - Is the size of a message that the link can accommodate fixed or variable?
  - Is a link unidirectional or bi-directional?



#### Message Passing (Cont.)

- Implementation of communication link
  - Physical:
    - Shared memory
    - Hardware bus
    - Network
  - Logical:
    - Direct or indirect
    - Synchronous or asynchronous
    - Automatic or explicit buffering



#### **Direct Communication**

- Processes must name each other explicitly:
  - send (P, message) send a message to process P
  - receive(Q, message) receive a message from process Q
- Properties of communication link
  - Links are established automatically
  - A link is associated with exactly one pair of communicating processes
  - Between each pair there exists exactly one link
  - The link may be unidirectional, but is usually bi-directional



### Indirect Communication

- Messages are directed and received from mailboxes (also referred to as ports)
  - Each mailbox has a unique id
  - Processes can communicate only if they share a mailbox
- Properties of communication link
  - Link established only if processes share a common mailbox
  - A link may be associated with many processes
  - Each pair of processes may share several communication links
  - Link may be unidirectional or bi-directional



### Indirect Communication

- Operations
  - create a new mailbox (port)
  - send and receive messages through mailbox
  - destroy a mailbox
- Primitives are defined as:
- send(A, message) send a message to mailbox A
- receive(A, message) receive a message from mailbox A



### Indirect Communication

- Mailbox sharing
  - $P_1$ ,  $P_2$ , and  $P_3$  share mailbox A
  - $P_1$ , sends;  $P_2$  and  $P_3$  receive
  - Who gets the message?
- Solutions
  - Allow a link to be associated with at most two processes
  - Allow only one process at a time to execute a receive operation
  - Allow the system to select arbitrarily the receiver. Sender is notified who the receiver was.



## Synchronization

Message passing may be either blocking or non-blocking

### **Blocking** is considered **synchronous**

- Blocking send -- the sender is blocked until the message is received
- Blocking receive -- the receiver is blocked until a message is available

#### Non-blocking is considered asynchronous

- Non-blocking send -- the sender sends the message and continue
- Non-blocking receive -- the receiver receives:
  - ? A valid message, or
  - Null message

### nDifferent combinations possible

If both send and receive are blocking, we have a rendezvous



## Synchronization (Cont.)

#### nProducer-consumer becomes trivial

```
message next_produced;
while (true) {
    /* produce an item in next produced */
send(next_produced);
}
message next_consumed;
while (true) {
    receive(next_consumed);
    /* consume the item in next consumed */
}
```



# Buffering

- Queue of messages attached to the link.
- Implemented in one of three ways
  - Zero capacity no messages are queued on a link.
     Sender must wait for receiver (rendezvous)
  - 2. Bounded capacity finite length of *n* messages Sender must wait if link full
  - 3. Unbounded capacity infinite length Sender never waits



# Process Synchronization

The contents in this presentation are selected from Operating Systems Concepts – 9<sup>th</sup> Edition, Silberschatz, Galvin and Gagne @2013



## Background

- Processes can execute concurrently
  - May be interrupted at any time, partially completing execution
- Concurrent access to shared data may result in data inconsistency
- Maintaining data consistency requires mechanisms to ensure the orderly execution of cooperating processes
- Illustration of the problem:

Suppose that we wanted to provide a solution to the consumer-producer problem that fills **all** the buffers. We can do so by having an integer **counter** that keeps track of the number of full buffers. Initially, **counter** is set to 0. It is incremented by the producer after it produces a new buffer and is decremented by the consumer after it consumes a buffer.



### Producer



### Consumer



### Race Condition

```
counter++ could be implemented as
      register1 = counter
      register1 = register1 + 1
      counter = register1
counter-- could be implemented as
      register2 = counter
      register2 = register2 - 1
      counter = register2
Consider this execution interleaving with "count = 5" initially:
  S0: producer execute register1 = counter
                                                      \{register1 = 5\}
  S1: producer execute register1 = register1 + 1
                                                       \{register1 = 6\}
  S2: consumer execute register2 = counter
                                                      \{register2 = 5\}
  S3: consumer execute register2 = register2 - 1
                                                      \{register2 = 4\}
  S4: producer execute counter = register1
                                                       {counter = 6 }
  S5: consumer execute counter = register2
                                                      \{counter = 4\}
```



### Critical Section Problem

Consider system of n processes  $\{p_0, p_1, ..., p_{n-1}\}$ 

Each process has critical section segment of code

- Process may be changing common variables, updating table, writing file, etc
- When one process in critical section, no other may be in its critical section

*Critical section problem* is to design protocol to solve this

Each process must ask permission to enter critical section in **entry section**, may follow critical section with **exit section**, then **remainder section** 



## Critical Section

General structure of process  $P_i$ 

```
do {
     entry section
          critical section
          exit section
          remainder section
} while (true);
```



# Algorithm for Process P

```
do {
    while (turn == j);
        critical section
    turn = j;
        remainder section
} while (true);
```



### Solution to Critical-Section Problem

- 1. Mutual Exclusion If process  $P_i$  is executing in its critical section, then no other processes can be executing in their critical sections
- 2. **Progress** If no process is executing in its critical section and there exist some processes that wish to enter their critical section, then the selection of the processes that will enter the critical section next cannot be postponed indefinitely
- 3. **Bounded Waiting** A bound must exist on the number of times that other processes are allowed to enter their critical sections after a process has made a request to enter its critical section and before that request is granted
  - Assume that each process executes at a nonzero speed
  - No assumption concerning relative speed of the n processes



## Critical-Section Handling in OS

Two approaches depending on if kernel is preemptive or non-preemptive

- **Preemptive** allows preemption of process when running in kernel mode
- Non-preemptive runs until exits kernel mode, blocks, or voluntarily yields CPU
  - Essentially free of race conditions in kernel mode



## Peterson's Solution

Good algorithmic description of solving the problem

Two process solution

Assume that the **load** and **store** machine-language instructions are atomic; that is, cannot be interrupted

The two processes share two variables:

- int turn;
- Boolean flag[2]

The variable turn indicates whose turn it is to enter the critical section

The flag array is used to indicate if a process is ready to enter the critical section. flag[i] = true implies that process  $P_i$  is ready!



# Algorithm for Process Pi

```
do {
    flag[i] = true;
    turn = j;
    while (flag[j] && turn = = j);
        critical section

flag[i] = false;
    remainder section
} while (true);
```



# Peterson's Solution (Cont.)

Provable that the three CS requirement are met:

- 1. Mutual exclusion is preserved
  - P<sub>i</sub> enters CS only if:

```
either flag[j] = false or turn = i
```

- 2. Progress requirement is satisfied
- 3. Bounded-waiting requirement is met



### Synchronization Hardware

Many systems provide hardware support for implementing the critical section code.

All solutions below based on idea of locking

Protecting critical regions via locks

Uniprocessors – could disable interrupts

- Currently running code would execute without preemption
- Generally too inefficient on multiprocessor systems
  - Operating systems using this not broadly scalable

Modern machines provide special atomic hardware instructions

- **Atomic** = non-interruptible
- Either test memory word and set value
- Or swap contents of two memory words



### Solution to Critical-section Problem Using Locks



## test\_and\_set Instruction

#### Definition:

```
boolean test_and_set (boolean *target)
{
    boolean rv = *target;
    *target = TRUE;
    return rv:
}
```

- 1.Executed atomically
- 2. Returns the original value of passed parameter
- 3.Set the new value of passed parameter to "TRUE".



## Solution using test\_and\_set()

- Shared Boolean variable lock, initialized to FALSE
- **?** Solution:



## compare\_and\_swap Instruction

#### Definition:

```
int compare _and_swap(int *value, int expected, int new_value) {
   int temp = *value;

   if (*value == expected)
        *value = new_value;

   return temp;
}
```

- 1.Executed atomically
- 2. Returns the original value of passed parameter "value"
- 3.Set the variable "value" the value of the passed parameter "new\_value" but only if "value" =="expected". That is, the swap takes place only under this condition.



### Solution using compare\_and\_swap

```
Shared integer "lock" initialized to 0;
Solution:
       do {
         while (compare_and_swap(&lock, 0, 1) != 0)
            ; /* do nothing */
          /* critical section */
      lock = 0;
          /* remainder section */
     } while (true);
```



### Bounded-waiting Mutual Exclusion with test\_and\_set

```
do {
   waiting[i] = true;
  key = true;
while (waiting[i] && key)
     key = test and set(&lock);
  waiting[i] = false;
  /* critical section */
   j = (i + 1) \% n;
   while ((j != i) && !waiting[j])
      j = (j + 1) % n;
   if (j == i)
      lock = false;
   else
      waiting[j] = false;
   /* remainder section */
} while (true);
```



### Mutex Locks

- Previous solutions are complicated and generally inaccessible to application programmers
- OS designers build software tools to solve critical section problem
- Simplest is mutex lock
- Protect a critical section by first acquire() a lock then release() the lock
  - Boolean variable indicating if lock is available or not
- Calls to acquire() and release() must be atomic
  - Usually implemented via hardware atomic instructions
- But this solution requires busy waiting
  - This lock therefore called a spinlock



# acquire() and release()

```
acquire() {
     while (!available)
         ; /* busy wait */
     available = false;
  release() {
     available = true;
  do {
   acquire lock
     critical section
   release lock
    remainder section
} while (true);
```



## Semaphore

Synchronization tool that provides more sophisticated ways (than Mutex locks) for process to synchronize their activities.

Semaphore **S** – integer variable

Can only be accessed via two indivisible (atomic) operations

- o wait() and signal()
  - Originally called P() and V()



# Semaphore

```
Definition of the wait() operation
  wait(S) {
     while (S <= 0)
        ; // busy wait
     S--;
  }

Definition of the signal() operation
  signal(S) {
     S++;
}</pre>
```



## Semaphore Usage

**Counting semaphore** – integer value can range over an unrestricted domain

Binary semaphore – integer value can range only between 0 and 1

Same as a mutex lock

Can solve various synchronization problems

Consider  $P_1$  and  $P_2$  that require  $S_1$  to happen before  $S_2$ 

Create a semaphore "synch" initialized to 0

```
P1:
    S<sub>1</sub>;
    signal(synch);
P2:
    wait(synch);
    S<sub>2</sub>;
```

Can implement a counting semaphore **S** as a binary semaphore



## Semaphore Implementation

Must guarantee that no two processes can execute the **wait()** and **signal()** on the same semaphore at the same time

Thus, the implementation becomes the critical section problem where the wait and signal code are placed in the critical section

- Could now have busy waiting in critical section implementation
  - But implementation code is short
  - Little busy waiting if critical section rarely occupied

Note that applications may spend lots of time in critical sections and therefore this is not a good solution



### Semaphore Implementation with no Busy waiting

With each semaphore there is an associated waiting queue

Each entry in a waiting queue has two data items:

- value (of type integer)
- pointer to next record in the list

#### Two operations:

- block place the process invoking the operation on the appropriate waiting queue
- wakeup remove one of processes in the waiting queue and place it in the ready queue

```
typedef struct{
  int value;
  struct process *list;
} semaphore;
```



### Implementation with no Busy waiting (Cont.)

```
wait(semaphore *S) {
   S->value--;
   if (S->value < 0) {
      add this process to S->list;
     block();
signal(semaphore *S) {
   S->value++;
   if (S->value <= 0) {
      remove a process P from S->list;
      wakeup(P);
```



### Deadlock and Starvation

**Deadlock** – two or more processes are waiting indefinitely for an event that can be caused by only one of the waiting processes

Let S and Q be two semaphores initialized to 1

```
P_0 P_1 wait(S); wait(Q); wait(Q); ... signal(S); signal(Q); signal(S);
```

#### **Starvation – indefinite blocking**

• A process may never be removed from the semaphore queue in which it is suspended

**Priority Inversion** – Scheduling problem when lower-priority process holds a lock needed by higher-priority process

Solved via priority-inheritance protocol



### Classical Problems of Synchronization

Classical problems used to test newly-proposed synchronization schemes

- Bounded-Buffer Problem
- Readers and Writers Problem
- Dining-Philosophers Problem



### Bounded-Buffer Problem

*n* buffers, each can hold one item

Semaphore **mutex** initialized to the value 1

Semaphore **full** initialized to the value 0

Semaphore **empty** initialized to the value n



## Bounded Buffer Problem (Cont.)

The structure of the producer process

```
do {
     /* produce an item in next_produced */
      . . .
   wait(empty);
   wait(mutex);
    /* add next produced to the buffer */
       . . .
    signal(mutex);
    signal(full);
 } while (true);
```



## Bounded Buffer Problem (Cont.)

The structure of the consumer process

```
do {
    wait(full);
    wait(mutex);
    /* remove an item from buffer to next consumed */
       . . .
    signal(mutex);
    signal(empty);
    /* consume the item in next consumed */
 } while (true);
```



### Readers-Writers Problem

A data set is shared among a number of concurrent processes

- Readers only read the data set; they do not perform any updates
- Writers can both read and write

Problem – allow multiple readers to read at the same time

Only one single writer can access the shared data at the same time

Several variations of how readers and writers are considered — all involve some form of priorities

#### **Shared Data**

- Data set
- Semaphore rw\_mutex initialized to 1
- Semaphore mutex initialized to 1
- Integer read\_count initialized to 0



## Readers-Writers Problem (Cont.)

The structure of a writer process

```
do {
    wait(rw_mutex);
    ...
    /* writing is performed */
    ...
    signal(rw_mutex);
} while (true);
```



## Readers-Writers Problem (Cont.)

```
The structure of a reader process
       do {
            wait(mutex);
            read count++;
             if (\overline{r}ead count == 1)
               wait(rw mutex);
           signal(mutex);
             /* reading is performed */
           wait(mutex);
            read count--;
if (read_count == 0)
           signal(rw mutex);
           signal(mutex);
       } while (true);
```



### Readers-Writers Problem Variations

*First* variation – no reader kept waiting unless writer has permission to use shared object

Second variation - once writer is ready, it performs the write ASAP

Both may have starvation leading to even more variations

Problem is solved on some systems by kernel providing reader-writer locks



## Dining-Philosophers Problem

Philosophers spend their lives alternating thinking and eating

Don't interact with their neighbors, occasionally try to pick up 2 chopsticks (one at a time) to eat from bowl

Need both to eat, then release both when done

In the case of 5 philosophers

- Shared data
  - Bowl of rice (data set)
  - Semaphore chopstick [5] initialized to 1





### Dining-Philosophers Problem Algorithm

```
The structure of Philosopher i:
    do {
        wait (chopstick[i] );
         wait (chopStick[ (i + 1) % 5] );
                     // eat
         signal (chopstick[i] );
         signal (chopstick[ (i + 1) % 5] );
                      // think
    } while (TRUE);
 What is the problem with this algorithm?
```



### Dining-Philosophers Problem Algorithm (Cont.)

#### Deadlock handling

- Allow at most 4 philosophers to be sitting simultaneously at the table.
- Allow a philosopher to pick up the forks only if both are available (picking must be done in a critical section.
- Use an asymmetric solution -- an odd-numbered philosopher picks up first the left chopstick and then the right chopstick. Even-numbered philosopher picks up first the right chopstick and then the left chopstick.



# Problems with Semaphores

Incorrect use of semaphore operations:

- signal (mutex) .... wait (mutex)
- wait (mutex) ... wait (mutex)
- Omitting of wait (mutex) or signal (mutex) (or both)

Deadlock and starvation are possible.