

# 基于Openstack的VNF应用


BROCADE 张泽鹏 2015年10月



### 博科 SDN 和 NFV 产品线支持一览









# 博科涉足的软件网络产品


博科产品名称	功能	简称
博科 Vyatta 虚拟路由器	软件路由、防火墙、VPN	vRouter
博科 vADC	应用交付	SteelApp
	Web 防火墙	
	服务控制器	
博科 SDN 控制器	SDN 控制器	BSC
博科移动网络分析平台	网络可视化和分析平台	NVA
博科 vEPC	软件 EPC 解决方案平台	Connectem

## VNF应用场景




## 博科虚拟路由器Vyatta





# 第三方测试显示超强的性能

L3 data plane	• 70 million packets per second with 64B		
forwarding	80Gbps bi-directional traffic with 256B to 1518B		
	> 75Gps of throughput under IMIX frame sizes and		
	IPv4/ IPv6 dual-stack		
	2 million flows		
L3 control plane	BGP scalability up to 8 million routes from a single peer		
scaling	or up to 8 peers		
L4-7 performance	ateless Firewall		
	200K sessions/sec		
	2.5 million concurrent sessions		
	tateful Firewall		
	• 50K sessions/sec		
	1 million concurrent connections		



### SteelApp 虚拟应用交付 - 提供 ADC 即服务

#### Traffic Manager



- 负载均衡 / 流量管理 / ADC
- 提供可靠性,可用性, offload,安全,脚本等更多功能...

## Web Content Optimization Module (WCO)



- 网站加速
- 减少页面加载时间,减少带宽使用

#### Web App Firewall Module (WAF)



- 应用感知的防火墙
- 保护应用, 防范威胁

#### SteelCentral Services Director



- 极具弹性和适应性的服务 控制器
- 自动实现ADC服务的部署, 授权,提供服务,计费

# 全面实现应用交付完整解决方案 - 软件/虚拟设备/云/微型实例

### Activity 监控 - 完整的 ADC 的可视化

- Activity 监控
  - Real-time
  - 历史资料
  - 地图
  - 可从 WebUI 或 SNMP 获得
- Request 日志
  - 可从 WebUI 或 Sysog 获得
- Audit 日志
  - WebUI (可下载)
- Event 日志
  - 可从 WebUI, 或Syslog, SNMP, Email等获得




1903.08.147.3 -- (2009-02012) 0.10.08.58 +- 41002) "OFF Amag-Addapsing PTTS/1.1" 200 0207 "Millip/Amag-demolsted" (Madisoth (Madisoth) Obstantial) "Millip On 06.8 10.7" (millip 10.10) 10.7 (millip 10.10) 10






# Brocade OpenStack 的生态合作伙伴




# Brocade 实现L3 Router,FWaas,VPNaas增强服务



# OpenStack 的 LBaaS


#### • 应用交付的特性:

- Virtual Server
- Virtual Server Port
- Real Server
- Real Server Port
- Port Policy
- Bind of virtual Server Port to Real Server Port
- Monitor of connection related parameters.



# Rackspace 案例





CLOUD

#### Enhanced security and networking

Cloud Servers, Cloud Networks, and the Brocade Vyatta<sup>®</sup> vRouter together enable a comprehensive all-in-one networking and security solution—giving you an easy-to-configure firewall, advanced networking, and VPN capabilities, plus increased security in the cloud.

#### Key features



**Virtual private network (VPN) gateway**—Build a VPN tunnel from your data center into the Rackspace public cloud. You can use a standards-compliant VPN device from almost any vendor at the other end of the VPN connection; or provide secure remote access for users in your company to connect to your resources in the cloud. The Brocade Vyatta vRouter supports both IPsec and OpenVPN.



**Firewall**—Secure your cloud infrastructure with a network-based firewall that can perform stateful, IPv4/v6 packet inspections to intercept and inspect network activity and help protect your critical data. The Brocade Vyatta vRouter supports zone and time-based firewalling.



**Network address translation (NAT)**—You can provision application and database servers without public network interfaces, while still allowing your servers to access the Internet for OS updates and patches using Source NAT. Or you can hide your web servers behind the Vyatta with Destination NAT. This gives you added security in your cloud infrastructure with even less exposure to the Internet.



**Router**—If you want to create application tiers on different isolated networks by leveraging the capabilities of Cloud Networks, the Brocade Vyatta vRouter enables you to easily build connectivity between these isolated networks giving you greater flexibility in building secure applications.




**Support**—With the Managed Operations service level, leave the heavy lifting to us. We configure and manage your Brocade Vyatta vRouter to meet a range of security and networking requirements.

## Rackspace IPSec VPN 应用实例




here are three main components of the Internet Protocol security (IPsec) architecture:

- •The Authentication Header (AH) protocol
- •The Encapsulating Security Payload (ESP) protocol
- •The Internet Key Exchange (IKE) protocol, formerly referred to as ISAKMP/Oakley



#### IBM & Brocade VNFaaS — Eco-system Showcase

Highlighting IBM and Brocade Integration/Joint Value



### Financial Value of Virtual Router Deployment

#### ROI & Financial modeling:


- Physical routers vs. virtual instances
- Firewall Use Case Comparison

#### Key Vyatta Advantages:


- 56% CapEx Savings
- 86% OpEx Savings
- 8x Lower Administrative Time
- 27% Space Savings

HA Pair Comparison	Physical	Virtual
<b>Acquisition Costs</b>	\$ 31,824	\$14,000
<b>Administration Costs</b>	\$ 9,094	\$ 1,272
Administration Hours	29.1	4.1
Rack Units Consumed	15	0

#### Vyatta - Per HA Pair: 5-Yr TCO




Step 1: Launch Virtual System Pattern for Premium customer. No service yet.




#### Smart Cloud Orchestrator Interface


#### Launch Virtual System Pattern for *Premium* Customer




Step 2: Use Content Pack to configure Policy and create Premium customer service chain. (FW + IPsec VPN + NAT)




# Smart Cloud Orchestrator Interface Brocade VNFaaS Content Pack configuration




Self-Service > Brocade Vyatta > Manage Brocade Vyatta VNFs



Step 3: Watch the premium customer in action using remote desktop to access the web.




Step 4: Launch Virtual System Pattern for Standard Customer. No service yet.




#### Smart Cloud Orchestrator Interface


#### Launch Virtual System Pattern for Standard Customer



Step 5: Use Content Pack to configure Policy and Standard customer service chain.(FW + ROUTE)



### Smart Cloud Orchestrator Interface Brocade VNFaaS content pack configuration



Manage Brocade Vyatta VNFs

Manage Brocade Vyatta VNFs

Deploy/Undeploy Brocade Vyatta VNFs

Deploying Standard Service For Valero

Web Server Destination IP

10.10.15.0/24


Customer Source IP

10.10.10.0/24


Submit



Step 6: Watch standard customer in action accessing their web server.




Step 7: Different forwarding graphs for different customers.




### 某云客户LBaaS案例

- Upload vTM image(s) to OpenStack Glance repository
- Bring up Services Director instance
- Set up / configure licenses:
- Upload the Services Director license, SSL certificates into Services Director
- Generate the FLA license to be used for vTM instances and upload to Services Director instance
- Generate the bandwidth license (optional) and upload to Services Director instance
- vTM Device Driver retrieves the FLA license from the Services Director
- vTM Device Driver brings up a new vTM instance as a Nova VM
- vTM Device Driver adds the vTM instance to Services Director as unmanaged instance
- vTM Device Driver configures the request on the vTM via services directory proxy API




### 如何实现: Services Director for LBaaS



### 博科提供开放的开发者用户论坛

http://community.brocade.com/t5/DevNet/ct-p/APISupport



#### 用户论坛包含:

- 博科 SDN 控制器下载
- APIs 下载
- 文档资料
- 演示视频
- 样本脚本
- 专家回答

. . . . . .

BROCADE<sup>23</sup>

# 谢谢!