

Kuratowski Calculus Engine

Unified Code Manual

Juan Pablo Silva Alvarado

February 17, 2026

Part of Modulo Synthesis / Fractal Entropic Geometrodynamics

*“The universe is strictly computable, finite, and structurally
homeostatic. The rest is just counting.”*

Contents

1	Theory	1
1.1	Axiom 1 — Causal Sets	1
1.2	Axiom 2 — Quantum Dynamics	1
1.3	The Sole Principle of Interaction	1
1.4	Hasse Diagram	2
1.5	Causal Prism — The Fundamental Particle	2
1.6	Threat Contraction — Colour Confinement	2
1.7	Spectral Dimension — Gravity	2
1.8	Causal Flux — Electromagnetism	3
1.9	Three Generations — The Kuratowski Limit	3
1.10	Physics → Code Dictionary	3
2	Architecture	4
2.1	Data Flow	4
2.2	Phase Diagram	4
2.3	Execution Paths	4
2.3.1	In-Memory	4
2.3.2	Streaming	4
2.4	Tier System	5
3	Module Reference: <code>diamond</code> — Phase 1	6
3.1	Functions	6
3.1.1	<code>sprinkle(n, rng) → (Vec<[f64;4]>, f64)</code>	6
3.1.2	<code>build_hasse_sparse(pts) → (coords, adj_head, adj_data, momentum)</code>	6
3.1.3	<code>build_hasse_direct(pts) → (coords, adj_head, adj_data, momentum)</code>	6
3.1.4	<code>stream_edges_to_file(n_total, chunk_size, path, seed) ...</code>	6
3.1.5	<code>sprinkle_chunk(n_expected, t_min, t_max, half_t, rng, start_idx)</code>	6
3.2	Key Concepts	7
4	Module Reference: <code>skyrmion</code> — Phase 2	8
4.1	Algorithm	8
4.2	Functions	8
4.2.1	<code>apply_defect(n, adj_head, adj_data, bulk_momentum) → DefectResult</code>	8
4.2.2	<code>process_streaming(n_total, chunk_size, path, seed) → SpectralResult</code>	8
4.3	DefectResult Struct	9
4.4	Signature Encoding	9
5	Module Reference: <code>spectral</code> — Phase 3	10
5.1	Functions	10
5.1.1	<code>spectral_dimension(steps, p_vals) → Vec<f64></code>	10
5.1.2	<code>run_walkers(adj_head, adj_data, starts, steps, seed) → Vec<f64></code>	10
5.1.3	<code>run_transmission_walkers(...) → (Vec<f64>, Vec<f64>)</code>	10
5.1.4	<code>compute_eigen(n, rows, cols, steps, core) → SpectralResult</code>	10
5.1.5	<code>compute_monte_carlo(n, rows, cols, steps, core, n_w, rng) → SpectralResult</code>	10
5.1.6	<code>compute_monte_carlo_csr(n, head, data, steps, core, n_w, rng) → SpectralResult</code>	10
5.1.7	<code>build_adj_list(n, rows, cols) → (Vec<u32>, Vec<u32>)</code>	10

5.2	SpectralResult Struct	11
6	Module Reference: output — Phase 4	12
6.1	Function	12
6.1.1	write_csv(path, steps, vacuum, defect)	12
6.2	CSV Column Reference	12
7	Module Reference: memory — RAM-Aware Mode Selection	13
7.1	Functions	13
7.1.1	load_config(dir) → Config	13
7.1.2	ensure_config(dir)	13
7.1.3	recommend_mode(n, cfg) → (ExecMode, u64, u64)	13
7.1.4	prompt_mode(recommended, available, estimated, cfg) → ExecMode	13
7.1.5	estimate_memory_bytes(n) → u64	13
7.1.6	max_concurrent_runs(n) → usize	13
7.1.7	available_ram_bytes() → u64	13
7.2	Types	13
8	Usage	15
8.1	Options	15
8.2	Configuration	15
8.3	Examples	15
9	Expected Results	16
9.1	Spectral Dimension	16
9.2	Generation Classification	16
9.3	Causal Flux	16
10	Dependencies	17
	See Also	18

Theory

Chapter Overview

- *The two axioms of Fractal Entropic Geometrodynamics.*
- *The Sole Principle of Interaction (microscopic law).*
- *Kuratowski's Theorem and the origin of matter, forces, and generations.*
- *The Three Geometries: Order, Matter, and Logic.*
- *How each physics concept maps to a code module and data structure.*

1.1 Axiom 1 — Causal Sets

Spacetime is not a continuous manifold but a **discrete partial order** — a directed acyclic graph (DAG) where each node is a spacetime event and each edge encodes causal influence: $A \rightarrow B$ means “ A can causally influence B .” The DAG is generated by Poisson sprinkling N points into a 4D causal diamond ($|t| + r \leq T/2$) with fundamental density $\rho \approx 1$.

Axiom 1: Causal Sets (from Vol I)

Spacetime is a locally finite partially ordered set. The order relation encodes causal structure; the counting measure (number of elements in an Alexandrov set) encodes spacetime volume. All geometry is emergent from order + number.

1.2 Axiom 2 — Quantum Dynamics

Axiom 2: Quantum Dynamics: The Non-Commutative Postulate (from Vol II)

The geometry and quantum phases of the causal set are evaluated over a **non-commutative von Neumann algebra**. Macroscopic geometry is not fundamental; it is an emergent phenomenon dictated by the quantum Fisher Information Metric (Petz metric) defined over the density states of causal histories. Causal histories do not commute: if events A and B are spacelike separated, the order in which they are evaluated affects the quantum phase.

Together, Chentsov's Theorem (classical, macroscopic) and Petz's Theorem (quantum, microscopic) establish a single information-geometric foundation for all of physics. Gravity is the coarse-grained Fisher geometry at large N ; quantum mechanics is the fine-grained Petz geometry at small N .

1.3 The Sole Principle of Interaction

Axiom 3: The Sole Principle of Interaction (Microscopic Law)

The entirety of microscopic network dynamics is governed by a single mandate: **the preservation of unitarity** (probability conservation) across discrete, non-commutative causal links:

$$\sum_{\text{paths}} P(i \rightarrow f) = 1$$

All emergent forces (gauge fields) and geometric structures (gravity) are **homeostatic mechanisms** enacted by the causal network to satisfy this unitary principle under the topological constraints of Kuratowski's Theorem.

1.4 Hasse Diagram

The **transitive reduction** of the causal DAG. If $A \rightarrow B \rightarrow C$, the direct edge $A \rightarrow C$ is redundant and is removed. The Hasse diagram retains only nearest-neighbour causal links — the skeleton of spacetime.

1.5 Causal Prism — The Fundamental Particle

CRITICAL: The transitive reduction in Phase 1 produces a *triangle-free* DAG. K_4 complete subgraphs (4 mutually connected events) **cannot exist** in such a graph — transitive reduction eliminates all triangles by definition. The correct fundamental particle is the **Causal Prism** ($K_{2,N}$ bipartite, $N \geq 3$).

A Causal Prism consists of:

- Two **poles** (origin node u , destination node v)
- $N \geq 3$ **intermediates** (common successors w_i)
- Directed edges: $u \rightarrow w_i$ and $v \rightarrow w_i$ for all $i \in \{1 \dots N\}$

These topological defects:

- Anchor probability flow and define particle-like spectral signatures.
- Cannot be “untied” without breaking the graph’s connectivity — they are topologically stable.
- Are the *maximal* bipartite structures permitted by the triangle-free constraint.

1.6 Threat Contraction — Colour Confinement

Theorem 4: Kuratowski's Theorem (The Topological UV Limit)

A finite graph G is planar if and only if it does not contain a topological minor of K_5 (the complete graph on 5 vertices) or $K_{3,3}$ (the complete bipartite graph on $3 + 3$ vertices):

$$K_5 \not\leq_T G_{UV} \quad \text{and} \quad K_{3,3} \not\leq_T G_{UV}$$

This is the absolute UV boundary of the theory.

When an external node is connected to **both poles** of a Causal Prism AND ≥ 2 intermediates, it threatens the topological stability and is **absorbed** (vertex contraction) into the higher-degree pole — a discrete analogue of colour confinement. The topology enforces that quarks cannot exist in isolation.

Key Result

The Strong Force is not a fundamental gauge field. It is a strict topological obstruction — the causal network's response to the Kuratowski UV limit — preventing forbidden topological minors in the ultraviolet.

1.7 Spectral Dimension — Gravity

The spectral dimension measures how quickly a random walker returns to its starting point after t steps:

$$d_S(t) = -2 \frac{d(\ln P)}{d(\ln t)}$$

On a smooth 4D manifold, $d_S \rightarrow 4$. On the Hasse graph:

- **Vacuum:** d_S diverges (boundary saturation of the unstructured bulk).
- **With Causal Prism matter:** d_S stabilises at a finite value — the topological knot traps probability flow.

1.8 Causal Flux — Electromagnetism

Directed walkers follow the arrow of time (cause $\rightarrow$ effect only). The transmission probability between particle generations measures electromagnetic-like interactions:

- **Attraction:** Gen1 $\rightarrow$ AntiGen1 (opposite charges).
- **Repulsion:** Gen1 $\rightarrow$ Gen1 (same charges).

1.9 Three Generations — The Kuratowski Limit

The Standard Model has three copies of matter (electron/muon/tau, up/charm/top). In FEG the answer is a strict topological obstruction:

1. UV gravity compresses $d_S \rightarrow 2$ (effectively 2D topology).
2. Kuratowski's Theorem forbids K_5 in planar graphs.
3. The transitive reduction produces a triangle-free DAG.
4. Causal Prisms ($K_{2,N}$ bipartite) are the fundamental particles.

Causal Prisms are classified by their bit-packed topological signature $[q_0, q_1, q_2, q_3]$ (quartile bulk momentum across all components: origin, destination, and intermediates). Most abundant signature = Gen1 (electron-like), second = Gen2 (muon-like), third = Gen3 (tau-like). The CPT conjugate (reversed and negated components) = AntiGen1 (positron-like). The emergent discreteness of signatures enforces exactly 3 stable generations.

1.10 The Three Geometries

The theory rests on three geometric pillars, each discovered through the simulation engine:

Key Result

The Three Geometries of Fractal Entropic Geometrodynamics:

1. **Geometry of Order** (Vol I): *Transitive Reduction $\rightarrow$ Lorentz invariance. The Hasse diagram encodes the causal structure of spacetime; counting elements in an Alexandrov set reproduces the volume element. Code: `diamond.rs` builds the Hasse DAG.*
2. **Geometry of Matter** (Vol II): *Causal Prism $K_{2,N} \rightarrow$ mass hierarchy. Topological defects in the Hasse graph carry quantized topological mass N and are classified into exactly three generations by the Kuratowski limit. Code: `skyrmion.rs` detects prisms and classifies generations.*
3. **Geometry of Logic:** *$O(N)$ scaling $\Leftrightarrow$ physical locality. Bounded Hasse degree ($D \leq 15$) implies that every topological operation—prism detection, threat contraction, spectral walk—is local, yielding **provably linear** $O(N)$ computational complexity. This is not an engineering optimisation but a computational proof that the theory encodes physical locality as an information principle. Code: `2-hop`*

candidate search in skymion.rs; single-pass streaming in diamond.rs.

Theorem 5: $O(N)$ Locality Theorem

Let $\mathcal{H}$ be the Hasse diagram of N events sprinkled into a 4D causal diamond at density $\rho \approx 1$. Then:

1. Every Hasse link has bounded proper time: $\tau_{\text{link}} \leq 8$.
2. Hence every node has bounded Hasse degree: $D \leq D_{\text{max}} \approx 15$.
3. Causal Prism detection via 2-hop traversal is $O(N \cdot D_{\text{max}}^3) = O(N)$.
4. All other phases (edge generation, spectral walkers, output) are already $O(N)$ or $O(W \cdot t)$.

The entire simulation scales linearly with the number of spacetime events.

1.11 Physics $\rightarrow$ Code Dictionary

Physics Concept	Code Module	Data Structure
Spacetime	diamond.rs	DAG of [f64; 4] points
Causal link	diamond.rs	CSR edge (adj_head, adj_data)
Particle (matter)	skymion.rs	Causal Prism ($K_{2,N}$ bipartite)
Strong force	skymion.rs	Threat contraction merge_into[i]
Charge (bulk momentum)	diamond.rs	bulk_momentum: Vec<i32>
Particle generation	skymion.rs	Bit-packed signature u32
Antimatter	skymion.rs	CPT-conjugate signature
Gravity (geometry)	spectral.rs	Undirected walkers $\rightarrow P(t) \rightarrow d_S(t)$
Electromagnetism	spectral.rs	Directed walkers $\rightarrow$ transmission prob.
Locality ($O(N)$)	skymion.rs	2-hop traversal, bounded degree $D \leq 15$

Table 1.1: Mapping between physics concepts and code implementations.

Architecture

Chapter Overview

- *The four-phase pipeline: sprinkle → hasse → defect → walkers → csv.*
- *Two execution paths: in-memory vs streaming (single-pass $O(N)$).*
- *Tier system: eigendecomposition vs Monte Carlo.*

2.1 Data Flow

```

sprinkle(N) -> [f64;4] points
|
build_hasse() -> CSR adjacency (adj_head, adj_data) + bulk_momentum
|
apply_defect() -> Causal Prisms, K5 threat absorption, generation classification
|
run_walkers() -> P(t), dS(t) for vacuum/defect/generations/flux
|
write_csv() -> results.csv

```

2.2 Phase Diagram

Phase	Module	Physics
1	diamond.rs	Vacuum generation: Poisson sprinkling + Hasse diagram
2	skymion.rs	Kuratowski contraction: Causal Prism detection + K_5 absorption
3	spectral.rs	Spectral dimension: random walk return probability
4	output.rs	CSV serialisation of ensemble-averaged observables

Table 2.1: The four simulation phases.

2.3 Execution Paths

2.3.1 In-Memory

Selected by `--inmemory` flag or auto-selected when RAM is sufficient. All data structures live in RAM. Realisations run in parallel via Rayon with a concurrency limit (4 threads, or 2 for $N > 10M$) to avoid OOM. Causal Prism detection uses 2-hop local candidate search: $O(N \cdot D^3)$ with $D \leq 15$.

2.3.2 Streaming

Selected by `--stream` flag or auto-selected when RAM is insufficient. Phase 1 uses `scan_edges_with_analysis()` to perform a **single-pass** scan: degree counting, core classification, and core-edge collection are merged into one streaming pass over the edge generator. Causal Prism detection then operates on the core-induced CSR subgraph using the same 2-hop local search as the in-memory path. RAM usage stays under ~ 1.3 GB per realisation even at $N = 100M$. With 2 concurrent realisations this uses ~ 2.6 GB.

Mode selection is automatic based on available system RAM (via `sysinfo`), configurable via `causal_set.toml`, or overridable with CLI flags.

2.4 Tier System

Tier	Condition	Algorithm	Complexity
Eigendecomp	$N \leq 3,000$	Dense $S = D^{-1/2}AD^{-1/2}$ eigendecomp	$O(N^3)$
Monte Carlo	$N > 3,000$	Lazy random walkers on CSR	$O(W \cdot t)$

Table 2.2: Spectral dimension computation tiers.

Module Reference: **diamond** — Phase 1

Vacuum Generation

- *Poisson sprinkling in a 4D causal diamond.*
- *Hasse diagram construction (transitive reduction).*
- *Two tiers: sparse A^2 reduction ($N \leq 15k$) and OCI geometric construction ($N > 15k$).*

3.1 Functions

3.1.1 `sprinkle(n, rng) → (Vec<[f64;4]>, f64)`

Rejection-samples n points inside $|t| + r \leq T/2$ with $T = (24N)^{1/4}$ giving density $\rho \approx 1$. The causal diamond is the intersection of the future light cone of $(t = -T/2)$ and the past light cone of $(t = +T/2)$.

3.1.2 `build_hasse_sparse(pts) → (coords, adj_head, adj_data, momentum)`

Full causal closure followed by sparse A^2 reduction. Edge (i, j) is a Hasse link iff $A^2[i, j] = 0$ (no 2-hop path exists). Used for $N \leq 15,000$. Parallel over source nodes via Rayon.

3.1.3 `build_hasse_direct(pts) → (coords, adj_head, adj_data, momentum)`

Direct geometric construction using the **Occupied Cell Index (OCI)** — a spatial indexing paradigm that replaces naive geometric shell enumeration (96% empty cells) with per-time-layer lists of occupied cells, queried via binary search. Features:

- Points are quantised onto an integer lattice and sorted by cell index for cache-coherent traversal (GridPoint struct).
- Per-time-layer lists of occupied cells, sorted by X coordinate.
- Binary search for the active X-band within the light cone.
- **Topological cutoffs** (Phase 1 optimisations):
 - `MAX_CAUSAL_DEPTH = 4`: proper-time cutoff. Hasse links beyond $\Delta t > 4$ are exponentially suppressed at $\rho \approx 1$ (was 10).
 - `MAX_HASSE_DEGREE = 15`: degree cap — a node with 15+ descendants has fully populated its causal shadow (was unbounded).
- Tightened adaptive early termination: 1 dry Δt -shell + ≥ 2 descendants triggers cutoff (was 2 dry shells + ≥ 4 descendants).
- Hollow light-cone shell optimisation: skip deep interior points where proper time $> \text{MAX_CAUSAL_DEPTH}$ units.

3.1.4 `stream_edges_to_file(n_total, chunk_size, path, seed)`

Streaming variant that writes Hasse edges to disk using a sliding window, for N too large to fit in RAM. Output format: continuous stream of (u32, u32) in little-endian. Both physics invariants are preserved: full light cone search and transitive reduction via locally cached children coordinates.

3.1.5 `sprinkle_chunk(n_expected, t_min, t_max, half_t, rng, start_idx)`

Poisson-sprinkle points into a time-slab $[t_{\min}, t_{\max}]$. Used internally by the streaming path to fill the sliding window buffer.

3.1.6 `scan_edges_sparse_ext(n_total, chunk_size, seed, on_batch)`

Extended streaming edge scanner. Identical to `scan_edges_sparse` except the callback receives the current `safe_threshold` as a second argument: `FnMut(&[(u32, u32)], f64)`. This enables callers to track node finalization (a node's total degree is known once `safe_threshold > tnode + safety_margin`).

3.1.7 `scan_edges_with_analysis(n_total, chunk_size, seed, core_num, core_den)`

Single-pass streaming analysis that merges degree counting, core classification, and core-edge collection into one scan over the edge generator. Returns `(in_deg, out_deg, is_core, directed_core_edges)`.

Pipeline inside the callback:

1. Update `in_deg[v]` and `out_deg[u]` for each edge.
2. Track finalized nodes via safe-threshold delay (`safe_threshold - 2 · max_dt - 4.0`).
3. Running degree histogram (10,000 bins) estimates the core threshold after 5% warmup.
4. Classify finalized nodes as core or non-core.
5. Collect edges where both endpoints are classified core; buffer edges where one endpoint is pending.
6. Final exact $O(N)$ histogram pass corrects any drift ($\pm 0.5\%$) and re-checks all collected core edges.

Key Result

The single-pass architecture eliminates the two-pass bottleneck (degree counting + core-edge collection), halving wall-clock time for $N > 1M$ streaming runs. At $N = 100M$ each realisation uses ~ 1.3 GB RAM ($13 \cdot N$ bytes).

3.2 Key Concepts

Definition 1: GridPoint

A spacetime event quantised onto an integer lattice for cache-coherent traversal. Fields: `p` (coordinates), `orig_idx`, `cell` (linearised 4D grid coordinate), `qt/qx/qy/qz` (quantised coordinates). Points are sorted by cell index so that spatially nearby events are contiguous in memory.

Definition 2: Occupied Cell Index (OCI)

Paradigm shift from geometric to spatial indexing. The naive approach iterates all cells in the light-cone shell for each source node. At large N the grid is sparse ($> 96\%$ cells empty), making geometric enumeration wasteful. OCI inverts the lookup:

1. Build per-time-layer lists of *occupied* cells only.
2. Sort each layer by X coordinate.
3. For each source, binary-search the X-band of the light cone within the occupied list, skipping all empty space.

This reduces the inner-loop cost from $O(\text{shell_volume})$ to $O(\text{occupied_cells})$, a $\sim 20\times$ speedup at $N > 100k$.

Module Reference: **skyrmion** — Phase 2

Kuratowski Contraction

- *Pure integer topology — zero floating-point.*
- *Core identification $\rightarrow$ Causal Prism ($K_{2,N}$ bipartite) detection $\rightarrow$ threat contraction $\rightarrow$ generation classification.*
- *Bit-packed topological signature encoding (quartile bulk momentum).*

4.1 Algorithm

CRITICAL: The transitive reduction produces a triangle-free DAG. K_4 complete subgraphs **cannot exist**. The fundamental particle is the **Causal Prism** ($K_{2,N}$ bipartite, $N \geq 3$): two poles with $N \geq 3$ shared successors (intermediates).

1. **Core selection:** Top 10% of nodes by undirected Hasse degree ($\approx$ the diamond's combinatorial centre).
2. **Causal Prism formation ($O(N)$ 2-hop search):** For each core node u , collect 2-hop candidates via the forward-reverse path $u \rightarrow w \leftarrow v$: for each directed successor w of u , find all predecessors v of w (using a reverse CSR). Any such v shares w as a common directed successor with u . Then count shared successors $|N^+(u) \cap N^+(v)|$ only for these local candidates. If ≥ 3 , the pair forms a Prism candidate. Greedy best-partner selection maximizes N per pole.

Complexity: $O(N_{\text{core}} \cdot D^3)$. With bounded Hasse degree $D \leq 15$: $O(10\text{M} \times 3,375) \approx 3.4 \times 10^{10}$ operations at $N = 100\text{M}$ — minutes instead of days.

Completeness proof: In a triangle-free Hasse graph, if u and v share directed successor z , then $u \rightarrow z$ and $v \rightarrow z$ are Hasse links. The path $u \rightarrow z \leftarrow v$ guarantees v appears as a candidate of u . Every valid prism partner *must* share at least 3 intermediates, each providing such a forward-reverse path. The 2-hop search is therefore **complete**: no valid partner is missed.

3. **Threat contraction:** Any external node connected to BOTH poles AND ≥ 2 intermediates is absorbed into the higher-degree pole (vertex contraction).
4. **Generation classification:** Prisms classified by bit-packed topological signature (quartile bulk momentum across all components).
5. **Transitive merge chain resolution:** Pointer chase to resolve chains ($O(N)$).
6. **Defect CSR construction:** Zero-copy CSR from merge map + pole-completion edges (one edge per Prism: origin $\leftrightarrow$ destination).

4.2 Functions

4.2.1 `apply_defect(n, adj_head, adj_data, bulk_momentum) $\rightarrow$ DefectResult`

Main entry point. Finds Causal Prisms ($K_{2,N}$ bipartite structures with shared successors), classifies them by topological signature into generations, performs threat contraction, and builds the defect CSR by adding pole-completion edges.

4.2.2 `process_streaming(n_total, chunk_size, path, seed) $\rightarrow$ SpectralResult`

Out-of-core variant for streaming mode. Single-pass analysis via `scan_edges_with_analysis()`:

1. **Single pass:** Stream edges through `scan_edges_with_analysis()` to simultaneously count degrees, classify core nodes, and collect core-induced edges. Returns `(in_deg, out_deg, is_core, directed_core_edges)`.
2. **Prism detection:** Build CSR for the core-induced subgraph, run $O(N)$ 2-hop Causal Prism detection and generation classification.
3. **Spectral measurement:** Run random walkers on the core CSR for spectral dimension; build directed CSR for causal flux.

4.3 DefectResult Struct

Field	Description
<code>vac_head, vac_data</code>	Vacuum Hasse CSR (row pointers + column indices).
<code>def_head, def_data</code>	Defect CSR after threat contraction + Prism pole-completion edges.
<code>vacuum_core</code>	Core node indices (top 10% by degree) in the vacuum graph.
<code>defect_core</code>	Core node indices surviving threat contraction.
<code>gen1_nodes</code>	Generation 1 Prism node indices — most abundant signature (electron-like).
<code>gen2_nodes</code>	Generation 2 Prism node indices — second most abundant (muon-like).
<code>gen3_nodes</code>	Generation 3 Prism node indices — third most abundant (tau-like).
<code>anti1_nodes</code>	Anti-Generation 1 Prism node indices — CPT conjugate (positron-like).
<code>merge_into</code>	Merge map: <code>merge_into[i] = canonical node for node i</code> . For threat-absorbed nodes, points to the absorbing Prism pole.

Table 4.1: DefectResult fields.

4.4 Signature Encoding

Each Causal Prism signature is computed from the bulk momentum of ALL components (origin, destination, and intermediates):

1. Collect bulk momentum $[M_{\text{origin}}, M_{\text{destination}}, M_{w_1}, M_{w_2}, \dots]$ for all nodes in the Prism.
2. Sort the list and extract quartile values: $[q_0, q_1, q_2, q_3]$ (0th, 25th, 50th, 75th percentiles).
3. Normalise each quartile to $[-10, +10]$ via $q_i \times 10 / \max(|q|)$.
4. Offset by +16 to make non-negative (range $[6, 26]$, fits in 5 bits).
5. Pack four 5-bit components into a single u32:

$$\text{sig} = c_0 \mid (c_1 \ll 5) \mid (c_2 \ll 10) \mid (c_3 \ll 15)$$

The anti-signature (CPT conjugate) is computed by reversing and negating: $\bar{c}_i = -c_{3-i} + 16$.

Module Reference: **spectral** — Phase 3

Spectral Dimension Measurement

- *Random walk return probability via undirected and directed walkers.*
- *Two tiers: eigendecomposition (exact, $N \leq 3k$) and Monte Carlo ($N > 3k$).*
- *Per-generation and causal flux measurements.*

5.1 Functions

5.1.1 `spectral_dimension(steps, p_vals) → Vec<f64>`

$d_S(t) = -2d(\ln P)/d(\ln t)$ via centred finite differences. Forward difference at $t = 1$, backward at $t = t_{\max}$, centred elsewhere.

5.1.2 `run_walkers(adj_head, adj_data, starts, steps, seed) → Vec<f64>`

Run W independent lazy-walk walkers in parallel. At each step: 50% stay, 50% move to a uniformly random neighbour. Returns $P(t)$ = fraction of walkers that returned to their starting node at each step. Parallel via Rayon.

5.1.3 `run_transmission_walkers(...) → (Vec<f64>, Vec<f64>)`

Directed walkers (mandatory move along causal arrow). Returns two vectors: attraction flux (Gen1 → AntiGen1) and repulsion flux (Gen1 → Gen1). Walkers that reach a dead end (edge of causal set) escape and stop.

5.1.4 `compute_eigen(n, rows, cols, steps, core) → SpectralResult`

Exact $P(t) = N^{-1} \sum_k \lambda_k^t$ from eigendecomposition of the symmetric normalised adjacency $S = D^{-1/2} A D^{-1/2}$. Complexity: $O(N^3)$. Used only for small graphs ($N \leq 3k$). Local $P(t)$ uses eigenvector-weighted sums over core indices.

5.1.5 `compute_monte_carlo(n, rows, cols, steps, core, n_w, rng) → SpectralResult`

Monte Carlo $P(t)$ from random walkers. Builds CSR adjacency internally, then launches lazy random walkers. Complexity: $O(W \cdot t)$, independent of N .

5.1.6 `compute_monte_carlo_csr(n, head, data, steps, core, n_w, rng) → SpectralResult`

Zero-copy variant — avoids rebuilding adjacency when CSR is already available from Phase 2. This is the hot path for large N in-memory runs.

5.1.7 `build_adj_list(n, rows, cols) → (Vec<u32>, Vec<u32>)`

Build sorted undirected adjacency list in CSR format from edge lists.

5.2 SpectralResult Struct

Field	Description
p_global	$P(t)$ from uniformly random starts. Probes global geometry.
ds_global	$d_S(t)$ of the bulk (derived from p_global).
p_local	$P(t)$ from walkers starting on core nodes.
ds_local	$d_S(t)$ from core walkers. Sensitive to topological defects.
p_gen1, ds_gen1	$P(t)$ and d_S for Generation 1 Causal Prism nodes (electron-like).
p_gen2, ds_gen2	$P(t)$ and d_S for Generation 2 Prism nodes (muon-like).
p_gen3, ds_gen3	$P(t)$ and d_S for Generation 3 Prism nodes (tau-like).
p_anti1, ds_anti1	$P(t)$ and d_S for Anti-Generation 1 (positron-like, CPT conjugate).
flux_attraction	Directed transmission: Gen1 $\rightarrow$ AntiGen1 (opposite charge).
flux_repulsion	Directed transmission: Gen1 $\rightarrow$ Gen1 (same charge).

Table 5.1: SpectralResult fields (14 total).

Module Reference: **output** — Phase 4

CSV Serialisation

- *Ensemble-averaged observables written to CSV.*
- *15-column format: return probabilities, spectral dimensions, and causal flux.*

6.1 Function

6.1.1 `write_csv(path, steps, vacuum, defect)`

Serialise vacuum and defect spectral results to a CSV file. Each row corresponds to one diffusion step t . The vacuum result provides control measurements (unmodified Hasse graph); the defect result provides measurements after Kuratowski contraction (Causal Prism + K_5 threat absorption).

6.2 CSV Column Reference

Column	Physics	Units
step	Diffusion time t	integer steps
P_vac	Return probability on vacuum graph	probability
dS_vac	Spectral dimension of vacuum	dimensionless
P_def	Return probability on defect graph	probability
dS_def	Spectral dimension with matter	dimensionless
P_Gen1	Return probability for Generation 1	probability
dS_Gen1	Spectral dimension, Generation 1	dimensionless
P_Gen2	Return probability for Generation 2	probability
dS_Gen2	Spectral dimension, Generation 2	dimensionless
P_Gen3	Return probability for Generation 3	probability
dS_Gen3	Spectral dimension, Generation 3	dimensionless
P_Anti1	Return probability for antimatter	probability
dS_Anti1	Spectral dimension of antimatter	dimensionless
Flux_Attr	Causal flux: Gen1→AntiGen1 (attraction)	probability
Flux_Repu	Causal flux: Gen1→Gen1 (repulsion)	probability

Table 6.1: CSV output columns (15 total).

Module Reference: **memory** — RAM-Aware Mode Selection

Chapter Overview

- *Automatic detection of available system RAM.*
- *Memory estimation heuristics for each simulation tier.*
- *Interactive mode selection with config file override.*

7.1 Functions

7.1.1 `load_config(dir) → Config`

Load configuration from a TOML file, or return defaults. Searches for `causal_set.toml` in the given directory first, then falls back to the current working directory.

7.1.2 `ensure_config(dir)`

Write the default config file if it doesn't already exist.

7.1.3 `recommend_mode(n, cfg) → (ExecMode, u64, u64)`

Recommend an execution mode based on config + available RAM vs estimated usage. The estimate accounts for concurrent realisations (8 for $N > 10M$, 4 otherwise).

7.1.4 `prompt_mode(recommended, available, estimated, cfg) → ExecMode`

Prompt the user to confirm or override the recommended execution mode.

7.1.5 `estimate_memory_bytes(n) → u64`

Heuristic peak memory estimate for in-memory mode:

- $N \leq 3,000$: $\sim N^2 \times 24$ bytes (dense eigendecomp matrices).
- $3,000 < N \leq 50,000$: $\sim N \times 2,000$ bytes (sparse structures).
- $N > 50,000$: $\sim N \times 500$ bytes (OCI + CSR + defect).

7.1.6 `estimate_streaming_memory_bytes(n) → u64`

Peak memory estimate for streaming mode: $13N + 100$ MB. Components: $8N$ (degree arrays) + $50 \cdot (N/10)$ (core CSR) + 100 MB (buffer). At $N = 100M$: ~ 1.3 GB per realisation.

7.1.7 `max_concurrent_runs(n) → usize`

Returns 2 for $N > 10M$ (streaming: 2×1.3 GB = 2.6 GB), 4 otherwise.

7.1.8 `available_ram_bytes() → u64`

Detect available system RAM in bytes via the `sysinfo` crate.

7.2 Types

Definition 1: ExecMode

An enum: InMemory (keep all data in RAM) or Streaming (single-pass edge analysis via `scan_edges_with_analysis()`, ~ 1.3 GB per realisation at $N = 100M$).

Definition 2: Config

User-configurable settings: `max_ram_bytes` (hard ceiling, `0 = auto`), `safety_fraction` (0.0–1.0), `output_dir` (default output directory).

Usage

8.1 Options

Argument	Description	Default
N	Number of spacetime events	5000
M	Ensemble realisations	10
output_dir	Directory for results	current dir
--stream	Force streaming mode	—
--inmemory	Force in-memory mode	—
--help	Show help message	—

8.2 Configuration

Place a `causal_set.toml` in the working directory (auto-generated on first run if absent):

```
# Hard limit on RAM (GB). 0 = auto-detect from system.
max_ram_gb = 0

# Fraction of available RAM considered safe (when auto-detecting).
safety_fraction = 0.70

# Default output directory for results and streaming edge files.
output_dir = "."
```

8.3 Examples

```
# Standard in-memory run
cargo run --release -- 50000 10

# Streaming run (large N, single-pass O(N))
cargo run --release -- 1000000 5 --stream

# Custom output directory
cargo run --release -- 50000 10 /path/to/output
```

Expected Results

9.1 Spectral Dimension

- **Vacuum (global):** d_S diverges toward ~ 15.79 at late diffusion times (boundary saturation of the unstructured bulk).
- **Defect (with Causal Prism matter):** d_S stabilises at ~ 8.36 (topological retention — the Prism bipartite structure traps probability flow).
- **Coupling constant:** $\alpha_{\text{trans}} \approx 0.31$, consistent with the observed strong coupling at the tau mass scale.

Key Result

Mass is not a continuous parameter assigned to a particle, but a quantized topological property: the integer count N of intermediate nodes in the Causal Prism. This topological inertia stabilises the spectral dimension at a finite value, while the vacuum diverges.

9.2 Generation Classification

Causal Prisms are classified by their topological signature (normalised bulk momentum vector of poles and intermediates):

Generation	Physics Analogue	Signature
Gen1	Electron-like	Most abundant $[M_0, M_1, M_2, M_3]$
Gen2	Muon-like	Second most abundant
Gen3	Tau-like	Third most abundant
AntiGen1	Positron-like	CPT conjugate of Gen1

9.3 Causal Flux

Directed walker transmission probabilities measure electromagnetic-like interactions:

- **Attraction:** Gen1 $\rightarrow$ AntiGen1 (opposite charge, positive flux).
- **Repulsion:** Gen1 $\rightarrow$ Gen1 (same charge, lower transmission).

Dependencies

Crate	Purpose
nalgebra	Dense eigendecomposition (Tier 1, $N \leq 3k$)
sprs	Sparse matrix algebra for A^2 Hasse reduction
rand	Deterministic PRNG (seeded StdRng)
rayon	Data-parallel iteration across walkers and nodes
sysinfo	System RAM detection for automatic mode selection
smallvec	Stack-allocated small vectors for inner-loop optimisation

Table 10.1: Rust crate dependencies.

See Also

- *Modulo Synthesis Vol I: The Geometry of Time* — Axiom 1, causal sets, spectral dimension flow, the Geometry of Logic ($O(N)$ Locality Theorem), Law of Large Numbers.
- *Modulo Synthesis Vol II: The Geometry of Matter* — Axiom 2, Kuratowski's Theorem, generation theorem, colour confinement, gauge forces, the Three Geometries.
- *Emma's Thought Experiments* — Pedagogic companion with intuitive explanations, dimensional adjustment, and locality.

Author

Juan Pablo Silva Alvarado

License

MIT License

*“The universe is strictly computable, finite, and structurally homeostatic.
The rest is just counting.”*