Medeco Original (75 Series)

	Full Step	Half Step		
MACS:	4	8		
Increment:	.030"	.015"		
Progression:	Single Step	Two Step		
E.P.D.	.503"	.503"		
Included Angle:	86°	86°		
Root Cut:	.015"	.015"		

Key Origination								
Full Step Half Step								
Blackhawk	Card 191	N/A						
CodeMax	DSD #51	DSD #75						
HPC Blitz	C36	CX4						
HPC Punch	N/A	N/A						
ITL	298	302						

Root Depths								
Full Ste	р (.030")	Half Step (.015")						
1	.258"	0	.258"					
2	.228"	1	.243"					
3	.198"	2	.228"					
4	.168"	3	.213"					
5	.138"	4	.198"					
6	.108"	5	.183"					

1) Read and cut bow-to-tip.
2) Cut angles are Left (L, -20°), Center (C, 0°), or Right(R, +20°).
3) Medeco pins are .135" diameter with a 85° angle tip.
4) Medeco pins will measure .012" shorter than listed and cut depths
will measure .008" shallower when using standard calipers.
5) The first position should not use cuts deeper .138" to maintain key
strength.

Notes

Spacing						
1	.244"					
2	.414"					
3	.584"					
4	.754"					
5	.924"					
6	.1094"					
	·					

6	.168"
7	.153"
8	.138"
9	.123"
Х	.108"

T.F.C: .244"

B.C.C: .170"

	0	1	2	3	4	5	6	7	8	9	х
Full Step Pins	.080"	.110"	.140"	.170"	.200"	.230"					
Half Step Pins	.080"	.095"	.110"	.125"	.140"	.155"	.170"	.185"	.200"	.215"	.230"

	1&2	2&3	3&4	4&5	5&6			
Master Pins	.110"	.140"	.170"	.200"	.230"			

 $^{^{\}star}$ 75 series master pins are only available in Full Step (.030") increments.

Notes:

^{** 75} Series cam locks are mastered by adding a second hole for the sidebar at the necessary height and angle to match the position used for both cuts.

^{*** 75} series cam lock master pins are available in the following angle combinations: L & L, L & C, L & R, C & L, C & C, C & R, R & L, R & C, R & R.