

hw2: C Programming 2 and Virtual Address Space

Results for VARDAAAN KAPOOR (He/him)

Score for this attempt: **8** out of 8

Submitted Feb 20 at 11:39pm

This attempt took 39 minutes.

Question 1

1 / 1 pts

What is the output of the following program?

```
#include <stdio.h>

void func(void) {
    static int a = 10;
    a++;
    printf("%d ", a);
}

int main(void) {
    func();
    func();
    printf("\n");
    return 0;
}
```

☐ 11 11

☐ 10 12

☐ 10 11

☒ 11 12

☐ 10 10

Correct!

Question 2

1 / 1 pts

To avoid a limitation in Canvas, array code below has an extra space before the index.

```
typedef struct {
    char name[ 11];
    char *type;
    float weight;
} Pokemon;

int main(void) {
    Pokemon pokedex[ 7];
}
```

The description of `pokedex` is an array of Pokemon structures ?
The description of `pokedex[3]` is a Pokemon structure ?

Answer 1:

an array of Pokemon structures

Answer 2:

a Pokemon structure

Correct!

Correct!

Question 3

1 / 1 pts

```
typedef struct {
    char firstname[22];
    char lastname[22];
    char position[22];
} Teammate;

typedef struct {
    int size;
    char name[22];
    Teammate roster[33];
} Team;
```

Assume `team` has been initialized as follows:

```
Team team;
```

Which of the following code fragments will access the `lastname` data member of the teammate at index 0. Select all that are correct.

Correct!



team.roster[0].lastname



team->roster[0].lastname



(*team).roster.lastname



(*team->roster).lastname

Correct!



(*team.roster).lastname

Question 4

1 / 1 pts

I'm the only memory segment that a process uses that is read only. Who could I be?



Data Segment



Code Segment



Heap



Kernel



Stack

Correct!

Question 5

1 / 1 pts

```
#include <stdlib.h>
#include <string.h>

typedef struct {
```

```

char title[55];
char *author;
int pages;
} Book;

typedef struct {
    int numBooks;
    Book *books[22];
} Shelf;

int main(void) {
    Shelf bookShelf[11];
    Book book;
    bookShelf[3].books[7] = NULL;
    //statement(s) added here
    strcpy(bookShelf[3].books[7]->author, "Seuss");
}

```

Which of the following statements are required to allocate heap memory so that the last statement will make "Seuss" the author of a book in the bookshelf? Select all that are required and don't worry about their order if more than one statement is selected.

Correct!

☒ bookShelf[3].books[7] = malloc(sizeof(Book));

☐ bookShelf = malloc(sizeof(Shelf) * 11);

☐ bookShelf[3] = malloc(sizeof(Shelf));

Correct!

☒ bookShelf[3].books[7]->author = malloc(sizeof(char) * 50);

☐ bookShelf[3].books[7]->author = malloc(sizeof(char));

Question 6

1 / 1 pts

Consider the following code:

```

#include <stdio.h>
#include <stdlib.h>

int a = 32;
int b;

```

```
int func(int arg) {
    static int tmp = 0;
    tmp++;
    return tmp;
}

int main(int argc, char *argv[]) {
    int *p = malloc(sizeof(int));
    *p = 43;
    char *str = "where am I?";
    printf("%s\n", str);
    return 0;
}
```

Where are `p` and `*p` stored in the program's virtual address space?

Correct!

☒ Stack, Heap

☐ Stack, Stack

☐ Heap, Heap

☐ Heap, Stack

☐ Code, Heap

Question 7

1 / 1 pts

Below is a basic implementation of the Linux command "cat". This command is used to print the contents of a file on the console/terminal window.

```
#include <stdio.h>
#include <stdlib.h>

int main(int argc, char* argv[]) {

    FILE *fp;
    if(2 != argc) {
        printf("Usage: cat <filename>\n");
        exit(1);
    }
    if ((fp = fopen(argv[1], "r")) == NULL) {
        fprintf(stderr, "Can't open input file %s\n", argv[1]);
        exit(1);
    }
    char buffer[256];
```

```
while (fgets(X, 256, fp) != NULL)
    fprintf(Y, "%s", buffer);
fclose(Z);
return 0;
}
```

Which one of the following replacements for X, Y and Z will result in correct execution?

Correct!

- ☒ X = buffer, Y = stdout, Z = fp
- ☐ X = buffer, Y = fp, Z = stdout
- ☐ X = buffer, Y = stdin, Z = fp
- ☐ X = fp, Y = stdout, Z = buffer
- ☐ X = buffer, Y = fp, Z = fp

Question 8

1 / 1 pts

A process's memory segments in the virtual address space for a Linux based IA-32 system listed from high to low address are?

Correct!

- ☒ Stack, Heap, Data, Code
- ☐ Stack, Data, Code, Heap
- ☐ Data, Stack, Heap, Code
- ☐ Heap, Stack, Code, Data
- ☐ Code, Data, Heap, Stack

Quiz Score: **8** out of 8