

CS 354 - Machine Organization & Programming

Tuesday Jan 31 and Thursday Feb 2nd, 2023

Project p1: DUE on or before Friday 2/11 (get it done and submit this week if possible)

Project p2A: Released Friday and due on or before Friday 2/18 p2B will overlap

Homework hw1: Assigned soon

Exam Conflicts (check entire semester): Report by 2/11 to: <http://tiny.cc/cs354-conflicts>

TA Lab Consulting & PM Activities are scheduled. See links on course front page.

Last Week

Welcome Course Infor Getting Started in Linux EDIT COMPILE, RUN, DEBUG(see recordings)	C Program Structure (L2-6) C Logical Control Flow Recall Variables Meet Pointers Practice Pointers
--	--

This Week

Tuesday	Thursday
Practice Pointers (from L02) Recall 1D Arrays 1D Arrays and Pointers Passing Addresses	1D Arrays on the Heap Pointer Caveats Meet C Strings Meet <code>string.h</code>
Read before Thursday K&R Ch. 7.8.5: Storage Management (malloc and calloc) K&R Ch. 5.5: Character Pointers and Functions K&R Ch. 5.6: Pointer Arrays; Pointers to Pointers	

Next Week

Topic: 2D Arrays and Pointers

Read:

K&R Ch. 5.7: Multi-dimensional Arrays

K&R Ch. 5.8: Initialization of Pointer Arrays

K&R Ch. 5.9: Pointers vs. Multi-dimensional Arrays

K&R Ch. 5.10: Command-line Arguments

Do: Finish project p1 (handin this week Friday to ensure time on p2A next week)

Start project p2A

Recall 1D Arrays

What? An array is

◆

◆

◆

Why?

◆

◆

How?

```
void someFunction() {  
    int a[5];
```

- How many integer elements have been allocated memory?
- Where in memory was the array allocation made?
- Write the code that gives the element at index 1 a value of 11.
- Draw a basic memory diagram showing array a.

✳ *In C, the identifier for a stack allocated array (SAA)*

✳ *A SAA identifier used as a source operand*


e.g., `printf("%p\n", a);`

✳ *A SAA identifier used as a destination operand*


1D Arrays and Pointers

Given:

```
void someFunction() {  
    int a[5];  
}
```



a



Address Arithmetic

* $a[i]$

1. compute the address

2. dereference the computed address to access the element

→ Write address arithmetic code to give the element at index 3 a value of 33.

→ Write address arithmetic code equivalent to $a[0] = 77;$

Using a Pointer

→ Write the code to create a pointer p having the address of array a above.

→ Write the code that uses p to give the element in a at index 4 a value of 44.

* *In C, pointers and arrays*

Passing Addresses

Recall Call Stack Tracing:

◆

◆

◆

➤ What is output by the code below?

```
void f(int pv1, int *pv2, int *pv3, int pv4[]) {
    int lv = pv1 + *pv2 + *pv3 + pv4[0];
    pv1    = 11;
    *pv2    = 22;
    *pv3    = 33;
    pv4[0] = lv;
    pv4[1] = 44;
}
int main(void) {
    int lv1 = 1, lv2 = 2;
    int *lv3;
    int lv4[] = {4,5,6};
    lv3 = lv4 + 2;
    f(lv1, &lv2, lv3, lv4);
    printf("%i,%i,%i\n",lv1,lv2,*lv3);
    printf("%i,%i,%i\n",lv4[0],lv4[1],lv4[2]);
    return 0;
}
```

Pass-by-Value

- ◆ scalars: param is a scalar variable that gets a copy of its scalar argument
- ◆ pointers: param is a
- ◆ arrays: param is a

✳ *Changing a callee's parameter*

✳ *Passing an address*

1D Arrays on the Heap

What? Two key memory segments used by a program are the
STACK and HEAP
static (fixed in size) allocations
allocation size known during compile time

Why? Heap memory enables

◆

◆

How?

```
void* malloc(size_in_bytes)
```

```
void free(void* ptr)
```

```
sizeof(operand)
```

→ For IA-32 (x86), what value is returned by `sizeof(double)`? `sizeof(char)`? `sizeof(int)`?

→ Write the code to dynamically allocate an integer array named `a` having 5 elements.

```
void someFunction() {
```

→ Draw a memory diagram showing array `a`.

→ Write the code that gives the element at indexes 0, 1 and 2 a values of 0, 11 and 22 by using pointer dereferencing, indexing, and address arithmetic respectively.

→ Write the code that uses a pointer named `p` to give the element at index 3 a value of 33.

→ Write the code that frees array `a`'s heap memory.

Pointer Caveats

✴ *Don't dereference uninitialized or NULL pointers!*

```
int *p;                int *q = NULL;
*p = 11;               *q = 11;
```

✴ *Don't dereference freed pointers!*

```
int *p = malloc(sizeof(int));
int *q = p;
. . .
free(p);
. . .
*q = 11;
```

dangling pointer.

✴ *Watch out for heap memory leaks!*

memory leak:

```
int *p = malloc(sizeof(int));
int *q = malloc(sizeof(int));
. . .
p = q;
```

✴ *Be careful with testing for equality!*

assume p and q are pointers

compares nothing because it's assignment

compares values in pointers

compares values in pointees

✴ *Don't return addresses of local variables!*

```
int *ex1() {
    int i = 11;
    return &i;
}

int *ex2(int size) {
    int a[size];
    return a;
}
```

Meet C Strings

What? A string is

- ◆
- ◆

What? A string literal is

- ◆
- ◆

C	S	3	5	4	␣
---	---	---	---	---	---

✱ *In most cases, a string literal used as a source operand*

How? Initialization

```
void someFunction() {  
    char *sptr = "CS 354";  
}
```

→ Draw the memory diagram for `sptr`.

→ Draw the memory diagram for `str` below.

```
char str[9] = "CS 354";
```

→ During execution, where is `str` allocated?

How? Assignment

→ Given `str` and `sptr` declared in `somefunction` above, what happens with the following code?

```
sptr = "mumpsimus";
```

```
str = "folderol";
```

✱ *Caveat: Assignment cannot be used*

Meet `string.h`

What? `string.h` is

```
int strlen(const char *str)
```

Returns the length of string `str` up to but *not* including the null character.

```
int strcmp(const char *str1, const char *str2)
```

Compares the string pointed to by `str1` to the string pointed to by `str2`.

returns: < 0 (a negative) if `str1` comes before `str2`
0 if `str1` is the same as `str2`
> 0 (a positive) if `str1` comes after `str2`

```
char *strcpy(char *dest, const char *src)
```

Copies the string pointed to by `src` to the memory pointed to by `dest` and terminates with the null character.

```
char *strcat(char *dest, const char *src)
```

Appends the string pointed to by `src` to the end of the string pointed to by `dest` and terminates with the null character.

✱ *Ensure the destination character array*

buffer overflow:

How? `strcpy`

→ Given `str` and `sptr` as declared in `somefunction` on the previous page, what happens with the following code?

```
strcpy(str, "folderol");
```

```
strcpy(str, "formication");
```

```
strcpy(sptr, "vomitory");
```

✱ *Rather than assignment, `strcpy` (or `strncpy`) must be used to*

✱ *Caveat: Beware of*