



CS 540 Introduction to Artificial Intelligence **Logic**

University of Wisconsin-Madison

Fall 2023

Logic & AI

Why are we studying logic?


- **Traditional** approach to AI ('50s-'80s)
 - “Symbolic AI”
 - The Logic Theorist – 1956
 - Proved a bunch of theorems!
- Logic also the language of:
 - Knowledge rep., databases, etc.





Symbolic vs Connectionist

Rival approach: **connectionist**

- Probabilistic models
- Neural networks
- **Extremely popular** last 20 years



Stanford CS231n




M. Minsky

Symbolic vs Connectionist

Which is better?

- Future: combination; best-of-both-worlds.
 - “Neurosymbolic AI”
 - **Example:** Markov Logic Networks



Propositional Logic Basics

Logic Vocabulary:

- Sentences, symbols, connectives, parentheses
 - Symbols: P, Q, R, ... (**atomic** sentences)
 - Connectives:

\wedge	and	[conjunction]
\vee	or	[disjunction]
\Rightarrow	implies	[implication]
\Leftrightarrow	is equivalent	[biconditional]
\neg	not	[negation]
 - Literal: P or negation $\neg P$

Propositional Logic Basics

Examples:

- $(P \vee Q) \Rightarrow S$
 - “If it is cold or it is raining, then I need a jacket”
- $Q \Rightarrow P$
 - “If it is raining, then it is cold”
- $\neg R$
 - “It is not hot”



Propositional Logic Basics

Several rules in place

- Precedence: \neg , \wedge , \vee , \Rightarrow , \Leftrightarrow
- Use parentheses when needed
- Sentences: **well-formed** or not well-formed:
 - $P \Rightarrow Q \Rightarrow S$ **not well-formed (not associative!)**

Sentences & Semantics

- Sentences: built up from symbols with connectives
 - **Interpretation**: assigning True / False to symbols (a row in truth table)
 - **Semantics**: interpretations for which sentence evaluates to True
 - **Model**: (of a set of sentences) interpretation for which all sentences are True

Evaluating a Sentence

- Example:

P	Q	$\neg P$	$P \wedge Q$	$P \vee Q$	$P \Rightarrow Q$	$P \Leftrightarrow Q$
<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>true</i>
<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>false</i>
<i>true</i>	<i>false</i>	<i>false</i>	<i>false</i>	<i>true</i>	<i>false</i>	<i>false</i>
<i>true</i>	<i>true</i>	<i>false</i>	<i>true</i>	<i>true</i>	<i>true</i>	<i>true</i>

- Note:
 - If P is false, $P \Rightarrow Q$ is true regardless of Q (“5 is even implies 6 is odd” is True!)
 - Causality not needed: (“5 is odd implies the Sun is a star” is True!)

Evaluating a Sentence: Truth Table

- **Ex:**

P	Q	R	$\neg P$	$Q \wedge R$	$\neg P \vee Q \wedge R$	$\neg P \vee Q \wedge R \Rightarrow Q$
0	0	0	1	0	1	0
0	0	1	1	0	1	0
0	1	0	1	0	1	1
0	1	1	1	1	1	1
1	0	0	0	0	0	1
1	0	1	0	0	0	1
1	1	0	0	0	0	1
1	1	1	0	1	1	1

- **Satisfiable**

- There exists some interpretation where the sentence is true.

Break & Quiz

Q 1.1: Suppose P is false, Q is true, and R is true. Does this assignment satisfy

(i) $\neg(\neg p \rightarrow \neg q) \wedge r$

(ii) $(\neg p \vee \neg q) \rightarrow (p \vee \neg r)$

- A. Both
- B. Neither
- C. Just (i)
- D. Just (ii)

Break & Quiz

Q 1.1: Suppose P is false, Q is true, and R is true. Does this assignment satisfy

(i) $\neg(\neg p \rightarrow \neg q) \wedge r$

(ii) $(\neg p \vee \neg q) \rightarrow (p \vee \neg r)$

- A. Both
- B. Neither
- **C. Just (i)**
- D. Just (ii)

Break & Quiz

Q 1.1: Suppose P is false, Q is true, and R is true. Does this assignment satisfy

(i) $\neg(\neg p \rightarrow \neg q) \wedge r$

(ii) $(\neg p \vee \neg q) \rightarrow (p \vee \neg r)$

Plug interpretation into each sentence.

- A. Both
- B. Neither
- **C. Just (i)**
- D. Just (ii)

For (i): $(\neg p \rightarrow \neg q)$ will be false so $\neg(\neg p \rightarrow \neg q)$ will be true and r is true by assignment.

For (ii): $(\neg p \vee \neg q)$ is true and $(p \vee \neg r)$ is false which makes the implication false.

Break & Quiz

Q 1.2: Let A = “Aldo is Italian” and B = “Bob is English”.
Formalize “Aldo is Italian or if Aldo isn’t Italian then Bob is English”.

- a. $A \vee (\neg A \rightarrow B)$
- b. $A \vee B$
- c. $A \vee (A \rightarrow B)$
- d. $A \rightarrow B$

Break & Quiz

Q 1.2: Let A = “Aldo is Italian” and B = “Bob is English”.
Formalize “Aldo is Italian or if Aldo isn’t Italian then Bob is English”.

- a. $A \vee (\neg A \rightarrow B)$
- b. $A \vee B$ (equivalent!)
- c. $A \vee (A \rightarrow B)$
- d. $A \rightarrow B$

Break & Quiz

Q 1.2: Let A = “Aldo is Italian” and B = “Bob is English”. Formalize “Aldo is Italian or if Aldo isn’t Italian then Bob is English”.

- a. $A \vee (\neg A \rightarrow B)$
- b. $A \vee B$ (equivalent!)
- c. $A \vee (A \rightarrow B)$
- d. $A \rightarrow B$

Answer a. is the exact translation of the English sentence into a logic sentence. You can see that answer b. is also correct by writing out the truth table for all answers and seeing that a and b have the same truth tables.


Or you can use the fact that $\neg A \rightarrow B = A \vee B$ and that $A \vee A \vee B = A \vee B$ to prove equivalence.

Knowledge Bases

- **Knowledge Base (KB):** A set of sentences $\{A_1, A_2, \dots, A_n\}$.
 - Like a long sentence, connect with conjunction:
 - KB is $A_1 \wedge A_2 \wedge \dots \wedge A_n$.

Model of a KB: interpretations where all sentences are True


Goal: inference to discover new sentences



Entailment

Entailment: a sentence B logically follows from A

- Write $A \models B$
- $A \models B$ iff in every interpretation where A is true, B is also true



Methods of Inference: **1. Enumeration**

- Enumerate all interpretations; look at the truth table
 - “Model checking”
- Downside: 2^n interpretations for n symbols

Methods of Inference: 2. Using Rules

- *Modus Ponens*: $(A \Rightarrow B, A) \models B$
- And-elimination
- Other rules on the next page
 - Commutativity, associativity, de Morgan's laws, distribution for conjunction/disjunction



Logical equivalences

$$(\alpha \wedge \beta) \equiv (\beta \wedge \alpha) \quad \text{commutativity of } \wedge$$

$$(\alpha \vee \beta) \equiv (\beta \vee \alpha) \quad \text{commutativity of } \vee$$

$$((\alpha \wedge \beta) \wedge \gamma) \equiv (\alpha \wedge (\beta \wedge \gamma)) \quad \text{associativity of } \wedge$$

$$((\alpha \vee \beta) \vee \gamma) \equiv (\alpha \vee (\beta \vee \gamma)) \quad \text{associativity of } \vee$$

$$\neg(\neg\alpha) \equiv \alpha \quad \text{double-negation elimination}$$

$$(\alpha \Rightarrow \beta) \equiv (\neg\beta \Rightarrow \neg\alpha) \quad \text{contraposition}$$

$$(\alpha \Rightarrow \beta) \equiv (\neg\alpha \vee \beta) \quad \text{implication elimination}$$

$$(\alpha \Leftrightarrow \beta) \equiv ((\alpha \Rightarrow \beta) \wedge (\beta \Rightarrow \alpha)) \quad \text{biconditional elimination}$$

$$\neg(\alpha \wedge \beta) \equiv (\neg\alpha \vee \neg\beta) \quad \text{de Morgan}$$

$$\neg(\alpha \vee \beta) \equiv (\neg\alpha \wedge \neg\beta) \quad \text{de Morgan}$$

$$(\alpha \wedge (\beta \vee \gamma)) \equiv ((\alpha \wedge \beta) \vee (\alpha \wedge \gamma)) \quad \text{distributivity of } \wedge \text{ over } \vee$$

$$(\alpha \vee (\beta \wedge \gamma)) \equiv ((\alpha \vee \beta) \wedge (\alpha \vee \gamma)) \quad \text{distributivity of } \vee \text{ over } \wedge$$

You can use these equivalences to modify sentences.


First Order Logic (FOL)

Propositional logic has some limitations

- Ex: how to say “all squares have four sides”
- No context, hard to generalize; express facts

FOL is a more expressive logic; works over

- Facts, Objects, Relations, Functions



First Order Logic Syntax

- **Term:** an object in the world
 - **Constant:** Alice, 2, Madison, Green, ...
 - **Variables:** x, y, a, b, c, ...
 - **Function**(term₁, ..., term_n)
 - Sqrt(9), Distance(Madison, Chicago)
 - Maps one or more objects to another object
 - Can refer to an unnamed object: LeftLeg(John)
 - Represents a user defined functional relation
- A **ground term** is a term without variables.
 - Constants or functions of constants.

FOL Syntax

- **Atom**: smallest T/F expression
 - **Predicate**(term₁, ..., term_n)
 - Teacher(Jerry, you), Bigger(sqrt(2), x)
 - Convention: read “Jerry (is)Teacher(of) you”
 - Maps one or more objects to a truth value
 - Represents a user defined relation
 - **term₁ = term₂**
 - Radius(Earth)=6400km, 1=2
 - Represents the equality relation when two terms refer to the same object.

FOL Syntax

- **Sentence:** T/F expression
 - Atom
 - Complex sentence using connectives: $\wedge \vee \neg \Rightarrow \Leftrightarrow$
 - $\text{Less}(x,22) \wedge \text{Less}(y,33)$
 - Complex sentence using quantifiers \forall, \exists
- Sentences are evaluated under an interpretation
 - Which objects are referred to by constant symbols
 - Which objects are referred to by function symbols
 - What subsets defines the predicates

FOL Quantifiers

- Universal quantifier: \forall
- Sentence is true **for all** values of x in the domain of variable x .
- Main connective typically is \Rightarrow
 - Forms if-then rules
 - “all humans are mammals”
$$\forall x \text{ human}(x) \Rightarrow \text{mammal}(x)$$
 - Means if x is a human, then x is a mammal

FOL Quantifiers

- Existential quantifier: \exists
- Sentence is true **for some** value of x in the domain of variable x .
- Main connective typically is \wedge
 - “some humans are male”
$$\exists \mathbf{x} \text{ human}(\mathbf{x}) \wedge \text{male}(\mathbf{x})$$
 - Means there is an x who is a human and is a male

Break & Quiz

Q 2.1: How many entries does a truth table have for a FOL sentence with k variables where each variable can take on n values?

- A. Truth tables are not applicable to FOL.
- B. 2^k
- C. n^k
- D. It depends

Break & Quiz

Q 2.1: How many entries does a truth table have for a FOL sentence with k variables where each variable can take on n values?

- A. Truth tables are not applicable to FOL.
- B. 2^k
- C. n^k
- D. It depends

Break & Quiz

Q 2.1: How many entries does a truth table have for a FOL sentence with k variables where each variable can take on n values?

- A. Truth tables are not applicable to FOL.
- B. 2^k
- C. n^k
- D. It depends

Must have one entry for every possible assignment of values to variables. That number is (C).