



THE UNIVERSITY OF
WESTERN
AUSTRALIA

Electrical, Electronic & Computer Engineering

SEMESTER 1, 2021 EXAMINATIONS

ENSC3014

ELECTRONIC MATERIALS AND DEVICES -ATTACHMENT

FAMILY NAME: _____ GIVEN NAMES: _____

STUDENT ID:

| | | | | | | | |
|--|--|--|--|--|--|--|--|
| | | | | | | | |
|--|--|--|--|--|--|--|--|

 SIGNATURE: _____

This attachment contains: 15 pages (including this page)

| |
|---------------|
| INSTRUCTIONS: |
|---------------|

| |
|--------------------|
| PLEASE NOTE |
|--------------------|

Examination candidates may only bring authorised materials into the examination room. If a supervisor finds, during the examination, that you have unauthorised material, in whatever form, in the vicinity of your desk or on your person, whether in the examination room or the toilets or en route to/from the toilets, the matter will be reported to the head of school and disciplinary action will normally be taken against you. This action may result in your being deprived of any credit for this examination or even, in some cases, for the whole unit. This will apply regardless of whether the material has been used at the time it is found.

Therefore, any candidate who has brought any unauthorised material whatsoever into the examination room should declare it to the supervisor immediately. Candidates who are uncertain whether any material is authorised should ask the supervisor for clarification.

| |
|--|
| <i>Supervisors Only - Student left at:</i> |
|--|

This page has been left intentionally blank

| CONSTANTS | |
|-------------------------------------|---|
| Charge on an electron, q , or e | $1.60 \times 10^{-19} \text{ C}$ |
| Boltzmann's constant, k | $1.38 \times 10^{-23} \text{ JK}^{-1}$ |
| Speed of light in free space, c | $3.00 \times 10^8 \text{ ms}^{-1}$ |
| Plank's constant, h | $6.62 \times 10^{-34} \text{ Js}$ |
| Reduced Plank's constant, \hbar | $\frac{h}{2\pi}$ |
| Mass of an electron | $9.11 \times 10^{-31} \text{ kg}$ |
| Mass of a proton or a neutron | $1.67 \times 10^{-27} \text{ kg}$ |
| Permittivity of free space | $8.85 \times 10^{-14} \text{ Fcm}^{-1}$ |

| PROPERTIES | | | |
|---|---|---|------------------|
| Material | Si | GaAs | SiO ₂ |
| Intrinsic carrier concentration, n_i | $1.45 \times 10^{10} \text{ cm}^{-3}$ | $1.79 \times 10^6 \text{ cm}^{-3}$ | |
| Electron mobility, μ_e | $1350 \text{ cm}^2\text{V}^{-1}\text{s}^{-1}$ | $8500 \text{ cm}^2\text{V}^{-1}\text{s}^{-1}$ | |
| Hole mobility, μ_h | $480 \text{ cm}^2\text{V}^{-1}\text{s}^{-1}$ | $400 \text{ cm}^2\text{V}^{-1}\text{s}^{-1}$ | |
| Relative Permittivity, ϵ_r | 11.7 | 13.1 | 3.9 |
| Energy band gap, E_G | 1.12 eV | 1.42 eV | 8.9 eV |
| Effective density of states in conduction band, N_C | $4.3 \times 10^{19} \text{ cm}^{-3}$ | $4.7 \times 10^{17} \text{ cm}^{-3}$ | |
| Effective density of states in valence band, N_V | $2.5 \times 10^{19} \text{ cm}^{-3}$ | $7 \times 10^{18} \text{ cm}^{-3}$ | |

| QUANTUM MECHANICS | |
|---|--|
| Shroedinger's wave equations in one dimension | $i\hbar \frac{\partial \Psi}{\partial t} = -\frac{\hbar^2}{2m} \frac{\partial^2 \Psi}{\partial x^2} + V\Psi \text{ (full)}$ $\Psi = \psi(x)\phi(t) \text{ (separable solutions)}$ $E\psi = -\frac{\hbar^2}{2m} \frac{\partial^2 \psi}{\partial x^2} + V\psi \text{ (time-independent)}$ $\phi(t) = e^{-j\frac{E}{\hbar}t} \text{ (time-dependent part)}$ |
| De-Broglie's wave-particle duality | $p = \frac{h}{\lambda}$ |
| Energy of a photon | $E = h\nu, \text{ where } \nu \text{ is the frequency of light}$ |


| | |
|---|--|
| Effective mass | $m^* = \hbar^2 / \left(\frac{d^2 E}{dk^2} \right)$ |
| The Fermi Level in a semiconductor | $E_F - E_V = \frac{E_G}{2} + \frac{3}{4} kT \ln \left(\frac{m_h^*}{m_e^*} \right) + \frac{1}{2} kT \ln \left(\frac{n}{p} \right)$ |
| Maxwell-Boltzmann approximation of carrier concentrations | $n = N_C \exp \left(-\frac{E_C - E_F}{kT} \right)$ $p = N_V \exp \left(-\frac{E_F - E_V}{kT} \right)$ where, $N_C = 2 \left(\frac{2\pi m_e^* kT}{h^2} \right)^{\frac{3}{2}}$ $N_V = 2 \left(\frac{2\pi m_h^* kT}{h^2} \right)^{\frac{3}{2}}$ |
| Alternative Maxwell-Boltzmann expressions of carrier concentrations | $n = n_i \exp \left(\frac{E_F - E_i}{kT} \right)$ $p = n_i \exp \left(\frac{E_i - E_F}{kT} \right)$ |
| Thermal equilibrium condition | $p(x)n(x) = n_i^2$ |

| | |
|---|---|
| Conductivity, resistivity and resistance | $\sigma = nq\mu_n + pq\mu_p$ $\rho = \frac{1}{\sigma}$ $R = \frac{\rho l}{A}$ |
| Current Density | $J_n = nq\mu_n \mathcal{E} + qD_n \frac{dn}{dx}$ $J_p = pq\mu_p \mathcal{E} - qD_p \frac{dp}{dx}$ |
| Continuity equations | $\frac{\partial n}{\partial t} = \frac{1}{q} \nabla \cdot J_n + G_n - R_n$ $\frac{\partial p}{\partial t} = -\frac{1}{q} \nabla \cdot J_p + G_p - R_p$ |
| Net rate of recombination | $U = R - G_{th}$ |
| Trap assisted (Shockley-Read-Hall) net recombination rate | $U = \sigma v_{th} N_t \frac{pn - n_i^2}{p + n + 2n_i \cosh\left(\frac{E_F - E_i}{kT}\right)}$ <p>where σ is the capture cross-section and v_{th} is the average thermal energy of carriers.</p> |
| Approximate net rate of recombination in neutral regions | $U = R - G_{th}$ $= \frac{pn - p_{n0}}{\tau_p} \text{ n-type material}$ $= \frac{n_p - n_{p0}}{\tau_n} \text{ p-type material}$ |

| | |
|---|--|
| Poisson's Equation | $\frac{d\mathcal{E}}{dx} = \frac{\rho}{\epsilon_r \epsilon_0}$ |
| Relationship between electric field and electrostatic potential | $\mathcal{E} = -\frac{d\psi}{dx}$ |
| Relationship between electrostatic potential and band structure | $\psi = -\frac{E_i}{q}$ |

| | |
|--|---|
| Built in potential of pn junction | $V_{bi} = \frac{1}{q} (E_{Fn} - E_{Fp})$ $\approx \frac{kT}{q} \ln \left(\frac{N_A N_D}{n_i^2} \right)$ |
| Depletion region widths (abrupt junctions) | $x_n = \sqrt{\frac{2\epsilon_r \epsilon_0}{q N_D} \left(\frac{N_A}{N_A + N_D} \right) (V_{bi} - V_J)}$ $x_p = \sqrt{\frac{2\epsilon_r \epsilon_0}{q N_A} \left(\frac{N_D}{N_A + N_D} \right) (V_{bi} - V_J)}$ $W = x_n + x_p = \sqrt{\frac{2\epsilon_r \epsilon_0}{q} \left(\frac{N_A + N_D}{N_A N_D} \right) (V_{bi} - V_J)}$ |
| Diode depletion region differential capacitance per unit area | $C = \frac{dQ_J}{dV_J}$ $= \frac{\epsilon_r \epsilon_0}{W}$ $= \frac{\epsilon_r \epsilon_0}{\sqrt{\frac{2\epsilon_r \epsilon_0}{q} \left(\frac{N_A + N_D}{N_A N_D} \right) (V_{bi} - V_J)}}$ |
| Approximate max net rate of generation in an depletion region (works for both forward bias and reverse bias) | $U_{MAX} = \frac{n_i}{2\tau_0} (\exp(\frac{qV_J}{2kT}) - 1)$ <p>where,</p> $\tau_0 = \frac{1}{\sigma v_{th} N_t}, \text{ is the minority carrier lifetime}$ |
| pn junction diffusion currents (works for both forward and reverse bias). Replace L_p or L_n by W for a short-base diode, where W is the length of the neutral region between the depletion region to the contact. | $I_{diff,p} = q D_p \frac{p_{n0}}{L_p} A_J (\exp(\frac{qV_J}{kT}) - 1)$ $I_{diff,n} = q D_n \frac{n_{p0}}{L_n} A_J (\exp(\frac{qV_J}{kT}) - 1)$ <p>where,</p> $L_p = \sqrt{D_p \tau_p} \text{ (in neutral n-region)}$ $L_n = \sqrt{D_n \tau_n} \text{ (in neutral p-region)}$ |
| pn junction generation/recombination currents in depletion region (works for both forward and reverse bias.) | $I_{rec/gen} = q A_J W \frac{n_i}{2\tau_0} (\exp(\frac{qV_J}{2kT}) - 1)$ |
| Total pn junction currents | $I = I_{rec/gen} + I_{diff,p} + I_{diff,n}$ |
| Quasi-static approximation for carrier concentrations at the edge of a depletion region in a pn junction | $p_n(x=0) = p_{n0} \exp(\frac{qV_J}{kT})$ $n_p(x=-W) = n_{p0} \exp(\frac{qV_J}{kT})$ |

Excess minority carrier concentration in the base in forward active.



Excess minority carrier charge in the base in forward active.

$$q_F = Q_{F0} \left(\exp \left(\frac{qV_{EB}}{kT} \right) - 1 \right)$$

where,

$$Q_{F0} = \frac{qA_J W_B p_{b0}}{2}$$

Static collector current in forward active.

$$I_C \approx qA_J D_b \frac{p'_b(0)}{W_B}$$

$$= I_1 \left(\exp \left(\frac{qV_{EB}}{kT} \right) - 1 \right)$$

$$= \frac{q_F}{\tau_F}$$


where,

$$I_1 = \frac{qA_J D_b p_{b0}}{W_B}$$

$$\tau_F = \frac{(W_B)^2}{2D_b}$$

| | |
|--|--|
| Static base current in forward active | $I_B = I_{BA} + I_{BB}$ $= \frac{qA_J W_B}{2\tau_b} p'_b(0) + \frac{qA_J D_e}{W_E} \left(\frac{n_{e0}}{p_{b0}} \right) p'_b(0)$ $= \frac{q_F}{\tau_{BF}}$ <p>where,</p> $\tau_{BF} = \frac{1}{\frac{1}{\tau_b} + \frac{2D_e n_{e0}}{W_B W_E p_{b0}}}$ |
| Static base current as a fraction of the static collector current in forward active. | $I_B = \delta I_C$ <p>where,</p> $\delta = \frac{\frac{W_B}{2\tau_B} + \frac{D_e}{W_E} \left(\frac{n_{e0}}{p_{b0}} \right)}{D_b/W_b} \text{ (called the base defect)}$ |
| Static emitter current in forward active | $I_E = I_C + I_B = (1 + \delta)I_C$ |
| Charge control equations in forward active | $i_C = \frac{q_F}{\tau_F} - \frac{dq_{VC}}{dt}$ $i_B = \frac{dq_F}{dt} + \frac{dq_{VE}}{dt} + \frac{dq_{VC}}{dt} + \frac{q_F}{\tau_{BF}}$ $i_E = \frac{dq_F}{dt} + \frac{dq_{VE}}{dt} + \frac{q_F}{\tau_{BF}} + \frac{q_F}{\tau_F}$ |

Charge control model in forward active



Complete charge control model equations

$$i_C = \frac{q_F}{\tau_F} - \frac{dq_R}{dt} - q_R \left(\frac{1}{\tau_{BR}} + \frac{1}{\tau_R} \right) - \frac{dq_{VC}}{dt}$$


$$i_B = \frac{dq_F}{dt} + \frac{q_F}{\tau_{BF}} + \frac{dq_R}{dt} + \frac{q_R}{\tau_{BF}} + \frac{dq_{VE}}{dt} + \frac{dq_{VC}}{dt} + \frac{q_F}{\tau_{BF}}$$

$$i_E = -\frac{q_R}{\tau_R} + \frac{dq_F}{dt} + q_F \left(\frac{1}{\tau_{BF}} + \frac{1}{\tau_F} \right) + \frac{dq_{VE}}{dt}$$

where,

$$q_R = Q_{R0} \left(e^{\frac{qV_{CB}}{kT}} - 1 \right)$$


Complete charge-control model (valid in all regions of operation)



| | |
|--------------------------------------|---|
| Ideal n-channel MOSFET drain current | <p>Triode: $I_D = \frac{Z}{L} \mu_n C_{ox} [(V_G - V_T) V_D - \frac{1}{2} V_D^2]$</p> <p>Saturation: $I_{Dsat} = \frac{1}{2} \frac{Z}{L} \mu_n C_{ox} (V_G - V_T)^2$</p> |
| Fermi Potential | <p>p-type silicon: $\phi_p = \frac{kT}{q} \ln \left(\frac{N_A}{n_i} \right)$</p> <p>n-type silicon: $\phi_n = \frac{kT}{q} \ln \left(\frac{N_D}{n_i} \right)$</p> |
| MOS Depletion width | <p>p-type silicon: $W_d = \left(\frac{2\epsilon_S \phi_s}{q N_A} \right)^{\frac{1}{2}}$</p> <p>n-type silicon: $W_d = \left(\frac{2\epsilon_S \phi_s}{q N_D} \right)^{\frac{1}{2}}$</p> |
| MOS silicon charge | $V_G - V_{FB} = -\frac{Q_s}{C_{ox}} + \phi_s$ |
| MOS voltage relationship | $V_G = \phi_{MS} + V_{ox} + \phi_s$ |
| MOS inversion layer charge (p-type) | $Q_n = -(V_G - V_T) C_{ox}$ |
| Ideal MOS saturation voltage | $V_{Dsat} = V_G - V_T$ |

| | |
|--|---|
| Kinetic Energy | $E_{KE} = \frac{1}{2}mv^2 = \frac{p^2}{2m}$ |
| Relationship between frequency and wavelength of light | $\nu = \frac{c}{\lambda}$ |
| Lorentz Force | $F = q(v \times B)$ |
| Hall coefficient | $R_H = \frac{\mathcal{E}_H}{JB} = \frac{\mu}{\sigma} = \frac{1}{ne} = \frac{1}{pq}$ |

***Actinide series



Identities and Formulas

Tangent and Cotangent Identities

$$\tan \theta = \frac{\sin \theta}{\cos \theta} \quad \cot \theta = \frac{\cos \theta}{\sin \theta}$$

Reciprocal Identities

$$\begin{aligned} \sin \theta &= \frac{1}{\csc \theta} & \csc \theta &= \frac{1}{\sin \theta} \\ \cos \theta &= \frac{1}{\sec \theta} & \sec \theta &= \frac{1}{\cos \theta} \\ \tan \theta &= \frac{1}{\cot \theta} & \cot \theta &= \frac{1}{\tan \theta} \end{aligned}$$

Pythagorean Identities

$$\sin^2 \theta + \cos^2 \theta = 1$$

$$\tan^2 \theta + 1 = \sec^2 \theta$$

$$1 + \cot^2 \theta = \csc^2 \theta$$

Even and Odd Formulas

$$\sin(-\theta) = -\sin \theta \quad \csc(-\theta) = -\csc \theta$$

$$\cos(-\theta) = \cos \theta \quad \sec(-\theta) = \sec \theta$$

$$\tan(-\theta) = -\tan \theta \quad \cot(-\theta) = -\cot \theta$$

Periodic Formulas

If n is an integer

$$\sin(\theta + 2\pi n) = \sin \theta \quad \csc(\theta + 2\pi n) = \csc \theta$$

$$\cos(\theta + 2\pi n) = \cos \theta \quad \sec(\theta + 2\pi n) = \sec \theta$$

$$\tan(\theta + \pi n) = \tan \theta \quad \cot(\theta + \pi n) = \cot \theta$$

Double Angle Formulas

$$\sin(2\theta) = 2 \sin \theta \cos \theta$$

$$\begin{aligned} \cos(2\theta) &= \cos^2 \theta - \sin^2 \theta \\ &= 2 \cos^2 \theta - 1 \\ &= 1 - 2 \sin^2 \theta \end{aligned}$$

$$\tan(2\theta) = \frac{2 \tan \theta}{1 - \tan^2 \theta}$$

Degrees to Radians Formulas

If x is an angle in degrees and t is an angle in radians then:

$$\frac{\pi}{180^\circ} = \frac{t}{x} \quad \Rightarrow \quad t = \frac{\pi x}{180^\circ} \quad \text{and} \quad x = \frac{180^\circ t}{\pi}$$

Half Angle Formulas

$$\sin \theta = \pm \sqrt{\frac{1 - \cos(2\theta)}{2}}$$

$$\cos \theta = \pm \sqrt{\frac{1 + \cos(2\theta)}{2}}$$

$$\tan \theta = \pm \sqrt{\frac{1 - \cos(2\theta)}{1 + \cos(2\theta)}}$$

Sum and Difference Formulas

$$\sin(\alpha \pm \beta) = \sin \alpha \cos \beta \pm \cos \alpha \sin \beta$$

$$\cos(\alpha \pm \beta) = \cos \alpha \cos \beta \mp \sin \alpha \sin \beta$$

$$\tan(\alpha \pm \beta) = \frac{\tan \alpha \pm \tan \beta}{1 \mp \tan \alpha \tan \beta}$$

Product to Sum Formulas

$$\sin \alpha \sin \beta = \frac{1}{2} [\cos(\alpha - \beta) - \cos(\alpha + \beta)]$$

$$\cos \alpha \cos \beta = \frac{1}{2} [\cos(\alpha - \beta) + \cos(\alpha + \beta)]$$

$$\sin \alpha \cos \beta = \frac{1}{2} [\sin(\alpha + \beta) + \sin(\alpha - \beta)]$$

$$\cos \alpha \sin \beta = \frac{1}{2} [\sin(\alpha + \beta) - \sin(\alpha - \beta)]$$

Sum to Product Formulas

$$\sin \alpha + \sin \beta = 2 \sin \left(\frac{\alpha + \beta}{2} \right) \cos \left(\frac{\alpha - \beta}{2} \right)$$

$$\sin \alpha - \sin \beta = 2 \cos \left(\frac{\alpha + \beta}{2} \right) \sin \left(\frac{\alpha - \beta}{2} \right)$$

$$\cos \alpha + \cos \beta = 2 \cos \left(\frac{\alpha + \beta}{2} \right) \cos \left(\frac{\alpha - \beta}{2} \right)$$

$$\cos \alpha - \cos \beta = -2 \sin \left(\frac{\alpha + \beta}{2} \right) \sin \left(\frac{\alpha - \beta}{2} \right)$$

Cofunction Formulas

$$\sin \left(\frac{\pi}{2} - \theta \right) = \cos \theta \quad \cos \left(\frac{\pi}{2} - \theta \right) = \sin \theta$$

$$\csc \left(\frac{\pi}{2} - \theta \right) = \sec \theta \quad \sec \left(\frac{\pi}{2} - \theta \right) = \csc \theta$$

$$\tan \left(\frac{\pi}{2} - \theta \right) = \cot \theta \quad \cot \left(\frac{\pi}{2} - \theta \right) = \tan \theta$$