



CS 231


Lecture 2: Edge detection

Edge detection




- Convert a 2D image into a set of curves
 - Extracts salient features of the scene
 - More compact than pixels

Origin of Edges



- Edges are caused by a variety of factors

Images as functions...



- Edges look like steep cliffs

Characterizing edges

- An edge is a place of *rapid change* in the image intensity function




Image derivatives

- How can we differentiate a *digital* image $F[x,y]$?
 - Option 1: reconstruct a continuous image, f , then compute the derivative
 - Option 2: take discrete derivative (finite difference)

$$\frac{\partial f}{\partial x}[x, y] \approx F[x + 1, y] - F[x, y]$$

How would you implement this as a linear filter?

$$\frac{\partial f}{\partial x} : \begin{array}{|c|c|c|} \hline & & \\ \hline & & \\ \hline & & \\ \hline \end{array}$$

H_x




$$\frac{\partial f}{\partial y} : \begin{array}{|c|c|c|} \hline & & \\ \hline & & \\ \hline & & \\ \hline \end{array}$$

H_y

Image gradient

- The *gradient* of an image: $\nabla f = \left[\frac{\partial f}{\partial x}, \frac{\partial f}{\partial y} \right]$

The gradient points in the direction of most rapid increase in intensity



The *edge strength* is given by the gradient magnitude:



$$\|\nabla f\| = \sqrt{\left(\frac{\partial f}{\partial x}\right)^2 + \left(\frac{\partial f}{\partial y}\right)^2}$$

The gradient direction is given by:


$$\theta = \tan^{-1} \left(\frac{\partial f}{\partial y} / \frac{\partial f}{\partial x} \right)$$

- how does this relate to the direction of the edge?

Image gradient




Effects of noise




Noisy input image




$$f(x)$$



$$\frac{d}{dx}f(x)$$




Where is the edge?



Source: S. Seitz

Solution: smooth first




To find edges, look for peaks in $\frac{d}{dx}(f * h)$


Associative property of convolution

- Differentiation is convolution, and convolution is associative:

- This saves us one operation $\frac{d}{dx}(f * h) = f * \frac{d}{dx}h$




2D edge detection filters



Gaussian


$$h_{\sigma}(u, v) = \frac{1}{2\pi\sigma^2} e^{-\frac{u^2+v^2}{2\sigma^2}}$$





derivative of Gaussian (x)

$$\frac{\partial}{\partial x} h_{\sigma}(u, v)$$


Derivative of Gaussian filter



x-direction



y-direction



The Sobel operator

- Common approximation of derivative of Gaussian

$$\frac{1}{8} \begin{array}{|c|c|c|} \hline -1 & 0 & 1 \\ \hline -2 & 0 & 2 \\ \hline -1 & 0 & 1 \\ \hline \end{array}$$



s_x

$$\frac{1}{8} \begin{array}{|c|c|c|} \hline 1 & 2 & 1 \\ \hline 0 & 0 & 0 \\ \hline -1 & -2 & -1 \\ \hline \end{array}$$

s_y

- The standard defn. of the Sobel operator omits the $1/8$ term
 - doesn't make a difference for edge detection
 - the $1/8$ term **is** needed to get the right gradient magnitude

Sobel operator: example



Example




- original image (Lena)

Finding edges



gradient magnitude

Finding edges



where is the edge?

thresholding