

ris-enrich: An automated Python tool for enriching bibliographic RIS files with full abstracts

Eduardo S. A. Santos  true

1 COSSEE, Collaboration for Open Science and Synthesis in Ecology and Evolution, Department of Biological Sciences, University of Alberta, Edmonton, AB, T6G 2E9, Canada

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Open Journals](#) 

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

Systematic reviews and meta-analyses require rigorous literature screening, a process highly dependent on the availability of accurate abstracts for each bibliographic record. However, researchers often encounter a bottleneck during the discovery phase: some academic search engines, such as Google Scholar, routinely truncate abstracts in their bibliographic records. `ris-enrich` is an open-source Python package designed to resolve this data loss. It parses `.ris` files and cascades searches across four major open academic databases (Semantic Scholar, OpenAlex, Europe PMC, and Crossref) to retrieve and append the full-text abstracts, utilizing strict NFKC Unicode normalization and fuzzy string matching to prevent false-positive data contamination. Our case study demonstrates that `ris-enrich` can recover complete abstracts for 21% of records across six languages, significantly enhancing the efficiency and accuracy of title-and-abstract screening in evidence synthesis workflows. By automating this enrichment process, `ris-enrich` empowers researchers to conduct more comprehensive and inclusive literature reviews, ultimately advancing the quality of systematic reviews and meta-analyses in ecology, evolution, psychology, and beyond.

Statement of need

The preparation of a preregistration protocol and the subsequent screening workload in evidence synthesis studies (e.g., in fields like ecology, evolution, and psychology) are reliant on the quality and integrity of the initial bibliographic dataset. While tools exist to optimize search string generation ([Grames et al., 2019](#)) or facilitate the literature screening process, for example, Rayyan or SysRev ([Bozada et al., 2021](#); [Ouzzani et al., 2016](#)), there is a distinct lack of lightweight tools focused strictly on bibliographic data enrichment post-export.

When researchers export search results, they are frequently left with snippets rather than full abstracts, rendering title-and-abstract screening virtually impossible without manual intervention. While manual intervention can be conducted when the number of records is manageable, it becomes infeasible at scale (e.g., when you have thousands of records to process). This is especially common from search records exported from Google Scholar, because records in Google Scholar present only truncated abstracts. Google Scholar is one of the few search engines available that is capable of retrieving academic records in non-English languages, thus being an important search engine in attempts to minimize bias in data collection for evidence synthesis studies. `ris-enrich` automates the recovery of this missing metadata. By prioritizing a sequential API fallback architecture and enforcing an 80% title-similarity threshold using the `difflib` and `unicodedata` libraries, the software ensures high-fidelity data retrieval even across international, diacritic-heavy, and logographic languages.

`ris-enrich` was developed to directly support the screening workflows of evidence synthesis studies, seamlessly preparing enriched `.ris` datasets of bibliographic records that can be

42 incorporated in the record screening process of the synthesis studies.

43 In practice

44 To install the current version of the `ris-enrich` package, run the command:

```
45 pip install git+https://github.com/esantos2ua/ris-enrich.git
```

46 After installation, you can use the `ris-enrich` command line tool:

```
47 ris-enrich data/GoogleScholarPortugueseMateChoiceExample.ris
```

48 Reading 'GoogleScholarPortugueseMateChoiceExample.ris'...

49 Found 68 references. Starting enrichment...

50 No email provided for Crossref API. Rate limits may be lower. Use `--email` or set `RIS_ENRICH_EMAIL`

51 [1/68] Searching: Caracterização da reprodução e ensaios de crescime...

52 -> Found abstract via OpenAlex (3887 chars)

53 [2/68] Searching: The role of olfaction in sexual interactions of ba...

54 -> No exact matching abstract found.

55 [3/68] Searching: Marcadores genéticos de previsão de fenótipos em c...

56 -> No exact matching abstract found.

57 [4/68] Searching: Benchmarking na gestão de unidades de saúde: relev...

58 -> Found abstract via OpenAlex (466 chars)

59 [5/68] Searching: O impacto da terceirização sobre os custos de mão-...

60 -> Found abstract via OpenAlex (1232 chars)

61 ...

62 Done! Safely updated 22 abstracts.

63 Using the `ris-enrich` command above will output to screen information about the `.ris` file
64 being enriched. It will display the file name, followed by the number of references found in the
65 file and the command will print a run-time statement of each record that is being enriched,
66 with a message to the user on whether or not a complete abstract was found. At the end of
67 the file, the output will display how many records had abstract information updated.

68 The `ris-enrich` command will also create a `enrichment_log.txt` log file with the record of
69 the enrichment information. Finally, the command will create a new `.ris` file with the suffix
70 `_Enriched.ris` that contains the original inputted records with the updated abstract field
71 containing the new complete abstract, when available.

72 Arguments

73 The `ris-enrich` command can be implemented with the following arguments:

- 74 ■ `input_file`: Path to the original `.ris` file (Required).
- 75 ■ `-o, --output`: Path to save the enriched `.ris` file. Defaults to `*_Enriched.ris`.
- 76 ■ `-l, --log`: Path to save the execution log. Defaults to `enrichment_log.txt`.
- 77 ■ `-e, --email`: **(optional)** Your email address, which will be included in the User-Agent
78 header when querying the Crossref API. Providing an email helps Crossref identify
79 polite usage and may increase rate limits. You can also set this value by exporting
80 `RIS_ENRICH_EMAIL` in your environment before running the tool:

```
export RIS_ENRICH_EMAIL=you@example.com  
ris-enrich input_file.ris -o output_file.ris
```

81 or pass it directly on the command line:

```
ris-enrich input_file.ris -o output_file.ris --email you@example.com
```

Current applications

ris-enrich was developed as part of an evidence synthesis study that is updating two meta-analyses in Ecology and Evolution. ris-enrich was used to enrich bibliographic records that were retrieved from literature searches conducted in Japanese, Polish, Portuguese, Russian, Simplified/Traditional Chinese, and Spanish on Google Scholar using the application Publish or Perish software (Harzing, 2007). With ris-enrich, I was able to enrich a set of 425 bibliographic records with 89 complete abstracts, a 21% average improvement considering the six languages. This improvement has clear benefits for screeners that are reading titles and abstracts of these records to make decisions on whether a record should be included for full-text screening in the data pipeline of the study.

Our open source Python tool, ris-enrich, has proven to be an effective and easy to use tool for automating the enrichment of bibliographic records, and can be used in a variety of evidence synthesis workflows.

Conflict of interest disclosure

The author declares that no competing interests exist.

Acknowledgements

ESAS, as well as this research work, are supported by the Canada Excellence Research Chairs (CERC) program (grant number CERC-2022-00074). ESAS would like to thank Ayumi Mizuno and Santiago Ortega for testing the software and providing feedback on the user experience.

AI usage disclosure

- **Tool use:** For this paper, I used Google Gemini 3.1 Pro to write the main code of this open-source Python package, and to prepare the initial versions of the documents of the github repository.
- **The nature and scope of assistance:** Assistance was used for code generation, refactoring, and test scaffolding.
- **Confirmation of review:** ESAS reviewed, edited, validated all AI-assisted outputs and made the core design decisions in this project.

References

- Bozada, T., Borden, J., Workman, J., Del Cid, M., Malinowski, J., & Luechtefeld, T. (2021). Sysrev: A FAIR platform for data curation and systematic evidence review. *Frontiers in Artificial Intelligence*, 4. <https://doi.org/10.3389/frai.2021.685298>
- Grames, E. M., Stillman, A. N., Tingley, M. W., & Elphick, C. S. (2019). An automated approach to identifying search terms for systematic reviews using keyword co-occurrence networks. *Methods in Ecology and Evolution*, 10(10), 1645–1654. <https://doi.org/10.1111/2041-210X.13268>
- Harzing, A. W. (2007). *Publish or Perish*. <https://harzing.com/resources/publish-or-perish>

- 118 Ouzzani, M., Hammady, H., Fedorowicz, Z., & Elmagarmid, A. (2016). Rayyan—a web and
119 mobile app for systematic reviews. *Systematic Reviews*, 5(1), 210. [https://doi.org/10.](https://doi.org/10.1186/s13643-016-0384-4)
120 [1186/s13643-016-0384-4](https://doi.org/10.1186/s13643-016-0384-4)

DRAFT