FRENCH - DETECTED

ENGLISH

Salut à tous. On a toujours des problèmes d'étanchéité sur notre turbinator, mais ce weekend on a fait un test des plus révélateur !! On a tout simplement détourné le puits d'émulsion du carbu d'origine du moteur (donc exit notre spirale, configuration d'origine). On a percé un trou dans le carbu à l'opposé de la sortie du puits, bouché le puits en inversant la buse et monté le gicleur d'air et d'essence sur un tube acier. On a fait un S avec le tube relativement long afin de pouvoir le chauffer au chalumeau. But du jeu : voir si le moteur tourne toujours à l'essence avec un puits de plus de 20cm de long, et voir si l'eau se dissocie en passant à travers le tube chauffé au rouge à pas loin de 900°C. Résultat : le moteur tourne à l'essence, avec un léger trou à l'accélération, mais après il reprend ses tours. Vu la précarité de notre montage, trop dangereux de chauffer le tuyau avec l'essence dedans. mais on y réflechit. Par contre on a chauffé à l'eau devinez ce qui sort de la buse ? DE L'EAU !!! et sous forme liquide !! Température en sortie de buse 12°C. Biensur le moteur tourne au ralenti (car on a pas détourné le gicleur de ralenti ni la pompe de reprise) mais dès qu'on accélère, ça broute, et ça cale. et on a du mettre un gicleur 2x plus gros pour que l'eau soit pulvérisée (ce qui rejoint les dires de s1r9a9m9 de changer les gicleurs sur son moteur à eau + plasma) Conclusion : Vous envoyez de la flotte dans vos moteurs avec vos systèmes G ! Autant mettre un goute à goute au dessus de l'admission, sans se faire chier à modifier l'échappement, faire un bulleur etc ... Mon collègue qui hésitait à fabiquer un pantone, là au moins il sait qu'il n'en fera pas ! J'essayerai de faire des photos ce soir. Nous on continue notre principe mais on a déjà pensé à quelque chose de plus étanche, difficile à décrir juste avec des mots, mais en gros, on aurait un tube en cuivre recuit, cintré en escargot. Dans ce tube passe l'admission et autour l'échapement. Ce tube est pris en sandwich entre 2 plaques d'acier ce qui fait que l'échappement suit la spirale. Et même si il en passe une petite quantité entre le tube et une plaque, peu importe, il n'y aura pas de fuite admission / échappement. Sdc

Hi all. We still have sealing problems on our turbinator, but this weekend we did a most revealing test !! We simply diverted the emulsion well of the original fuel of the engine (so exit our spiral, original configuration). We drilled a hole in the carburetor opposite the outlet of the well, plugged the well by inverting the nozzle and mounted the air and fuel nozzle on a steel tube. We made an S with the relatively long tube in order to be able to heat it with a torch. Aim of the game: to see if the engine is still running on petrol with a well more than 20cm long, and to see if the water dissociates by passing through the red-hot tube not far from 900 ° C. Result: the engine runs on gasoline, with a slight hole on acceleration, but then it takes its turns. Considering the precariousness of our assembly, it is too dangerous to heat the hose with petrol in it. but we think about it. By cons we heated with water guess what comes out of the nozzle? SOME WATER !!! and in liquid form !! Nozzle outlet temperature 12 ° C. Of course the engine idles (because we did not divert the idle jet or the recovery pump) but as soon as we accelerate, it grazes, and it stalls. and we had to put a 2x larger nozzle so that the water is sprayed (which joins the statements of s1r9a9m9 to change the jets on its water + plasma engine) Conclusion: You send fleet in your engines with your systems G! You might as well put a drip above the intake, without being pissed at modifying the exhaust, making a bubbler etc ... My colleague who hesitated to make a pantone, there at least he knows he doesn't won't do! I will try to take photos this evening. We continue our principle but we have already thought of something more waterproof, difficult to describe just with words, but basically, we would have an annealed copper tube, bent into a snail. In this tube passes the admission and around the exhaust. This tube is sandwiched between 2 steel plates which means that the exhaust follows the spiral. And even if a small amount passes between the tube and a plate, whatever, there will be no intake / exhaust leak. Sdc