

88A Cont, 1838A @ 10 sec, 0.24 mH		FREQUENCY 60		PHASE 1		TYPE COIL & AIR CORE	
VOLTAGE		13800V L-L					
CENTER LEG N/A		TUBE 3-1/2 OD Circular Tube*			COIL LENGTH 16 1/8		
		Wind 1 Coil					
WINDING		Single Winding					
WIRE SIZE		(3 wide) 6 Sq Heavy Cu Wire (340500: 6 SQ, 200C, Polyamide Imide, Non-Solderable, Copper Wire)					
TURNS		59 1/2					
LEADS		H1 H2					
		0 59 1/2					
KEEPBACK		5 1/4 PO					
WDG LENGTH		5 5/8					
TURNS/LAYER		10					
LAYERS		6					
LAYER INSULATION		(3) 0.015 TV + 1/4 Stick AR after layers 3 (3) 0.015 TV all other layers					
WRAPPER		(2) 0.010 TV + Glass Tape					
MLT		16.2					
WIRE WEIGHT		26.1					
LEADS:				NOTES:			
H1 Braze to TC-800818 Item 1, out 1/2" to 1st bend. LV Sleeve 1" past 2nd bend.				*See Winding Tube Sheet for mold and tube details **Place sticks 2.5" or less apart to ensure gap between layers.			
H2 Braze to TC-800818 Item 2, out face of coil. See location below							
PADS: (4) 0.015 TV, flush, 5" Wide							
Top Bottom Top Finished Coil				Coil Diagram			
Calculated Coil Size: 7 x 7 5/8				Either dimension 1/2" less check winding and alert engineering			
Maximum Coil Size: 7 1/4 x 7 7/8							
Measured Coil Size:							
Revision Notes				ENGINEERED BY		RM	
9/23/25 rdm correct H2 location				REVIEWED BY			
				REVISION DATE		7/8/25	
				REVISION NUMBER		0	
						WINDING SHEET	
						WS -800818	