

140A Cont, 380A @ 5 sec, 26.5 mH		FREQUENCY 60		PHASE 1	TYPE	COIL & AIR CORE	
VOLTAGE		12470V L-L					
CENTER LEG	N/A	TUBE 9-3/4 OD Circular Tube*			COIL LENGTH	20 15/16	
		Wind 1 Coil					
WINDING	Single Winding						
WIRE SIZE	(2 wide) 0.114 x 0.325 Heavy CU Wire (340110: .114 x .325, 200C, Polyamide Imide, Non-Solderable, Copper Wire)						
URNS	329 1/2						
LEADS	H1		H2				
		0		329 1/2			
KEEPBACK	5-1/8 PO						
WDG LENGTH	10 5/8						
TURNS/LAYER	15						
LAYERS	22						
LAYER INSULATION	0.015 TV + 1/2 Stick AR after layers 4, 8, 12, 16						
		0.015 TV all other layers					
WRAPPER	(2) 0.010 TV + Glass Tape						
MLT	46.8						
WIRE WEIGHT	361.0						
LEADS:				NOTES:			
H1 Self out 28" with DOUBLE HV SLEEVE in margin out 18"				*See Winding Tube Sheet for mold and tube details			
H2 Braze to TC-800820 Item 1 out face of coil at position shown				**Place sticks 2.5" or less apart to ensure gap between layers.			
PADS: (4) 0.015 TV, flush, 5" Wide							
Top H1 9-3/4 H2 6" Bottom Coil Diagram				6"			
Calculated Coil Size: 20 1/4 x 21				Either dimension 1/2" less check winding and alert engineering			
Maximum Coil Size: 21 1/4 x 22							
Measured Coil Size:							
Revision Notes				ENGINEERED BY	RM	WINDING SHEET	
				REVIEWED BY			
				REVISION DATE	1/24/24		
				REVISION NUMBER	0	WS -800820	