

269A Cont, 8070A @ 10 sec, 0.09 Ohms		FREQUENCY 60		PHASE 1		TYPE COIL & AIR CORE	
VOLTAGE		4160V L-L (45kV BIL)					
CENTER LEG N/A		TUBE 5-7/8 OD Circular Tube*			COIL LENGTH 15 1/8		
		Wind 1 Coil					
WINDING		Single Winding					
WIRE SIZE		(3 wide x 2 tall) 0.144 x 0.408 Heavy Cu Wire (340622: .144 x .408, 200C, Polyamide Imide, Non-Solderable, Copper Wire)					
TURNS		47-1/2					
LEADS		H1 H2					
		0 47-1/2					
KEEPBACK		2 PO					
WDG LENGTH		11 1/8					
TURNS/LAYER		8					
LAYERS		6					
LAYER INSULATION		(2) 0.015 TV + 1/4 Stick AR after layer 2, 4** (2) 0.015 TV all other layers					
WRAPPER		(2) 0.010 TV + Glass Tape					
MLT		26.6					
WIRE WEIGHT		144.0					
LEADS:				NOTES:			
H1 Braze to TC-800822 Item 1, out 1/2" to 1st bend. LV Sleeve 1/2" past 2nd bend.				*See Winding Tube Sheet for mold and tube details			
H2 Braze to TC-800822 Item 2, out face of coil. See position below.				**Place sticks 2.5" or less apart to ensure at least 3/16 gap between layers.			
PADS: H1: (4) 0.015 TV, 4" out, 5" Wide. Fold and tape to match bends. H2: Pad under (4) 0.015 TV, Flush, 5" Wide.							
Top H1 5-7/8 H2 ~ 2" Bottom Coil Diagram				Finished Coil			
Size over Layer 3: 8 1/2 x 8 13/16							
Calculated Coil Size: 11 1/8 x 11 3/4				Either dimension off by 3/4 (high or low) check winding and alert engineering			
Max Coil Size: 11 1/2 x 12 1/8							
Measured Coil Size:							
Revision Notes				ENGINEERED BY		RM	
				REVIEWED BY			
				REVISION DATE		6/12/25	
				REVISION NUMBER			
				WINDING SHEET			
						WS-800822	