

130A Cont, 2250A @ 10 sec, 29 Ohms		FREQUENCY 60		PHASE 1		TYPE COIL & AIR CORE						
VOLTAGE		12470V L-L (95kV BIL)										
CENTER LEG		N/A		TUBE		9-3/4 OD Circular Tube*		COIL LENGTH		25 1/8		
						Wind 1 Coil						
WINDING		Single Winding										
WIRE SIZE		(2 wide) 0.144 x 0.365 Nomex CU Wire (340825: .144 x .365 220C, Nomex, Non-Solderable, Copper Wire)										
TURNS		563 1/2										
LEADS		H1		H2								
		0		563 1/2								
KEEPBACK		5-1/8 PO Every 3rd Layer**										
WDG LENGTH		14 7/8										
TURNS/LAYER		19										
LAYERS		30										
LAYER INSULATION		0.015 TV + 3/8 Stick AR after layers 4, 8, 11, 15, 19, 23, 26*** 0.015 TV all other layers										
WRAPPER		(2) 0.010 TV + Glass Tape										
MLT		55.5										
WIRE WEIGHT		1044.0										
LEADS:				NOTES:								
H1 Self out top of coil 23" with DOUBLE HV SLEEVE in margin out 18".				*See Winding Tube Sheet for mold and tube details								
H2 Braze to TC-800830 Item 1 out face of coil at position shown				**Bottom packout- make out of layered GPO3. Either 1/32 or 1/16 red board. Must be full width and full thickness. Top packout - like normal.								
PADS: (4) 0.015 TV, flush, 5" Wide				***Place sticks 2.5" or less apart to ensure gap between layers.								
Top H1 9-1/4 6" H2 Bottom Coil Diagram				Top 6 Finished Coil								
Size over Layer 14:				17	x	17 1/4	Either dimension 1/2" less check winding and alert engineering					
Calculated Coil Size:				25 1/2	x	26						
Maximum Coil Size:				26	x	26 1/2						
Measured Coil Size:					x							
Revision Notes					ENGINEERED BY		NF		WINDING SHEET			
					REVIEWED BY							
					REVISION DATE		7/9/25					
					REVISION NUMBER		0					
								WS -800830				