

Stake Engine

Deep Technical Research Report

English + Armenian / Անգլերեն + Հայերեն

Knowledge base for an AI development team evaluating a single-player “hold to run, cash out anytime” game.

Research date: 7 September 2026

Primary sources only: Stake Engine official site, official documentation, and official StakeEngine GitHub repositories.

Critical compatibility finding: Stake Engine clearly supports dynamic Burst/crash-style gameplay presentations. The current approval rule is narrower: third-party published Engine games must be stateless and cannot use continuation or early-cashout mechanics that change the monetary settlement after the bet has begun.

Source / Աղբյուր: [Stake Engine Approval Guidelines](#)

Research scope, evidence rules & reading guide /

Հետազոտության շրջանակ և աղբյուրների կանոններ

This report is intentionally conservative. A statement is marked as CONFIRMED only when the current official Stake Engine website, documentation, or the official StakeEngine GitHub organization directly supports it. Where the official material is silent, login-gated, internally inconsistent, or ambiguous, the report says so and does not fill the gap with community knowledge.

Source / Աղբյուր: <https://stake-engine.com/docs>

Այս զեկույցը դիտավորյալ պահպանողական է: Փաստը նշվում է որպես ՀԱՍՏԱՏՎԱԾ միայն այն դեպքում, երբ այն ուղղակիորեն հաստատվում է Stake Engine-ի պաշտոնական կայքով, պաշտոնական փաստաթղթերով կամ StakeEngine-ի պաշտոնական GitHub կազմակերպությամբ: Եթե պաշտոնական նյութը լուռ է, մուտքով փակված է, հակասական է կամ երկիմաստ, դա բացահայտ նշվում է՝ առանց ենթադրություններով լրացնելու:

Source / Աղբյուր: <https://github.com/StakeEngine>

Terminology used in this report: CONFIRMED = directly documented; INFERENCE = engineering interpretation derived from confirmed behavior; GAP = the public official material does not establish the answer. The report does not treat example values such as a 97% target RTP as universal platform limits unless the official docs explicitly call them limits.

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

Table of contents / Բովանդակություն

- 1. Executive answer and crash-style feasibility
- 2. Platform overview, onboarding and commercial model
- 3. Math SDK and the books-based outcome model
- 4. Web / Frontend SDK
- 5. RGS API and round lifecycle
- 6. Packaging, upload and validation
- 7. Certification, compliance and review
- 8. Crash-style mechanic: architecture implications and prohibited patterns
- 9. Gaps & open questions
- 10. AI-team implementation blueprint
- 11. Glossary
- 12. Official-source inventory

Հայերեն բաժինները տեղադրված են համապատասխան անգլերեն բաժինների անմիջապես հետո, որպեսզի տեխնիկական թիմը կարողանա օգտագործել նույն կառուցվածքը երկու լեզուներով:

1. Executive answer: can Stake Engine host the requested crash-style game?

English

CONFIRMED: Stake Engine is built around pre-generated, static game outcomes. Every possible published outcome is represented by a simulation/book; a lookup-table weight controls its probability; the RGS selects a simulation when /wallet/play is called and returns that simulation's event data to the frontend. The frontend does not determine the payout.

Source / Աղբյուր: <https://stake-engine.com/docs>

Source / Աղբյուր: <https://stake-engine.com/docs/math>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/general-disclaimer>

CONFIRMED: the current Approval Guidelines require published third-party Engine games to be strictly stateless: each bet must be independent of previous outcomes, and continuation or early-cashout options are prohibited. This does NOT mean the game presentation must be visually static. It is a restriction on round state and economic decision flow, not on animation, arcade presentation, physics-like sequences, or multiplier progression shown during a round.

Source / Աղբյուր: [Stake Engine Approval Guidelines](#)

CONFIRMED: Stake's own live catalog demonstrates this distinction. Angry Balls is explicitly labeled a Stake Engine Burst Game and Stake describes it as using 'crash game mechanics'. Penguins Can Fly is also a Stake Engine Burst Game whose multiplier grows while the penguin remains airborne and changes as pre-rendered/game events unfold. Therefore, 'pre-generated/static outcomes' must not be interpreted as 'static gameplay' or 'slots only'.

Source / Աղբյուր: [Stake - Angry Balls](#)

Source / Աղբյուր: [Stake - Penguins Can Fly](#)

CONFIRMED / IMPORTANT LIMIT: these official game pages prove that crash-style and arcade-style presentation can run on Stake Engine, but they do not establish that those games use a true player-controlled mid-round cashout. The current approval text still explicitly prohibits early cashout.

Source / Աղբյուր: [Stake Engine Approval Guidelines](#)

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

CONFIRMED: Engine nevertheless supports long event sequences inside a single pre-generated book, and provides POST /bet/event to persist an in-progress event marker so a disconnected player can resume viewing an active round. This is a resume/display mechanism, not documented as a way to alter the predetermined payout.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/events>

CONFIRMED + INFERENCE: a running-character game can visually progress through checkpoints, hazards, multiplier updates, and other ordered events inside the selected outcome. Stake's published Engine Burst games confirm that this kind of dynamic arcade/crash-style presentation is viable. The remaining approval boundary is whether the player's in-round input changes the wallet-settled result; if it does, it appears to become the prohibited early-cashout/continuation case.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

Հայերեն

ՀԱՍՏԱՏՎԱԾ. Stake Engine-ը կառուցված է նախապես գեներացված, ստատիկ արդյունքների մոդելի վրա: Հրապարակված յուրաքանչյուր հնարավոր արդյունք ներկայացվում է simulation/book-ով, lookup table-ի weight-ը որոշում է ընտրության հավանականությունը, իսկ /wallet/play կանչի ժամանակ RGS-ը ընտրում է simulation-ը և frontend-ին վերադարձնում դրա event-երը: Frontend-ը payout չի որոշում:

Source / Աղբյուր: <https://stake-engine.com/docs>

Source / Աղբյուր: <https://stake-engine.com/docs/math>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/general-disclaimer>

ՀԱՍՏԱՏՎԱԾ. ընթացիկ Approval Guidelines-ը publication-ի համար պահանջում է, որ third-party Engine խաղերը լինեն strictly stateless. յուրաքանչյուր bet անկախ լինի նախորդ outcome-ներից, իսկ continuation և early cashout տարբերակները արգելված են: Բայց սա Չի նշանակում, որ gameplay-ը կամ animation-ը պետք է «ստատիկ» լինի: Սահմանափակումը վերաբերում է round state-ին և payout-ը փոխող mid-round որոշումներին, ոչ թե arcade/crash presentation-ին:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

ՀԱՍՏԱՏՎԱԾ. մեկ book-ի ներսում կարելի է ունենալ երկար event sequence, իսկ POST /bet/event-ը պահպանում է ընթացիկ event marker-ը՝ disconnect-ից հետո նույն ռաունդի ցուցադրումը շարունակելու համար: Պաշտոնական docs-ը սա չի նկարագրում որպես payout-ը փոխելու մեխանիզմ:

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

2. Platform overview, onboarding and commercial model

English

CONFIRMED: Stake Engine presents itself as a game-development and RGS platform that lets independent developers and studios build, upload, version, test, submit and distribute games to Stake and Stake US. SDK access is described as open to anybody. Developers may use Engine's SDKs or their own compatible frontend/math tooling, provided the uploaded artifacts match Engine's required static formats.

Source / Աղբյուր: <https://stake-engine.com/>

Source / Աղբյուր: <https://stake-engine.com/docs>

CONFIRMED: the public launch sequence is: build the frontend and game logic; balance/validate the math; upload and submit versions; then go live on partner websites such as Stake and track analytics.

Source / Աղբյուր: <https://stake-engine.com/>

CONFIRMED: the homepage advertises perpetual royalties equal to 10% of GGR, payments on the 1st of every month, and transparent analytics. The public homepage describes this as the commercial model; the detailed public payment documentation was not retrievable in this research pass, so definitions of GGR, deductions, payment rails, minimum thresholds, tax treatment, dispute rules, and contract termination are GAP items.

Source / Աղբյուր: <https://stake-engine.com/>

CONFIRMED: the homepage also states that developers can upload multiple games and submit directly to Stake. The exact ACP account-creation/KYC/legal-entity onboarding sequence is not fully exposed on the public docs reviewed here.

Source / Աղբյուր: <https://stake-engine.com/>

CONFIRMED: Engine's public 'Provably Fair' page states that all compatible stateless Engine games publish every possible result and selection probability, and that client/server seed entropy is used to select among those published results so the selection can later be verified.

Source / Աղբյուր: <https://stake-engine.com/fair>

Հայերեն

ՀԱՍՏԱՏՎԱԾ. Stake Engine-ը խաղերի զարգացման և RGS հարթակ է, որը անկախ developer-ներին ու studio-ներին թույլ է տալիս ստեղծել, upload անել, version անել, test անել, submit անել և խաղերը տարածել Stake ու Stake US հարթակներում: SDK access-ը ներկայացվում է որպես բաց բոլորի համար: Կարելի է օգտագործել Engine SDK-ները կամ սեփական frontend/math լուծումը, եթե վերջնական ֆայլերը համապատասխանում են պահանջվող static format-ին:

Source / Աղբյուր: <https://stake-engine.com/>

Source / Աղբյուր: <https://stake-engine.com/docs>

ՀԱՍՏԱՏՎԱԾ. հանրային launch flow-ը հետևյալն է՝ frontend և game logic, math balance/validation, upload + submit, ապա go-live և analytics:

Source / Աղբյուր: <https://stake-engine.com/>

ՀԱՍՏԱՏՎԱԾ. homepage-ը նշում է 10% GGR perpetual royalty, վճարում յուրաքանչյուր ամսվա 1-ին և transparent analytics: Սակայն GGR-ի կոնկրետ պայմանները, deductions-ը, tax/KYC/payment rails-ը և contract termination-ը հանրային նյութերում ամբողջությամբ հաստատված չեն և այս զեկույցում նշվում են որպես բաց հարցեր:

Source / Աղբյուր: <https://stake-engine.com/>

Area	Confirmed public fact	Status for AI team
SDK access	Open to anybody	CONFIRMED
Distribution	Stake / Stake US and partner websites	CONFIRMED
Royalty	10% GGR perpetual royalties (homepage wording)	CONFIRMED wording; contract details GAP
Payment timing	1st of every month (homepage wording)	CONFIRMED wording
Own tools	Allowed if outputs match required formats	CONFIRMED
Account/KYC contract details	Not fully public in reviewed docs	GAP

3. Math SDK: architecture, books, RTP, simulation and verification

English

CONFIRMED: the Math SDK is a Python-based engine. The official repository requires Python ≥ 3.12 ; PIP is required; Rust/Cargo is required only when using the included optimization algorithm. The official repository is MIT-licensed.

Source / Աղբյուր: <https://github.com/StakeEngine/math-sdk>

Source / Աղբյուր: <https://stake-engine.com/docs/math/setup>

CONFIRMED: the Math SDK defines game rules, simulates outcomes, writes books and lookup tables, generates backend/frontend/optimization configuration, and can optimize discrete outcome weights. It is optional: developers may generate compatible static files with their own system.

Source / Աղբյուր: <https://stake-engine.com/docs/math>

Source / Աղբյուր: <https://stake-engine.com/docs>

CONFIRMED: Engine requires all outcomes to be known at publication time. Instead of executing live random game logic on the RGS, developers publish a finite set of outcomes. For each round the RGS uses the lookup table to choose a simulation ID with frequency proportional to its weight, then returns the corresponding events from the compressed game-logic file.

Source / Աղբյուր: <https://stake-engine.com/docs/math>

Source / Աղբյուր: <https://stake-engine.com/docs>

CONFIRMED: a book contains at least an id, an events array and payoutMultiplier. The Math SDK's book objects may additionally include criteria and base/free-game contribution data. The events array is what the RGS play response gives the frontend.

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

Source / Աղբյուր: <https://stake-engine.com/docs/math/source-files/outputs>

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

CONFIRMED: production math publication minimally uses index.json, one CSV lookup table per mode, and one Zstandard-compressed JSON Lines book file per mode. index.json maps mode name and cost multiplier to the events filename and weights filename. CSV rows are unsigned integer values in the form simulation ID, probability/weight, payoutMultiplier. The payoutMultiplier in the CSV must exactly match the game logic.

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

CONFIRMED: the game-logic format currently requires .jsonl compressed with Zstandard (.zst). Each JSONL simulation requires id, events and payoutMultiplier. The docs' example explains that payoutMultiplier is expressed relative to the mode cost; e.g. 1150 represents 11.5x in the shown convention.

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

CONFIRMED: Math SDK output folders include books/books_compressed, configs, forces and lookup_tables. Uncompressed books are intended for frontend testing/debugging; compressed books are uploaded and consumed by the RGS. Force files record developer-defined criteria/event keys and help analysis/optimization.

Source / Աղբյուր: <https://stake-engine.com/docs/math/high-level-structure/game-structure>

Source / Աղբյուր: <https://stake-engine.com/docs/math/source-files/outputs>

CONFIRMED: three notable config outputs are config_math.json (optimization settings and RTP splits), config_fe.json (frontend-visible symbol/padding/bet-mode data), and config.json (RGS-facing bet-mode and file hash information).

Source / Աղբյուր: <https://stake-engine.com/docs/math/source-files/outputs>

CONFIRMED: all newly simulated lookup weights initially start at 1 in the documented workflow. The optimizer changes weights to achieve a target RTP and distribution shape. Exact RTP can be computed from the weighted payout vector because the outcome set and weights are finite and published.

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

Source / Աղբյուր: https://stake-engine.com/docs-content/distribution_optimization.pdf

CONFIRMED: BetMode configuration includes name, cost, rtp, max_win, distribution criteria, and flags such as auto_close_disabled, is_feature, and is_buybonus. max_win is therefore game/mode configuration, and the engine verifies that simulation winnings do not exceed the configured cap.

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/setup/betmode>

Source / Աղբյուր: <https://stake-engine.com/docs/math/source-files/state>

GAP: no universal public Engine-wide minimum/maximum RTP range was found in the reviewed official materials. The docs use targets such as 97% in examples, but examples are not stated as platform-wide limits. Similarly, no universal numeric maximum-win multiplier cap was found; max_win is documented as configurable per BetMode.

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/setup/betmode>

CONFIRMED: the official quickstart recommends starting with a small number of uncompressed simulations for debugging, then producing larger sets. It says a production-ready game is typically recommended to have 100k+ simulations per mode to create payout diversity and reduce repeated outcomes. This is described as a recommendation, not a strict publication minimum.

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

CONFIRMED: run_analysis can produce an .xlsx/PAR-style analysis containing hit rates, RTP contributions and simulation counts. The optimization process can explicitly control subsets such as max wins, freegame entries and zero-win outcomes, provided the conditions are exclusive and ordered correctly.

Source / Աղբյուր: <https://stake-engine.com/docs/math/utilities>

Source / Աղբյուր: <https://stake-engine.com/docs/math/optimization-algorithm>

CONFIRMED: events are arbitrary developer-defined JSON objects as long as the frontend understands them. The usual shape contains index, type and custom fields. Events should encode every piece of player-visible state needed to render the outcome; the docs say information not contained in or implied by events cannot be shown to the player.

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/events>

Հայերեն

ՀԱՍՏԱՏՎԱԾ. Math SDK-ը Python-ի վրա է: Պաշտոնական repo-ն պահանջում է Python >=3.12 և PIP, իսկ Rust/Cargo անհրաժեշտ է միայն ներառված optimization algorithm-ի համար:

Source / Աղբյուր: <https://github.com/StakeEngine/math-sdk>

Source / Աղբյուր: <https://stake-engine.com/docs/math/setup>

ՀԱՍՏԱՏՎԱԾ. Engine-ում բոլոր արդյունքները պետք է հայտնի լինեն publication-ի պահին: Live RNG logic-ը RGS-ում հաշվարկելու փոխարեն հրապարակվում է finite outcome set: /play-ի ժամանակ RGS-ը lookup table-ի weight-երով ընտրում է simulation ID և compressed book-ից frontend-ին վերադարձնում դրա event sequence-ը:

Source / Աղբյուր: <https://stake-engine.com/docs/math>

Source / Աղբյուր: <https://stake-engine.com/docs>

ՀԱՍՏԱՏՎԱԾ. publication-ի նվազագույն math structure-ը յուրաքանչյուր mode-ի համար index.json + CSV lookup + Zstandard-compressed JSONL book է: CSV payout-ը պետք է ճշգրիտ համընկնի book-ի payoutMultiplier-ի հետ:

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

ՀԱՍՏԱՏՎԱԾ. BetMode-ում առանձին սահմանվում են rtp, max_win, cost և distribution պայմանները: Engine-ը նաև ստուգում է, որ simulation-ի win-ը չանցնի տվյալ configured win cap-ը:

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/setup/betmode>

Source / Աղբյուր: <https://stake-engine.com/docs/math/source-files/state>

ԲԱՑ ՀԱՐՑ. հանրային պաշտոնական docs-ում չի գտնվել ընդհանուր պարտադիր RTP range կամ մեկ global numeric max-win cap: 97% նման թվերը օրինակային target-ներ են, ոչ հրապարակված universal limit:

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

Artifact	Required / role	Official format
index.json	Required for math publication	JSON; modes[] with name, cost, events, weights
Lookup table	Required per mode	CSV: uint64 ID, weight/probability, payout
Book/game logic	Required per mode	JSONL compressed with Zstandard (.zst)
config_math.json	SDK output	Optimization/RTP setup
config_fe.json	SDK output	Frontend game config
config.json	SDK output	RGS-facing mode + hash metadata
force*.json	Analysis/optimizer support	Developer-recorded criteria/event indices

4. Web / Frontend SDK

English

CONFIRMED: the official frontend SDK is described as a Pixijs/Svelte toolkit for browser games. The documented repository architecture uses SvelteKit, TypeScript, Turborepo, Storybook, XState, pnpm and an in-house pixi-svelte package. The docs' setup page specifies Node 18.18.0 and pnpm 10.5.0 for that tutorial; the separate basic RGS example uses Svelte 5 + Vite and notes NPM 22.16.0. These are example/setup versions, not stated universal runtime requirements.

Source / Աղբյուր: <https://stake-engine.com/docs/front-end>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/dependencies>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/getting-started>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/example>

CONFIRMED: use of the frontend SDK is optional. The simple RGS tutorial demonstrates a custom Svelte/Vite static frontend and instructs developers to upload the contents of dist/ under frontend files. The web SDK can be ignored in favor of a custom frontend as long as Engine communication and approval constraints are met.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/example>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/ui>

CONFIRMED: the web SDK consumes a 'book' returned by the RGS and processes book events sequentially. The documented playBookEvents() flow iterates through events in order, dispatching handlers based on event.type; event order therefore determines animation order.

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/flowchart>

Source / Աղբյուր: <https://github.com/StakeEngine/web-sdk>

CONFIRMED: Storybook is central to the sample workflow. The SDK supports testing an entire book, random books for a mode, a sequence of book events, or an individual event handler. This is especially useful for replaying rare deterministic states such as max wins.

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/storybook>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

CONFIRMED: the approval rules require mobile support on commonly used devices, correct scaling of all UI functionality, and support for Stake's mini-player/popout view without visibly distorting the board. Games must also tolerate currencies and languages used during review.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/rgs-communication>

CONFIRMED: all images and fonts must be loaded from Engine's CDN, and the build must consist only of static files and cannot reach external sources. External font/CDN requests are therefore a rejection/communication risk.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/rgs-communication>

CONFIRMED: UI approval requires rules/paytable access, mode cost explanations, RTP and max-win disclosure, selectable RGS bet levels, current balance, final win display, a mute control, spacebar mapped to bet, and

controlled autoplay behavior. If autoplay exists, the player must confirm it; one click cannot initiate indefinite consecutive bets.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

CONFIRMED: Bet Replay is mandatory for new games. In replay mode the frontend must detect `replay=true`, fetch a specific round from `GET {rgs_url}/bet/replay/{game}/{version}/{mode}/{event}`, disable all wagering/session actions, reproduce the full animation and result, and offer replay controls.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

Հայերեն

ՀԱՍՏԱՏՎԱԾ. պաշտոնական frontend SDK-ը Pixijs/Svelte browser toolkit է: Docs-ում նշվում են նաև SvelteKit, TypeScript, Turborepo, Storybook, XState, npm և pixi-svelte: Բայց SDK-ը պարտադիր չէ. կարելի է ունենալ սեփական static frontend, եթե RGS contract-ը և approval requirements-ը պահվում են:

Source / Աղբյուր: <https://stake-engine.com/docs/front-end>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/example>

ՀԱՍՏԱՏՎԱԾ. frontend-ը ստանում է book-ը և event-երը հերթով խաղարկում է: Event order-ը animation order-ի համար կարևոր է, ու յուրաքանչյուր custom event type-ի համար պետք է handler լինի:

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/flowchart>

ՀԱՍՏԱՏՎԱԾ. նոր խաղերի համար Bet Replay-ը պարտադիր է: Replay mode-ը session չի պահանջում, betting controls-ը անջատված են, իսկ frontend-ը պետք է նույն event-ը ամբողջությամբ վերարտադրի:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

ՀԱՍՏԱՏՎԱԾ. mobile responsiveness, mini-player/popout support, exact bet levels, balance, mute, rules, RTP/max-win display, և Engine CDN-only assets/font loading-ը review-ի մասն են:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/rgs-communication>

5. RGS API: endpoints, lifecycle, settlement and errors

English

CONFIRMED: the game is loaded with query parameters including sessionID, lang, device and rgs_url. rgs_url must be used dynamically and must not be hardcoded. sessionID is required for authenticated wallet calls.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

CONFIRMED: the normal lifecycle begins with `POST /wallet/authenticate`. If authentication has not occurred, subsequent wallet calls return HTTP 400 with `ERR_IS`. Authenticate returns balance, config (including minBet, maxBet, stepBet, defaultBetLevel, betLevels and jurisdiction controls) and a round object that may be active or last completed.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

CONFIRMED: `POST /wallet/play` takes amount, sessionID and mode. It initiates a game round and debits the bet. The play response contains updated balance and round data. In the books model, the round/event state corresponds to a selected pre-generated simulation.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

Source / Աղբյուր: <https://stake-engine.com/docs>

CONFIRMED: `POST /wallet/end-round` completes the round, triggers the payout and closes round activity. The basic documented flow is `authenticate -> play -> render animations -> end-round`. A positive win in the simple tutorial is manually finalized with `end-round`.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/example>

CONFIRMED: `POST /wallet/balance` retrieves current balance. The official TypeScript client can also emit balance update events and periodically refresh balance after player inactivity.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

Source / Աղբյուր: <https://github.com/StakeEngine/ts-client>

CONFIRMED: `POST /bet/event` persists an event marker within an active round. The docs describe it as useful for resuming gameplay after disconnect. Authenticate can return `round.event`, allowing the frontend to continue displaying the selected book from the appropriate point.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

CONFIRMED: replay uses GET {rgs_url}/bet/replay/{game}/{version}/{mode}/{event}, which does not require a player session. The response contains payoutMultiplier, costMultiplier and a game-specific state object.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

CONFIRMED: money values in wallet APIs use six decimal places of integer precision: 1,000,000 represents 1 unit. Bet amounts must be between minBet and maxBet and divisible by stepBet. The frontend is encouraged to use returned betLevels.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

CONFIRMED: documented client errors are ERR_VAL invalid request, ERR_IPB insufficient balance, ERR_IS invalid session/session timeout, ERR_ATE authentication/token expired, ERR_GLE gambling limits exceeded and ERR_LOC invalid location. Server errors include ERR_GEN and ERR_MAINTENANCE.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

GAP: the public docs reviewed do not define idempotency keys, retry semantics, exact timeout values, concurrency behavior for double-clicked /play requests, or a complete response schema for every round field. An AI implementation should not invent these details; use the official client and test environment, then confirm with Engine support.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

Հայերեն

ՀԱՍՏԱՏՎԱԾ. հիմնական flow-ը /wallet/authenticate → /wallet/play → book event-երի ցուցադրում → /wallet/end-round է: Authenticate չանելու դեպքում հետագա wallet call-երը կարող են ստանալ 400 ERR_IS:

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

ՀԱՍՏԱՏՎԱԾ. /wallet/play-ը debit է անում bet-ը և վերադարձնում round-ը, իսկ /wallet/end-round-ը վերջացնում է round-ը և կատարում payout settlement-ը: /bet/event-ը նախատեսված է ընթացիկ event position-ը պահպանելու և disconnect-ից հետո resume անելու համար:

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

ՀԱՍՏԱՏՎԱԾ. API monetary values-ը 6 decimal integer precision ունի՝ 1,000,000 = 1 currency unit: Bet-ը պետք է լինի minBet/maxBet սահմաններում և բաժանվի stepBet-ի վրա:

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

ԲԱՑ ՀԱՐՑ. public docs-ը չի սահմանում idempotency/retry contract, double-play concurrency semantics կամ բոլոր round field-երի ամբողջական schema-ն: Դրանք պետք է ստուգվեն Engine test environment/support-ի հետ, ոչ թե ենթադրվեն:

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

Endpoint	Purpose	Key implementation note
POST /wallet/authenticate	Validate session; config/balance/round	Must be first authenticated call
POST /wallet/play	Debit and start round	Pass amount + mode; returns selected round
POST /wallet/end-round	Finalize payout/round	Ends all activity for round
POST /wallet/balance	Refresh balance	Use for periodic balance refresh
POST /bet/event	Persist in-round event marker	Resume/display position; not documented as payout change
GET /bet/replay/{game}/{version}/{mode}/{event}	Public replay	No authenticated player session

6. Game packaging, upload and validation

English

CONFIRMED: Engine uploads must be static. Developers may use their own frontend or math generator, but the final files must match Engine's expected formats. The RGS performs preliminary math format checks and analyzes payout multipliers/probabilities.

Source / Աղբյուր: <https://stake-engine.com/docs>

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

CONFIRMED: for a single math mode the minimum publication package is index.json + one lookup CSV + one .jsonl.zst event/book file. Additional modes add corresponding entries/files. The index structure is strictly enforced.

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

CONFIRMED: SDK-generated publishable math files are placed under library/publish_files/. The basic RGS tutorial generates a Zstandard-compressed result set, lookup table and index.json there.

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/example>

CONFIRMED: a custom frontend example uses a normal static build output and uploads the contents of dist/ as frontend files. The Vite example explicitly sets base: './', which avoids absolute asset-path assumptions in the hosted CDN environment.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/example>

CONFIRMED: frontend builds must not fetch external resources. All images/fonts must come through Engine CDN/static package. Network-console errors, missing assets, visual bugs, unsupported small/popout view or mobile UI breakage can cause review issues.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/rgs-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

CONFIRMED: submission also requires tile assets: background, foreground and provider logo. The background + foreground combined must not exceed 3 MB; the docs prescribe high-resolution PNG/JPG formats and naming conventions.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-tile-requirements>

CONFIRMED: submitted games must use unique audio/visual assets. Assets copied from the web-sdk samples will not be approved. IP/copyright infringement, Stake-branded assets, third-party pre-purchased/licensed games already present elsewhere, underage-appealing content, offensive/explicit/poor-taste material, and insufficient quality can lead to rejection.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

COMMON REJECTION / HOLD RISKS, confirmed by official review pages: incomplete checklist; low-quality/generic AI art; shallow gameplay; inconsistent visuals; performance/load issues; missing replay; rules/RTP/max-win communication gaps; external network calls; and non-original assets. The submission page warns that incomplete/non-compliant submissions may be held and deprioritized.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/submission-checklist>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-quality-rankings>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

GAP: a complete public ACP click-by-click upload specification, hard frontend bundle-size ceiling, maximum file count, compression limit, filename charset restrictions and automated rejection-code catalog were not found in the public pages reviewed. The 3 MB rule found is specifically for tile background + foreground, not the whole game bundle.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-tile-requirements>

Source / Աղբյուր: <https://stake-engine.com/docs>

Հայերեն

ՀԱՍՏԱՏՎԱԾ. Engine upload-ը static files է: Math-ի նվազագույն մեկ-mode package-ը index.json + lookup CSV + .jsonl.zst book է: SDK-ը publishable math ֆայլերը դնում է library/publish_files/:

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

ՀԱՍՏԱՏՎԱԾ. custom frontend-ը նույնպես կարող է լինել սովորական static dist build: External network resource-ները արգելված են, images/fonts-ը պետք է Engine CDN-ից լինեն, իսկ mobile/mini-player/visual stability-ն review-ի մաս է:

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/example>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/rgs-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

ՀԱՍՏԱՏՎԱԾ. game tile-ի համար պետք են background, foreground և provider logo, background+foreground-ը միասին առավելագույնը 3 MB:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-tile-requirements>

ԲԱՅ ՀԱՐՑ. public docs-ում չկա ամբողջ ACP upload UI-ի քայլ առ քայլ specification, ամբողջ game bundle-ի hard size cap կամ automated rejection code catalog:

Source / Աղբյուր: <https://stake-engine.com/docs>

7. Certification, compliance and review process

English

CONFIRMED: a review request is tied to a specific frontend version and math version. Engine technical support reviews functionality, clarity, communication and technical performance, and can request changes or reject case-by-case. A short promotional description of theme and mechanics must accompany the request.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

CONFIRMED: the submission page says three independent reviewers are assigned. Each scores design, gameplay and math compliance from 0 to 3 stars, with ratings hidden until all three are submitted. That page says average ≥ 1 star results in approval for production, while average < 1 star results in rejection and possible resubmission.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/submission-checklist>

CONFLICT IN OFFICIAL MATERIAL: the separate Quality Rankings page says a one-star game is 'not published' and the developer will be asked to improve/resubmit, while the Submission Checklist says an average ≥ 1 is approved. The public docs therefore do not give a perfectly consistent publication threshold. Treat this as a GAP to confirm directly with Engine.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/submission-checklist>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-quality-rankings>

CONFIRMED: review can be as quick as a couple of hours, but incomplete/non-compliant submissions can extend the process to weeks. This is not an SLA; no guaranteed review timeline is published in the reviewed pages.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/submission-checklist>

CONFIRMED: Bet Replay is mandatory for new games and is tested in review. Reviewers may request event IDs for normal win, big win, max win, loss and bonus trigger scenarios.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

CONFIRMED: review includes RGS bet-level verification, currencies/languages, UI behavior, mobile/popout scaling, rules/paytable, exact RTP/max-win disclosure, network errors and matching game behavior to written rules.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/rgs-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

CONFIRMED: Stake US introduces social-casino wording restrictions. The RGS exposes social=true/false and the docs recommend a sweeps_<lang> translation file. Terms such as bet, cash, wager, deposit and withdraw have prescribed alternative wording for US social mode.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/jurisdiction-requirements>

CONFIRMED: after approval, only minor visual fixes are normally permitted unless Engine requests otherwise. The published rule says underlying math changes, new game modes or gameplay-mechanic modifications are not allowed after release.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

GAP: no requirement for a named external lab certificate, GLI/BMM test report, jurisdiction-by-jurisdiction mathematical certificate, source-code audit, or formal certification fee was found in the public material reviewed. This does not prove such obligations never apply; it means the current public docs examined here do not state them.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

Հայերեն

ՀԱՍՏԱՏՎԱԾ. review request-ը կապվում է կոնկրետ frontend version-ի և math version-ի հետ: Engine-ը ստուգում է functionality, clarity, communication և technical performance:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

ՀԱՍՏԱՏՎԱԾ. submission page-ը նկարագրում է 3 անկախ reviewer՝ design/gameplay/math compliance 0-3 star գնահատմամբ: Բայց մյուս Quality Rankings էջը 1-star-ի publication status-ը այլ կերպ է նկարագրում: Սա պաշտոնական նյութերի ներքին հակասություն է և պետք է support-ի հետ ճշտել:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/submission-checklist>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-quality-rankings>

ՀԱՍՏԱՏՎԱԾ. review-ը կարող է տևել մի քանի ժամ, բայց incomplete/non-compliant game-ը կարող է շաբաթներով ձգվել: Սա guaranteed SLA չէ:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/submission-checklist>

ՀԱՍՏԱՏՎԱԾ. Bet Replay-ը նոր խաղերի approval-ի պարտադիր մաս է, և reviewer-ը կարող է պահանջել տարբեր edge-case event ID-ներ:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

8. Crash/Burst mechanics: static outcomes, dynamic gameplay, and the real cashout boundary

Correction to the earlier interpretation: STATIC FILES / PRE-GENERATED OUTCOMES ≠ STATIC GAMEPLAY.

CONFIRMED: Stake Engine's official documentation says games are uploaded as static files and that outcomes can be pre-generated and selected by weight. Separately, Stake's official casino catalog contains Stake Engine Burst titles with crash-style, arcade-style, physics-like and progressive multiplier presentations. The correct model is therefore: the authoritative monetary outcome can be predetermined while the frontend still presents a rich, time-based, interactive-looking sequence.

Source / Աղբյուր: [Stake Engine API Documentation](#)

Source / Աղբյուր: [Stake - Burst Games](#)

Source / Աղբյուր: [Stake - Angry Balls](#)

Source / Աղբյուր: [Stake - Penguins Can Fly](#)

OFFICIAL-SOURCE CONFLICT: the Web SDK README explicitly distinguishes stateless games from stateful games and uses Mines as the example of a stateful game that requires multiple RGS requests. However, the current Approval Guidelines say Engine games submitted for publication are strictly stateless and prohibit continuation/early cashout. The safest interpretation is that the SDK architecture contains or documents broader stateful capability, while current third-party publication policy is narrower. This must be confirmed with Engine before building a truly stateful Mines/cashout product.

Source / Աղբյուր: [Official StakeEngine Web SDK](#)

Source / Աղբյուր: [Stake Engine Approval Guidelines](#)

English - confirmed constraints

CONFIRMED: crash-style or Burst-style gameplay itself is compatible with Stake Engine; Stake already publishes Engine games in that category. The incompatible part, under the current published approval rule, is a TRUE EARLY CASHOUT in which the player makes an in-round economic decision that changes the wallet-settled payout after the bet has started.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

CONFIRMED: the selected book already contains the payoutMultiplier and ordered event state. The general disclaimer requires developers to tell players that winnings are settled according to the RGS result and not browser events. This makes frontend-held timing or release timing unsuitable as an authoritative source of payout.

CONFIRMED EXAMPLES: Angry Balls (Coreffect Interactive) is officially tagged Stake Engine + Burst Games and described by Stake as having crash-game mechanics. Penguins Can Fly (Paperclip Gaming) is officially tagged Stake Engine + Burst Games; its multiplier grows over the flight and is modified by collected items. These are strong primary-source examples that a Run Daddy Run-style moving character, increasing multiplier display, hazards and an eventual loss/win can be presented on Engine.

Source / Աղբյուր: [Stake - Angry Balls](#)

Source / Աղբյուր: [Stake - Penguins Can Fly](#)

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/general-disclaimer>

CONFIRMED: frontend event handlers may animate a long sequence and increment displayed wins along the path, but the final payout is predetermined. The approval docs explicitly require incremental display to ultimately match the final payout when an outcome contains multiple winning actions.

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/flowchart>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

CONFIRMED: /bet/event can save a viewer-progress marker. It can support disconnect-resume for a long 'run' sequence, but no official source says it changes the book, payoutMultiplier, selection probability, or wallet settlement.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

English - safe engineering interpretations to discuss with Engine (INFERENCES)

INFERENCE A - visual crash game, predetermined settlement: /play selects a book whose events define a run trajectory and crash point. The character runs through milestones, UI reveals a growing displayed multiplier, and the predetermined end event settles. A button may skip/reveal/accelerate animation, but should not change the economic outcome. This preserves the books model but is not 'cash out anytime' in the player-choice sense.

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/events>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

INFERENCE B - pre-bet risk selection: separate BetModes could represent different predefined risk profiles or target curves selected before /play. Because mode is supplied to /wallet/play and each BetMode has its own cost/RTP/max-win/distribution, pre-round choice is structurally compatible with the documented API. It does not provide mid-round cashout.

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/setup/betmode>

INFERENCE C - non-economic hold interaction: a hold gesture could influence animation speed, camera movement, cosmetic choices or reveal pacing while the monetary result remains unchanged. This may preserve the desired tactile 'hold to run' feel, but Engine approval should be obtained because reviewers judge whether actual behavior matches game rules.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

DO NOT IMPLEMENT WITHOUT WRITTEN ENGINE CONFIRMATION: any design where release/press time chooses a payout checkpoint; where multiple payout branches remain economically open after /play; where the client sends a 'cashout multiplier' to be settled; or where /bet/event is treated as a cashout endpoint. None of those behaviors is documented, and the first two directly resemble the forbidden early-cashout/continuation mechanics.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

Հայերեն - crash մեխանիկայի իմաստը

ՀԱՍՏԱՏՎԱԾ. crash/Burst style խաղը ինքնին թույլատրելի ուղղություն է. Stake-ում արդեն կան Stake Engine Burst խաղեր: Խնդիրը միայն այն կետն է, երբ «cash out anytime»-ը /play-ից հետո խաղացողին թույլ է տալիս ընտրել payout checkpoint-ը և այդ գործողությամբ փոխել wallet-ի վերջնական settlement-ը. current Approval Guidelines-ը հենց այդ early-cashout/continuation մոդելն է արգելում:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

ՀԱՍՏԱՏՎԱԾ. book-ը արդեն պարունակում է payoutMultiplier-ը և ordered event sequence-ը, իսկ պաշտոնական disclaimer-ը պահանջում է ասել, որ վճարումը որոշվում է RGS արդյունքով, ոչ browser event-երով:

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/general-disclaimer>

ԵՆԹԱԴՐՈՒԹՅՈՒՆ՝ որը պետք է նախապես հաստատել Engine-ի հետ. կարելի է պահել crash-like visual experience՝ նախապես ընտրված crash point-ով և աճող multiplier animation-ով, բայց button-ը միայն animation/pacing փոխի, ոչ payout-ը: Կարելի է նաև pre-bet BetMode-երով առաջարկել տարբեր risk profile-ներ:

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/setup/betmode>

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/events>

ՉԻ ԿԱՐԵԼԻ ՀԻՄՆՎԵԼ որպես փաստ. /bet/event-ը cashout endpoint չէ: Պաշտոնական docs-ում այն միայն progress marker/resume մեխանիզմ է:

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

9. Gaps & open questions that must be resolved before production

English

- Cashout boundary / Burst approval: Burst/crash-style presentation is clearly publishable on Engine. Open question: is there any approved third-party pattern where an in-round player action changes the final monetary settlement, despite the current early-cashout prohibition?
- RTP limits: What exact min/max RTP values are accepted for Stake and Stake US? No universal range is published in reviewed public docs.
- Global max-win limit: Is there an operator-level numeric cap beyond per-BetMode max_win? Public docs do not state one.
- GGR contract definition: What deductions, refunds, chargebacks, bonuses, taxes or operator costs are included/excluded from the advertised 10% GGR royalty?
- Payment mechanics: Supported payout rails/currencies, minimum threshold, invoice/KYC/tax requirements, failed-payment handling.
- ACP onboarding: Exact account/team approval, KYC/KYB, legal agreement and permissions needed before upload.
- Frontend hard limits: Maximum bundle size/file count, supported MIME types, filename restrictions and upload timeouts.
- RGS reliability contract: Idempotency, retries, duplicate /play semantics, timeout values, rate limits and concurrent-session behavior.
- Review threshold conflict: Submission page says average ≥ 1 approves; Quality Rankings says 1-star is not published.
- External certification: Whether any specific game/jurisdiction requires an external testing lab beyond Engine's internal math/technical review.

- Post-release emergency changes: How math/security defects are handled given the published restriction on math/gameplay changes after approval.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/submission-checklist>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-quality-rankings>

Source / Աղբյուր: <https://stake-engine.com/>

Հայերեն

- Crash exception policy: արդյո՞ք Engine-ը երբևէ գրավոր exception է տալիս mid-round economic cashout-ի համար: Public rule-ը currently արգելում է այն:
- RTP limits: Stake/Stake US-ի պարտադիր min/max RTP-ը public docs-ում չի հաստատվել:
- Global max-win: per-BetMode max_win-ից բացի operator-level hard numeric cap public docs-ում չկա:
- 10% GGR contract: պետք է ճշտել GGR-ի հաշվարկի deductions, refunds, bonuses, tax և այլ պայմանները:
- ACP onboarding: KYC/KYB, legal agreement, permissions և upload-ի account flow-ը ամբողջությամբ public չէ:
- RGS idempotency: retries, duplicate play, timeout/rate-limit semantics-ը public docs-ում ամբողջական չեն:
- Review threshold: երկու պաշտոնական էջերի star threshold wording-ը հակասական է:

10. Recommended AI-team implementation blueprint

English

This blueprint now separates two questions: (1) can Engine support a Run Daddy Run-style crash/Burst presentation? Yes - official Stake Engine titles demonstrate that it can. (2) can the player's release/cashout timing change the monetary settlement after /play? Current approval rules say no, so that single interaction remains the approval gate.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

Phase 0 - interaction gate: proceed with the runner/Burst presentation. Before implementing wallet-affecting mid-round cashout, obtain written Engine clarification. If cashout cannot alter settlement, design the hold/release input as pacing, reveal, skip, cosmetic control, or move the risk/target choice to pre-bet BetModes.

Phase 1 - math prototype: Build a custom Math SDK game folder or compatible generator. Define BetMode(s), target RTP, max_win and distribution criteria. Generate 100-1000 uncompressed books first and inspect every custom event contract.

Phase 2 - deterministic run event model: Represent the runner timeline as ordered events: start, milestone/progress, multiplier-display update, hazard/reveal, finalWin/end. The final payoutMultiplier must already match the lookup CSV.

Phase 3 - simulation scale: After correctness, generate a large diverse book set. The official quickstart typically recommends 100k+ outcomes per mode for production diversity. Run optimization and analysis/PAR outputs.

Phase 4 - frontend: Use custom Pixijs/Svelte or another static stack. Implement one deterministic handler for each event type; no payout calculation in client. Respect rgs_url and authenticate config.

Phase 5 - resume/replay: Use /bet/event only for in-round viewing progress if needed. Implement mandatory public Bet Replay and edge-case event IDs.

Phase 6 - compliance UI: Rules, RTP, max win, bet controls, balance, mute, spacebar, responsive mobile and mini-player. Ensure US social wording when social=true.

Phase 7 - packaging: Static frontend dist; no external calls; Engine-hosted assets/fonts. Math: index.json + mode CSV + .jsonl.zst books. Validate hashes/format and upload.

Phase 8 - review evidence: Prepare event IDs for loss/normal/big/max/feature cases, tile assets, short description, rules, and internal QA matrix.

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

Հայերեն

ԹԱՐԱՄԱՅՎԱԾ ԵԶՐԱԿԱՑՈՒԹՅՈՒՆ. Run Daddy Run-ի նման Burst/crash presentation-ը Engine-ի համար իրատեսական է և պաշտոնական Stake Engine խաղերը դա հաստատում են: Approval blocker-ը ամբողջ mechanic-ը չէ, այլ միայն այն տարբերակը, երբ խաղացողի mid-round release/cashout գործողությունը փոխում է wallet settlement-ը:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

- Փուլ 0. approval gate - մինչև coding-ը ճշտել՝ hold interaction-ը կարող է լինել միայն cosmetic, և mid-round settlement-ը ամբողջությամբ արգելված է:
- Փուլ 1. math prototype - սահմանել BetMode, RTP, max_win, distribution criteria և գներացնել փոքր uncompressed book set՝ event contract-ը debug անելու համար:
- Փուլ 2. runner event model - runner progress-ը դարձնել ordered events, բայց final payoutMultiplier-ը նախապես որոշված պահել:
- Փուլ 3. scale - correctness-ից հետո մեծացնել simulations-ը, անել optimization և analysis/PAR:
- Փուլ 4. frontend - յուրաքանչյուր event type-ի deterministic handler, payout calculation չանել client-ում:
- Փուլ 5. replay/resume - /bet/event միայն progress marker-ի համար, իսկ mandatory Bet Replay-ը լիարժեք իրականացնել:
- Փուլ 6. compliance - rules, RTP, max win, bet levels, balance, mute, spacebar, mobile, mini-player, US social wording:
- Փուլ 7. package/upload - static dist, no external calls, index.json + CSV + .jsonl.zst math files:

11. Glossary / Բառարան

Term	English definition	Հայերեն
ACP	Admin Control Panel; the Engine interface referenced for uploading compatible game files.	Admin Control Panel՝ upload/publish կառավարման ինտերֆեյս:
BetMode	A configured game mode with name, cost, RTP, max win, distributions and behavior flags.	Խաղի mode՝ cost/RTP/max_win/distribution պարամետրերով:
Book	One pre-generated simulation outcome containing payoutMultiplier and ordered events.	Մեկ նախապես գներացված outcome՝ payoutMultiplier + event sequence:
Book event	A JSON object describing one player-visible state/action in a book.	JSON event՝ frontend-ին ցուցադրվող վիճակ/գործողություն:
RGS	Remote Game Server; authenticates, selects outcomes, handles wallet round lifecycle and replay.	Remote Game Server՝ auth/outcome/wallet/replay backend:
Lookup table	CSV mapping simulation IDs to weights/probabilities and payout multipliers.	CSV՝ simulation ID → weight/probability + payout multiplier:
Weight	Unsigned integer selection weight used in the discrete outcome draw.	Outcome ընտրության integer weight:
RTP	Return to Player; exactly computable from published payouts and weights in this finite model.	Return to Player՝ weighted outcome-ներից հաշվվող վերադարձ:
payoutMultiplier	The monetary multiplier attached to the selected simulation/book.	Ընտրված book-ի վերջնական payout multiplier:
cost multiplier	BetMode multiplier applied to the base bet amount.	Base bet-ի վրա կիրառվող mode cost multiplier:
force file	SDK analysis file that indexes simulations by recorded criteria/events.	Simulation-ները criteria/event-երով ինդեքսավորող analysis file:
config_fe.json	Frontend configuration generated by the Math SDK.	Frontend-ի համար գներացված config:
config_math.json	Optimization/RTP configuration generated by the Math SDK.	Optimizer/RTP config:
config.json	RGS-facing mode and file-hash metadata generated by the Math SDK.	RGS-ի mode/hash metadata:
Bet Replay	Mandatory public replay mode that loads a specific simulation without an authenticated session.	Պարտադիր public replay mode՝ առանց active session-ի:
Stateless	Each bet is independent; the current rules prohibit continuation and early cashout.	Յուրաքանչյուր bet անկախ է, continuation/early cashout արգելված են:

Provably Fair	Published outcomes/probabilities plus seed-based verifiable selection for compatible stateless games.	Հրապարակված outcomes/probabilities + seed-based ստուգելի ընտրություն:
---------------	---	---

12. Official-source inventory consulted

Only official Stake Engine / StakeEngine sources are used for factual claims in this report. Community mirrors and unofficial tutorials were excluded from the evidence base.

Source / Աղբյուր: <https://stake-engine.com/>

Source / Աղբյուր: <https://stake-engine.com/docs>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/wallet>

Source / Աղբյուր: <https://stake-engine.com/docs/rgs/example>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/dependencies>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/getting-started>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/storybook>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/flowchart>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/file-structure>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/context>

Source / Աղբյուր: <https://stake-engine.com/docs/front-end/ui>

Source / Աղբյուր: <https://stake-engine.com/docs/math>

Source / Աղբյուր: <https://stake-engine.com/docs/math/setup>

Source / Աղբյուր: <https://stake-engine.com/docs/math/quick-start>

Source / Աղբյուր: <https://stake-engine.com/docs/math/math-file-format>

Source / Աղբյուր: <https://stake-engine.com/docs/math/sdk-directory>

Source / Աղբյուր: <https://stake-engine.com/docs/math/high-level-structure/game-structure>

Source / Աղբյուր: <https://stake-engine.com/docs/math/high-level-structure/game-format>

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/setup/configs>

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/setup/betmode>

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/wins>

Source / Աղբյուր: <https://stake-engine.com/docs/math/game-state-structure/events>

Source / Աղբյուր: <https://stake-engine.com/docs/math/source-files/outputs>

Source / Աղբյուր: <https://stake-engine.com/docs/math/source-files/state>

Source / Աղբյուր: <https://stake-engine.com/docs/math/source-files/events>

Source / Աղբյուր: <https://stake-engine.com/docs/math/optimization-algorithm>

Source / Աղբյուր: <https://stake-engine.com/docs/math/utilities>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/submission-checklist>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-replay-requirements>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-quality-rankings>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/rgs-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/front-end-communication>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/game-tile-requirements>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/general-disclaimer>

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines/jurisdiction-requirements>

Source / Աղբյուր: <https://stake-engine.com/fair>

Source / Աղբյուր: https://stake-engine.com/docs-content/distribution_optimization.pdf

Source / Աղբյուր: <https://github.com/StakeEngine>

Source / Աղբյուր: <https://github.com/StakeEngine/math-sdk>

Source / Աղբյուր: <https://github.com/StakeEngine/web-sdk>

Source / Աղբյուր: <https://github.com/StakeEngine/ts-client>

Source / Աղբյուր: <https://github.com/StakeEngine/docs>

Final decision note / Վերջնական որոշման նշում

For the requested AI game team, the corrected decision is: do NOT discard the game concept. Stake Engine demonstrably supports Burst/crash-style arcade games. Build the runner, book-event timeline, multiplier progression and hazards around a predetermined authoritative outcome. Treat only true wallet-affecting mid-round cashout as unresolved/prohibited unless Engine gives written approval.

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>

Ձեր AI development team-ի համար ուղղված եզրակացությունը սա է. խաղի գաղափարը պետք չէ մերժել: Stake Engine-ը փաստացի աջակցում է Burst/crash-style arcade խաղերի: Կարելի է կառուցել runner-ը, multiplier progression-ը, obstacles/hazards-ը և book-event timeline-ը: Միայն իրական wallet-affecting mid-round cashout-ը պահեք որպես approval blocker, մինչև Engine-ից գրավոր հաստատում չլինի:

Source / Աղբյուր: <https://stake-engine.com/docs/approval-guidelines>