

Project Configuration Report

wifi_http_otaf_camera

Target Device:

Target Part: SIWG917Y111MGABA

Boards:

- SiWx917Y Module Wi-Fi 6 and Bluetooth LE Explorer Kit Board (BRD2708A Rev A02)

Target SDK

Simplicity SDK Suite v2025.6.3: Bluetooth 10.1.2, Bluetooth Mesh 9.1.0, Connect 4.1.3, EmberZNet 8.2.2.0, Micrium OS Kernel 5.18.02, OpenThread 2.7.3.0 (GitHub-fb0446f53), Platform 5.2.3.0, RAIL 2.19.3, Sidewalk 2.7.0, Silicon Labs AI/ML 2.1.3, Silicon Labs Matter 2.7.0-1.4, USB 1.5.1.0, Wi-Fi SDK 3.5.2, Wi-SUN 2.9.2, Z-Wave SDK 7.24.3.0
SDK Version: 2025.6.3

Project Generators

- VS Code (GCC)

Installed Software Components:

- Board

- **Radio Board**

- BRD2708A**

- Configurable: false

- Common

- WiSeConnect3 Common Library**

- Sources: sl_utility.c

- Configurable: false

- Device

- **Si91x**

- MCU

- Common

- System Calls**

- Sources: syscalls.c

- Configurable: false

- HAL

- Soft Reset**

- Sources: sl_si91x_hal_soc_soft_reset.c

- Configurable: false

- Memory Configuration

Default RAM Memory Configuration

Configurable: false

- Wireless

- Buffer Manager

Memory Pool buffers With Quota

Sources: mem_pool_buffer_quota.c

Configurable: false

- Network Stack

Internal Network Stack

Sources: sl_si91x_http_client_callback_framework.c,

sl_si91x_net_internal_stack.c, sl_net_ping.c

Configurable: false

- Platform

- Device

- Si91x
 - MCU
 - Family
 - SIWG917Y

SIWG917Y111MGABA

Sources: system_si91x.c, startup_si91x.c

Configurable: false

- Protocol

Wi-Fi

Sources: sl_wifi_callback_framework.c, sl_wifi.c

Configurable: false

- RTOS

- FreeRTOS

FreeRTOS Heap 4

Sources: heap_4.c

Configurable: false

FreeRTOS Kernel

Sources: event_groups.c, timers.c, list.c, queue.c, stream_buffer.c, tasks.c, croutine.c

Configurable: true

Configs: FreeRTOSConfig.h

- Resources

WiSeConnect3 Resources

Configurable: true

Configs: sl_net_default_values.h, lwipopts.h, sl_wifi_region_db_config.h, aws_iot_config.h

- Services

- System Setup

- System Setup (sl_main)

- Configurable: true

- Configs: sl_main_start_task_config.h

- Service

- Network Management

- Network Manager

- Sources: sli_net_common_utility.c, sl_net_for_dual_stack.c, sl_net_for_lwip.c,
sl_net_basic_certificate_store.c, sl_net.c

- Configurable: false

- Configuration

- Basic Network Configuration Manager

- Sources: sl_net_basic_profiles.c, sl_net_credentials.c

- Configurable: false

Pins:

Peripherals:

Peripheral	Software Component	Custom Peripheral Name
I2C0		
I2C1		
ULP_I2C		
USART0		
UART1		
QEI		
OPAMP1		
OPAMP2		
OPAMP3		
ULP_UART		
SSI_MASTER		
SSI_SLAVE		
HSPI_SECONDARY		
ULP_SSI		
GSPI_MASTER		
I2S0		
ULP_I2S		
SCT		
PWM_CH0		
PWM_CH1		
PWM_CH2		
PWM_CH3		
PWM		

SDC_CH1		
SDC_CH2		
SDC_CH3		
SDC_CH4		
ADC_CH1		
ADC_CH2		
ADC_CH3		
ADC_CH4		
ADC_CH5		
ADC_CH6		
ADC_CH7		
ADC_CH8		
ADC_CH9		
ADC_CH10		
ADC_CH11		
ADC_CH12		
ADC_CH13		
ADC_CH14		
ADC_CH15		
ADC_CH16		
COMP1		
COMP2		
DAC0		
DAC1		
SYSRTC		
UULP_VBAT_GPIO		
GPIO		