
acsefunctions

Release 0.1

Your Name

Apr 19, 2025

CONTENTS

Python Module Index	3
Index	5

`acsefunctions.special.cosh(x, n_terms=20)`

Compute the hyperbolic cosine function $\cosh(x)$ using a Taylor series approximation.

Parameters

- **x** (*float or numpy.ndarray*) – Input value(s) for which to compute $\cosh(x)$.
- **n_terms** (*int, optional*) – Number of terms to use in the Taylor series (default is 20).

Returns

Computed $\cosh(x)$ for the input(s).

Return type

float or numpy.ndarray

Examples

```
>>> cosh(0)
1.0
>>> cosh(1)
1.5430806348152437
>>> cosh(np.array([0, 1, 2]))
array([1.          , 1.54308063, 3.76219569])
```

`acsefunctions.special.exp(x, n_terms=20)`

Compute the exponential function e^x using a Taylor series approximation.

Parameters

- **x** (*float or numpy.ndarray*) – Input value(s) for which to compute e^x .
- **n_terms** (*int, optional*) – Number of terms to use in the Taylor series (default is 20).

Returns

Computed e^x for the input(s).

Return type

float or numpy.ndarray

Examples

```
>>> exp(0)
1.0
>>> exp(1)
2.718281828459045
>>> exp(np.array([0, 1, 2]))
array([1.          , 2.71828183, 7.3890561  ])
```

`acsefunctions.special.sinh(x, n_terms=20)`

Compute the hyperbolic sine function $\sinh(x)$ using a Taylor series approximation.

Parameters

- **x** (*float or numpy.ndarray*) – Input value(s) for which to compute $\sinh(x)$.
- **n_terms** (*int, optional*) – Number of terms to use in the Taylor series (default is 20).

Returns

Computed $\sinh(x)$ for the input(s).

Return type

float or numpy.ndarray

Examples

```
>>> sinh(0)
0.0
>>> sinh(1)
1.1752011936438014
>>> sinh(np.array([0, 1, 2]))
array([0.          , 1.17520119, 3.62686041])
```

`acsefunctions.special.tanh(x, n_terms=20)`Compute the hyperbolic tangent function $\tanh(x)$ as $\sinh(x) / \cosh(x)$.**Parameters**

- **x** (*float or numpy.ndarray*) – Input value(s) for which to compute $\tanh(x)$.
- **n_terms** (*int, optional*) – Number of terms to use in the Taylor series for \sinh and \cosh (default is 20).

ReturnsComputed $\tanh(x)$ for the input(s).**Return type**

float or numpy.ndarray

Raises**ZeroDivisionError** – If $\cosh(x)$ equals zero, which can occur in rare numerical edge cases.**Examples**

```
>>> tanh(0)
0.0
>>> tanh(1)
0.7615941559557649
>>> tanh(np.array([0, 1, 2]))
array([0.          , 0.76159416, 0.96402758])
```

PYTHON MODULE INDEX

a

`acsefunctions.special`, [1](#)

INDEX

A

`acsefunctions.special`
module, 1

C

`cosh()` (*in module `acsefunctions.special`*), 1

E

`exp()` (*in module `acsefunctions.special`*), 1

M

module
 `acsefunctions.special`, 1

S

`sinh()` (*in module `acsefunctions.special`*), 1

T

`tanh()` (*in module `acsefunctions.special`*), 2