

UNIVERSITÀ DEGLI STUDI DI TORINO

SCUOLA DI SCIENZE DELLA NATURA

Corso di Laurea Magistrale in Fisica



Tesi di Laurea Magistrale

TESTING OF THE TD26 TYPE
CAVITY UNDER BEAM LOADING
FOR THE CLIC PROJECT

Relatore:
Prof.
Martino Gagliardi

Controrelatore:
Prof.
Ferruccio Balestra

Candidato:
Eugenio Senes

Anno Accademico 2015/2016

Considerate la vostra semenza:
fatti non foste a viver come bruti,
ma per seguir virtute e canoscenza

Dante, *La Divina Commedia*
Canto XXVI

Abstract

A new generation of colliders capable of reaching TeV energies is under development nowadays, and to succede in this task is necessary to show that the technology for such machine is available. The CLIC project is one of the most advanced design among the possible lepton colliders, and is formed by two normal conducting LINACs. To reach such high energies are necessary accelerating structures carrying gradient beyond 100MV/m and one of the biggest limitations is developing accelerating structures that present a sufficient low occurrence of vacuum arcs. This is pursued both with the design and the *conditioning*, which is the process of increasing the resilience to vacuum arcs of a structure using repetitive RF pulsing sessions.

The focus of this work is on the breakdown rate testing of the TD26 type cavity with and without beam presence inside. At CERN this test has been carried out on the cavity installed in the *dogleg* line in the CLIC-test-facility 3 (CTF3), and connected on the RF side to the X-band test stand 1 (Xbox1).

Other peculiar properties of the operation have been studied also, such has beam-induced RF generation into the cavity after the breakdowns, breakdown migration,

Italian abstract

(Translate once you have the ok to the english one)

Contents

1	Introduction	1
1.1	Generalities on colliders	2
1.2	The CLIC project and the CTF3 facility	5
1.2.1	Physics and staging	5
1.2.2	Main parameters and main issues	7
1.2.3	CTF3	8
2	Theoretical background	9
2.1	Vacuum arcs	9
2.1.1	General background	9
2.1.2	Applications to particle accelerators	10
2.2	Accelerating structures theory	10
2.3	Signal processing techniques	10
2.3.1	Interaction with the RF	11
2.4	Signal processing techniques	11
3	Experimental setup	12
3.1	Main beam accelerating structure	12
3.2	Linac and dogleg	12
3.3	RF power generation	12
3.4	DAQ system	13
3.4.1	Hardware	13
3.4.2	Online selection of the events	13
3.5	Other systems	13
4	Data analysis tools	14
4.1	Offline selection of the events	14
4.2	Time and space positioning of the breakdowns	14
4.3	Migration of the breakdowns	14
4.4	Beam induced RF	14
4.5	Neural network based events selection	14
5	Results and future developments	15
5.1	Results	15
5.2	Further developments	15

CONTENTS

List of abbreviations	16
Bibliography	19

Chapter 1

Introduction

Particle accelerators occupy a key role both in fundamental research and in all the applications and industrial processes that uses technology and processes developed initially for the physical research.

A number of examples could be named among the spin-offs of accelerators' science, but the most notable nowadays is the relevant progress of nanosciences in the last decade, that was made possible by the availability of high-brilliance light sources provided by synchrotrons. In the same way to inquire a much smaller scale are necessities machines involving higher energies, and the development of the latter will lead the one of the former and so forth. Hence in this perspective keep developing the accelerators for the physical research is a fundamental requirement to assure that the cutting-edge technology of today turns into the labware of tomorrow for all the other sciences and the industry, in addition of the contribution that pursuing the fundamental research can give to our understanding of the world of the elementary particles.

At the moment the most successful model to explain the behaviour of the elementary particles is the *Standard Model*, but it's not conclusive and not able to answer to all the questions still open in particle physics. A milestone in favour of the Standard Model was the observation of the Higgs Boson in 2012, and was made possible by the construction of the *Large Hadron Collider* at CERN[1, 2, 3]. However the full understanding of the physics at the particle scale still needs to be achieved. Partially this will be realised with the increase of the collision energy of the LHC, but also the International Committee for Future Accelerators (ICFA) consider that the results of LHC needs to be complemented by the results of a lepton collider in the TeV-range[4].

The reason of this decision is that according to the standard model the hadrons are particles composed by quarks, that are continuously interacting exchanging gluons. This peculiarity cause the collision at high energy not to be between the hadrons themselves, but between partons composing them. In addition, there is no way to know in advance the energy of the partons involved, so it's not possible to know in advance which will be the energy of the collision. For example it is improbable for a parton in the 14 TeV centre-of-mass energy LHC to have much more than 1-2 TeV of energy at the

interaction point[5]. On the other hand, the leptons are punctual particles, so the interaction is directly involving the two bullets themselves, and the number of possible processes that can take place is definitely smaller. This behaviour of particles of different kinds makes hadron colliders *machines for discovery*, because involve all the possible processes that can take place, and the lepton machines *machines for precision*, because the reduced number of possible processes guarantees the observation of the events of interest much easier.

1.1 Generalities on colliders

In a collider the rate of observation of a particular interaction process A is given by

$$\frac{dN(A)}{dt} = \mathcal{L} \sigma(A)$$

where σ is the process cross-section, which depends by the physics of the process itself, and \mathcal{L} is the luminosity, which depends entirely by the machine. Therefore the figure of merit when it comes to talk about accelerators is the luminosity, which is given by

$$\mathcal{L} = H_d \frac{N^2}{\sigma_x \sigma_y} n_b f_r$$

where N is the number of particles per bunch, σ_x and σ_y are the beam dimensions in the horizontal and vertical plane, n_b is the number of particle per bunch, f_r is the collision frequency of the bunches and H_d is a correction factor that takes in account the non ideality of the collision, such as crossing angle, collision offset, hour glass effect, non gaussian beam profile and so on.

Then becomes obvious try to reach the highest luminosity possible since the events that are going to be studied are rare. This is realised using two kinds of machines:

- linear accelerators (LINACs): present a low repetition frequency, typically lower than hundred of Hz and the beam is passing just once to be accelerated through the machine.
- circular accelerators (typically synchrotrons): have a higher repetition frequency, up to tenth of KHz, and are keeping the particle beam in orbit for many turns, so can accelerate it over a long period of time

The key issue in the realisation of a lepton circular collider is the emission of synchrotron radiation, and is known that the power irradiated by a single particle in a circular machine scales according to the law

$$P \propto \frac{1}{\rho^2} \frac{E^4}{m_0^4}$$

Parameter	LEP2	FCC-ee	CLIC		ILC
\sqrt{s} [GeV]	209	350	500	3000	500
\mathcal{L}_{peak} [$10^{34} \text{ cm}^{-2} \text{ s}^{-1}$]	0.012	1.3	2.3	5.9	1.8
Total lenght [km]	26.7	100	13	48.4	31
Loaded acc. gradient [MV/m]			80	100	31.5
Bunch population [10^9]	105	170	6.8	3.72	500
Bunch spacing [ns]		4000	0.5	0.5	554
Collision rate [Hz]			50	50	5
$\epsilon_x^* / \epsilon_y^*$ [μm]/[nm]			2.4/25	0.66/20	10/35
σ_x^* / σ_y^* [nm]		3600/70	202/2.3	40/1	474/5.9
Energy loss per turn [GeV]	3.34	7.55	-	-	-
Power consumption [MW]	3.34	7.55			163

Table 1.1: Comparison of two circular machines, LEP[7] and FCC-ee[7, 8] and the two projects for linear machines, the fist and last stage of the CLIC implementation [9] and the final stage of ILC[10]

where ρ is the bending radius of the machine, E is the particle energy and m_0 is its rest mass. As can be noted in the table 1.1, the energy loss per turn is a relevant fraction of the beam energy, e.g for the LEP machine over than 3 GeV were lost per turn, while the record energy per beam was 104.5 GeV. To raise the beam energy and combat the energy loss, the radius of circular machines escalates quickly. Simply scaling LEP, it is possible to show that in order to reach the centre-of-mass energy of 3 TeV, the circumference should be increased to thousands of kilometers [6]. To solve the issue the development of new lepton colliders is so focusing on two different solutions:

1. Use muons instead of electrons: this approach has to deal with the short life of muons, which is roughly $2 \mu\text{s}$ in the laboratory frame
2. Limit the losses caused by synchrotron radiation, or increasing the bending radius or abandon the circular topology for the linear one

Also has to be noted that the former technology is rather new and needs to still be fully developed, while the latter profits of the progresses achieved in the last half century mainly in SLAC and KEK on the LINAC technology.

In this perspective a number of project are under study at the moment, of wich the most ambitious are FCC-ee, *Future Circular Collider*, ILC, *International Linear Collider*, and CLIC, *Compact Linear Collider*. The first one consist in a circular collider which is supposed to be placed in a 80-100 km long tunnel before of the installation of the FCC-hh, the other are LINACs even if based on completely different technologies and solutions. A comparison of the features of these projects in the final stage is presented in the table 1.1, and also LEP is presented as example of circular lepton machine.

Furthermore a recent interest arose on more compact technologies, e.g. plasma acceleration techniques, but the reliability of such designs still need to

be proven in the perspective of creating a fully functional machine that goes beyond the demonstration of the working physical principle.

1.2 The CLIC project and the CTF3 facility

The *Compact Linear Collider* is the project for a linear electron-positron collider capable of reaching a centre-of-mass collision energy of 3 TeV and a luminosity of $2 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$ in the final stage.

The realisation of such machine implies many technological challenges in order to keep the power consumption and the dimension limited. These have been faced developing the novel *two-beam acceleration scheme*, in which the idea is to use a high-current and low-energy beam, the *drive beam*, in order to generate the RF power to accelerate a low-current and high-energy beam used for the experiments, named *main beam*.

The main beam is produced using a 3 GHz linac, and then the current is multiplied using a delay loop and two recombination rings. This topology provokes a raise of the frequency of the bunches from 3 to 12 GHz, and is the motivation because of the RF for the main beam is using the latter frequency, as described later. More information about how the recombination process works can be found in [9] and on how the working principle have been demonstrated in the CTF3 in [11].

The main beam is produced [?]

Once both beams have been produced, both are sent to the Two-beams modules, where the main beam passes through the PETS, *Power Extraction and Transfer Structures*, and the RF power extracted is transferred to power the accelerating structures for the main beam. The structure of a Two-beams module is exploited in figure 1.2

1.2.1 Physics and staging

The machine is designed to be built in 3 stages, with a final energy of 3 TeV. The energy of the stages have been chosen in order to offer the possibility to explore both Higgs boson and top quark physics. This modular scheme should allow a physics programme that last for several decades.

Since the CDR[9] was released just before the discovery of the Higgs boson, the centre of mass energy stages have been reshaped in order to be able to access to interesting measurements, anyway for a given centre-of-mass energy, the energy can be modified by a third with limited loss of performance[12], allowing an eventual retuning of the energy of the stages following the results of the last LHC physics campaign.

The energy staging have been chosen as follows, further informations can be found in[13, 14]. As reference is useful to keep in mind the behaviour of the cross sections of the processes involving the Higgs boson, that are presented in figure ?? as function of the centre-of-mass energy.

The first stage is proposed to be 380 GeV, and it gives access to the Standard model Higgs physics and top-quark physics. The measurements on the former can be conducted through Higgsstrahlung and WW-fusion processes, thereby providing accurate model-independent measurements of Higgs cou-




Figure 1.1: Layout of the final stage of CLIC




Figure 1.2: Design of a Two-beam module.

plings to bosons and fermions[15]; the latter measurements will be focused on the $t\bar{t}$ pair production threshold in the vicinity of $\sqrt{s} = 350$ GeV.

The second stage is proposed at 1.5 TeV and allows to access new physics phenomena and additional properties of the Higgs boson and the top quark, such as Higgs self-coupling and rare Higgs branching ratios.

The third stage is proposed at 3 TeV and will give direct access to pair-produced particles with mass up to 1.5 TeV or single particles with mass up to 3 TeV. This stage is particularly interesting as test for the BSM theories, since such high energy in a lepton machine makes the observation of new particles much easier than in the LHC.

A further remodulation of these steps is possible after the publication of the results of the run 2 of the LHC, but anyway the advantage of a linear machine in this sense is that the top energy can be reshaped modifying the total length of the machine. In figure 1.3 is shown the track of a possible CLIC build in the Geneva area, in order to give an idea about the order of magnitude of that kind of facility.




Figure 1.3: Map of the CLIC facility, if implemented in the Geneva area

1.2.2 Main parameters and main issues

In lobortis augue porta dui venenatis sollicitudin. In sagittis quis ipsum non dictum. Sed tempus, quam non vehicula dictum, mauris nisl posuere metus, eu lobortis odio risus at dui. Nullam non ante vulputate nulla ultrices euismod eu a diam. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Nulla nec augue a risus viverra mattis. Ut tincidunt egestas nulla at semper. Fusce pretium, leo quis consectetur viverra, arcu

lectus ornare leo, quis commodo ex risus sit amet velit. Nullam finibus lorem in mi tincidunt, sed feugiat lectus tincidunt. In hac habitasse platea dictumst. Sed quis auctor odio, at sodales nunc. Donec vulputate massa sit amet dolor sollicitudin, vel pretium quam scelerisque. Nullam et massa eleifend, venenatis ante vitae, ornare libero. Suspendisse potenti. Nam ante lacus, porttitor vel turpis quis, pellentesque auctor velit.

In lobortis augue porta dui venenatis sollicitudin. In sagittis quis ipsum non dictum. Sed tempus, quam non vehicula dictum, mauris nisl posuere metus, eu lobortis odio risus at dui. Nullam non ante vulputate nulla ultrices euismod eu a diam. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Nulla nec augue a risus viverra mattis. Ut tincidunt egestas nulla at semper. Fusce pretium, leo quis consectetur viverra, arcu lectus ornare leo, quis commodo ex risus sit amet velit. Nullam finibus lorem in mi tincidunt, sed feugiat lectus tincidunt. In hac habitasse platea dictumst. Sed quis auctor odio, at sodales nunc. Donec vulputate massa sit amet dolor sollicitudin, vel pretium quam scelerisque. Nullam et massa eleifend, venenatis ante vitae, ornare libero. Suspendisse potenti. Nam ante lacus, porttitor vel turpis quis, pellentesque auctor velit.

1.2.3 The CLIC Test Facility 3

In lobortis augue porta dui venenatis sollicitudin. In sagittis quis ipsum non dictum. Sed tempus, quam non vehicula dictum, mauris nisl posuere metus, eu lobortis odio risus at dui. Nullam non ante vulputate nulla ultrices euismod eu a diam. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Nulla nec augue a risus viverra mattis. Ut tincidunt egestas nulla at semper. Fusce pretium, leo quis consectetur viverra, arcu lectus ornare leo, quis commodo ex risus sit amet velit. Nullam finibus lorem in mi tincidunt, sed feugiat lectus tincidunt. In hac habitasse platea dictumst. Sed quis auctor odio, at sodales nunc. Donec vulputate massa sit amet dolor sollicitudin, vel pretium quam scelerisque. Nullam et massa eleifend, venenatis ante vitae, ornare libero. Suspendisse potenti. Nam ante lacus, porttitor vel turpis quis, pellentesque auctor velit.

In lobortis augue porta dui venenatis sollicitudin. In sagittis quis ipsum non dictum. Sed tempus, quam non vehicula dictum, mauris nisl posuere metus, eu lobortis odio risus at dui. Nullam non ante vulputate nulla ultrices euismod eu a diam. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Nulla nec augue a risus viverra mattis. Ut tincidunt egestas nulla at semper. Fusce pretium, leo quis consectetur viverra, arcu lectus ornare leo, quis commodo ex risus sit amet velit. Nullam finibus lorem in mi tincidunt, sed feugiat lectus tincidunt. In hac habitasse platea dictumst. Sed quis auctor odio, at sodales nunc. Donec vulputate massa sit amet dolor sollicitudin, vel pretium quam scelerisque. Nullam et massa eleifend, venenatis ante vitae, ornare libero. Suspendisse potenti. Nam ante lacus, porttitor vel turpis quis, pellentesque auctor velit.

Chapter 2

Theoretical background

Lorem ipsum dolor sit amet¹, consectetur adipiscing elit. Sed dui sem, aliquam id ultricies sit amet, fermentum at magna. Aenean vitae rhoncus leo. Fusce gravida consequat lacus, a porta risus bibendum semper. Morbi eget auctor velit. Pellentesque eu lacinia nisi. Maecenas sed orci eu erat porta imperdiet ac non dui. Pellentesque a odio ac quam euismod tempor. Nulla in dapibus mauris, a sodales ex. In imperdiet enim sed ornare sollicitudin. Pellentesque² habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec vehicula metus eu nisi ornare euismod. Proin at ex non ex iaculis porta.

2.1 Vacuum arcs

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed dui sem, aliquam id ultricies sit amet, fermentum at magna. Aenean vitae rhoncus leo. Fusce gravida consequat lacus, a porta risus bibendum semper. Morbi eget auctor velit. Pellentesque eu lacinia nisi. Maecenas sed orci eu erat porta imperdiet ac non dui. Pellentesque a odio ac quam euismod tempor. Nulla in dapibus mauris, a sodales ex. In imperdiet enim sed ornare sollicitudin. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec vehicula metus eu nisi ornare euismod. Proin at ex non ex iaculis porta.

Here I want to test[?] some[?] quote[?]

2.1.1 General background

Nulla interdum molestie bibendum. Quisque condimentum justo quis lectus pretium, eget porttitor odio elementum. In dignissim sed justo et congue. In pulvinar feugiat odio eu vehicula. In ut malesuada est, sit amet porttitor dolor. Donec ullamcorper libero eros, vitae blandit nibh pellentesque quis. Aliquam aliquet ex id sapien lobortis, at molestie sem commodo. Donec quis accumsan lectus. Sed eget turpis id mi iaculis accumsan. Maecenas eget rutrum leo. Nam eu purus vitae lorem semper vestibulum. Phasellus mattis euismod faucibus.

¹first foot note

²another foot note

Vestibulum ornare sem a mattis placerat. Donec interdum blandit erat, eu iaculis risus cursus sed. Donec magna sem, finibus nec scelerisque nec, auctor in turpis.

2.1.2 Applications to particle accelerators

Morbi eget elementum tellus. Sed varius lacus ac nulla maximus, et varius lacus varius. Nulla faucibus magna sit amet magna auctor, vitae placerat turpis imperdiet. Duis blandit bibendum tellus nec accumsan. Aliquam arcu nulla, efficitur vitae sodales eu, tincidunt ac tortor. Cras gravida vulputate porttitor. Etiam ornare est at efficitur convallis. Quisque pulvinar tellus pulvinar lacus tristique, bibendum dapibus velit ultricies. Suspendisse id faucibus dui. Sed quis convallis dui. Etiam aliquam suscipit eros id pellentesque. Aliquam a suscipit leo, sit amet convallis dui. Donec sed pretium quam. Mauris nec tincidunt mi, in feugiat quam.

2.2 Accelerating structures theory

2.3 Signal processing techniques

In lobortis augue porta dui venenatis sollicitudin. In sagittis quis ipsum non dictum. Sed tempus, quam non vehicula dictum, mauris nisl posuere metus, eu lobortis odio risus at dui. Nullam non ante vulputate nulla ultrices euismod eu a diam. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Nulla nec augue a risus viverra mattis. Ut tincidunt egestas nulla at semper. Fusce pretium, leo quis consectetur viverra, arcu lectus ornare leo, quis commodo ex risus sit amet velit. Nullam finibus lorem in mi tincidunt, sed feugiat lectus tincidunt. In hac habitasse platea dictumst. Sed quis auctor odio, at sodales nunc. Donec vulputate massa sit amet dolor sollicitudin, vel pretium quam scelerisque. Nullam et massa eleifend, venenatis ante vitae, ornare libero. Suspendisse potenti. Nam ante lacus, porttitor vel turpis quis, pellentesque auctor velit.

Sed convallis pulvinar dui et ullamcorper. Maecenas facilisis, ante a tristique convallis, nunc ipsum fermentum odio, a auctor ligula risus ut nibh. Praesent sit amet tempus metus. Proin enim ipsum, mollis in nunc sed, tempus tempor magna. Nam ultricies lacus et porttitor bibendum. Suspendisse sit amet placerat nibh. Curabitur rutrum massa eu tortor sodales iaculis. Mauris sit amet odio eget velit tempus auctor. Pellentesque nec posuere neque. Nam in orci vehicula, ullamcorper sapien quis, pellentesque mauris. Sed eu porta ex.

2.3.1 Interaction with the RF

2.4 Signal processing techniques

In lobortis augue porta dui venenatis sollicitudin. In sagittis quis ipsum non dictum. Sed tempus, quam non vehicula dictum, mauris nisl posuere metus, eu lobortis odio risus at dui. Nullam non ante vulputate nulla ultrices euismod eu a diam. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Nulla nec augue a risus viverra mattis. Ut tincidunt egestas nulla at semper. Fusce pretium, leo quis consectetur viverra, arcu lectus ornare leo, quis commodo ex risus sit amet velit. Nullam finibus lorem in mi tincidunt, sed feugiat lectus tincidunt. In hac habitasse platea dictumst. Sed quis auctor odio, at sodales nunc. Donec vulputate massa sit amet dolor sollicitudin, vel pretium quam scelerisque. Nullam et massa eleifend, venenatis ante vitae, ornare libero. Suspendisse potenti. Nam ante lacus, porttitor vel turpis quis, pellentesque auctor velit.

Sed convallis pulvinar dui et ullamcorper. Maecenas facilisis, ante a tristique convallis, nunc ipsum fermentum odio, a auctor ligula risus ut nibh. Praesent sit amet tempus metus. Proin enim ipsum, mollis in nunc sed, tempus tempor magna. Nam ultricies lacus et porttitor bibendum. Suspendisse sit amet placerat nibh. Curabitur rutrum massa eu tortor sodales iaculis. Mauris sit amet odio eget velit tempus auctor. Pellentesque nec posuere neque. Nam in orci vehicula, ullamcorper sapien quis, pellentesque mauris. Sed eu porta ex.

Chapter 3

Experimental setup

3.1 The TD26 accelerating structure

3.2 The LINAC and the Dogleg

Bullet list example

- first point
- second point
- third point

3.3 RF power generation

Enumeration example

1. first point
2. second point
3. third point

Description example

first descr first point

second descr second point

third descr third point

3.4 DAQ system

3.4.1 Hardware

3.4.2 Online selection of the events

describe the online, but then the offline is in the next chapter
...but you can also build nested lists

- first point
 - first point
 - second point
- second point
- third point

3.5 Other systems

mention here thermal systems for the structure and something else ???

Chapter 4

Data analysis tools

4.1 Offline selection of the events

A tabular example

Tit1	Tit2
el1	el2
el1	el2
el1	el2

but tabulars cannot be captioned ! (are in text elements)

Using the table environment, the caption works ! BUT BECOMES FLOATING OBJECTS (in fact is on the bottom of the page due to no more text inserted afterwards).

Same thing for the figure environment

4.2 Time and space positioning of the breakdowns

4.3 Migration of the breakdowns

4.4 Beam induced RF

4.5 Neural network based events selection

1	2	3
4	5	6
7	8	9

Table 4.1: A simple table

Chapter 5

Results and future developments

5.1 Results

A figure example, with text in line (NO CAPTION)



A figure example, with floating object and caption

5.2 Further developments



Figure 5.1: the logo of UniTo

List of abbreviations

BSM	Beyond Standard Model
CDR	Conceptual Design Report
CERN	Conseil européen pour la Recherche nucléaire, Geneva, Switzerland
CLIC	Compact Linear Collider
CTF3	CLIC test facility 3
FCC-ee	Future Circular Collider, lepton version
FCC-hh	Future Circular Collider, hadron version
ICFA	International Committee for Future Accelerators
ILC	International Linear Collider
cKEK	High Energy Accelerator Research Organization, Tsukuba, Japan
LEP	Large Electron Positron Collider
LHC	Large Hadron Collider
LINAC	Linear Accelerator
PETS	Power Extraction and Transfer Structure
RF	Radio frequency
SLAC	Stanford Linear Accelerator, Menlo Park, California
SM	Standard Model
TBM	Two-Beams module
TDR	Technical Design Report
XBOX	X-band high power RF test stand

List of Figures

1.1	Layout of the final stage of CLIC	6
1.2	Design of a Two-beam module.	6
1.3	Map of the CLIC facility, if implemented in the Geneva area . .	7
5.1	the logo of UniTo	15

List of Tables

1.1	Comparison of two circular machines, LEP[7] and FCC-ee[7, 8] and the two projects for linear machines, the fist and last stage of the CLIC implementation [9] and the final stage of ILC[10]	3
4.1	A simple table	14

Bibliography

- [1] S. Chatrchyan *et al.*, “Observation of a new boson at a mass of 125 GeV with the CMS experiment at the LHC,” *Phys. Lett.*, vol. B716, pp. 30–61, 2012.
- [2] G. Aad *et al.*, “Observation of a new particle in the search for the Standard Model Higgs boson with the ATLAS detector at the LHC,” *Phys. Lett.*, vol. B716, pp. 1–29, 2012.
- [3] O. S. Bruening, P. Collier, P. Lebrun, S. Myers, R. Ostojic, J. Poole, and P. Proudlock, *LHC Design Report*. Geneva: CERN, 2004.
- [4] “Icfa statement on linear colliders.” http://icfa.fnal.gov/statements/icfa_lcstatement/.
- [5] A. D. Martin, W. J. Stirling, R. S. Thorne, and G. Watt, “Parton distributions for the lh,” *The European Physical Journal C*, vol. 63, no. 2, pp. 189–285, 2009.
- [6] J. R. Ellis and I. H. Wilson, “New physics with the compact linear collider,” *Nature*, vol. 409, pp. 431–435, 2001.
- [7] J. W. et al., “Future Circular Collider Study - Lepton Collider Parameters,” Tech. Rep. FCC-1401201640-DSC, CERN, Geneva, Jun 2016.
- [8] F. Zimmermann, M. Benedikt, K. Oide, A. Bogomyagkov, E. Levichev, M. Migliorati, and U. Wienands, “Status and Challenges for FCC-ee,” Tech. Rep. CERN-ACC-2015-0111, CERN, Geneva, Aug 2015.
- [9] M. Aicheler, P. Burrows, M. Draper, T. Garvey, P. Lebrun, K. Peach, N. Phinney, H. Schmickler, D. Schulte, and N. Toge, “A Multi-TeV Linear Collider Based on CLIC Technology: CLIC Conceptual Design Report,” Tech. Rep. CERN-2012-007. SLAC-R-985. KEK-Report-2012-1. PSI-12-01. JAI-2012-001, Geneva, 2012.
- [10] T. Behnke, J. E. Brau, B. Foster, J. Fuster, M. Harrison, J. M. Paterson, M. Peskin, M. Stanitzki, N. Walker, and H. Yamamoto, “The International Linear Collider - Volume 1: Executive Summary,” Tech. Rep. CERN-ATS-2013-037. ILC-REPORT-2013-040. KEK-Report-2013-1., Geneva, Jun 2013.

BIBLIOGRAPHY

- [11] R. Corsini, “Experimental verification of the CLIC two-beam scheme, status and outlook,” *Conf. Proc.*, vol. C1205201, p. TUOBC01. 3 p, May 2012.
- [12] P. Lebrun, L. Linssen, A. Lucaci-Timoce, D. Schulte, F. Simon, S. Staples, N. Toge, H. Weerts, and J. Wells, “The CLIC Programme: Towards a Staged e^+e^- Linear Collider Exploring the Terascale: CLIC Conceptual Design Report,” Tech. Rep. CERN-2012-005, Geneva, 2012.
- [13] M. J. Boland, U. Felzmann, P. J. Giansiracusa, T. G. Lucas, R. P. Rassool, C. Balazs, T. K. Charles, K. Afanaciev, I. Emeliantchik, and Ignatenko, “Updated baseline for a staged Compact Linear Collider,” Tech. Rep. arXiv:1608.07537. CERN-2016-004, Geneva, Aug 2016.
- [14] I. Bozovic-Jelisavcic, “CLIC Physics Overview,” Tech. Rep. CLICdp-Conf-2016-006, CERN, Geneva, Jun 2016.
- [15] P. G. Roloff, “Higgs Physics at the CLIC Electron-Positron Linear Collider,” Tech. Rep. CLICdp-Pub-2016-001, CERN, Geneva, Aug 2016.