Dominion

Analysis, Design and Software Architecture

Jakob Melnyk, jmel@itu.dk Christian Jensen, chrj@itu.dk Frederik Lysgaard, frly@itu.dk

December 14th, 2011

Abstract

This project is about a virtual representation of the card game Dominion in C#. Dominion is a turn-based, deck-building game, where the objective is to gather more points than the other players. The game is played by 2 - 4 players.

Contents

1	Requirements				
	1.1	Mandatory	4		
	1.2	Secondary	4		
2	Ove	rview	5		
3	Dic	tionary	6		
	3.1	General terms	6		
	3.2	In-Game terms	7		
4	Exa	mple	9		
	4.1	Starting the game, hotseat or LAN	9		
		4.1.1 LAN	9		
		4.1.2 Hot-Seat	9		
	4.2	Getting started, what is Dominion really about?	9		
	4.3	T	0		
	4.4	e	0		
5	Rev	evision History 12			
6 Milestones					
	6.1	System analysis	4		
	6.2	System design	5		
		6.2.1 General	5		
		6.2.2 GUI	5		
		6.2.3 Client & Server and Control (Server and start-up parts) 1	5		
		6.2.4 Gamestate and Control (Game Logic)	5		
		6.2.5 BON specification	5		
	6.3	System production	0		

	6.3.1	General	40
	6.3.2	GUI	40
	6.3.3	Server and Control (Server and start-up parts)	40
6.4	Game	state and Control (Game Logic)	40

1 Requirements

1.1 Mandatory

Must be able to play a full game of Dominion

- Must support 2 players in Hot-Seat configuration
- At least 10 Kingdom cards must work
- The game must be playable in a Picture-based GUI

1.2 Secondary

High priority

- Be able to play the game with 3 or more players
- Be able to use at least 20 Kingdom cards
- Be able to select Game Mode
 - Be able to play 'First Game' Card-set
 - Be able to play with 10 randomly select Kingdom cards
- Be able to see all Available Kingdom cards without scrolling

Medium priority

- Be able to view a Tooltip when mousing over any Card in the game
- Be able to play the game over LAN
- Be able to use all Kingdom cards (from the original version of the game)
- Be able to play all the Card-sets defined in the original rules

Low priority

- Be able to Draft Kingdom cards
- Be able to play the game over the Internet
- Be able to select different screensizes
- Be able to play in fullscreen

- Be able to create a User, that is saved across multiple games, with the following information:
 - Statistics
 - Options (if any)
 - Achievements (if implemented)
- Be able to support Extensions of the basic game
- Implement Achievements for funny and/or hard accomplishments

2 Overview

This project is about our virtual representation of the card game Dominion. Dominion is a turn-based, deck-building game. The objective of the game is to use Action cards to improve your chances or damage the opponent players and using Treasure cards to buy more powerful Action/Treasure/Victory cards to gain the upper hand.

We are planning on using a Model-View-Controller architecture. We want to separate our GUI from both the game rules and the state of the game via the controller. In essence we are likely to have a somewhat static model of the rules and a more dynamic and changing model of the state of the current game.

Frederik Lysgaard is the guy responsible for the design of our graphical interface. He is also the best Dominion player in our group. Because of this, he knows a lot of the usual strategies and is our general "go-to" guy when it comes to the tactics of the game.

Christian Jensen is responsible for implementing the way the different cards interact with the state of the game when used. Christian is also the guy who will be looking into the networking portion of the project if/when it becomes relevant.

Jakob Melnyk is responsible for modeling the state of the game and the communication between the GUI and the model (in our model-view-controller architecture). Jakob Melnyk is also the "version-control-guy", the person with the final word in discussions and the general log-keeper for the group.

3 Dictionary

3.1 General terms

This section describes the general "out-of-game" terms.

- **Achievements** An achievement is token rewarded for funny and/or hard accomplishments within the game.
- Card-set A card-set is 10 different Kingdom cards. Card-sets are used to create a different play experience every time you play.
- **Dominion** The card-game we are making a virtual representation of. A link to the full rules can be found at Rio Grande Games [2].
- **Draft** Drafting is done by player 1 selecting one Kingdom card to be used in the game, then player 2 selects a Kingdom card, player 3 selects a Kingdom card, player 4 selects a Kingdom card, then back to player 1. This cycle repeats until a set number of Kingdom cards have been selected.
- **Extensions** Expansion packs add additional types of cards to the pool of cards.
- Game Mode There are different possible game modes: draft, random card selection and predefined card-sets. These are selected before the game starts.
- **Hot-Seat** Hot-Seat is the act of having 2 or more players play on the same computer. The active player "sits" in the hot-seat while playing, then passing the spot to the next player when his turn ends.
- **Message Type** Messages of different types can be passed around in our server-client network.
- Model-View-Control Often abbreviated MVC, Model-View-Control is often used to seperate something "showing" data and the actual representation of the data on the disk. Control is usually the middle-link that takes care of the communication between the two.
- **Picture-based GUI** A pictured-based GUI is a visual representation of the state of the game. The different cards are shown as pictures in the GUI.
- **Server-Client** In a client-server design, the clients communicate with the server and the server then relays the information it was given by the client to the other clients.
- **Statistics** Statistics such as number of games played, numbers of games won/lost, and other similar data about gameplay.
- **Tooltip** A box with text describing something in the GUI in detail.
- **User** A user is an entity storing statistics and achievements over the course of different games.

3.2 In-Game terms

This section describes the types of cards, supply and other "in-game" terms.

Available Available Cards are the Cards that can be bought from the Supply.

- Action Phase In an action phase, a player have one Action, which he or she may use to play an Action Card. Playing an action card this way always costs one Action. Cards played may allow a player to receive additional actions. The Action Phase ends when a player has no more Actions left or chooses not to use his or her remaining Actions.
- Buy Phase When a player's Action Phase ends, the Buy Phase begins. In this, the player receives a "Coin" amount, which is the combined value of all Treasure Cards in his or her hand and any Action Cards, that add "Coins". The player can then use a Buy to buy any Card they want from the Supply. Played Action Cards can allow more Buys. Bought Cards are added to the Discard Stack. After the Buy Phase, the Clean-Up Phase begins
- Card A Card is the basic playing unit in Dominion. Everything you 'own' is represented by a Card in your deck. Cards are primarily added to the deck through the Buy phase. Each Card has a value, which represents what it costs to get during the Buy Phase.
 - Curse Card A Curse Card is a special type of Victory Card, which gives a negative amount of Victory Points. While these cards can technically be bought by any player and added to his or her deck, they are usually given to other players by using Attack Cards against them.
 - **Kingdom Card** Kingdom Cards are what make each game of Dominion unique. With one exception all Cards here are Action Cards (one is a special Victory Card) and there are no Action Cards which are not Kingdom Cards. Each game requires selecting 10 of the 25 Kingdom Cards to use.
 - Action Card An Action Card is used during the Action Phase.
 - Attack Card An Attack Card is a type of Card which affects other players negatively. All Attack Cards are Action Cards and the "Attack" actives when the Card is used as an Action.
 - Action-Reaction Card A Reaction card is used to respond to an Attack by another player. When an Attack Card is used against a player, that player may reveal a Reaction Card from his or her hand and do what the Reaction allows. Only one Reaction Card is in this game, 'Moat', which allows the player to negate the attack used against them.
 - **Kingdom Victory Card** A Kingdom Victory Card is a card that does generally not behave like usual Victory Card, but instead have special effects granting the player Victory Points.

- Treasure Card A Treasure Card adds a number of "Coins" to spend in the Buy Phase. Note that a Treasure Cards value (the price to buy it) are usually different from what they cost to buy.
- **Victory Card** A Victory Card gives a number of Victory Points at the end of the game. The player with the most Victory Points win the game.
- Clean-up Phase The Clean-up Phase consists of putting all bought Cards, played Cards and Cards remaining in the Hand into the Discard Stack.
- **Deck** A players Deck is his or her representation in the game. It consists of all the Cards that player started with and have bought during the game. A player's Draw Stack, Discard Stack and Hand is that player's Deck.
- **Discard Stack** This contains previously played cards and any newly bought cards.
- **Draw Stack** This contains face-down Cards for a player to draw. When there are no more cards available for a player to draw, the Discard Stack is shuffled and used as a new Draw Stack. Each player have their own Draw Stack and Discard Stack.
- **Hand** The Hand represents a players current options in the following turn. These are drawn at the start of the game and each player draws a new hand after a turn has finished. When drawing a new hand, it always consists of 5 Cards.
- **Supply** The Supply consists of 10 types of Kingdom Cards, 3 types of Treasure Cards, 3 types of Victory Cards and Curse Cards.
- **Round** A game of Dominion consists of a number of rounds. Each Round is divided in to Turns, one for each player.
- **Trash Stack** Sometimes a Card calls for itself or some other card to be Trashed. This means that it should be completely removed from the game and the Trashed Card is put on to the Trash Stack. All players share the Trash Stack.
- **Turn** The player usually take turns in clockwise order. A players next Turn will be in the following Round.

4 Example

Frederik Roden Lysgaard This will be a example of our project, which is a graphical representation of the cardgame "Dominion", published by riogrande games. The walk-through will be built up around certain screenshots and will cover the following points:

- Starting the game, hotseat or LAN.
- Getting started, what is Dominion really about?
- The user interface.
- end of game.

4.1 Starting the game, hotseat or LAN.

4.1.1 LAN

When starting the application you will be presented with a console window asking you to take the role of either Client or Server pic(clientinput) often one of the players will choose server and will then be able to give his fellow players who choosed client, a IP to connect to. pic(startserver) when the appropriate amount of players has joined the server (usually 3-4) then the person with the server program runing will call startgame (command is $\langle STGM \rangle$) and the game will then start. pic(startgame) pic(startscreen)

4.1.2 Hot-Seat

This is done almost identically to the procedure for a LAN game the only exception is, that instead of leting other computers create a client, you just run multi instance of the application on your computer like so: pic(serverclient) and after that it's just that same as with LAN games.

4.2 Getting started, what is Dominion really about?

Dominion is a deckbuilding game which means, that the object of the game is to build yourself a deck which will give you the best hands, and there by giving you the edge in getting the most victory points which in the end determines who wins. I all ready introduced some of the game specific words and i will now show where they are placed on the playing board and what their responsibility is:

4.3 T

he user interface. pic (actioncard)

- hand The hand is where you see what you have drawn each turn. In Dominion there's three kind of cards: Treasure, Victory or Action all three kinds can be drawn into this field. If you click on a Action card while it's placed in hand and you got actions left then the card will be moved from the hand to the actionzone.
- actionzone The actionzone is where the actioncards that is played from the hand is shown. Only actioncards can be drawn in this zone. When a turn ends the actionzone will be cleared and the actioncards will all be moved to the discard.
- discard the discard zone is where the cards go when they are not in use anymore, you can't click on cards while they are in the discardzone, while in the discardzone the cards can only wait to be shuffled into the deck again.
- deck the deck is where the cards is held until they are drawn at new.
- supply the supplyzone that are drawn to right side of the GUI is crucial to the game this is where you can buy your kingdom cards and there by increase your decks size and strength, as we can see, we draw both the seven static victory/treasure cards and 10 extra kingdomcards, which also was one of our mandatory requirements.

4.4 e

nd of game. As stated by the Dominion game rules the game ends when either the province victory pile is empty or three kingdomcard piles are empty. When this happens we check which player has earned the titel of winer. If you are indeed the winner then you will be greated with a lovely congratulations message printed acrose the screen. pic(youarewinner) but if you loose you will be meet with disgust. pic(youloose) So to summarize our digital representation of Dominion let's you play with 10 preset kingdomcards in graphical interface with your friends either over hotseat or local area network. Which by total coincidence also is our mandatory requirements.

5 Revision History

Some of our commits to our Github (https://github.com/esfdk/BDSADominion) with commit ID. The commits are sorted by time of commit, descending. Full commit log can be found at: https://github.com/esfdk/BDSADominion/commits

——————————————————————Code freeze

c2dcc6786210ecf5ac74a8d34bcf07e72cf8360c: pex snapshot

a397b2b79291e8349e106ef1773406e3c3a57e55: made a dotcover solitaire run

cae05ae98caefbeaf2cf31fa4eb9473507486ce1: contract

00782159d83baf89bf3a41acea7f87d6484e263f: network design done.

28cb2b5c8f343793662fa0cec0d8dae0e8476564 : Fixed bug in shuffling of cards. Not as random as it was before.

234ca16500ee52cbf8f37dff117de83c07febebe: informal is now legit

e22f402855a48cc2ce93ce651305bb801e121d75: Key and control update

fe7e9ba83b41594a5ef91560af0fb505a55da627: Some pex tests, better shuffle method, fixed adventurer and more.

 $3074885 \\ da9f22646 \\ bac0 \\ becbfe8 \\ bc45 \\ ae975723 \\ a: Made some changes to GUI it looks good now$

e083766fe15b127f0a9ae03528e1eea956a6702e: dotCover solo run added

 $1951 \mathrm{adb} 1e07 \mathrm{b} 4d9735847e0 \mathrm{b} f3e622464380 \mathrm{aa} 2f$: Trying to get these weird bugs out of the game.

7c53affdf9aba583efc71dedab9476fe1441eeea: Done with some of the docs for the GUI

1173a01763032deb6b033d01471039be84a61f0f : Wrote some of system design and started on system production

a35c4939236770661fb751f378be4c7e5259d0fe: Formal bon 99% done for Melnyk.

97ae13e744b2283f0a0aecafae954b357d0e2c04 : Minor fix in Control to possibly prevent crashes. Also added some more Contracts to the formal BON.

aa1c0af808bc536cc50e5e988e185834ca34bd13: GUI start update working now

9d4d9b2bcf0b8acda2544fd3c93ad926122237c4 : added the listeners

44f6bb367f5b56014069c2bfd8b1e8fd1a61da7c: Made files to be used in the hand-in.

911af507af6ec9e64a36d470280d1b4d7e9707d7: Network starts the game

b7210739f2ed0b37875ab7d4a858559602e029b2 : Server PreGame messaging working. Still lots of WriteLines.

9a3c7bfc2334e04a0709a09eeb0d1b4a532327a7: Much of Melnyk's part of Control is done! Mainly need communication with server!

3417bf70282d5b3bdfd39c8855f258eeb05e57a2 : Network seems to be working alright.

c710a8d4a93dfdc6623be4022bcb8da2a0259d4d : GUIInterface done. Network testing

bb1b5dbabccfc6c7d3c1d25ffa97fcf5e8d37b64: Starting tests on network interface

537f2f25db57b263d63cac1ab298a69de5e80bf3 : GUI-Interface almost done, only need endPhase button in gamestate.

9f2a6f20d46e0037a2dfa2d917b3030b720551c3 : GUI Interface getting up and running. Console added :D

a883a6fd4d552fe71cb3aae641a7ec0af4037e06: GUI now draws what needs to be drawn

7c368444740ed2bc8d49027e7a7d666674600ec2: Finished gamestate and player for now

24454e804bde99435b2022244e6307d89a9c323a : GUI now updated to work with Card-Name

1ddb9247acd2f32b0e979f7dd561bd98edf4d570: Alfa GUI is done. LOCK AND LOAD!

5c28c48e556fea810b4dec2e3db4108f6c455ae4: Diary and some gamestate stuff done.

857d25376348dd601579e20899eb76efc074a30d : Networking added. More or less direct copy of work done outside of project. Interfacing with Control added, but not completed

bec4f5f40ae4aca6189ab41078fbd9c0475ca8e5: Started coding gamestate

 $523\mathrm{bd}81\mathrm{b}3a6\mathrm{e}0\mathrm{e}20185\mathrm{ff}5\mathrm{e}2\mathrm{b}3aa5\mathrm{fce}13\mathrm{ccbc}25$: Arranged classes into folders for better overview.

ff7248e0612f9f2e53525fde41de536b22d624b7: Started creating gamestate in code

5e858aff8cab0331b3a504f4d4280a4dbf774cc7: Did lots of BON

1d7eb386c7839a9c97ac1b8efb286b12fdaf7d97: Added all the necessary classes for the GUI part of the project

6af320925f540af6842e9b6156355738d3cc94b1: Did a lot of informal BON

 $25 \mathrm{ff} 80260 \mathrm{b} 970 \mathrm{e} \mathrm{c} 14 \mathrm{e} 36728249 \mathrm{e} 3\mathrm{f} 9 \mathrm{c} \mathrm{b} 324052 \mathrm{b} 0$: Did some BON and added some diary entries

e0ce1ea7ec8bd8345bfb6f66c77c3d908d40af03: Put in BON files

86029d88fde9a403f777855e433cd3fd8775ff7e: Added diary files

 $533\mathrm{e}909\mathrm{a}8\mathrm{d}36\mathrm{d}\mathrm{b}\mathrm{ffb}1\mathrm{c}6953\mathrm{c}\mathrm{f}99639\mathrm{a}5\mathrm{baa}90\mathrm{fbc}$: Added GUI classes

905a2d3a02218dec666bff65c4738306e9e7877c : Starting project

6 Milestones

6.1 System analysis

6.2 System design

6.2.1 General

We decided to use an MVC pattern for our overall structure, because we felt we could seperate the model (the Gamestate), the View (GUI) and Control (Game Logic and more). We also use a Client-Server architecture to do the network communication.

6.2.2 GUI

Frederik Lysgaard In terms of system design, there isn't really much to say to the GUI part since none of us knew the XNA framework, and therefore didn't have any knowledge of the limitations and benefits. This led to a very ad hoc way of designing the GUI system, for the first draft I used my exstensive knowledge of the game to try and get a overview of the components needed to properly display and play a game of Dominion. This resulted in the basic design for the GUI, but since I was still a newbeginner to XNA, this led to a design with almost all the right classes but with some strange inheritance, all in all it felt weird which made me study XNA some more, and after having used some days getting familiar with the framework I came up with the second and final draft.

Even though this was the final draft, it was far from perfect, I would for example if had, had more time with XNA before the project suggested some inheritance between the zones since they all is made from the same sprite "template". So to summarize there wasn't really any general battle plan for the GUI system design at the start of the project, which was a challenge, that taught me one thing, if you know you're going to work in a new framework, learn it beforehand.

6.2.3 Client & Server and Control (Server and start-up parts)

Christian Jensen

6.2.4 Gamestate and Control (Game Logic)

Jakob Melnyk

6.2.5 BON specification

In this sub section, we have included all of our BON. If we had had more time, we would have focused on doing scenarioes - especially in a context that could give us more code coverage.

```
system_chart BDSADominion
   indexing
            author: "Frederik Lysgaard (frly@itu.dk), Christian 'Troy' Jensen, Jakob Melnyk (jmel@itu.dk
3
            supervisor: "Joe Kiniry";
            course: "BDSA-E2011";
5
            created: "28th November 2011";
6
            lastModified: "14th December 2011";
    explanation
            "System chart for the BDSADominion project in the Analysis, Design and Software Architecture
   cluster DOMINION_SYSTEM
10
            description "The Dominion game system."
11
12
   end
13
   cluster_chart DOMINION_SYSTEM
14
   class CONTROL
15
            description "The man in the middle between the three parts of the architecture. Contains gam
16
   cluster GUI
17
            description "Used to display the current state of the model and to interact with the user."
18
    cluster GAMESTATE_CLUSTER
19
            description "The 'model' of the project. Remembers information about most of the states and
20
   cluster NETWORK_CLUSTER
21
            description "Communicates between different instances of the application across LAN."
22
   end
23
    cluster_chart GAMESTATE_CLUSTER
1
            indexing
2
                    author: "Jakob Melnyk (jmel@itu.dk)";
3
            explanation "The classes making up the 'dynamic' state of the game. This includes decks, han
4
5
            class GAMESTATE
                    description "The overall 'state' of the current game."
6
            class PLAYER
7
                    description "Represents a player and everything a player owns."
9
            class ZONE
                    description "List of zones that can be targets of events."
10
            cluster CARD_CLUSTER
11
                    description "The different kinds of cards."
   end
13
14
   class_chart GAMESTATE
15
            indexing
16
                    author: "Jakob Melnyk (jmel@itu.dk)";
17
            explanation "Keeps track of the players and everything the players share, such as the trash
18
            query
19
                    "May I have a new gamestate with this set-up?",
20
                    "Who is the active player?",
21
                    "How many players are in the game?",
22
                    "Is the active player in the Action Phase?",
23
                    "Is the active player in the Buy Phase?",
                    "What cards are in the trash pile?",
25
                    "What players are in the game?",
26
                    "What does the supply look like?",
27
                    "Number of actions left?",
28
                    "Number of buys left?",
29
                    "Number of coins left?",
30
31
                    "How many points does each player have?",
```

```
command
32
                     "Make this player the active player!",
33
                    "Begin Action Phase",
34
                    "End Action Phase",
35
                     "Begin Buy Phase",
36
                     "End Buy Phase",
37
                    "Do Clean-up phase",
38
                    "Increase the amount of actions the active player has by this much!",
39
                    "Increase the amount of buys the active player has by this much!",
40
                    "Increase the amount of coins the active player has by this much!",
41
                    "That player gains this card type in this zone from the supply.",
42
            constraint
43
                     "Can have 2, 3 OR 4 players.",
44
                    "Cannot begin Action Phase while in Action Phase or Buy Phase.",
45
                    "Cannot end Action Phase while not in Action Phase.",
46
                    "Cannot begin Buy Phase while in Action Phase or Buy Phase.",
47
                     "Cannot end Buy Phase while not in Buy Phase.",
48
                     "The active player cannot be made the active player."
49
   end
50
51
   class_chart PLAYER
52
53
            indexing
                    author: "Jakob Melnyk (jmel@itu.dk)";
54
            explanation "Each player is represented by a player object that keeps track of their decks,
55
            query
56
                     "May I have a new Player?",
57
                    "What cards do you have?",
                     "How many cards do you have in your deck?",
59
                     "How many cards do you have in your discard pile?",
60
                    "What card is on top of your discard pile?",
61
                    "What card is on top of your deck?",
62
                    "What cards do you have in your hand?",
63
                    "What number are you?",
64
                     "What cards have you played?",
65
                     "What have you put in your temporary zone?",
            command
67
                     "Move this card from that zone to the temporary zone!",
68
                    "Move this card from the temporary zone to that zone!",
69
                    "Move this card from the hand to the temporary zone!",
70
                    "Add this card to that zone!",
71
                    "Remove this card from that zone!",
72
                    "Draw a card!",
73
                    "Draw this many cards!",
74
            constraint
75
                     "A player cannot have a card in his deck, discard pile, hand, or 'played field' that
76
    end
77
78
   class_chart ZONE
79
            indexing
80
                    author: "Jakob Melnyk (jmel@itu.dk)";
81
            explanation "Represents the values used to refer to the zones in the player class and gamest
82
            query
83
                     "May I have the value 'v'?",
84
            constraint
                     "The values allowed for this class are exactly one of 'DECK', 'DISCARD', 'HAND', 'SU
86
```

```
cluster_chart CARD_CLUSTER
            indexing
2
                     author: "Jakob Melnyk (jmel@itu.dk)";
            explanation "Cluster showing how card system works."
4
            class CARD
5
                     description "A card."
6
            class CARD_NAME
                    description "The names of all the cards."
            class CARD_FACTORY
9
                    description "Produces cards."
10
11
            cluster CARD_TYPES
                    description "The different meta-types of cards."
12
            cluster CARDS
13
                    description "Contains all the cards from the game."
14
   end
15
16
   class_chart CARD
17
            indexing
18
                     author: "Jakob Melnyk (jmel@itu.dk)";
19
            explanation "A card is the representation of the cards within the game."
20
21
            query
                     "What is your card name?",
22
                     "What is your card number?",
23
                     "Have you been initialized yet?",
24
                     "Are you equal to this object?",
25
                     "Are you and this other card the same?"
26
27
            command
                     "Initialize yourself like this!"
28
   end
29
30
31
   cluster_chart CARD_TYPES
            indexing
32
                    author: "Jakob Melnyk (jmel@itu.dk)";
33
            explanation "The different types of cards that exist."
34
            class TREASURE
35
                    description "A card used to buy new cards."
36
37
            class VICTORY
                     description "A card that grants the points used to win the game."
            class ACTION
39
                    description "A card used to help the player buy more cards, get rid of unwanted card
40
            class ACTION_ATTACK
41
                    description "A card that is used to 'attack' other players."
42
            class ACTION_REACTION
43
                    description "A card used to react to opponent attacks."
44
            class KINGDOM_VICTORY
45
                    description "A special kind of victory card."
46
   end
47
48
    class_chart TREASURE
49
            indexing
50
                    author: "Jakob Melnyk (jmel@itu.dk)";
51
            explanation "A card used to buy new cards."
52
            inherit CARD
```

```
end
54
55
    class_chart VICTORY
56
             indexing
57
                     author: "Jakob Melnyk (jmel@itu.dk)";
58
             explanation "A card that grants the points used to win the game."
59
             inherit CARD
60
    end
61
62
    class_chart ACTION
63
64
             indexing
                     author: "Jakob Melnyk (jmel@itu.dk)";
65
             explanation "A card used to help the player buy more cards, get rid of unwanted cards, etc."
66
             inherit CARD
67
68
    end
69
    class_chart ACTION_ATTACK
70
             indexing
71
                     author: "Jakob Melnyk (jmel@itu.dk)";
             explanation "A card that is used to 'attack' other players."
73
             inherit ACTION
74
75
    end
76
    class_chart ACTION_REACTION
77
             indexing
78
                     author: "Jakob Melnyk (jmel@itu.dk)";
79
             explanation "A card used to react to opponent attacks."
             inherit ACTION
81
    end
82
83
    class_chart KINGDOM_VICTORY
84
             indexing
85
                     author: "Jakob Melnyk (jmel@itu.dk)";
86
             explanation "A special kind of victory card."
87
             inherit VICTORY
    end
89
90
    class_chart CARD_NAME
91
             indexing
92
                     author: "Jakob Melnyk (jmel@itu.dk)";
93
             explanation "Represents the values used to refer to the card names."
94
             query
                     "May I have the value 'v'?"
96
             constraint
97
                     "The values allowed for this class are exactly one of \
98
                     \'COPPER', 'SILVER', 'GOLD', 'CURSE', 'ESTATE', 'DUCHY', 'PROVINCE', \
99
                     \'CELLAR', 'CHAPEL', 'MOAT', 'CHANCELLOR', 'VILLAGE', 'WOODCUTTER', \
100
                     \'WORKSHOP', 'BUREAUCRAT', 'FEAST', 'GARDENS', 'MILITIA', 'MONEYLENDER', \
101
                     \'REMODEL', 'SMITHY', 'SPY', 'THIEF', 'THRONE_ROOM', 'COUNCIL_ROOM', 'FESTIVAL', \
102
                     \'LABORATORY', 'LIBRARY', 'MARKET', 'MINE', 'WITCH', 'ADVENTURER', 'EMPTY', 'BACKSID
103
    end
104
105
    class_chart CARD_FACTORY
106
107
             indexing
```

author: "Jakob Melnyk (jmel@itu.dk)";

```
explanation "Factory for producing cards with the correct values."
109
             query
110
                      "Has the factory been set up?",
111
                      "What cards have been made already?",
             command
113
                      "Set up the factory with these cards!",
114
                      "Give me a card with this name!",
115
             constraint
116
                      "A card that has already been made cannot be made again.",
117
    end
118
    cluster_chart CARDS
 1
 2
             indexing
 3
                     author: "Jakob Melnyk (jmel@itu.dk)";
             explanation "Contains all the cards from a standard Dominion game."
 4
             class COPPER
 5
                     description "The Copper card."
             class SILVER
 7
                     description "The Silver card."
             class GOLD
 9
                     description "The Gold card."
10
             class CURSE
11
                     description "The Curse card."
12
             class ESTATE
13
                     description "The Estate card."
14
             class DUCHY
15
                     description "The Duchy card."
16
             class PROVINCE
17
                     description "The Province card."
18
             class CELLAR
19
                     description "The Cellar card."
20
             class CHAPEL
21
22
                     description "The Chapel card."
             class MOAT
23
                     description "The Moat card."
24
             class CHANCELLOR
25
                     description "The Chancellor card."
26
             class VILLAGE
27
                     description "The Village card."
28
             class WOODCUTTER
                     description "The Woodcutter card."
30
             class WORKSHOP
31
                     description "The Workshop card."
32
             class BUREAUCRAT
33
                     description "The Bureaucrat card."
34
             class FEAST
35
                     description "The Feast card."
36
             class GARDENS
37
                     description "The Gardens card."
38
             class MILITIA
39
                     description "The Militia card."
40
             class MONEYLENDER
41
                     description "The Moneylender card."
42
             class REMODEL
43
                     description "The Remodel card."
44
```

```
class SMITHY
45
                     description "The Smithy card."
46
            class SPY
47
                     description "The Spy card."
            class THIEF
49
                     description "The Thief card."
50
            class THRONE_ROOM
51
                     description "The Throne Room card."
52
            class COUNCIL_ROOM
53
                     description "The Council Room card."
54
            class FESTIVAL
55
                     description "The Festival card."
56
            class LABORATORY
57
                     description "The Laboratory card."
58
            class LIBRARY
59
                     description "The Library card."
60
            class MARKET
61
                     description "The Market card."
62
            class MINE
63
                     description "The Mine card."
64
            class WITCH
65
                     description "The Witch card."
66
            class ADVENTURER
67
                     description "The Adventurer card."
68
    end
69
70
    class_chart COPPER
71
72
            indexing
                     author: "Jakob Melnyk (jmel@itu.dk)";
73
            explanation "Worth one coin. Costs no coins."
74
            inherit TREASURE
75
    end
76
77
    class_chart SILVER
78
            indexing
79
                     author: "Jakob Melnyk (jmel@itu.dk)";
80
            explanation "Worth two coins. Costs three coins."
81
            inherit TREASURE
82
    end
83
84
    class_chart GOLD
85
86
            indexing
                     author: "Jakob Melnyk (jmel@itu.dk)";
87
            explanation "Worth three coins. Costs six coins."
88
            inherit TREASURE
89
90
    end
91
    class_chart CURSE
92
            indexing
93
                     author: "Jakob Melnyk (jmel@itu.dk)";
94
            explanation "Worth minus one victory point. Costs no coins."
95
96
    end
97
    class_chart ESTATE
98
99
            indexing
```

```
author: "Jakob Melnyk (jmel@itu.dk)";
100
             explanation "Worth one victory point. Costs two coins."
101
             inherit VICTORY
102
    end
103
104
    class_chart DUCHY
105
             indexing
106
                      author: "Jakob Melnyk (jmel@itu.dk)";
107
             explanation "Worth three victory points. Costs five coins."
108
             inherit VICTORY
109
110
    end
111
    class_chart PROVINCE
112
             indexing
113
                      author: "Jakob Melnyk (jmel@itu.dk)";
114
             explanation "Worth six victory points. Costs eight coins."
115
             inherit VICTORY
116
    end
117
    class_chart GARDENS
119
             indexing
120
                      author: "Jakob Melnyk (jmel@itu.dk)";
121
             explanation "Worth one victory point for every ten cards in your deck (rounded down) at the
122
             inherit KINGDOM_VICTORY
123
    end
124
125
    class_chart CELLAR
126
             indexing
127
                      author: "Jakob Melnyk (jmel@itu.dk)";
128
             explanation "Grants one action. \
129
                      \Discard any number of cards - draw one card for each card discarded. \
130
                      \Costs two coins."
131
             inherit ACTION
132
    end
133
    class_chart CHAPEL
135
             indexing
136
                      author: "Jakob Melnyk (jmel@itu.dk)";
137
             explanation "Trash up to four cards from your hand. Costs two coins."
138
             inherit ACTION
139
    end
140
141
    class_chart CHANCELLOR
142
             indexing
143
                      author: "Jakob Melnyk (jmel@itu.dk)";
144
             explanation "Grants two coins. The player may immediately put your deck into your discard pi
145
                                        \Costs three coins."
146
             inherit ACTION
147
148
    end
    class_chart VILLAGE
150
             indexing
151
                      author: "Jakob Melnyk (jmel@itu.dk)";
152
             explanation "Grants one card. Grants two actions. Costs three coins."
153
```

inherit ACTION

```
156
    class_chart WOODCUTTER
157
             indexing
                      author: "Jakob Melnyk (jmel@itu.dk)";
159
             explanation "Grants one buy. Grants two coins. Costs three coins."
160
             inherit ACTION
161
    end
162
163
    class_chart WORKSHOP
164
165
             indexing
                      author: "Jakob Melnyk (jmel@itu.dk)";
166
             explanation "Player gains a card costing up to four coins. Costs three coins."
167
             inherit ACTION
168
169
    end
170
    class_chart FEAST
171
             indexing
172
                      author: "Jakob Melnyk (jmel@itu.dk)";
             explanation "Player trashes this card. Gain a card costing up to five coins. Costs 4 coins."
174
             inherit ACTION
175
176
    end
177
    class_chart MONEYLENDER
178
             indexing
179
                      author: "Jakob Melnyk (jmel@itu.dk)";
180
             explanation "Player trashes a Copper card from his/her hand. \
                           \If the player does so, he is granted three coins. Costs four coins."
182
             inherit ACTION
183
184
    end
185
    class_chart REMODEL
186
             indexing
187
                      author: "Jakob Melnyk (jmel@itu.dk)";
188
             explanation "Player trashes a card from his/her hand. Player gains a card costing up to two
                                       \than the trashed card. Costs 4 coins."
190
             inherit ACTION
191
192
    end
193
    class_chart SMITHY
194
             indexing
195
                      author: "Jakob Melnyk (jmel@itu.dk)";
             explanation "Grants three cards. Costs four coins."
197
             inherit ACTION
198
    end
199
200
    class_chart THRONE_ROOM
201
             indexing
202
                      author: "Jakob Melnyk (jmel@itu.dk)";
203
             explanation "Player chooses an Action card in his/her hand. That card is played twice. Costs
204
             inherit ACTION
205
206
    end
207
    class_chart COUNCIL_ROOM
208
             indexing
209
```

end

```
author: "Jakob Melnyk (jmel@itu.dk)";
210
             explanation "Grants four cards. Grants one buy. All other players are granted one card. Cost
211
             inherit ACTION
212
    end
213
214
    class_chart FESTIVAL
215
216
             indexing
                      author: "Jakob Melnyk (jmel@itu.dk)";
217
             explanation "Grants two actions. Grants one buy. Grants two coins. Costs five coins."
218
             inherit ACTION
219
220
    end
221
    class_chart LABORATORY
222
             indexing
223
                     author: "Jakob Melnyk (jmel@itu.dk)";
224
             explanation "Grants two cards. Grants one action. Costs five coins."
226
             inherit ACTION
    end
227
     class_chart LIBRARY
229
             indexing
230
                      author: "Jakob Melnyk (jmel@itu.dk)";
231
             explanation "Player draws until he/she has seven cards in hand. Player may set aside any act
232
                                       \ drawn this way; discard the set aside cards after the Player is fi
233
             inherit ACTION
234
    end
235
    class_chart MARKET
237
             indexing
238
                     author: "Jakob Melnyk (jmel@itu.dk)";
239
             explanation "Grants one card. Grants one action. Grants one buy. Grants one coin. Costs five
240
             inherit ACTION
241
242
    end
243
     class_chart MINE
244
             indexing
245
                      author: "Jakob Melnyk (jmel@itu.dk)";
246
247
             explanation "Player trashes a Treasure card from his/her hand. Player gains a treasure card
                                       \up to three coins more. Costs five coins."
248
             inherit ACTION
249
    end
250
    class_chart ADVENTURER
252
             indexing
253
                     author: "Jakob Melnyk (jmel@itu.dk)";
254
             explanation "Player reveals cards from his/her deck until two Treasure have been revealed. \
255
                                       \Player puts the two Treasure cards into hand and discard the other
256
             inherit ACTION
257
    end
258
     class_chart BUREAUCRAT
260
             indexing
261
                      author: "Jakob Melnyk (jmel@itu.dk)";
262
             explanation "Player gains a silver card on top of deck. Each other Player reveals a Victory
263
```

264

\and puts it on top of his deck (or reveals a hand with no Victory

```
inherit ACTION_ATTACK
265
    end
266
    class_chart MILITIA
268
             indexing
269
                     author: "Jakob Melnyk (jmel@itu.dk)";
270
271
             explanation "Grants two coins. Each other player discards down to three cards in his/her han
             inherit ACTION_ATTACK
    end
273
274
    class_chart SPY
275
276
             indexing
                     author: "Jakob Melnyk (jmel@itu.dk)";
277
             explanation "Grants one card. Grants one action. Each Player (including the active Player) r
278
                                      \and the active Player decides to either put the card back or discar
279
             inherit ACTION_ATTACK
280
281
    end
282
    class_chart THIEF
283
             indexing
284
                     author: "Jakob Melnyk (jmel@itu.dk)";
285
             explanation "Each other Player reveals the top two cards of his/her deck. If any Treasure ca
286
                                      \ the active Player can choose to trash one of them. The active play
287
                                       \ The other revealed cards are discarded. Costs four coins."
288
             inherit ACTION_ATTACK
289
    end
290
    class_chart WITCH
292
             indexing
293
                     author: "Jakob Melnyk (jmel@itu.dk)";
294
             explanation "Grants two cards. Each other player gains a Curse card. Costs five coins."
295
             inherit ACTION_ATTACK
296
297
    end
298
    class_chart MOAT
299
             indexing
300
                     author: "Jakob Melnyk (jmel@itu.dk)";
301
             explanation "Grants two cards. When another Player plays an Attack card and this card is in
302
                                       ackslash this card makes you unaffected by that Attack. Costs two coins."
303
             inherit ACTION_REACTION
304
    end
305
    cluster_chart GUI
     indexing
             author: "Frederik Lysgaard (frly@itu.dk)";
 3
     explanation " The graphical representation part of the project"
 4
     class GAMECLASS description " The game class"
 5
     class DECKZONE description " The deck class"
     class ACTIONZONE description " The card class"
     class DISCARDZONE description " The discardzone class"
     class HANDZONE description " The handzone class"
     class SUPPLYZONE description " The supplyzone class"
 10
     class BUTTONSPRITE description " The buttonsprite class"
11
     class CARDSPRITE description " The cardsprite class"
12
```

class PROGRAM description " The program class"

```
class GUICONSTANTS description " The constant class"
14
     class GUIINTERFACE description " The interface class for the gui"
15
   end
16
   class_chart DECKZONE
18
     indexing
19
            author: "Frederik Lysgaard (frly@itu.dk)";
20
     explanation " responsible for representing the deck"
21
22
            "Draw the content!"
23
24
   end
25
   class_chart BUTTONSPRITE
26
     indexing
27
            author: "Frederik Lysgaard (frly@itu.dk)";
28
     explanation " the basic class which all graphical objects should inherit from"
29
30
            "Draw the content!"
31
32
   end
33
   class_chart CARDSPRITE
34
     indexing
35
            author: "Frederik Lysgaard (frly@itu.dk)";
36
     explanation " responsible for representing the cards"
37
38
            "Is this cardsprite equal to this cardsprite?"
39
40
      command
            "Draw the content!"
41
42
43
    class_chart PROGRAM
44
     indexing
45
            author: "Frederik Lysgaard (frly@itu.dk)";
46
     explanation " responsible for executing the game"
47
     command
           " Run a clinet!",
49
            " Run a Host!",
50
            " Start the GUI!",
51
52
53
   class_chart GAMECLASS
54
55
     indexing
            author: "Frederik Lysgaard (frly@itu.dk)";
56
     explanation " responsible for creating the initial GUI with the components from the other classes"
57
     command
58
            " Initialize the content!",
59
            " Load the content!",
60
            " Unload the content!",
61
            " Update the game!",
62
            " Draw the content!",
63
   end
64
65
   class_chart GUICONSTANTS
66
67
     indexing
            author: "Frederik Lysgaard (frly@itu.dk)";
68
```

```
explanation " responsible for keeping all the constants used in GUI i one place"
69
   end
70
   class_chart GUIINTERFACE
72
     indexing
73
            author: "Frederik Lysgaard (frly@itu.dk)";
74
     explanation " responsible for the interface between the GUI and the Controller"
75
     command
76
            "Run the game!",
77
            "Draw the hand!",
78
            "Draw the actionzone!",
79
80
            "Draw the discardzone!",
            "Draw the deck!",
81
            "Set actions!",
82
            "Set buys!",
83
            "Set coins!"
84
            "Set endgame!",
85
            "Set the turn!",
86
            "Set the phase!",
            "Set the playernumber!",
88
            "Make the supplyzone!",
89
90
   end
   cluster_chart NETWORK_CLUSTER
            author: "Christian 'Troy' Jensen, chrj@itu.dk";
3
   explanation "The part of the program responsible for running the network"
4
   class CLIENT description "A network client"
   class SERVER description "A network server"
   class CONNECTION description "A connection between a server and a client"
   class NETWORKING_INTERFACE description "A network interface"
10
   end
11
   class_chart CLIENT
12
   indexing
13
            author: "Christian 'Troy' Jensen, chrj@itu.dk";
14
   explanation "Represents a player in a game of Dominion, one for each player"
15
16
            "Can I have the connection for this client?",
17
   command
18
            "Begin recieving more messages!",
19
20
   end
21
   class_chart SERVER
22
   indexing
23
            author: "Christian 'Troy' Jensen, chrj@itu.dk";
24
   explanation "Responsible for managing the clients of a game, only one per game"
26
            "Can I have the IP of the server?",
27
            "Can I have a list of the known clients",
    command
29
            "Start the server!",
30
            "Send this as a system message to this client!",
31
            "Send this as a system message to all clients!",
```

```
"Forward this message!",
33
   end
34
35
   class_chart CONNECTION
36
   indexing
37
            author: "Christian 'Troy' Jensen, chrj@itu.dk";
38
   explanation "Responsible for holding all the information on a client that a server has, one for each
39
40
            "Can I have the IP of the client",
41
            "Can I have the Id of the Client",
42
43
    command
            "Send this message!",
44
            "Begin recieving more messages!",
45
46
   end
47
   class_chart NETWORKING_INTERFACE
48
   indexing
49
            author: "Christian 'Troy' Jensen, chrj@itu.dk";
50
   explanation "The outward face of a networking session, keeps track of a client and maybe a server"
51
52
            "Is this interface running a server?",
53
            "Can I have the IP of the server?",
54
    command
55
            "This is the number of clients!",
56
            "Send this message, and you better give me some answers!",
57
            "Send this message",
58
   end
   static_diagram GAMESTATE_CLUSTER
   component
2
            class GAMESTATE
3
4
                    indexing
                             author: "Jakob Melnyk (jmel@itu.dk)";
5
                    feature
6
                    --Queries
                    ActivePlayer : PLAYER
                    InActionPhase : BOOLEAN
9
                    InBuyPhase : BOOLEAN
10
                    GetPhase : NATURAL
11
                    GetPlayers : SEQUENCE[PLAYER]
12
                    GetSupply : TABLE[CARD_NAME, NATURAL]
13
                    GetTrash : SEQUENCE[CARD]
14
                    NumberOfPlayers : NATURAL
15
                             ensure Result >= 2 and Result <= 4
16
                    end
17
                    NumberOfActionsLeft : NATURAL
18
                    NumberOfBuysLeft : NATURAL
19
                    NumberOfCoinsLeft : NATURAL
20
                    NewGamestate : GAMESTATE
21
                             -> numberOfPlayers : NATURAL
22
                             -> startSupply : TABLE[CARD_NAME, NATURAL]
23
                             require numberOfPlayers >= 2 and numberOfPlayers <= 4 and startSupply /= voi
24
25
                    GetScores : SEQUENCE[INTEGER]
26
```

```
--Ccmmands
28
                     SetActivePlayer
29
                             -> player : PLAYER
30
                             require playerNumber >= 1 and playerNumber <= NumberOfPlayers and player /=
31
32
                     StartActionPhase
33
                             require InActionPhase = false and InBuyPhase = false
34
                             ensure InActionPhase = true and InBuyPhase = false
35
36
                     EndActionPhase
37
                             require InActionPhase = true and InBuyPhase = false
39
                             ensure InActionPhase = false and InBuyPhase = false and NumberOfActionsLeft
                     end
40
                     StartBuyPhase
41
                             require InActionPhase = false and InBuyPhase = false
42
                             ensure InActionPhase = false and InBuyPhase = true
43
                     end
44
                     EndBuyPhase
45
                             require InActionPhase = false and InBuyPhase = true
46
                             ensure InActionPhase = false and InBuyPhase = false and NumberOfBuysLeft = 0
47
                     end
48
                     DoCleanUp
49
                             require InActionPhase = false and InBuyPhase = false
50
                     end
51
                     IncreaseActions
52
                             -> amount : INTEGER
53
                             require amount + NumberOfActionsLeft >= 0
                     end
55
                     IncreaseBuys
56
                             -> amount : INTEGER
57
                             require amount + NumberOfBuysLeft >= 0
58
                     end
59
                     IncreaseCoins
60
                             -> amount : INTEGER
61
                             require amount + NumberOfCoinsLeft >= 0
                     end
63
                     PlayerGainsCard
64
65
                             -> player : PLAYER
                             -> card : CARD_NAME
66
                             require player member_of GetPlayers and player /= void
67
                     end
68
            end
            class PLAYER
70
                     indexing
71
                             author: "Jakob Melnyk (jmel@itu.dk)";
72
                     feature
73
                     --Queries
74
                     GetAllCards : SET[CARD]
75
                     GetDeckSize : NATURAL
76
                     GetDiscardSize : NATURAL
77
                     GetHand : SEQUENCE[CARD]
78
                     GetPlayerNumber : NATURAL
79
                     GetTopOfDiscard : CARD
80
                             require GetDiscardSize /= 0
81
                     end
82
```

```
GetTopOfDeck : CARD
83
                             require GetDiscardSize /= 0
84
                     end
                     GetPlayed : SEQUENCE[CARD]
86
                     GetTemporaryZone : SEQUENCE[CARD]
87
88
                     --Commands
89
                     MoveFromZoneToTemporary
                             -> zone : ZONE
91
                             require (zone = DECK or zone = DISCARD) and (zone = DECK -> (GetDeckSize = 0
92
                                              and (zone = DISCARD -> (GetDiscardSize /= 0))
93
94
                             ensure GetTemporaryZone.Count = old GetTemporaryZone.Count + 1
                                                                                                       and (z
95
                                              and (zone = DISCARD -> GetDiscardSize = old GetDiscardSize -
96
                     end
97
                     MoveFromHandToTemporary
98
                             ->card : CARD
99
                             require GetHand.Contains(card) = false and card /= void
100
                             ensure GetHand.Contains(card) = false and GetTemporaryZone.Contains(card)
101
                     end
102
                     MoveFromTemporary
103
                             -> card : CARD
104
                             -> zone : ZONE
105
                             require (zone = DECK or zone = DISCARD or zone = HAND or zone = PLAYED) and
106
                             ensure (GetTemporaryZone.Count = old GetTemporaryZone.Count - 1) and
107
                                              (zone = DECK -> GetDeckSize = old GetDeckSize +1 ) and
108
                                              (zone = DECK -> GetTopOfDeck = old GetTemporaryZone.Get(old
                                              (zone = DISCARD -> GetDiscardSize = old GetDiscardSize + 1)
110
                                              (zone = DISCARD -> GetTopOfDiscard = old GetTemporaryZone.Ge
111
                                              (zone = HAND -> GetHand.Count = old GetHand.Count + 1) and G
112
                                              (zone = HAND -> GetHand.Get(GetHand.Count - 1) = old GetTemp
113
                                              (zone = PLAYED -> GetPlayed.Count = old Played.Count + 1) an
114
                                              (zone = PLAYED -> GetPlayed.Get(Played.Count - 1) = old GetT
115
                     end
116
                     AddCardToZone
                             -> card : CARD
118
                             -> zone : ZONE
119
                             require (zone = DECK or zone = DISCARD or zone = HAND or zone = PLAYED) and
120
                             ensure GetAllCards.Contains(card) and
121
                                              (zone = HAND -> GetHand.Get(GetHand.Count - 1) = card) and
122
                                              (zone = HAND -> GetHand.Count = old GetHand.Count + 1) and
123
                                              (zone = PLAYED -> GetPlayed.Get(GetPlayed.Count - 1) = card)
                                              (zone = PLAYED -> GetPlayed.Count = old GetPlayed.Count + 1)
125
                                              (zone = DISCARD -> GetDiscardSize = old GetDiscardSize + 1)
126
                                              (zone = DISCARD -> GetTopOfDiscard = card) and
127
                                              (zone = DECK -> GetDeckSize = old GetDeckSize +1 ) and
128
                                              (zone = Deck -> GetTopOfDeck = card)
129
                     end
130
                     RemoveCardFromZone
131
                             -> card : CARD
132
                              -> zone : ZONE
133
                             require (zone = DECK or zone = DISCARD or zone = HAND or zone = PLAYED) and
134
                                                          (zone = HAND -> GetHand.Contains(card))
135
                                              and
136
                                              and (zone = PLAYED -> GetPlayed.Contains(card))
                                              and (zone = DECK -> (GetDeckSize = 0 and GetDiscardSize = 0)
```

```
and (zone = DISCARD -> GetDiscardSize /= 0)
138
                              ensure GetAllCards.Contains(card) = false and
139
                                               (zone = HAND -> GetHand.Contains(card) = false) and
140
                                                (zone = HAND -> GetHand.Count = old GetHand.Count - 1) and
                                                (zone = PLAYED -> GetPlayed.Contains(card) = false) and
142
                                                (zone = PLAYED -> GetPlayed.Count = old GetPlayed.Count - 1)
143
                                                (zone = DISCARD -> GetDiscardSize = old GetDiscardSize - 1)
144
                                                (zone = DECK -> GetDeckSize = old GetDeckSize - 1)
145
                     end
146
                     DrawCards
147
                              -> amount : NATURAL
148
149
                     DrawCard
                              require GetDeckSize + GetDiscardSize /= 0
150
                              ensure GetHand.Count = old GetHand.Count + 1
151
                     end
152
153
                     --Invariant: A card cannot be in the DECK, DISCARD, HAND or PLAYED zones of a player
154
                                   if it is not in the 'ALL CARDS'.
155
             end
156
             class ZONE
157
                     indexing
158
                              author: "Jakob Melnyk (jmel@itu.dk)";
159
                     feature
160
                     --Queries
161
                     value : STRING
162
                              ensure Result = "DECK" or Result = "DISCARD" or Result = "HAND" or Result =
163
                     end
                      --Commands
165
             end
166
167
    end
    static_diagram CARD_TYPES_CLUSTER
 2
             component
                     class TREASURE
 3
 4
                              indexing
                                       author: "Jakob Melnyk (jmel@itu.dk)";
                              inherit CARD
 6
                     end
 8
                     class VICTORY
                              indexing
10
                                       author: "Jakob Melnyk (jmel@itu.dk)";
 11
 12
                              inherit CARD
                      end
 13
14
                     class ACTION
15
                              indexing
16
                                       author: "Jakob Melnyk (jmel@itu.dk)";
17
                              inherit CARD
18
                     end
19
20
                     class ACTION_ATTACK
21
                              indexing
22
                                       author: "Jakob Melnyk (jmel@itu.dk)";
23
                              inherit ACTION
24
```

```
end
25
26
                     class ACTION_REACTION
27
                              indexing
                                      author: "Jakob Melnyk (jmel@itu.dk)";
29
                              inherit ACTION
30
                     end
31
32
                     class KINGDOM_VICTORY
33
                              indexing
34
                                      author: "Jakob Melnyk (jmel@itu.dk)";
35
36
                              inherit VICTORY
                     end
37
    end
38
    static_diagram CARD_CLUSTER
    component
            class CARD
3
                     indexing
4
                              author: "Jakob Melnyk (jmel@itu.dk)";
5
                     feature
6
                     --Queries
                     EqualsOtherObj : BOOLEAN
                              -> obj : VALUE -- Object in C#.
9
                     EqualsOtherCard: BOOLEAN
10
                              -> other : CARD
11
                     GetName : CARD_NAME
12
                     GetNumber : NATURAL
13
                     SetUp : BOOLEAN
14
                     --Commands
15
                     Initialize
16
                             -> name : CARD
17
                              -> number : NATURAL
18
                             require SetUp = false
19
                              ensure SetUp = true
20
                     end
            end
22
23
            class CARD_FACTORY
24
                     indexing
                              author: "Jakob Melnyk (jmel@itu.dk)";
26
                     feature
27
                     --Queries
                     SetUp : BOOLEAN
29
                     CreatedCards : SET[CARD]
30
                     CardsMade : TABLE[CARD_NAME, NATURAL] --private
31
32
                     --Commands
33
                     CreateCard : CARD
34
                              -> Card : CARD_NAME
35
                              ensure Result.GetName = CARD_NAME
36
                     end
37
                     SetUpCards
38
                              -> cards : COLLECTION[CARD_NAME]
39
                              require SetUp = false and cards /= void
```

```
ensure SetUp = true
41
                    end
42
                    --Invariant commented because I could not get it to compile, but below is a rough id
43
                    --for_all c member_of CreatedCards it_holds c.GetNumber < CardsMade.get(c.GetName)
            end
45
46
            class CARD_NAME
47
                    indexing
48
                             author: "Jakob Melnyk (jmel@itu.dk)";
49
                    feature
50
                    --Queries
51
                    value: STRING --This looks very akward, but we felt it best described what we wante
52
                             ensure Result = "COPPER" or Result = "GOLD" or Result = "SILVER" or
53
                             Result = "CURSE" or Result = "ESTATE" or Result = "DUCHY" or Result = "PROVI
54
                             Result = "CELLAR" or Result = "CHAPEL" or Result = "MOAT" or Result = "CHANC
55
                             Result = "VILLAGE" or Result = "WOODCUTTER" or Result = "WORKSHOP" or
56
                             Result = "BUREAUCRAT" or Result = "FEAST" or Result = "GARDENS" or Result =
57
                             Result = "MONEYLENDER" or Result = "REMODEL" or Result = "SMITHY" or Result
58
                             Result = "THIEF" or Result = "THRONE_ROOM" or Result = "COUNCIL_ROOM" or Res
                             Result = "LABORATORY" or Result = "LIBRARY" or Result = "MARKET" or Result =
60
                             Result = "EMPTY" or Result = "BACKSIDE"
61
62
                    end
                    --Commands
            end
64
   end
65
   static_diagram CARDS_CLUSTER
            component
2
3
                    class COPPER
                             indexing
4
                                     author: "Jakob Melnyk (jmel@itu.dk)";
5
                             inherit TREASURE
6
                    end
                    class SILVER
9
                             indexing
10
                                     author: "Jakob Melnyk (jmel@itu.dk)";
11
                             inherit TREASURE
12
13
                    end
14
                    class GOLD
15
                             indexing
16
                                     author: "Jakob Melnyk (jmel@itu.dk)";
17
                             inherit TREASURE
18
                    end
19
20
                    class CURSE
21
                             indexing
22
                                     author: "Jakob Melnyk (jmel@itu.dk)";
23
                    end
24
25
                    class ESTATE
26
                             indexing
27
                                     author: "Jakob Melnyk (jmel@itu.dk)";
28
29
                             inherit VICTORY
```

```
end
30
31
                     class DUCHY
32
33
                              indexing
                                       author: "Jakob Melnyk (jmel@itu.dk)";
34
                              inherit VICTORY
35
                     end
36
37
                     class PROVINCE
38
                              indexing
39
                                       author: "Jakob Melnyk (jmel@itu.dk)";
40
41
                              inherit VICTORY
                     end
42
43
                     class GARDENS
44
45
                              indexing
                                       author: "Jakob Melnyk (jmel@itu.dk)";
46
                              inherit KINGDOM_VICTORY
47
                     end
48
49
                     class CELLAR
50
                              indexing
51
                                       author: "Jakob Melnyk (jmel@itu.dk)";
52
                              inherit ACTION
53
                     end
54
55
                     class CHAPEL
56
                              indexing
57
                                       author: "Jakob Melnyk (jmel@itu.dk)";
58
                              inherit ACTION
59
                     end
60
61
                     class CHANCELLOR
62
                              indexing
63
                                       author: "Jakob Melnyk (jmel@itu.dk)";
64
                              inherit ACTION
65
                     end
66
67
                     class VILLAGE
68
                              indexing
69
                                       author: "Jakob Melnyk (jmel@itu.dk)";
70
                              inherit ACTION
                     end
72
73
                     class WOODCUTTER
74
                              indexing
75
                                       author: "Jakob Melnyk (jmel@itu.dk)";
76
                              inherit ACTION
77
                     end
78
79
                     class WORKSHOP
80
                              indexing
81
                                       author: "Jakob Melnyk (jmel@itu.dk)";
82
                              inherit ACTION
83
84
                     end
```

```
85
                       class FEAST
86
                                indexing
87
                                         author: "Jakob Melnyk (jmel@itu.dk)";
88
                                inherit ACTION
89
                       end
90
91
                       class MONEYLENDER
92
                                indexing
93
                                         author: "Jakob Melnyk (jmel@itu.dk)";
94
                                inherit ACTION
95
96
                       \quad \text{end} \quad
97
                       class REMODEL
98
                                indexing
99
                                         author: "Jakob Melnyk (jmel@itu.dk)";
100
                                inherit ACTION
101
                       end
102
103
                       class SMITHY
104
                                indexing
105
                                         author: "Jakob Melnyk (jmel@itu.dk)";
106
                                inherit ACTION
107
                       end
108
109
                       class THRONE_ROOM
110
                                indexing
111
                                         author: "Jakob Melnyk (jmel@itu.dk)";
112
                                inherit ACTION
113
                       end
114
115
                       class COUNCIL_ROOM
116
                                indexing
117
                                         author: "Jakob Melnyk (jmel@itu.dk)";
118
                                inherit ACTION
119
                       end
120
121
                       class FESTIVAL
122
123
                                         author: "Jakob Melnyk (jmel@itu.dk)";
124
                                inherit ACTION
125
                       end
126
127
                       class LABORATORY
128
                                indexing
129
                                         author: "Jakob Melnyk (jmel@itu.dk)";
130
                                inherit ACTION
131
                       end
132
133
                       class LIBRARY
134
                                indexing
135
                                         author: "Jakob Melnyk (jmel@itu.dk)";
136
                                inherit ACTION
137
138
                       end
139
```

```
class MARKET
140
                               indexing
141
                                        author: "Jakob Melnyk (jmel@itu.dk)";
142
                               inherit ACTION
                      end
144
145
                      class MINE
146
147
                               indexing
                                        author: "Jakob Melnyk (jmel@itu.dk)";
148
                               inherit ACTION
149
                      end
150
151
                      class ADVENTURER
152
                               indexing
153
                                        author: "Jakob Melnyk (jmel@itu.dk)";
154
                               inherit ACTION
155
                      end
156
157
                      class BUREAUCRAT
158
159
                                        author: "Jakob Melnyk (jmel@itu.dk)";
160
                               inherit ACTION_ATTACK
161
162
                      end
163
                      class MILITIA
164
                               indexing
165
                                        author: "Jakob Melnyk (jmel@itu.dk)";
                               inherit ACTION_ATTACK
167
                      end
168
169
                      class SPY
170
                               indexing
171
                                        author: "Jakob Melnyk (jmel@itu.dk)";
172
                               inherit ACTION_ATTACK
173
                      end
175
                      class THIEF
176
177
                               indexing
                                        author: "Jakob Melnyk (jmel@itu.dk)";
178
                               inherit ACTION_ATTACK
179
                      end
180
                      class WITCH
182
                               indexing
183
                                        author: "Jakob Melnyk (jmel@itu.dk)";
184
                               inherit ACTION_ATTACK
185
                      end
186
187
                      class MOAT
188
                               indexing
                                        author: "Jakob Melnyk (jmel@itu.dk)";
190
                               inherit ACTION_REACTION
191
                      end
192
193
    end
```

```
static_diagram GUI
   component
            class GuiInterface
3
                     indexing
                              author: "Christian 'Troy' Jensen, chrj@itu.dk";
5
                     feature
6
                              --Commands
                              Run
                              DrawHand
9
                                      -> cards : SEQUENCE[CARD]
10
                              {\tt DrawAction}
11
                                      -> cards : SEQUENCE[CARD]
12
                              DrawDiscard
13
                                      -> card : CARD
14
                              DrawDeck
15
                                      -> filled : bool --Whether there are any cards in the deck
16
17
                              SetAction
                                      -> number : INTEGER
18
                              SetBuys
19
                                      -> number : INTEGER
20
                              {\tt SetCoins}
21
                                      -> number : INTEGER
22
23
                              {\tt EndGame}
                                      -> playerId : INTEGER
24
                              {\tt YourTurn}
25
                                      -> yourTurn : BOOLEAN
26
                              SetPhase
27
                                       -> phase : INTEGER
28
                              UsedCards
29
                                      -> cards : SEQUENCE[CARD]
30
                              {\tt SetPlayerNumber}
31
                                      -> id : INTEGER
32
            end
33
34
   end
   --NOTICE: This network design is based heavily on code I got
   --from Simon Henriksen (shen@itu.dk) and where there are similarities
   --between our code, he deserves the full credit for its design.
3
4
   --Receiving
6
   static_diagram NETWORK_CLUSTER
7
8
   component
9
            class CONNECTION
10
                     indexing
                              author: "Christian 'Troy' Jensen, chrj@itu.dk";
11
                     feature
12
                              --Queries
                              GetClientIp : IPADDRESS --C# object
14
                              GetId : INTEGER
15
                              --Commands
16
                              Send
17
                                       -> message : STRING
18
                              BeginRecieve
19
20
```

```
end
21
22
             class SERVER
23
                      indexing
                              author: "Christian 'Troy' Jensen, chrj@itu.dk";
25
                     feature
26
                               --Queries
27
                              GetIp : IPADDRESS
28
                              GetClientList : SEQUENCE[CONNECTION]
29
30
                              --Commands
31
32
                              Start
                              SystemMessageToClient --Sent to a particular client
33
                                       -> message : STRING
34
                                       -> CONNECTION : CONNECTION -- C# object
35
                              SystemMessageToAll --Sent to all clients
36
                                       -> message : STRING
37
                              ForwardMessage
38
                                       -> message : STRING
39
                                        -> clientId : INTEGER
40
                                       -> type : MESSAGETYPE
41
42
43
             end
44
             class CLIENT
45
                     indexing
46
                               author: "Christian 'Troy' Jensen, chrj@itu.dk";
47
                     feature
48
                               --Queries
49
                              GetComm : SOCKET --C# object
50
51
                               --Commands
52
                              BeginReceive
53
54
             end
55
56
             class NETWORKCONST
57
58
                     indexing
                              author: "Christian 'Troy' Jensen, chrj@itu.dk";
59
                     feature
60
                              \operatorname{\mathsf{--All}} these are constants
61
                              GetEncoder : UTF8ENCODING --C# object
62
                              GetPort : INTEGER
63
                              GetBuffersize : INTEGER
64
             end
65
66
             class NETWORKINGINTERFACE
67
                     indexing
68
                              author: "Christian 'Troy' Jensen, chrj@itu.dk";
69
                     feature
70
                               --Queries
71
                                       IsServer : BOOLEAN
72
                                       GetServerIP : STRING
73
                                       SetNumberOfClients
74
                                                -> TotalClients : INTEGER
75
```

--Commands
SendTurnMessage: SEQUENCE[STRING] --Responses from the other player
-> Message: STRING
SendPreGameMessage
-> Message: STRING
end
end
end

6.3 System production

6.3.1 General

Our split into the different, very seperate parts of the code, made it somewhat cumbersome to combine at the end, but once it actually combined, it was quite an easy ride home in terms of getting the game to play. The different parts of the architecture should be quite replaceable, especially considering the GUIInterface and NetworkingInterface concepts and the way Gamestate works.

6.3.2 GUI

Frederik Lysgaard The production of the GUI can be split into three parts:

- The initial idea.
- The attempt to write it.
- And at last the rewrite of it all.

So let's start at the begining. The initial idea of how to produce the gui was that all drawn classes should inherit from a super Sprite class but as I began coding I realized that the idea wouldn't be so optimal, since we had different objects with different positions which at that point, in my XNA traning, semmed to make it all very hard to draw, at least with different positions.

So after realizing that my first attempt of code was not going to work, I set to rewriting what I already had and try and reform it with my new knowledge of XNA. I then ended up with what is our end GUI which consist of a lot of zones where you can either draw buttons or cards sprites to, this seemed like a extremly easy straight forward solution, even though if I had had more time, I would have loved to code in some inheritance, especially a super zoneclass that would act as template for the other zoneclasses.

6.3.3 Server and Control (Server and start-up parts)

Christian Jensen

6.4 Gamestate and Control (Game Logic)

Jakob Melnyk

References

- $[1] \ http://www.riograndegames.com/games.html?id=278$
- $[2] \ http://www.riograndegames.com/uploads/Game/Game_278_gameRules.pdf$
- $[3]\ Simon\ Henriksen\ shen@itu.dk$