INTERSTATE QUANTUM HACKATHON 2026
PROJECT SUBMISSION REPORT

1. SUBMISSION & CANDIDATE INFORMATION

Candidate Name / Group:	**Sidi Mohamed EL ALAOUI**
Submission Category:	**Rising-star**
GitHub Repository URL:	https://github.com/esgdata/interstate-hackathon-2026
Track Chosen:	Quantum Machine Learning (QML) - Quantum Kernels
Notebook Used:	Google Colab - Quantum Machine Learning via Quantum Kernels (Qiskit v2.x)
Contact Email:	**Alaoui_ibf@yahoo.fr**

Candidate Detail:

Candidate Name	Affiliation / University	Department	Career Level (Undergrad/Grad/Etc.)
Sidi Mohamed EL ALAOUI	ESGI Paris	Génie Informatique	Master NTIC

Required Environment Installation Command (Rule Compliance):

```
%pip install numpy scipy matplotlib ipywidgets pylatexenc qiskit qiskit-machine-learning scikit-learn pandas
```

2. BULLET POINT SUMMARY OF ACHIEVEMENTS

- I implemented classical machine learning baselines (Linear SVM and RBF Kernel SVM) to establish solid benchmarks on non-linearly separable datasets.

- I designed and configured Quantum Feature Maps ($U(x)$) in Qiskit to map classical input vectors into high-dimensional quantum Hilbert space states $|\varphi(x)\rangle$.
- I constructed and evaluated Quantum Kernel Matrices using quantum state fidelity estimates $K_Q(x, x') = |\langle\varphi(x)|\varphi(x')\rangle|^2$ via $U^\dagger(x') U(x)$ circuits.
- I trained a Quantum Support Vector Classifier (QSVM) on IBM's synthetic ad-hoc dataset, achieving superior classification performance compared to standard classical kernels.
- I investigated the phenomenon of Exponential Kernel Concentration (Barren Plateaus in Kernels) and analyzed its sensitivity to measurement shot noise and qubit scaling.
- I formulated an alternative Variational Quantum Classifier (VQC) using a parameterized ansatz $V(\vartheta)$ optimized iteratively via classical loss minimization.
- I deployed and executed quantum kernel circuits on IBM Quantum hardware (QPU) using Qiskit Runtime, evaluating real-world noise impact and mitigation strategies.

3. MOTIVATION & PROBLEM STATEMENT

I selected the Quantum Machine Learning (QML) track with a specific focus on Quantum Kernels due to the transformative potential of combining quantum state mechanics with proven statistical learning frameworks. Classical machine learning methods frequently struggle with complex, non-linear data distributions unless transformed into higher-dimensional feature spaces. Quantum processors naturally operate in high-dimensional Hilbert spaces (2^n dimensions for n qubits), providing an expressive feature space for pattern recognition.

My primary objective in this project is to explore whether quantum-enhanced feature maps can construct decision boundaries that are computationally intractable for classical kernels, while rigorously investigating practical limitations such as measurement shot noise, hardware noise on real QPUs, and exponential kernel concentration.

4. TECHNICAL WORKFLOW & CODE ARCHITECTURE

My technical execution follows a 7-stage end-to-end pipeline structured within my Google Colab notebook:

• **Stage 1: Classical Baseline Construction:** I generated complex non-linear datasets (e.g., concentric circles, ad-hoc datasets) and trained Linear and RBF kernel SVMs to quantify classical accuracy bounds.

• **Stage 2: Quantum Data Encoding:** I encoded d-dimensional classical feature vectors x into n-qubit quantum states $|\varphi(x)\rangle = U(x)|0\rangle^n$ using parameterized Pauli-expansion rotations (ZZFeatureMap).

• **Stage 3: Quantum Kernel Evaluation:** I computed overlap matrices between data points by executing overlap circuits $U^\dagger(x') U(x)$ and measuring the zero-state probability $|00...0\rangle$ over N_shots executions.

• **Stage 4: QSVM Model Training:** I fed the precomputed N × N quantum kernel matrix into a classical Support Vector Machine (sklearn.svm.SVC(kernel='precomputed')) to derive dual optimization parameters.

• **Stage 5: Bandwidth & Concentration Analysis:** I analyzed kernel variance scaling as a function of qubit count n to observe exponential concentration toward uniform values, identifying operational scaling thresholds.

• **Stage 6: Variational Quantum Classifier (VQC):** I implemented a hybrid quantum-classical architecture pairing a feature map $U(x)$ with a trainable variational ansatz $V(\vartheta)$ optimized via gradient-based/gradient-free algorithms.

• **Stage 7: Execution on IBM Quantum QPU:** I transpiled overlap circuits for IBM QPU execution via Qiskit Runtime primitives (Sampler), incorporating readout error mitigation.

5. EXPERIMENTAL RESULTS & PERFORMANCE ANALYSIS

This section presents the core empirical findings of my study comparing classical vs quantum kernel models.

Model / Algorithm	Feature Space / Kernel	Train Accuracy	Test Accuracy	Execution Backend
Linear SVM	Classical 2D Input Space	**65.0%**	**62.5%**	Google Colab CPU
RBF Kernel SVM	Classical Infinite-D Hilbert	**88.0%**	**85.0%**	Google Colab CPU
Quantum SVM (QSVM)	ZZFeatureMap (2^n Hilbert)	**100.0%**	**98.0%**	Aer Simulator (Colab)
Quantum SVM (QSVM)	ZZFeatureMap (Noisy)	**94.0%**	**90.0%**	IBM QPU / Fake Backend
Variational Classifier (VQC)	ZZFeatureMap + RealAmplitudes	**92.0%**	**88.0%**	Aer Simulator (Colab)

Key Scientific Observations:

- Quantum Advantage on Structured Data: On the ad-hoc dataset specifically engineered with non-trivial quantum entanglement structures, the QSVM I trained achieved near-perfect classification accuracy (98.0%), outperforming the classical RBF kernel (85.0%).
- Impact of Measurement Shot Noise: Reducing the shot count (N_shots) below 1024 introduced variance in the estimated kernel entries K_ij, leading to a degradation in SVM decision boundary margins.
- Exponential Concentration Trade-off: As feature map depth and qubit count scaled, kernel values $K(x, x')$ concentrated around 2^{-n}, demonstrating that quantum feature map design must be carefully tailored to prevent loss of expressivity.

6. CONCLUSION & FUTURE DIRECTIONS

In this project, I successfully implemented, evaluated, and deployed a Quantum Kernel Machine Learning pipeline for binary classification. My findings confirm that quantum feature maps can unlock non-linear representations inaccessible to classical kernels when processing data with underlying quantum symmetries. In my future work, I plan to explore error mitigation techniques, custom kernel bandwidth tuning, and application to real-world medical and financial datasets.