

Review of Generative Adversarial Imitation Learning

Guannan Hu

April 9, 2018

Algorithm 1 Generative adversarial imitation learning

- 1: **Input:** Expert trajectories $\tau_E \sim \pi_E$, initial policy and discriminator parameters θ_0, w_0
- 2: **for** $i = 0, 1, 2, \dots$ **do**
- 3: Sample trajectories $\tau_i \sim \pi_{\theta_i}$
- 4: Update the discriminator parameters from w_i to w_{i+1} with the gradient

$$\hat{\mathbb{E}}_{\tau_i}[\nabla_w \log(D_w(s, a))] + \hat{\mathbb{E}}_{\tau_E}[\nabla_w \log(1 - D_w(s, a))] \quad (1)$$

- 5: Take a policy step from θ_i to θ_{i+1} , using the TRPO rule with cost function $\log(D_{w_{i+1}}(s, a))$. Specifically, take a KL-constrained natural gradient step with

$$\begin{aligned} & \hat{\mathbb{E}}_{\tau_i}[\nabla_{\theta} \log \pi_{\theta}(a|s)Q(s, a)] - \lambda \nabla_{\theta} H(\pi_{\theta}) \\ & \text{where } Q(\bar{s}, \bar{a}) = \hat{\mathbb{E}}_{\tau_i}[\log(D_{w_{i+1}}(s, a)) | s_0 = \bar{s}, a_0 = \bar{a}] \end{aligned} \quad (2)$$

- 6: **end for**
-