Review of Generative Adversarial Imitation Learning

Guannan Hu

April 11, 2018

Algorithm 1 Generative adversarial imitation learning

- 1: Input: Expert trajectories $\tau_E \sim \pi_E$, initial policy and discriminator parameters θ_0, w_0
- 2: **for** i = 0, 1, 2, ... **do**
- 3: Sample trajectories $\tau_i \sim \pi_{\theta_i}$
- 4: Update the discriminator parameters from w_i to w_{i+1} with the gradient

$$\hat{\mathbb{E}}_{\tau_i}[\nabla_w \log(D_w(s, a))] + \hat{\mathbb{E}}_{\tau_E}[\nabla_w \log(1 - D_w(s, a))] \tag{1}$$

5: Take a policy step from θ_i to θ_{i+1} , using the TRPO rule with cost function $\log(D_{w_{i+1}}(s,a))$. Specifically, take a KL-constrained natural gradient step with

$$\hat{\mathbb{E}}_{\tau_i}[\nabla_{\theta} \log \pi_{\theta}(a|s)Q(s,a)] - \lambda \nabla_{\theta}H(\pi_{\theta})$$
where $Q(\bar{s}, \bar{a}) = \hat{\mathbb{E}}_{\tau_i}[\log(D_{w_{i+1}}(s,a))|s_0 = \bar{s}, a_0 = \bar{a}]$
(2)

6: end for