

Chongqing Xiongzhong Agriculture Co., Ltd, founded in 2019, specializes in agricultural machinery under the "Yilong" brand. Our diverse range includes water pumps, micro-tillers, engines, and generators designed for modern farming needs.

The flagship "Yilong" micro-tiller stands out with its durable, compact and energy-efficient design. Perfect for various terrains like hills, orchards and greenhouses, it has become farmers' trusted choice for boosting productivity. Driven by innovation and customer needs, we continue to develop reliable solutions that power the future of agriculture.



170 Gasoline Mini tiller

Serial Number	Item	Unit	Design Value
1	Model Name	/	JWG4.0-1000FZ-QC Micro-tiller
2	Structural Type	/	Hand-held
3	Rated Power of Matching Engine	kw	4
4	Rated Speed of Matching Engine	r/min	3600
5	Starting Method of Matching Engine	/	Hand-crank start
6	Fuel Type of Matching Engine	/	Gasoline
7	Overall Dimensions (Length×Width×Height)	mm	1550×1000×990
8	Operating Speed	m/s	0.1~0.3
9	Vibration	m/s ²	≤50
10	Hourly Work Capacity	hm ² / (h·m)	≥0.04
11	Fuel Consumption per Unit Area	kg/hm ²	≤35
12	Working Width	mm	1000
13	Engine Output Transmission Mode	/	Direct Drive
14	Cutter Shaft Transmission Mode	/	Gear Transmission
15	Handle Adjustment Degree (Horizontal)	(°)	0
16	Handle Adjustment Degree (Vertical)	(°)	140
17	Adjustable Speed of Knife Shaft	r/min	Fast Gear: 117; Slow Gear: 70
18	Maximum Swing Radius of Cutter Head	mm	180
19	Total Number of Installed Cutters	/	24
20	Cutter Type	/	Rotary Blade
21	Main Clutch Type	/	Friction Plate Type
22	Main Clutch State	/	Normally Open



173 Diesel Mini tiller

Serial Number	Item	Unit	Design Value
1	Model Name	/	1WG4.05-105FC-ZC Micro-tiller
2	Structural Type	/	Handheld
3	Rated Power of Equipped Engine	kw	4.05
4	Rated Speed of Equipped Engine	r/min	3600
5	Starting Method of Equipped Engine	/	Pull Start
6	Fuel Type of Equipped Engine	/	Diesel
7	Overall Dimension (Length×Width×Height)	mm	1450×1050×990
8	Working Speed	m/s	0.1~0.3
9	Handle Vibration	m/s ²	≤50
10	Hourly Productivity	hm ² / (h·m)	≥0.04
11	Fuel Consumption per Unit Working Area	kg/hm ²	≤30
12	Working Width	mm	1050
13	Engine Output Transmission Mode	/	Direct Drive
14	Cutter Shaft Transmission Mode	/	Gear Transmission
15	Handle Adjustment Range (Horizontal Direction)	(°)	0
16	Handle Adjustment Range (Vertical Direction)	(°)	140
17	Designed Speed of Cutter Shaft	r/min	High gear: 130; Low gear: 90
18	Maximum Rotation Radius of Cutter	mm	180
19	Total Number of Installed Cutters	/	24
20	Rotary Cutter Type	/	Dry Land Cutter
21	Main Clutch Type	/	Friction Plate Type
22	Main Clutch State	/	Normally Open



178 diesel Mini tiller

Serial Number	Item	Unit	Design Value
1	Model Name	/	1WG4.1-120FC-ZC Micro-tiller
2	Rated Power of Equipped Engine	kw	4.1
3	Rated Speed of Equipped Engine	r/min	3600
4	Starting Method of Equipped Engine	/	Rebound Rope Start
5	Fuel Type of Equipped Engine	/	Diesel
6	Overall Dimension (Length×Width×Height)	mm	1700×1200×1050
7	Working Speed	m/s	0.1~0.3
8	Hourly Productivity	hm ² / (h·m)	≥0.04
9	Fuel Consumption per Unit Working Area	kg/hm ²	≤30
10	Working Width	mm	1200
11	Engine Output Transmission Mode	/	Direct Drive
12	Cutter Shaft Transmission Mode	/	Gear Transmission
13	Handle Adjustment Range (Horizontal Direction)	(°)	0
14	Handle Adjustment Range (Vertical Direction)	(°)	100
15	Designed Speed of Cutter Shaft	r/min	High gear: 120; Low gear: 70
16	Maximum Rotation Radius of Cutter	mm	180
17	Total Number of Installed Cutters	/	32
18	Rotary Cutter Type	/	Dry Land Cutter
19	Main Clutch Type	/	Friction Plate Type
20	Main Clutch State	/	Normally Open



186 diesel Mini tiller

Serial Number	Item	Unit	Design Value
1	Model Name	/	1WG6.3-135FC-ZC Micro-tiller
2	Structural Type	/	Hand-held
3	Rated Power of Matching Engine	kw	6.3
4	Rated Speed of Matching Engine	r/min	3600
5	Starting Method of Matching Engine	/	Hand Starting
6	Fuel Type of Matching Engine	/	Diesel
7	Overall Dimension (Length×Width×Height)	mm	1670×1360×970
8	Operating Speed	m/s	0.1~0.3
9	Handle Vibration	m/s ²	≤50
10	Hourly Productivity in Operation	hm ² / (h·m)	≥0.04
11	Fuel Consumption per Unit Operating Area	kg/hm ²	≤30
12	Working Width	mm	1350
13	Engine Output Transmission Mode	/	Direct Connection
14	Cutter Roller Transmission Mode	/	Gear Transmission
15	Handle Adjustment Range (Horizontal Direction)	(°)	0
16	Handle Adjustment Range (Vertical Direction)	(°)	145
17	Designed Speed of Cutter Roller	r/min	Fast gear: 110; Slow gear: 75
18	Maximum Rotation Radius of Cutter Roller	mm	180
19	Total Installed Number of Cutter Roller Blades	/	38
20	Rotary Tiller Blade Type	/	Dry Land Blade
21	Main Clutch Type	/	Friction Plate Type
22	Main Clutch State	/	Normally Open



188 diesel Mini tiller

Serial Number	Item	Unit	Design Value
1	Model Name	/	1WG6.3-135FC-ZC Micro-tiller
2	Structural Type	/	Hand-held
3	Rated Power of Matching Engine	kw	7.5
4	Rated Speed of Matching Engine	r/min	3600
5	Starting Method of Matching Engine	/	Hand Starting
6	Fuel Type of Matching Engine	/	Diesel
7	Overall Dimension (Length×Width×Height)	mm	1670×1360×970
8	Operating Speed	m/s	0.1~0.3
9	Handle Vibration	m/s ²	≤50
10	Hourly Productivity in Operation	hm ² / (h·m)	≥0.04
11	Fuel Consumption per Unit Operating Area	kg/hm ²	≤30
12	Working Width	mm	1350
13	Engine Output Transmission Mode	/	Direct Connection
14	Cutter Roller Transmission Mode	/	Gear Transmission
15	Handle Adjustment Range (Horizontal Direction)	(°)	0
16	Handle Adjustment Range (Vertical Direction)	(°)	145
17	Designed Speed of Cutter Roller	r/min	Fast gear: 110; Slow gear: 75
18	Maximum Rotation Radius of Cutter Roller	mm	180
19	Total Installed Number of Cutter Roller Blades	/	38
20	Rotary Tiller Blade Type	/	Dry Land Blade
21	Main Clutch Type	/	Friction Plate Type
22	Main Clutch State	/	Normally Open



192 small tractor

Serial Number	Item	Unit	Design Value
1	Model Name	/	1WG2.6-3-135C
2	Structural Type	/	Riding Front Type
3	Operation Mode	/	Manual Type
4	Rated Power of Equipped Engine	kW	6.3
5	Rated Speed of Equipped Engine	r/min	3600
6	Fuel Type of Equipped Engine	/	Diesel
7	Rated Voltage of Equipped Electric Machine	V	/
8	Rated Power of Equipped Electric Machine	kW	/
9	Rated Voltage of Equipped Generator	V	/
10	Rated Power of Equipped Generator	kW	/
11	Capacity of Equipped Rechargeable Energy Storage System	Ah	/
12	Working Voltage of Equipped Rechargeable Energy Storage System	V	/
13	Battery Type of Equipped Rechargeable Energy Storage System	/	/
14	Overall External Dimensions (Length × Width × Height)	mm	1900×830×1200
15	Working Width	mm	1350
16	Power Output Transmission Mode	/	Direct Connection
17	Cutter Shaft Transmission Mode	/	Gear Transmission
18	Driving Wheel Transmission Mode	/	Gear Transmission
19	Designed Speed of Cutter Shaft	r/min	Gear 1: 70; Gear 2: 160
20	Maximum Swing Radius of Cutter	mm	180
21	Rotary Tiller Blade Type	/	Dry Land Blade
22	Main Clutch Type	/	Friction Plate Type
23	Main Clutch State	/	Normally Open
24	Total Number of Blades Installed on Cutter Shaft	/	40
25	Steering Direction	/	Fold Steering
26	Driving Wheel Diameter	mm	Iron Wheel: 480; Rubber
27	Walking Wheel Diameter	mm	390
28	Designed Maximum Speed of Cutter Shaft	r/min	160
29	Designed Maximum Speed of Driving Wheel Shaft	r/min	36