


Date	SYM	REVISION RECORD	AUTH	DR.	CK.
12/26/03	A	Changed Material Specification	T.B.	B.S.	
03/29/13	B	Updated to "ROHS 2 COMPLIANT"	T.B.	B.S.	

MOUNTING INSTRUCTION:

USE 2-56 MACHINE SCREWS OR EYELETS 0.089" OD BY 0.15" FLANGE STIMPSON GS-3 SERIES OR EQUIVALENT ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

Estimated Weight: 13.95 g

NOTES:

MATERIAL:

HOUSING: IMPACT RESISTANCE NYLON #6, BLACK, UL 94V-0, MATERIAL FILE #UL E 48285
 SPRING: SPRING STEEL, NICKLE PLATED
 CONTACTS: SPRING STEEL, NICKLE PLATED
 EYELETS: BRASS, NICKLE PLTD.
 JUMPER: #24 AWG, 2.5" LONG
 WIRES: A.W.N. 80°C V W-1 PACIFIC CSA TR-64 90°C 24AWC, 300V, 1007 E41396 UL, 24 AWG PVC3
 ROHS 2 COMPLIANT

Tolerance (Inches)	 Memory Protection Devices, Inc. 200 Broad Hollow Road, Farmingdale, New York 11735			
Decimal			Scale	Drawn By B.S.
±.5 (.020)				Approved By T.B.
Fractional	Title			
±.8 (.030)	3AA BATTERY HOLDER WITH WIRE LEADS			
Angular	Date	Drawing Number		
± 3°	03/29/13	BH3AA-W		