SIL PROCUREMENT, SUPPLY CHAIN & INVENTORY

System administrator

For the system administrator

User manual · 28 October 2026

Figures, limits and approval chains are the system defaults; your hospital may have changed them.

Contents

1. The first administrator
2. Users (*Administration → Users*)
3. Roles (*Administration → Roles*)
4. Organisation and catalog
5. Settings you may be asked to change
6. Background jobs (*Administration → Background jobs*)
7. Integrations
8. Monitoring and support
9. Backups

System administrator

For the IT / system administrator who runs the application day to day: users and roles, reference data, integrations and background jobs. Installation, TLS, environment variables, backups and monitoring are in the technical **Deployment guide**. Read Getting started first.

The System Admin role can see and do everything. Use it for administration only. For daily work, give yourself the role you actually work in, and **turn on two-factor authentication**.

---

1. The first administrator

A new production installation has no users. After the reference data is loaded, create the first administrator from the server:

```
node dist/database/seeds/create-admin.js jdoe "Jane Doe" jdoe@hospital.org
```

The one-time password is printed once. Sign in, change it, and turn on 2FA (*My account*). Then create the other users in the application.

2. Users (*Administration → Users*)

New: **username** (lower case), **full name**, email (for notifications and approval emails), phone, **department** (it decides which department approvals the user receives as in-charge, and their default cost centre), **roles**, **stores** (for store-scoped roles) and an *Initial password*.

- The user must change the initial password at first sign-in.
- **Reset a password**: *New temporary password*. The user changes it at next sign-in.
- **Unlock**: accounts unlock by themselves after 15 minutes; resetting the password also helps.
- **Leavers**: untick **Active**. They are signed out at once and keep their history. Never delete or reuse accounts.
- **Store scope**: storekeepers, pharmacists and cashiers see only the stores you assign. Roles with *all stores* (procurement, finance, supply chain, audit, management) see every store.
- **Department in-charges** need the Department / Ward In-charge role **and** the right department. Approvals go to the in-charge of the requester's department.

3. Roles (*Administration → Roles*)

The built-in roles cover the usual jobs (see the index). You can create new roles and tick permissions. Each permission's description says what it allows.

Guidelines:

- Keep segregation of duties. Don't give one person `payments.prepare`, approval of vouchers (through the Finance manager role) **and** `payments.release`. The system blocks the same person acting twice on one voucher, but a role design that relies on it is fragile.

- Give `inventory.handle_controlled` only to staff allowed to handle controlled drugs.
- Supplier users get only the **Supplier** role and must be linked to their supplier.

4. Organisation and catalog

- **Stores** and **Bins** (*Organisation*): main store, pharmacies, satellites; parent store (who supplies whom); quarantine, controlled-drug and fridge bins.
- **Departments** (*Organisation*): code, name and **cost centre**.
- **Items / Generics** (*Catalog*): code, generic, brand, base unit and pack conversions, category, tax category, batch tracking, controlled / cold-chain flags, GTIN / barcode, sales class (OTC / P / POM / CD), VED class.
- **Bulk import** (*Catalog → Bulk import*): CSV / Excel. Validate first, review errors and duplicates, then import.

5. Settings you may be asked to change

Business settings are in the database (ask the vendor or a developer where there is no screen). Common ones, with their defaults:

Setting	Default	Effect
`security.maxFailedLogins` / `security.lockoutMinutes`	5 / 15	Lockout after wrong passwords or 2FA codes
`approvals.linkExpiryHours`	72	Lifetime of approve-by-email links
`requisitions.requireGlAccount`	false	GL account required on requisition lines
`purchasing.rfqMinSuppliers`	3	Minimum suppliers on an RFQ
`purchasing.matchPriceTolerancePct`	2	3-way match price tolerance
`purchasing.autoSendOnApproval` / `autoApproveMatchedInvoices`	false	Automation switches
`purchasing.lpoValidityDays`	60	Order validity
`purchasing.whtRates`	services 5 %	Withholding tax
`pettyCash.duplicateWindowDays` / `retirementDays`	7 / 7	Petty cash checks
`pos.discountLimits` , `pos.varianceTolerance`	5 % cashier / 50	Till rules
`accounting.autoSync`	false	Post to QuickBooks automatically
`jobs.schedules`	see below	Cron times of background jobs (applied when the worker restarts)

Approval **workflows** are edited in the application (*Approvals → Workflows*). See Supply chain § 2.

6. Background jobs (*Administration → Background jobs*)

Lists every job, its schedule, last run and result, with *run now*. Key jobs:

Job	When	Why it matters
`payments.mpesaFollowUp`	every 5 min	Follows up M-PESA payments with no result
`approvals.escalate`	every 15 min	Reminders and escalations
`accounting.dispatch` / `autoSync` / `refresh`	5 / 15 min / hourly	QuickBooks
`stock.expiry`, `stock.reorder`, `stock.amc`, `inventory.reconcile`	nightly / hourly	Stock alerts and checks
`purchasing.expireOrders`	01:30	Expires old LPOs
`pettyCash.retirementReminders`	07:00	Chases overdue advances
`reports.scheduled`	every 15 min	Emails scheduled reports
`etims.*`, `hmis.*`	every minute–daily	Integrations

A failed job shows its error. Most are safe to *run now* again.

7. Integrations

- **KRA eTIMS** (*Pharmacy & billing → KRA eTIMS*): one control unit per selling outlet (initialise it), code-table sync, **mappings** (items without a mapping can't be invoiced), the **outbox** (status, attempts, the call log, reprocess failed), and the *Specification notes*.
- **HMIS** (*Pharmacy & billing → HMIS integration*): connection (FHIR, REST, HL7 v2 or mock), *Test connection*, who bills (here or the HMIS), **code mappings** (drug codes, locations, wards, payers). The **dashboard** shows failed messages and **unmapped drug codes**: map them, then reprocess.
- **QuickBooks**: see Finance § 5.
- **M-PESA**:
  - till payments (STK / C2B): *Point of sale → POS setup → M-Pesa*;
  - supplier and petty cash **payouts**: configured on the server only (see the deployment guide). Credentials are never entered in the application.
- **API clients** (for the HMIS pushing invoices or orders): created through the API (`/api/v1/api-clients`, administrator only; there is no screen yet) with their scopes. The key is shown **once** and stored hashed.

8. Monitoring and support

- **Dashboard** integration tiles (eTIMS, HMIS, QuickBooks errors).
- **Audit log** (*Administration → Audit log*): who changed what and when.

- `ops/monitoring/check.sh` on the server (API, worker, jobs, mail queue, M-PESA, QuickBooks, eTIMS / HMIS, backup age). See the deployment guide.
- **Mail not arriving?** The outbox retries; check the SMTP settings with IT. Users can also have switched email off in *My account → Notification preferences*.

Common support requests:

Request	Answer
"I can't see menu X"	Add the role that has the permission; store-scoped roles also need the store
"I'm not getting approvals"	Check the user's role **and department** (in-charge approvals follow the requester's department), and their notification preferences
"Approval went to the wrong person"	Check *Approvals → Workflows*: band, department, category, priority
"Locked out"	Wait 15 minutes, or give a new temporary password
"Lost my phone (2FA)"	An administrator can't read the secret. Give a new temporary password; if 2FA must be removed, a developer clears it, and the user then sets it up again
"eTIMS PENDING on receipts"	Check the eTIMS outbox and control unit; documents are re-sent automatically

9. Backups

Nightly backups and a weekly restore drill are run by IT with `ops/backup/`. See the Deployment guide § 8. Keep the encryption keys and the backup passphrase in the secret store, not with the backups.