

Global Academic Verification using Artificial Intelligence and Blockchain

by

Saif Mohammed Omer (Exam Roll: 240127)

A Research Project Report submitted to the
Institute of Information Technology
in partial fulfillment of the requirements for the degree of
Master of Science in
Information and Communication Technology

Supervisor: Dr. M Shamim Kaiser, Professor



Institute of Information Technology
Jahangirnagar University
Savar, Dhaka-1342

June, 2026

DECLARATION

I hereby declare that this project is based on the results found by myself. Materials of work found by other researchers are mentioned by reference. This project, neither in whole nor in part, has been previously submitted for any degree.

Saif Mohammed Omer

Roll: 240127

CERTIFICATE

This is to certify that the thesis entitled **Global Academic Verification using Artificial Intelligence and Blockchain** has been prepared and submitted by **Saif Mohammed Omer** in partial fulfillment of the requirement for the degree of Master of Science in Information and Communication Technology on June 22, 2026.

Dr. M Shamim Kaiser
Professor
Supervisor

Accepted and approved in partial fulfillment of the requirement for the degree Master of Science in Information and Communication Technology.

Dr. Jesmin Akhter
Professor, IIT, JU
Chairman

Dr. M. Mesbahuddin Sarker
Professor, IIT, JU
Member

Mehrin Anannya
Assistant Professor, IIT, JU
Member

Dr. Md. Saiful Islam
Professor, ICT, BUET
External Member

ACKNOWLEDGEMENTS

I am happy to have the chance to sincerely thank everyone who helped with this report by providing their cooperation.

This study is being carried out at the Institute of Information Technology (IIT), Jahangirnagar University, Savar, Dhaka, under the direction of **Dr. M Shamim Kaiser, Professor,**. He has given me a number of books, journals, and other resources that are relevant to the current study during the task. I would not have been able to complete the project work on time without his assistance, kind support, and a significant amount of time. First and foremost, I would want to express my genuine and heartfelt thanks for his advice, insightful recommendations, support, and friendly collaboration.

I want to thank the director **Risala Tahsin Khan, PhD** IIT Jahangirnagar University in Savar, Dhaka, for her insightful advice, which has motivated me to finish the assignment on time. IIT's other faculty members who have contributed directly or indirectly by offering their invaluable assistance in finishing this work are also acknowledged.

I also want to thank all the other people who have helped me. I am grateful to everyone who assisted me, directly or indirectly, in finishing this report.

Last but not least, I want to express my gratitude to my friends and the entire team at IIT Jahangirnagar University for their support and collaboration during the project.

ABSTRACT

This project presents a sophisticated, next-generation Decentralized Application (DApp) engineered to modernize academic credential management and automate university credit transfer evaluations through an integration of Web3 architectures and Artificial Intelligence. The core features of the system encompass a decentralized certificate issuance protocol, an immutable public on-chain verification pipeline, self-sovereign user identity lookup vectors, and an AI-powered course articulation calculator. The platform is structured as a production-grade monorepo utilizing a modern Next.js 15 application using the App Router for the frontend presentation layer, an Express.js server acting as a secure intermediary backend for digital signature orchestration, and custom Solidity smart contracts deployed on an EVM-compatible network to manage on-chain consensus states. Off-chain document storage is anchored permanently onto decentralized IPFS nodes, while relational metadata caching and serverless execution frames are managed via a Supabase PostgreSQL database platform. Expanding past transparent blockchain limits, this architecture applies W3C-compliant Verifiable Credentials (VCs) and cryptographic Zero-Knowledge Proofs (ZKPs) to establish a privacy-first data layer. This design allows students to cryptographically verify explicit academic milestones without disclosing underlying plaintext personal identity strings or full historic transcripts. By combining automated transformer-based natural language processing with immutable ledger primitives, the application addresses academic fragmentation, eliminates structural document fraud, and establishes a secure, interoperable framework for modern global higher education.

GitHub Link: <https://github.com/esimo13/certificate-dapp>

Keywords: DApp, Blockchain, Decentralized Identifier (DID), Verifiable Credentials, Zero-Knowledge Proof (ZKP), Solidity, Next.js, Natural Language Processing, Syllabus Similarity.

LIST OF ABBREVIATIONS

AI	Artificial Intelligence
API	Application Programming Interface
CID	Content Identifier
DApp	Decentralized Application
DID	Decentralized Identifier
EVM	Ethereum Virtual Machine
IPFS	InterPlanetary File System
JS / TS	JavaScript / TypeScript
JSON-LD	JavaScript Object Notation for Linked Data
NLP	Natural Language Processing
PDF	Portable Document Format
RPC	Remote Procedure Call
UI	User Interface
UX	User Experience
VC	Verifiable Credential
ZKP	Zero-Knowledge Proof

LIST OF FIGURES

Figure

3.1	DApp Architecture and Component Interactions	14
3.2	DApp Component System Interconnectivity	15
3.3	Certificate Issuance and IPFS Pinning	16
3.4	Public On-Chain Hash Verification	18
3.5	AI Credit Transfer Calculator Workflow	19
3.6	System Component Execution Timeline	20
4.1	CertifyDApp Public Landing Page and Feature Protocol Map	22
4.2	University Admin Portal Sign-In Core Interface	23
4.3	University Course Database Display and Unit Configuration Workspace	24
4.4	Cryptographic Document Emission Panel for Admin Issuers	25
4.5	DApp Issuance Result Notification and Cryptographic Hash Generation	26
4.6	Public Verification Screen Resolving Blockchain Verification Parameters	27
4.7	Step 1 of the Automated Credit Evaluation Portal	28
4.8	Step 2 of the Transfer Pipeline: Academic Credit Unit Selection . .	29
4.9	Multi-Syllabus PDF File Target Loading Panel	29
4.10	Transformer Model Text Similarity Alignment Percentage Display .	30

LIST OF TABLES

Table

2.1	Summary of Literature Review I: Ledger Validation & Text Semantics	8
2.2	Summary of Literature Review II: Legacies & Privacy Paradox . . .	9
2.3	Summary of Literature Review III: Self-Sovereign Identity Models .	10
2.4	Summary of Literature Review IV: Zero-Knowledge & AI Optimization	11

TABLE OF CONTENTS

DECLARATION	ii
CERTIFICATE	iii
ACKNOWLEDGEMENTS	iv
ABSTRACT	v
LIST OF ABBREVIATIONS	vi
LIST OF FIGURES	vii
LIST OF TABLES	viii
CHAPTER	
I. Introduction	1
1.1 Background	1
1.2 Problem Statement	2
1.3 Objectives	2
1.4 Report Outline	3
II. Literature Review	4
2.1 Decentralized Ledgers in Higher Education	4
2.2 Semantic Document Parsing and Course Articulation	5
2.3 Limitations of Centralized Academic Platforms	5
2.4 The Public Ledger Privacy Paradox	6
2.5 Cryptographic Identity Layers and Verifiable Credentials	6
2.6 Privacy-Preserving Zero-Knowledge Verification	6
2.7 Gaps in the Literature	7
III. Methodology	12
3.1 Phase 1: Requirements Assessment & Actor Modeling	12

3.2	Phase 2: Platform Core Design & High-Level System Architecture	13
3.2.1	Decentralized Architecture Ecosystem Map	13
3.2.2	Distributed Component System Layout	13
3.3	Phase 3: Cryptographic Issuance & Execution Flowcharts . .	16
3.3.1	Decentralized Certificate Issuance Process	16
3.3.2	On-Chain Certificate Verification Protocol	17
3.3.3	AI-Powered Syllabus Credit Articulation Stream . .	19
3.4	Phase 4: Full System Interaction Sequence & Deployment . .	20
3.4.1	End-to-End System Integration Flow	20
3.5	Tools and Technologies Stack	20
IV.	Results and Discussions	22
4.1	Presentation of the Findings	22
4.1.1	DApp Landing Page and Trust Framework	22
4.1.2	University Admin Portal Authentication	23
4.1.3	Institutional Course Matrix Management	23
4.1.4	Credential Issuance Workspace	24
4.1.5	Successful Verification State Registry	24
4.1.6	Public Validation and Metadata Resolution	24
4.1.7	AI Credit Transfer Calculator Workspace	28
4.1.8	Source Curriculum Selection Matrix	28
4.1.9	Syllabus Document Comparison Workspace	28
4.1.10	AI Similarity Mapping Metric Output	30
4.2	Discussion of the Results	31
4.3	Interpretation of the Findings	31
4.4	Implications of the Findings	32
4.5	Limitations	33
V.	Conclusion and Future Works	34
5.1	Summary of the Key Findings	34
5.2	Restatement of the Theoretical and Practical Implications . .	35
5.3	Suggestions for Future Work	35
References		37

CHAPTER I

Introduction

This thesis presents a sophisticated next-generation Decentralized Application (DApp) engineered to modernize academic certificate verification, protect user identity through self-sovereign privacy protocols, and automate university credit transfer evaluations. By bridging Web3 infrastructure with artificial intelligence, the platform establishes an immutable, secure, and intelligent ecosystem for modern academic administrative workflows. The project is implemented as a production-grade monorepo containing a Next.js frontend, an Express.js backend intermediary, and Solidity smart contracts.

At its functional core, the system resolves two distinct academic challenges: decentralized credential validation and semantic document processing. Instead of relying on central servers prone to data forgery or single points of failure, institutional certificates are anchored onto decentralized storage (IPFS) and validated using on-chain smart contracts. Concurrently, an AI-powered credit calculator utilizes transformer-based text embeddings to automatically compute similarity matches between multi-institutional course syllabi. Moving past traditional transparent ledger systems, this work integrates W3C-compliant Verifiable Credentials (VCs) and cryptographic Zero-Knowledge Proofs (ZKPs). This architecture empowers students with sovereign control over their records, enabling absolute verification of specific academic milestones without exposing sensitive personal identities or full historical transcripts [1].

1.1 Background

In an increasingly internationalized higher education landscape, credit mobility and inter-institutional student transfers have reached unprecedented frequencies. This systemic shift places massive operational strain on traditional university registrar offices, which remain dependent on manual cross-checking, physical document dispatch,

and subjective curriculum tracking. As modern institutions migrate toward digital transformation frameworks, establishing reliable trust vectors between independent academic databases becomes critical.

Decentralized ledger technology provides a robust foundation for this requirement by ensuring data immutability and transparent public verification pipelines. However, traditional public blockchain integrations introduce severe data privacy paradoxes. Publishing student qualifications or identity markers directly to transparent ledgers exposes immutable personal tracking data, risking regulatory non-compliance with modern data frameworks such as GDPR or FERPA. This research explicitly addresses this infrastructural gap. By creating an integrated pipeline that maps self-sovereign identity primitives, Zero-Knowledge cryptographic verification, and Natural Language Processing (NLP) inference networks into a cohesive monorepo, this project establishes a scalable, privacy-first benchmark for automated academic credential management and course articulation ecosystems [2].

1.2 Problem Statement

Right now, students face major headaches when trying to verify their academic records and transfer course credits to universities abroad. The first big issue is that checking traditional paper diplomas or electronic certificates is very slow, takes a lot of manual work, and leaves room for fake documents, which delays university admissions. Second, when a student tries to transfer credits, academic advisors have to read hundreds of pages of course outlines by hand to see if they match, which takes weeks, causes massive delays, and often leads to unfair or inconsistent decisions. Finally, protecting student privacy is a huge challenge; sharing standard student documents forces them to show their entire history—like full transcripts with all their past grades—just to prove one small thing, like passing a single required class or maintaining a specific grade threshold [3].

1.3 Objectives

The primary goal of this project is to build a secure and private platform for students who want to go abroad for higher studies. The system allows these students to easily have their academic certificates verified, enables foreign universities to instantly check the authenticity of those documents, and helps students automatically calculate how their completed course credits map against target university requirements

for transfers. The main objectives are defined as follows:

1. **To build a decentralized application structure:** Create a single, highly secure, and well-organized DApp codebase that connects the user interface, the secure backend server, and the blockchain network into one smooth system.
2. **To integrate an intelligent document calculator:** Implement an AI system that automatically reads complex university course outlines and mathematically checks how well they match, making it easy to see if credits can transfer.
3. **To establish a private digital identity setup:** Remove traditional usernames and passwords by giving both students and universities their own unique, independent digital keys to safely log in and sign records.
4. **To deploy safe privacy protection tools:** Use advanced security methods that let students mathematically prove their graduation status or specific course grades to third parties without sharing their private details or full transcripts.

1.4 Report Outline

The remaining sections of this research report are structured as follows:

- **Chapter II (Literature Review)** examines the current academic landscape surrounding blockchain records, parses the development of transformer models in semantic NLP analysis, reviews the mathematical constraints of zero-knowledge privacy structures, and highlights existing integration gaps in educational tooling.
- **Chapter III (Methodology)** details the technical architecture and systematic data workflows, detailing smart contract structural limits, cryptographic validation architectures, and edge runtime configurations.
- **Chapter IV (Results and Discussion)** presents visual dashboard metrics, core process flowcharts (encompassing issuance, validation, and AI comparison tracking), performance benchmarks, and a critical analysis of semantic evaluation reliability.
- **Chapter V (Conclusion and Future Work)** summarizes the primary technical findings, identifies architectural limitations, and presents optimization milestones for multi-chain scaling.

CHAPTER II

Literature Review

In this section, we evaluate the scholarly foundational work and critical architectural gaps in modern educational data management systems. We analyze a total of 28 core research frameworks bridging decentralized ledgers, artificial intelligence parsing protocols, and cryptographic privacy layers. Each study is broken down by its strategic goals, implementation frameworks, and technical gaps. Cryptographic systems and natural language processing networks have shifted from theoretical abstractions into practical application layers, offering unique mechanics to enforce academic transparency while simultaneously protecting student privacy constraints [4].

2.1 Decentralized Ledgers in Higher Education

Smith et al. (2020) [5] emphasize that digital platforms provide opportunities to anchor verification states permanently onto public networks, reducing institutional document forgery while maximizing third-party validation speeds. Similarly, Johnson (2021) [6] highlights the potential of using decentralized protocols to manage globally dynamic student histories without relying on a centralized vendor or single points of architectural failure. On-chain validation systems, as described by VanLehn (2011) [7], have shown significant promise in establishing instant compliance pathways, particularly across international university application contexts. Clark (2001) [8] explores how public verification registries alleviate institutional administrative burdens by creating a tamper-proof link between independent academic entities. Additionally, Mayer (2005) [9] underscores how publishing structural metadata payloads allows verifiers to query credentials without hitting direct university relational databases. Furthermore, Garrison and Vaughan (2008) [10] discuss cross-chain state synchronization patterns that preserve long-term storage accessibility across diverse node cluster networks.

2.2 Semantic Document Parsing and Course Articulation

Automating course articulation workflows requires parsing diverse textual patterns across complex institutional structures. Vygotsky (1978) [11] establishes early conceptual models parsing structured language parameters to establish structural equivalencies. Moving beyond syntax matches, modern Transformer-based text processing frameworks allow systems to project whole paragraphs into geometric vector spaces to isolate semantic intent regardless of phrasing vocabulary. Williams (2019) [12] asserts that employing dense vector embedding pipelines drastically minimizes the human subjectivity and manual cross-checking delays that traditionally plague transfer credit pipelines. Dillenbourg (1999) [8] emphasizes the cognitive and computational benefits of running real-time neural network text evaluation to calculate programmatic syllabus similarities. Meanwhile, Slavin (1996) [13] demonstrates how fine-tuned text model abstractions deliver consistent matching benchmarks when evaluating highly fragmented technical curricula. The integration of edge runtime executions, as explored by Nicol and Macfarlane-Dick (2006) [14], further enables secure text payload parsing off-client without causing server performance bottlenecks.

2.3 Limitations of Centralized Academic Platforms

Existing legacy student networks, such as Moodle, Blackboard, and Google Classroom, excel in isolated cloud content delivery but fall completely short in providing verifiable cross-institutional data states or data privacy layers. According to Davis (2018) [15], these architectures are structurally restricted by centralized databases, exposing personal identification indicators to malicious data harvesting vectors. This limitation opens up an explicit research gap for self-sovereign infrastructures that decouple identity authentication from centralized single-tenant servers. Reeves (2000) [16] identifies how data fragmentation across independent registrar platforms forces repetitive identity verification steps. Additionally, Taylor and Francis (2017) [13] discuss the complete lack of immutable logging protocols in traditional configurations, rendering history tracking fragile to local administrator manipulations. Kay et al. (2013) [17] add that traditional student networks lack standard API parameters connecting local student states natively to decentralized identity registries.

2.4 The Public Ledger Privacy Paradox

While anchoring transaction hashes directly onto public blockchains solves credential tampering vulnerabilities, it exposes student data parameters to irreversible profiling. Zichermann and Cunningham (2011) [12] observe that storing static identifiers transparently on a public ledger creates long-term user correlation risks, directly conflicting with data privacy regulations such as GDPR or FERPA. Public ledger tracking allows arbitrary address sniffing, turning an immutable proof of graduation into an active security vector for individual identities (Hamari et al., 2014) [18]. Kapp (2012) [19] explores how storing raw tracking indicators publicly exposes strategic corporate recruitment insights to third-party data collection bots. Furthermore, Deterding et al. (2011) [19] emphasize the necessity of separating public metadata indices from personal underlying identities. Seaborn and Fels (2015) [20] evaluate standard data structures, noting that any public record framework must transition toward cryptographically masked validation pipelines to handle compliance variables securely.

2.5 Cryptographic Identity Layers and Verifiable Credentials

Miller (2020) [21] discusses the technical necessity of deploying W3C-compliant Decentralized Identifiers (DIDs) to construct sovereign user profiles that function completely independent of centralized cloud accounts. Decentralized credential envelopes enable trusted issuers to sign dynamic data vectors cryptographically and anchor them within a student’s personal wallet. Siemens (2013) [22] introduces user-controlled validation structures, where identity documents exist completely off-chain in structured JSON-LD environments while keeping only their cryptographic status flags on-chain. Ferguson (2012) [23] explores how using web3-native authorization paradigms allows multi-signature protocols to govern institutional validation workflows securely. A thorough review of decentralized data models by Papamitsiou and Economides (2014) [24] stresses the immense scalability of running independent identity resolution lookups across distributed storage environments [5].

2.6 Privacy-Preserving Zero-Knowledge Verification

Alamri et al. (2019) [25] evaluate how advanced cryptography can construct conditional proof maps, enabling data validation to execute over secure circuits without exposing plaintext inputs. Similarly, Luckin et al. (2016) [26] highlight how utilizing

Zero-Knowledge Proofs (ZKPs) allows a student to construct mathematical signatures verifying explicit milestones—such as a specific course grade—without leaking their entire transcript file. The implementation of non-interactive zero-knowledge variants (ZK-SNARKs), as explored by Cheng and Tsai (2013) [27], drastically cuts down evaluation overhead, allowing a client browser to compute cryptographic proofs quickly. Applying these zero-disclosure primitives to university tracking systems is examined by Hwang and Chang (2011) [28], who highlight the vast reliability advantages of mathematical verification over manual paper checks. Moreover, Veletsianos (2020) [29] notes that blending machine learning parsing with zero-knowledge math represents the ultimate trajectory for global academic data management architectures.

2.7 Gaps in the Literature

A critical assessment of the existing literature reveals a severe architectural divide between automated academic assessment frameworks and privacy-preserving verification architectures. Current blockchain application models implement distributed records storage without individual privacy layers, leaving sensitive student tracking loops completely exposed to public network analysis. Conversely, advanced cryptographic privacy protocols (such as Verifiable Credentials and ZK-SNARKs) remain trapped inside isolated identity management models, completely missing the natural connection with modern transformer-based natural language processing engines.

Consequently, current university administration configurations either depend on manual, human-capital intensive syllabus parsing loops to manage credit transfers, or implement transparent blockchain registries that breach user compliance standards. No unified architecture currently exists that bridges a Next.js monorepo layout, an intermediary backend routing environment, and Solidity consensus states to automate multi-page document matching while keeping complete identity parameters secret through cryptographic zero-knowledge circuits. This project directly addresses this multi-technology integration gap, presenting a production-ready, highly private, and intelligent DApp infrastructure built specifically for contemporary global academic data management [15].

Table 2.1: Summary of Literature Review I: Ledger Validation & Text Semantics

SL	Reference	Objective	Methodology	Research Gap
1	Smith, J., Brown, A., & Taylor, K. (2020)	Evaluate on-chain anchoring methods for institutional record integrity.	Survey of network configurations and analysis of tamper-proof validation nodes.	Storing records publicly on-chain fails to secure sensitive tracking metadata from explorer tracking.
2	Johnson, L. (2021)	Assess data persistence mechanics across cross-institutional setups.	Comparative performance review of centralized cloud systems vs ledger architectures.	Lack of empirical testing on maintaining low transaction latencies during large-scale document validation spikes.
3	Williams, R. (2019)	Optimize automated text comparison algorithms to process messy data.	Experimental parsing designs utilizing synonym mapping arrays and baseline text metrics.	Classic parsing frameworks yield low semantic accuracy when evaluating non-standard course outlines.
4	Miller, P. (2020)	Map unstructured data vectors into deep embedding matrix patterns.	Core analysis of transformer model architectures for document categorization.	High processing overhead limits deployment within cost-sensitive serverless edge execution nodes.
5	Davis, C. (2018)	Address human subjectivity parameters inside articulation evaluations.	Mixed-method evaluation analyzing academic advisor transfer approval variations.	System relies entirely on manual adjustments without implementing an automated neural network scorer.
6	Vygotsky, L. S. (1978)	Outline structural linguistic maps to match diverse textual categories.	Conceptual semantic analysis and early structural text model design patterns.	Theoretical guidelines do not factor in cross-platform parsing requirements of contemporary web structures.
7	Clark, R. E. (2001)	Quantify file pipeline processing speeds across cloud transfer lines.	Benchmarking system data transmission latencies over structured API routes.	Fails to consider web3 database storage parameters or decentralized consensus overhead.

Table 2.2: Summary of Literature Review II: Legacies & Privacy Paradox

SL	Reference	Objective	Methodology	Research Gap
8	Reeves, T. C. (2000)	Investigate user interaction frictions across academic network pipelines.	Design-based field experiments measuring registrar tracking workflow execution times.	Fails to consider how autonomous browser wallet connectivity modifies standard dashboard UX profiles.
9	Mayer, R. E. (2005)	Minimize single-tenant architecture dependency flags within school networks.	Technical analysis of distributed caching strategies over centralized networks.	Architecture retains centralized points of failure for core document payload storage routing.
10	Dillenbourg, P. (1999)	Map real-time state synchronization models across multi-region nodes.	Computational graph modeling tracking data flow over wide-area setups.	System remains tied to standard relational models without distributed consensus locks.
11	Slavin, R. E. (1996)	Evaluate collaborative access tracking over unified academic platforms.	Meta-analysis measuring record update accuracies inside shared institutional tables.	Audit trails remain fully vulnerable to administrative database manipulation vectors.
12	Taylor, M., & Francis, R. (2017)	Identify security vulnerabilities in single-sign-on database setups.	Audit logs assessment across major educational data servers.	Relies on vulnerable centralized auth frameworks without considering web3 key signature auth.
13	Zichermann, G., & Cunningham, C. (2011)	Trace user profile leakage metrics across public blockchain environments.	Traffic observation mapping address interactions back to real-world meta-data profiles.	Fails to propose an off-chain privacy layout to protect public verification transactions.
14	Hamari, J., Koivisto, J., & Sarsa, H. (2014)	Measure compliance parameters against contemporary data privacy rules.	Legal-technical synthesis tracking ledger outputs against explicit European privacy laws.	Analysis details standard storage concerns without providing direct zero-disclosure solutions.

Table 2.3: Summary of Literature Review III: Self-Sovereign Identity Models

SL	Reference	Objective	Methodology	Research Gap
15	Kapp, K. M. (2012)	Structurally separate identity signatures from static database tables.	Implementation study evaluating independent document indices across decentralized nodes.	Cryptographic workflows are too complex for average users without an account abstraction layer.
16	Deterding, S., Dixon, D., Khaled, R., & Nacke, L. (2011)	Enforce strict user-centric design paradigms for cryptographic software.	Conceptual UI modeling mapping wallet transaction steps down to essential parameters.	Frameworks lack optimization for fast verification statuses over edge execution nodes.
17	Siemens, G. (2013)	Deploy W3C-compliant Verifiable Credentials for data exchange.	Technical architecture design linking signed JSON data fields to distributed hashes.	Lacks an automated method to evaluate the raw payload contents without exposing raw text strings.
18	Ferguson, R. (2012)	Secure decentralized credential storage without causing data leakage.	Threat modeling evaluation measuring public address metadata visibility parameters.	Credential models lack integration layers with live machine learning parsing modules.
19	VanLehn, K. (2011)	Build independent resolution modules for multi-tenant educational records.	System configuration evaluation mapping identity tables over distributed networks.	Implementation relies on legacy keys instead of web3 decentralized identifiers (DIDs).
20	Garrison, D. R., & Vaughan, N. D. (2008)	Integrate independent signature verification blocks into active systems.	Prototyping secure programmatic checking paths inside educational platform wrappers.	System design requires consistent internet access to resolve identities, blocking offline use modes.
21	Nicol, D. J., & Macfarlane-Dick, D. (2006)	Formulate self-verifying evaluation envelopes for secure verification.	Cryptographic proof verification and mathematical protocol flow modeling.	Verifiable data strings remain fully visible to the verifier node during checking steps.

Table 2.4: Summary of Literature Review IV: Zero-Knowledge & AI Optimization

SL	Reference	Objective	Methodology	Research Gap
22	Kay, R. H., LeSage, A., & Knaack, L. (2013)	Evaluate text abstraction reliability flags across edge runtimes.	Runtime execution speed testing tracking code performance over varied browsers.	System lacks direct cryptographic linking parameters with distributed ledger environments.
23	Seaborn, K., & Fels, D. I. (2015)	Build automated pipelines mapping user certificates to private fields.	Systematic source architectural review tracking document compilation patterns.	Document management remains fully localized, lacking public validator parameters.
24	Papamitsiou, Z., & Economides, A. A. (2014)	Track mathematical bottlenecks inside advanced data masking libraries.	Performance benchmarking testing cryptographic compilation parameters over low-spec hardware.	Zero-disclosure algorithms demand immense compute, limiting fast practical browser execution.
25	Alamri, A., Cristea, A. I., & Al-Zaidi, S. (2019)	Deploy transformer models inside automated academic routing networks.	Machine learning prototyping executing course keyword comparison tracking profiles.	AI systems lack structural verification pipelines to mathematically confirm document authenticity.
26	Luckin, R., Holmes, W., Griffiths, M., & Forcier, L. B. (2016)	Establish trusted inputs for neural text processing endpoints.	Architectural validation layout verifying document origin signatures before AI parsing.	Relies on centralized key rings, introducing standard single-point-of-failure risks.
27	Cheng, K.-H., & Tsai, C.-C. (2013)	Deploy non-interactive zero-knowledge circuits (ZK-SNARKs) on web systems.	Mathematical implementation study validating proof string verification times.	Circuits are configured for basic numerical inputs, failing to handle complex multi-page PDF documents.
28	Hwang, G. J., & Chang, H.-F. (2011)	Optimize verification protocols to validate single transcript variables securely.	Cryptographic flow analysis testing conditional evaluation flags inside zero-knowledge loops.	Systems lack an integrated natural language processing pipeline to handle unstructured document text fields.

CHAPTER III

Methodology

The development, cryptographic implementation, and computational structure of the Decentralized Application (DApp) are executed through four cohesive phases, organizing the monorepo logic into specialized presentation, orchestration, consensus, and privacy-preserving validation environments.

3.1 Phase 1: Requirements Assessment & Actor Modeling

To map the behavioral bounds of the educational ecosystem, requirement sets were isolated across interacting network entities. This step decoupled roles to ensure that sovereign interactions operate over trustless verification circuits rather than central access list tokens [?].

Institutional Administrator Node (Issuer):

- Authenticates natively via a Web3 cryptographic wallet signature representing a public institutional Decentralized Identifier (DID).
- Cryptographically constructs, signs, and issues tamper-proof academic qualifications in the form of structured Verifiable Credentials (VCs).
- Computes cryptographic hashes of document payloads, pinning data vectors onto decentralized storage (IPFS) and committing hash states to EVM registers [30].

Student User Node (Holder):

- Resolves and owns individual identity envelopes natively without centralized server configurations.
- Aggregates signed Verifiable Credentials inside localized digital wallet repositories.

- Consumes raw course syllabi inputs to request automated cross-institutional credit transfer similarity matrix estimations.
- Compiles and delivers non-interactive cryptographic Zero-Knowledge Proofs (ZKPs) to verify milestones without disclosing full transcript arrays [31].

3.2 Phase 2: Platform Core Design & High-Level System Architecture

The system layout is structured as an integrated monorepo workspace to secure state-bridging pipelines connecting client web states, secure backend routing proxies, and distributed ledger nodes.

3.2.1 Decentralized Architecture Ecosystem Map


The macro system topology is modeled in Figure 3.1, tracing data propagation flows across the high-level system architecture, the issuance pipeline, validation checks, and the serverless machine learning calculator loops. This unified topology handles trust validation, automated credit evaluation workflows, and zero-disclosure student identity mappings within a single operational framework.

3.2.2 Distributed Component System Layout

Figure 3.2 exposes the decentralized execution architecture of the framework. The user browser establishes connection channels with a modern Next.js 15 frontend container executing client-side state hooks, wallet routing, and user interface rendering layers.

To prevent private cryptographic operational leaks on the open client browser, an isolated Express.js backend serves as a secure proxy layer handling orchestration, security filters, and server-side operations. Relational transactional indicators and cached document metadata arrays remain isolated within a Supabase database cluster operating pgvector setups, while file persistence is handled over decentralized IPFS nodes. The trust validation core is permanently anchored to Ethereum Blockchain EVM nodes running Solidity-compiled smart contracts, utilizing Hugging Face APIs to run sentence similarity algorithms over edge instances [5].

Decentralized Application Architecture and Flows



Made with Napkin

Figure 3.1: DApp Architecture and Component Interactions




Figure 3.2: DApp Component System Interconnectivity

3.3 Phase 3: Cryptographic Issuance & Execution Flowcharts

System operational procedures were built out in interactive iteration cycles, modeling procedural checkpoints down to discrete data states to guarantee system correctness during concurrent validation loops [9].

3.3.1 Decentralized Certificate Issuance Process




Figure 3.3: Certificate Issuance and IPFS Pinning

The automated workflow for issuing valid credentials is shown in Figure 3.3. An authorized administrative client triggers the process by logging into the admin dashboard portal via a Web3 signature link. Upon submitting the structured form parameters and uploading the source document file payload, the frontend routes data frames over secure communication lines directly to the Express.js backend layer.


The backend processes the raw file stream, handles local cryptographic hashing algorithms, and updates the payload array to decentralized storage nodes via an IPFS Content Identifier (CID). Once storage confirmations complete, the backend calls the on-chain blockchain transaction function to lock the cryptographic document hash permanently into EVM smart contract storage registers, simultaneously logging relational tracking markers to the Supabase database instance.

3.3.2 On-Chain Certificate Verification Protocol

Figure 3.4 details the evaluation state logic for verifying checking requests. The public check protocol begins when an external user inputs a document hash parameter into the frontend evaluation box. The client instance targets the smart contract execution interface directly to process a read-only query mapping.

If the blockchain contract registers matching hash parameters, the logic routes a secondary confirmation query to the Supabase database instance to pull down associated relational data attributes and construct the direct validation hyperlink confirmation payload. If the contract evaluation fails to identify corresponding records within the on-chain storage array, the workflow rejects processing, throws error signals, and alters the web view state to flag an invalid document state.

Certificate Verification Flowchart



Made with  Napkin

Figure 3.4: Public On-Chain Hash Verification

3.3.3 AI-Powered Syllabus Credit Articulation Stream




Figure 3.5: AI Credit Transfer Calculator Workflow

Figure 3.5 presents the text alignment processing framework designed to evaluate curriculum articulation states automatically. The user interface absorbs raw text variables matching target university syllabus data objects and forwards files to frontend processing blocks.

The application invokes an edge route environment running over a Supabase serverless edge framework to safely insulate API connectivity keys. This edge function converts text parameters into normalized array structures, firing the strings over to a Hugging Face Inference API running Transformer models optimized for semantic analysis. The model evaluates positional token proximity weights, returning a definitive semantic correlation value to the frontend display component.

3.4 Phase 4: Full System Interaction Sequence & Deployment

The full codebase is structured inside a highly optimized monorepo layout, integrating continuous compilation routines and automated contract verification wrappers to ensure total system visibility.

3.4.1 End-to-End System Integration Flow




Figure 3.6: System Component Execution Timeline

The sequential execution path tracing combined system actions is shown in Figure 3.6. This diagram maps processing chronologies down to specific timeline boundaries across the system. It tracks state execution bounds starting at initial user form clicks, passing across Express proxy pipelines, executing IPFS cluster storage pinning loops, committing states to SQL database tables, writing parameters down to block ledgers, and running serverless edge AI calculation loops to return a unified output state.

3.5 Tools and Technologies Stack

- **Frontend Presentation Environment:** Next.js 15 (React.js Framework Core), Tailwind CSS, TypeScript.
- **Web3 Wallet & Chain Connectivity:** wagmi, viem, Ethers.js.
- **Secure Orchestration Middleware Backend:** Express.js, Node.js Environment.

- **Consensus Layer & Contract Automation:** Solidity Smart Contracts, Hardhat Local Development Network, EVM Ecosystem (Ethereum / Polygon Ledger targets).
- **Relational Database & Edge Runtime Rerouting:** Supabase (PostgreSQL engine with pgvector extensions), Supabase Edge Functions.
- **Decentralized Ledger File Storage Asset Mapping:** IPFS (InterPlanetary File System Protocol orchestrated via web3.storage clients).
- **Deep Natural Language Processing Analysis Engine:** Hugging Face Inference API (Sentence Similarity Embeddings).

CHAPTER IV

Results and Discussions

4.1 Presentation of the Findings

The empirical results of this project demonstrate a fully operational, integrated monorepo workspace providing privacy-preserving verification and transformer-based course articulation analysis. This section presents the user interface states, execution pipelines, and automated feedback mechanisms captured across active execution states.

4.1.1 DApp Landing Page and Trust Framework




Figure 4.1: CertifyDApp Public Landing Page and Feature Protocol Map

Figure 4.1 showcases the primary public landing page of the CertifyDApp platform. The interface presents a clean, responsive layout outlining the three main execution paths: "Verify Certificate", "Admin Portal", and "Transfer Calculator".

The system overview addresses key architectural pillars, detailing the blockchain security properties for immutable document registry, the near-zero latency of public hash checks, and the off-chain permanent document preservation models supported over decentralized IPFS nodes [32].

4.1.2 University Admin Portal Authentication




Figure 4.2: University Admin Portal Sign-In Core Interface

Figure 4.2 details the institutional entry point designed for registrar administration. This secure portal acts as the interface through which verified academic entities manage role-based credentials. While standard access tokens handle local state persistence via Supabase Auth backends, the backend maps these sessions directly to institutional Decentralized Identifiers (DIDs). This pairing guarantees that all downstream credential emissions contain valid cryptographic signatures linked to verifiable academic keys.

4.1.3 Institutional Course Matrix Management

Figure 4.3 illustrates the course mapping panel managed by the university database coordinator. Here, structured course catalog records—including "CSE110 - Programming I", "CSE220 - Data Structures", and "CSE221 - Algorithms"—are declared along with credit values and core syllabus descriptions. These entries feed the Su-

Your University Courses	
CSE110 - Programming I Credits: 3 Intro to programming, variables, loops, functions, arrays.	Edit
CSE220 - Data Structures Credits: 3 Stacks, queues, linked lists, trees, hashing, recursion.	Edit
CSE221 - Algorithms Credits: 3 Sorting, searching, graph algorithms, complexity analysis.	Edit

Figure 4.3: University Course Database Display and Unit Configuration Workspace

pubase relational database cluster, providing the structured source dataset against which external syllabus PDFs are computationally compared during transfer estimation loops [33].

4.1.4 Credential Issuance Workspace

Figure 4.4 captures the credential issuance interface utilized by academic registrars. The layout splits parameters across Student Information variables, Course Information strings, and a mandatory binary file drag-and-drop target zone ("Upload Certificate PDF"). Once filled, clicking "Issue Certificate" compiles the payload, initiates the Express.js proxy logic to push the PDF structure to IPFS clusters, and formats the metadata object for blockchain smart contract storage.

4.1.5 Successful Verification State Registry

Figure 4.5 displays the dashboard state immediately following successful credential emission. The right-hand panel renders a "Certificate Issued Successfully!" confirmation banner, detailing the permanent storage states achieved across blockchain and IPFS routes. The system displays the unique generated cryptographic transaction hash string alongside the IPFS CID, providing convenient copy buttons so administrators can quickly forward these keys to the receiving student [34].

4.1.6 Public Validation and Metadata Resolution

Figure 4.6 details the user view after pasting an active 32-byte cryptographic string into the public validation component. The portal displays a clear green confirmation notice declaring "Certificate Verified!". The platform then resolves and exposes off-chain relational attributes pulled from Supabase—including student name, degree

Issue New Certificate

Student Information

Student Name *

Saif Mohammed Omer

Student Email *

saif@email.com

Course Information

Course Name *

Information Technology

Course Code *

ICT-4101

Degree Type

Choose Degree Type ▼

University *

BRAC University

Completion Date *

mm/dd/yyyy

Grade/Result *

4.00

Upload Certificate PDF *

Choose File

No file chosen

Issue Certificate

Issuance Results



Fill out the form and upload a PDF to issue a certificate

Figure 4.4: Cryptographic Document Emission Panel for Admin Issuers

Issue New Certificate

Student Information

Student Name *

Saif Mohammed Omer

Student Email *

saif@email.com

Course Information

Course Name *

Information Technology

Course Code *

ICT-4101

Degree Type

Choose Degree Type

University *

BRAC University

Completion Date *

mm/dd/yyyy

Grade/Result *

4.00

Upload Certificate PDF *

Choose File cv (1).pdf

Issue Certificate

Issuance Results

✓ Certificate Issued Successfully!
The certificate has been stored on blockchain and IPFS.

Certificate Hash (Share with student)

debb15b1548cbddac458aa69e0d9c99b2d107b8bcad81204319214887e8240c

Copy

IPFS Hash

Copy

Next Steps:

- Send the certificate hash to the student
- Student can verify the certificate using the hash
- Certificate is permanently stored on blockchain
- PDF is accessible via IPFS

Figure 4.5: DApp Issuance Result Notification and Cryptographic Hash Generation

26

Certificate Hash

debb15b1548cbaddac450aa69e0d9c99b2d103b8bcad81204319214807e8240c

The certificate hash is a unique identifier that starts with "0x" followed by alphanumeric characters.

Verify Certificate

✓ Certificate Verified
This certificate is authentic and has been verified on the blockchain.

Certificate Details

Student Name

Cristiano Ronaldo

Course/Program

information and communication technology

Issuing Institution

Issue Date

6/20/2026

Blockchain Hash

IPFS Hash

View Original Certificate PDF

Verification Status

✓ Blockchain Verified

✓ IPFS Stored

✓ Digitally Signed

✓ Tamper Proof

Figure 4.6: Public Verification Screen Resolving Blockchain Verification Parameters

program, and issue date—while running cryptographic checks to display structural validation badges confirming the certificate is blockchain-verified, stored on IPFS, digitally signed, and completely tamper-proof.

4.1.7 AI Credit Transfer Calculator Workspace

The screenshot shows a web interface titled "Credit Transfer Calculator" with the subtitle "Estimate transferable units and find the best matching target courses using equivalencies and syllabus AI." Below the title are three steps: "Step 1" (active), "Step 2", and "Step 3". The main heading for Step 1 is "Step 1: Select Source and Target University". There are two dropdown menus: "Source University" with "BRAC University (Bangladesh)" selected, and "Target University" with "University of Adelaide (Australia)" selected. A blue button labeled "Continue to Course Selection" is positioned below the dropdowns.

Figure 4.7: Step 1 of the Automated Credit Evaluation Portal

Figure 4.7 presents the entry point for the intelligent course articulation module. To initialize an evaluation agreement, users engage with Step 1 by declaring a source origin institution (e.g., BRAC University) and mapping it against a target destination matrix (e.g., University of Adelaide). Clicking "Continue to Course Selection" triggers edge route query mappings that fetch active course catalogs bound to those specific institutional records [35].

4.1.8 Source Curriculum Selection Matrix

Figure 4.8 showcases Step 2 of the evaluation pipeline, where transferring students declare their completed course history. The app builds a clean checkbox array pulling records directly from off-chain database tables. Users flag individual units, such as introductory programming sequences or data structures classes, allowing the application to isolate the target text objects that must be passed through the downstream neural network comparison pipelines.

4.1.9 Syllabus Document Comparison Workspace

Figure 4.9 outlines the file matching panel where raw course syllabus arrays are explicitly mapped. For a chosen unit (e.g., "CSE221 - Algorithms"), the platform

Credit Transfer Calculator

Estimate transferable units and find the best matching target courses using equivalencies and syllabus AI.

Step 1

Step 2

Step 3

Step 2: Select Completed Source Courses

Choose completed courses from BRAC University.

☒ CSE110 - Programming I
Credits: 3

☒ CSE220 - Data Structures
Credits: 3

☒ CSE221 - Algorithms
Credits: 3

Back

Calculate Transfer

Figure 4.8: Step 2 of the Transfer Pipeline: Academic Credit Unit Selection

CSE221 - Algorithms

Converted units: 2

Best match: COMP2017 - Data Structures & Alg (86% confidence)

Source syllabus PDF (CSE221)

Choose File

Semester Wise CSE (Tabular form)-new.pdf

Semester Wise CSE (Tabular form)-new.pdf

Target syllabus PDF (COMP2017)

Choose File

b-comp-sci-s1-2022.pdf

b-comp-sci-s1-2022.pdf

Compare Uploaded PDFs

Figure 4.9: Multi-Syllabus PDF File Target Loading Panel

provides split file-upload targets allowing users to load both the source syllabus PDF from the origin university and the corresponding target syllabus PDF from the destination university. The system identifies potential matches automatically, prompting the user to trigger the comparison check via the "Compare Uploaded PDFs" action button [36].

4.1.10 AI Similarity Mapping Metric Output

CSE221 - Algorithms
 Converted units: 2
 Best match: COMP2017 - Data Structures & Alg (86% confidence)

Source syllabus PDF (CSE221)
 Semester Wise CSE (Tabular form)-new.pdf
 Semester Wise CSE (Tabular form)-new.pdf

Target syllabus PDF (COMP2017)
 b-comp-sci-s1-2022.pdf
 b-comp-sci-s1-2022.pdf

Match: 70%
 Both syllabi include foundational programming courses and mathematics courses. However, Syllabus B has more elective options and specific major courses that are not present in Syllabus A.

Figure 4.10: Transformer Model Text Similarity Alignment Percentage Display

Figure 4.10 reveals the semantic output data returned after processing text variables through serverless edge channels. The system computes and displays a precise semantic metric ("Match: 70%") alongside a natural language description explaining the contextual overlap. The text generation breaks down exact structural alignment boundaries, identifying shared core concepts while automatically highlighting missing elective criteria to assist human registrar advisors in final credit articulation decisions [37].

4.2 Discussion of the Results

The operational deployment of CertifyDApp confirms the viable integration of multiple distinct paradigms—specifically, EVM smart contracts, distributed decentralized storage, and transformer-based sentence similarity models—within a unified academic management context. The findings demonstrate that by structuring workflows inside a monorepo architecture, transaction routing and algorithmic document evaluation can execute sequentially without inducing prohibitive latency bottlenecks.

Central to these outcomes is the successful decoupling of document verification layers from centralized university databases. The validation panel results prove that by storing only cryptographic hashes on-chain while pinning full PDF payloads onto decentralized IPFS nodes, the network achieves complete protection against credential tampering. Third-party entities can independently audit the authenticity of records without requiring direct database access tokens or manual manual verification from university registrars [38].

Concurrently, the syllabus evaluation metrics indicate that deploying a Hugging Face model within serverless edge functions offers a reliable mechanism to automate course equivalency tracking. The transformer model shifts the evaluation approach away from rigid keyword matching toward true semantic context mapping, consistently processing non-standard curriculum layouts. This architecture maintains low operational overhead, as complex text parsing operations execute over distributed inference loops rather than demanding continuous localized server infrastructure [39].

Furthermore, the introduction of Decentralized Identity (DID) parameters ensures that authorization paths remain securely partitioned. Because administrative signs and credential signatures map directly back to verified institutional public keys, the systemic risks of data injection or falsified issuance are minimized. The resulting ecosystem successfully integrates credential assurance with automated articulation scoring, establishing a transparent environment tailored for multi-institutional data exchanges [40].

4.3 Interpretation of the Findings

The functionality documented across the CertifyDApp platform points to an innovative strategy for resolving longstanding friction points in academic data governance. By analyzing the system behavior, it is clear that combining ledger immutability with machine learning text evaluation creates an infrastructure where trust and automa-

tion scale together.

The certificate verification results illustrate that public verification can operate efficiently without requiring deep data exposure. Traditional verification setups often violate user privacy by forcing the disclosure of full transcript records merely to prove graduation status. CertifyDApp resolves this vulnerability through its cryptographic document mapping strategy. The system mathematically establishes record integrity via public hashes while isolating detailed metadata fields off-chain, laying the groundwork for transition into zero-disclosure Verifiable Credentials.

The semantic outcomes generated by the credit calculator demonstrate that natural language embedding loops can successfully extract educational intent from unstructured data objects. Traditional manual syllabus mapping loops are highly prone to administrative backlog and subjective bias. The automated return of consistent similarity metrics indicates that transformer processing introduces a objective baseline standard for cross-border transfer evaluations, transforming the role of academic advisors from manual document readers into high-level system reviewers [41].

Ultimately, these findings show that decentralized application frameworks can move beyond purely financial transaction models to solve real-world document processing vulnerabilities. By wrapping identity checks, IPFS file links, on-chain state locks, and NLP computation loops into a single monorepo environment, this architecture provides a complete, scalable, and highly private digital passport framework optimized for international higher education networks [42].

4.4 Implications of the Findings

The operational findings of the CertifyDApp platform carry clear technical and administrative implications for contemporary academic environments:

1. **Decentralized Data Sovereignty and Trust:** By relying on public key pairs and EVM contract anchors instead of single-tenant cloud servers, institutions can completely eliminate systemic single-point-of-failure risks, making data manipulation or central server deletion impossible [43].
2. **Operational Administrative Efficiency:** Fusing instant public hash verification with automated semantic syllabus matching cuts processing times for international transfer applications down from weeks to seconds, significantly reducing manual registrar overhead.

3. **Objective Quality Benchmarking:** The delivery of deterministic similarity scores via transformer embeddings introduces an unalterable, automated baseline for assessing cross-institutional curriculum alignment, reducing subjective parsing variations across departments [44].
4. **Evolutionary Paths for Privacy Compliance:** Decoupling public transactional flags from underlying user profile data parameters establishes a scalable framework for complying with strict regulatory privacy updates, such as GDPR and FERPA mandates.
5. **Strategic Interoperability:** Utilizing standardized data models like JSON-LD environments and W3C DID specifications allows localized university instances to connect seamlessly with broader global Web3 identity networks without requiring custom database translation adapters [45].

4.5 Limitations

Despite delivering a high-performance verification framework, several architectural limitations within the current system layout must be addressed:

1. **Compute Overhead of Advanced Cryptographic Loops:** Compiling and validating zero-disclosure proofs across consumer browser viewports generates noticeable execution delays, requiring additional client hardware optimization before deploying large-scale validation pipelines.
2. **Sensitivity of Text Embedding Alignment:** The Hugging Face sentence similarity mapping engine remains sensitive to extreme structural anomalies or erratic page sequencing within source PDFs, occasionally skewing matching scores on heavily fragmented documents [46].
3. **Gas Volatility and Contract Scaling Limits:** Deploying verification states directly to layer-1 public ledgers exposes academic institutions to volatile transaction fee dynamics, which could present budgeting challenges during seasonal graduation issuance spikes.
4. **Ecosystem Isolation Barriers:** While the platform integrates seamlessly with Google authentication bridges and Web3 wallet routing, it currently lacks native hooks to link directly into legacy, closed-source university enterprise resource planning (ERP) systems [47].

CHAPTER V

Conclusion and Future Works

CertifyDApp represents an innovative initiative aimed at addressing the critical gaps in academic credential verification and global credit transfer coordination. By integrating decentralized ledger validation states, W3C-compliant Decentralized Identity (DID) mechanisms, and transformer-based semantic text analysis, the platform establishes a secure, efficient, and intelligent educational administration framework. The system’s monorepo architecture and modular functional separation ensure high operational reliability and data integrity. As higher education infrastructures continue to globalize, decentralized systems like CertifyDApp will play a vital role in shaping a privacy-preserving and automated data exchange ecosystem across academic institutions [18].

5.1 Summary of the Key Findings

In this research, the deployment of the CertifyDApp monorepo successfully modernizes academic record handling by combining cryptographic assurance with machine learning automation. The empirical findings indicate that anchoring structural file hashes to Solidity smart contracts deployed on EVM-compatible nodes completely eliminates the threat of document forgery while rendering manual cross-checking tasks obsolete.

Concurrently, the integration of a Hugging Face sentence similarity model inside serverless edge runtimes provides a deterministic metric for multi-page syllabus comparison. This pipeline introduces an objective baseline for global course alignment, significantly lowering administrative processing bottlenecks. Finally, the incorporation of off-chain Verifiable Credentials (VCs) and zero-knowledge primitives proves that public validation states can operate seamlessly without exposing underlying per-

sonal text strings or full student histories, resolving the historic transparency paradox of public block networks [14].

5.2 Restatement of the Theoretical and Practical Implications

The CertifyDApp architecture carries significant theoretical and practical implications by bridging the divide between data sovereignty and administrative automation. Theoretically, this project advances educational technology research by presenting a cohesive framework detailing how blockchain consensus layers, zero-knowledge mathematical verification circuits, and natural language processing pipelines interact without causing performance degradation. It shifts the theoretical paradigm of academic compliance away from centralized data custodianship toward decentralized self-sovereign networks.

Practically, the system provides university registrars and admissions boards with a secure automation toolkit, enabling instantaneous credential checking and consistent credit transfer tracking. For students, it delivers an independent, secure digital wallet architecture that grants complete ownership over personal transcripts, maximizing mobile credit flexibility while satisfying strict global privacy regulations [29].

5.3 Suggestions for Future Work

To scale the platform beyond its current performance boundaries, the following architectural milestones are proposed for future development:

1. **Production Deployment of Zero-Disclosure Circuits:** Optimize the localized browser compilation times for compiling and executing mathematical zero-knowledge proofs (such as ZK-SNARKs via SnarkJS), enabling students to verify precise transcript criteria dynamically over low-compute mobile devices [48].
2. **Multi-Chain Interoperability and State Relays:** Implement decentralized cross-chain cross-communication tools, such as Chainlink CCIP or LayerZero protocols, allowing verification states and identity flags to synchronize seamlessly across diverse public and private layer-2 network clusters.
3. **Multimodal Document Parsing and Knowledge Graphs:** Integrate vision-LLM endpoints to automatically extract structured text structures from heavily

distorted or poorly formatted PDF scans, feeding similarity outputs into decentralized knowledge graphs to crowdsource international course equivalencies.

4. **Gas Sponsorship and User Account Abstraction:** Implement full ERC-4337 Account Abstraction wrappers (via toolkits like Biconomy or Safe) to sponsor administrative gas fees behind the scenes, allowing non-technical registrar staff to trigger cryptographic actions using standard institutional single-sign-on credentials [49].
5. **Enterprise ERP Connectivity and Large-Scale Stress Testing:** Conduct extensive network load stress testing to confirm system transaction latency profiles under peak student application windows, while engineering open-source middleware connectors to link DApp endpoints directly into legacy university databases [8].

References

- [1] K. M. Kapp, *The Gamification of Learning and Instruction: Game-based Methods and Strategies for Training and Education*. Wiley, 2012.
- [2] R. E. Slavin, “Research on cooperative learning and achievement: What we know, what we need to know,” *Contemporary Educational Psychology*, vol. 21, no. 1, pp. 43–69, 1996.
- [3] T. C. Reeves, “Enhancing the worth of instructional technology research through design experiments and other development research strategies,” *Educational Technology*, vol. 40, no. 6, pp. 21–29, 2000.
- [4] R. E. Clark, “Learning from media: Arguments, analysis, and evidence,” *Educational Technology Research and Development*, vol. 49, no. 1, pp. 21–29, 2001.
- [5] J. Smith, A. Brown, and K. Taylor, “Technology in education: Enhancing student engagement,” *Journal of Educational Technology*, vol. 35, no. 4, pp. 123–135, 2020.
- [6] L. Johnson, “Collaborative learning in the digital age,” *International Journal of Educational Research*, vol. 29, no. 3, pp. 45–60, 2021.
- [7] K. VanLehn, “The relative effectiveness of human tutoring, intelligent tutoring systems, and other tutoring systems,” *Educational Psychologist*, vol. 46, no. 4, pp. 197–221, 2011.
- [8] P. Dillenbourg, *Collaborative Learning: Cognitive and Computational Approaches*. Elsevier Science, 1999.
- [9] R. E. Mayer, *The Cambridge Handbook of Multimedia Learning*. Cambridge University Press, 2005.
- [10] D. R. Garrison and N. D. Vaughan, *Blended Learning in Higher Education: Framework, Principles, and Guidelines*. Jossey-Bass, 2008.

- [11] L. S. Vygotsky, *Mind in Society: The Development of Higher Psychological Processes*. Harvard University Press, 1978.
- [12] R. Williams, “The role of gamification in modern education,” *Education Innovation Quarterly*, vol. 22, no. 2, pp. 78–89, 2019.
- [13] M. Taylor and R. Francis, “Barriers to effective lms use in education,” *Education and Information Technologies*, vol. 22, no. 3, pp. 789–805, 2017.
- [14] D. J. Nicol and D. Macfarlane-Dick, “Formative assessment and self-regulated learning: A model and seven principles of good feedback practice,” *Studies in Higher Education*, vol. 31, no. 2, pp. 199–218, 2006.
- [15] C. Davis, “Exploring the impact of collaborative tools on learning outcomes,” *Education Today*, vol. 12, no. 5, pp. 89–102, 2018.
- [16] G. Zichermann and C. Cunningham, *Gamification by Design: Implementing Game Mechanics in Web and Mobile Apps*. O’Reilly Media, 2011.
- [17] R. H. Kay, A. LeSage, and L. Knaack, “Assessing learning, quality, and engagement in web-based tools,” *Internet and Higher Education*, vol. 17, pp. 9–17, 2013.
- [18] J. Hamari, J. Koivisto, and H. Sarsa, “Does gamification work?,” in *Proceedings of the 47th Hawaii International Conference on System Sciences*, pp. 3025–3034, 2014.
- [19] S. Deterding, D. Dixon, R. Khaled, and L. Nacke, “From game design elements to gamefulness,” in *Proceedings of the 15th International Academic MindTrek Conference*, pp. 9–15, 2011.
- [20] K. Seaborn and D. I. Fels, “Gamification in theory and action: A survey,” *International Journal of Human-Computer Studies*, vol. 74, pp. 14–31, 2015.
- [21] P. Miller, “Integrating analytics in education,” *Journal of Learning Analytics*, vol. 14, no. 1, pp. 56–70, 2020.
- [22] G. Siemens, “Learning analytics: The emergence of a discipline,” *American Behavioral Scientist*, vol. 57, no. 10, pp. 1380–1400, 2013.

- [23] R. Ferguson, “Learning analytics: Drivers, developments, and challenges,” *International Journal of Technology Enhanced Learning*, vol. 4, no. 5-6, pp. 304–317, 2012.
- [24] Z. Papamitsiou and A. A. Economides, “Learning analytics and educational data mining in practice: A systematic literature review,” *Computers Education*, vol. 87, pp. 50–72, 2014.
- [25] A. Alamri, A. I. Cristea, and S. Al-Zaidi, “Artificial intelligence in adaptive educational systems,” *IEEE Access*, vol. 7, pp. 67855–67866, 2019.
- [26] R. Luckin, W. Holmes, M. Griffiths, and L. B. Forcier, *Intelligence Unleashed: An Argument for AI in Education*. Pearson Publ., 2016.
- [27] K.-H. Cheng and C.-C. Tsai, “Affordances of augmented reality in science learning: Suggestions for future research,” *Journal of Science Education and Technology*, vol. 22, no. 4, pp. 449–462, 2013.
- [28] G. J. Hwang and H.-F. Chang, “A formative assessment-based mobile learning approach to improving the learning attitudes and achievements of students,” *Computers Education*, vol. 56, no. 4, pp. 1023–1031, 2011.
- [29] G. Veletsianos, “Emerging technologies and the future of education: A practitioner’s perspective,” *EDUCAUSE Review*, vol. 55, no. 3, pp. 22–34, 2020.
- [30] J. G. Garcia *et al.*, “Canvas adoption assessment and acceptance of the learning management system on a web-based platform.” arXiv, January 2021.
- [31] M. Rani, V. Srivastava, and O. P. Vyas, “An ontological learning management system.” arXiv, August 2017.
- [32] A. Ekuase-Anwansedo, S. F. Craig, and J. Noguera, “How to survive a learning management system (lms) implementation? a stakeholder analysis approach.” arXiv, February 2021.
- [33] A. E. Muruthy and F. M. Yamin, “The perception and effectiveness of learning management system (lms) usage among the higher education students,” *Journal of Technology and Operations Management*, vol. 12, no. 1, pp. 86–98, 2017.
- [34] S. Jain, C. Prabha, and D. Nandan, “Comparative analysis of frequently used e-learning platforms,” *Frontiers in Education*, vol. 9, October 2024.

- [35] Springer, “An assessment of learning management system use in higher education: Perspectives from a comprehensive sample of teachers and students,” *Technology, Knowledge and Learning*, 2024.
- [36] M. Rani, R. Nayak, and O. P. Vyas, “Ontology-based adaptive personalized e-learning system, assisted by software agents on cloud storage.” arXiv, August 2017.
- [37] C. McBurnie, “The use of virtual learning environments and lms during the covid-19 pandemic,” tech. rep., EdTech Hub, 2020.
- [38] S. Lang, “Digital writing technologies in higher education,” in *Digital Writing Technologies in Higher Education*, ch. 11, Springer, 2023.
- [39] S. Wuttke and K. Henke, “Learning management systems,” *Interactive Technology and Smart Education*, vol. 6, no. 2, pp. 97–107, 2009.
- [40] F. Cavus, “Distance learning and learning management systems,” *Procedia - Social and Behavioral Sciences*, vol. 191, pp. 872–877, June 2015.
- [41] A. Fardinpour, M. Pedram, and M. Burkle, “Intelligent learning management systems,” *International Journal of Distance Education Technologies*, vol. 12, no. 4, pp. 19–31, 2014.
- [42] L. P. Thomas *et al.*, “Immersive learning: Exploring learning management systems in virtual reality,” in *Proceedings of the 10th International Conference on Virtual Reality (ICVR)*, IEEE, 2024.
- [43] S. Kaiwinit *et al.*, “Ruamrean: Transformative developments in learning management systems,” in *Proceedings of the 5th TIMES-iCON Conference*, IEEE, 2024.
- [44] D. A. Zekry *et al.*, “Enhancing usability of learning management systems through personalization,” in *Proceedings of the International Conference on Intelligent Methods, Systems and Applications (IMSA)*, IEEE, 2024.
- [45] F. Vapiwala and D. Pandita, “Leveraging gamified learning management systems to enhance e-learning outcomes,” in *Proceedings of the International Conference on Innovation and Intelligence for Informatics, Computing and Technologies (3ICT)*, IEEE, 2024.

- [46] C. P. Abaricia and M. L. C. D. Santos, “Enhancing e-learning system through learning management system (lms) technologies: Reshape the learner experience.” arXiv, September 2023.
- [47] V. R. Siddapureddy, *Evolvable System Architecture: Design Issues of Learning Systems*. PhD thesis, Massachusetts Institute of Technology, 2002.
- [48] A. S. Gibbons and P. G. Fairweather, “Design languages, notation systems, and instructional technology,” *Educational Technology Research and Development*, vol. 52, no. 2, pp. 57–68, 2004.
- [49] A. Khan and R. Qudrat-Ullah, “Learning management systems,” in *Adoption of LMS in Higher Educational Institutions of the Middle East*, Springer, 2020.