Clients Rot, Connections Don't: Degradation, Silent Failures and Refresh in Long-Lived WMI Connections

Author Name
Affiliation

Abstract

Windows management agents commonly recycle their WMI connections every few hours on the belief that long-lived connections degrade. We test that belief with a purpose-built client that follows COM's threading and memory rules by construction, checks every result against a non-WMI source of truth, and attributes resource use to the individual WMI provider host serving each query. On Windows Server 2019, a single set of connections served 381,600 queries over 6 h at 100× a production agent's query rate (about 25 production-days of queries) with no measurable growth in client memory (0.037 MB/h, 95% CI [−0.007, 0.082]), handles, provider-host memory or per-query latency. The degradation operators actually observe is client-induced: an unreleased `VARIANT` array leaks about **[ST-2 PENDING]** B per array-valued property read, and calls made across COM apartments cost about 3× the CPU per query. More consequential are *silent* failures, where an error becomes an empty but successful result: a popular Go COM library ends enumeration without reporting the error, three queries of a production agent have failed on every poll while being logged as successes, and `Win32_SystemDriver` omits a registered driver depending on which properties are selected. Fault injection shows where refresh matters: **[E-fault pending.]** We conclude that agents should invest in client correctness and result verification, and reconnect on errors rather than on a clock.

1 Introduction

Windows Management Instrumentation (WMI) is the standard inventory and telemetry interface on Windows; endpoint agents, monitoring systems and configuration tools poll it continuously. A widespread practice is to treat WMI connections as perishable: agents tear down and recreate their `IWbemServices` connections on a timer or a query budget. The production agent we studied ("Agent A") recycles every 6 h or 50,000 queries, a rule motivated by observed memory growth, latency creep and timeouts.

Whether those symptoms come from *connection age* or from the *client* has, to our knowledge, not been measured. It is hard to measure: an incorrect client produces exactly these symptoms, the usual metric (memory summed over all `WmiPrvSE.exe` processes) mixes every WMI client on the host, and many WMI failures are silent.

We make four contributions. (1) A measurement method that removes these confounders: a client that is correct by construction and self-tested, per-provider-host attribution, an ETW meter of foreign WMI clients, and non-WMI ground truth for results (§3). (2) Evidence that a correct client's connections do not degrade at accelerated query counts, with the age dimension in progress (§4). (3) Controlled measurements of two client bugs that produce the folklore symptoms, and a catalogue of silent failures (§5, §6). (4) A fault-injection comparison of refresh strategies (§7), which yields concrete guidance (§8).

2 Background

A client calls `IWbemServices` in the WMI service (`Winmgmt`), which dispatches each class to a provider. In-process providers run in shared `WmiPrvSE.exe` host processes, one per hosting model (e.g. `NetworkServiceHost`, `LocalServiceHost`) [1]. WMI unloads a provider once it has been idle for its cache-control `ClearAfter` interval ("anywhere from the interval … to twice that interval") [2, 3], and kills a host that exceeds the `__ProviderHostQuotaConfiguration` limits [4]. Queries issued with `wbemFlagReturnImmediately|wbemFlagForwardOnly` are semisynchronous: `ExecQuery` returns an enumerator at once, and errors surface from `IEnumWbemClassObject::Next`, which returns `WBEM_S_FALSE` at the normal end and an error `HRESULT` otherwise [5]. The scripting objects are apartment-threaded: a call from another apartment is marshalled to the owning single-threaded apartment (STA) [6], and property values arrive as `VARIANT`s that the caller must free with `VariantClear`, which frees strings and arrays [7].

3 Method

A correct client. The probe (Go, `go-ole`) gives every connection its own OS thread initialised as an STA, and makes every COM call for that connection, including release, on that thread. Every `VARIANT` is cleared exactly once; a ledger counts acquisitions and releases per query and flags outstanding or double releases. Enumeration uses a strict loop: `S_OK` yields an item, `S_FALSE` with no item ends the result, and any other code is an error recorded with its `HRESULT`, WBEM code and the operation that failed. A query that exceeds its deadline is abandoned on the caller's side and its row is written

when WMI eventually answers.

Workload. The catalogue reproduces Agent A's 23 production queries verbatim across 8 namespaces (22 queries in 7 namespaces exist on our host; BitLocker's namespace is absent) (processes, services, drivers, event logs, firewall rules and filters, Defender status, WMI subscriptions, scheduled tasks, Device Guard, TPM), each at its production rate: 636 queries/h in total on our host. An acceleration factor k multiplies every rate. A pre-flight calibration on the test host (10-minute steps, $k \in \{1,5,10,20,50,100\}$) gave probe-induced CPU (probe + all provider hosts + Winmgmt) of 0.4, 1.6, 3.3, 6.3, 15.6 and 29.9% with no dropped queries; we use $k_H = 100$, the top of the ramp, below a 40% budget.

Attribution and isolation. Every 10 s the probe samples itself, the `Winmgmt` service host (PID from the service control manager) and each `WmiPrvSE` by PID and creation time, labelled with its account and the provider DLLs it has loaded; this maps each queried class to the host serving it. Nothing here uses WMI. A real-time ETW session on `Microsoft-Windows-WMI-Activity` [8] counts operation starts by client PID, so foreign WMI clients are measured, not assumed absent. We found that `tasklist.exe`, the CIM cmdlets and PowerShell remoting all issue WMI calls; host inspection during runs was restricted to tools measured at zero WMI operations.

Ground truth. Results are compared with non-WMI sources taken immediately before and after each query: the process list (`NtQuerySystemInformation`), the service control manager, and invariants captured at the start. Five silent classes are counted: S1 impossible-empty, S2 truncated (a key present in both truth snapshots is missing), S3 enumeration ended by an error (what a lenient loop would report as success), S4 partial objects, S5 content mismatch.

Testbed and statistics. Windows Server 2019 Standard (build 17763.3650), 2 vCPU, 4 GB, Defender real-time protection on, no other WMI-heavy software. Growth is the OLS slope of 10 s samples after a 30-minute warm-up with Newey–West standard errors (15-minute lag window) [10]. Pass criteria were fixed before the runs: client private-byte slope < 1 MB/h and < 3 B per array read (upper 95% bound), handle range ≤ 50, and ≤ 5 MB retained after a 1-hour release test.

4 A correct client does not degrade

The self-test arm doubles as our longest correct-client run (Table 1). At $k = 100$, its 6 hours carry the query count of about 25 days at the production rate. All client invariants held on every query (correct apartment, no outstanding, double or leaked `VARIANT`s, no panics). Median latency per query key stayed flat across connection age, from about 1 ms (repository classes) to 250 ms (`MSFT_NetFirewallRule`, 260 rows),

Table 1: ST-1: one set of connections, strategy *none*, $k = 100$, 6 h (Server 2019). CIs are 95%, HAC.

Queries (ok / deterministic error / abandoned)	381,600 (360,000 / 21,600 / 0)
Silent failures above truth baseline	0
Client private bytes, slope	0.037 MB/h [−0.007, 0.082]
per array-valued read (3.48 M reads)	0.06 B [−0.01, 0.14]
Client handles: range; slope per 1k queries	17; 0.034 [0.029, 0.039]
Retained after 1 h release test	−0.39 MB
Provider hosts / Winmgmt over 6 h	flat (Fig. 1)
Connection recycles; induced CPU	0; 30.2%




Figure 1: ST-1. Top: median latency per 15-minute window against connection age for six query keys. Bottom: private bytes of the two provider hosts (labelled by account and provider DLLs) and of the Winmgmt host; connections were released at 6 h.

and neither the `NetworkServiceHost` provider host serving 6 providers nor the `Winmgmt` host grew (Fig. 1). The single handle step (339 to 347) coincides with one additional Go runtime thread and is flat before and after. A 7-day run at $k = 100$ (about 300 production-days of queries per connection) is in progress and will replace this section's age bound.

Providers reload anyway. On this host `ClearAfter` is 30 s (15 s for one class). At the production rate most classes are queried less often than that, and the WMI-Activity log showed the same providers reloading every 1–2 minutes *inside* a long-lived host process (event 5857 for `ntevt`, `wfascim`, `schedprov`, `tscfgwmi`, `win32_tpm` and `win32_deviceguard` in one host PID within 10 minutes), and the Defender provider's host itself was replaced. After the probe released its connections, idle hosts exited after 60–65 s. A production client therefore already receives a free refresh of provider state every few minutes; only the client-side connection and the

WMI service age with it.

5 What degrades is the client

Unreleased arrays (Agent A, issue 115). Property values read through `Properties_` that were never passed to `VariantClear` leak their `SAFEARRAY`s. In production this appeared as steady memory growth (+1.45 MB/h over 13.5 h on a Windows 10 VM, +2.29 MB/h over 20 h on a laptop) that scaled with the firewall collector's frequency ($+8.8 \pm 0.6$ MB/h with the collector at 60 s, $+0.44 \pm 0.52$ after the fix), and that *recycling did not cure*: with recycling working, the working set still grew 2.5 MB/h, because the leak is in the client process. Our positive control re-enables the bug in the probe: **[ST-2 result pending.]**

Cross-apartment calls (issue 118). Agent A called the apartment-threaded scripting objects from multi-threaded-apartment goroutines, so COM marshalled every call into a single host STA (confirmed in debugger stacks). Moving each connection to its own STA cut CPU per collection cycle about 3× (process poll 1.31–1.40 s to 0.42–0.44 s; firewall rules 8.5 s to 2.8 s) and steady-state CPU on a busy 16-CPU laptop from 28.3% to 3.5–3.9% of a core, eliminating 1,490 abandoned calls in 69 h (≈21/h). On a quiet 2-vCPU VM the same bug cost 5.0% vs 0.9% and caused no abandoned calls: the symptom scales with host load, which makes it look like ageing on busy machines. These production numbers are before/after measurements of one code change, not a controlled experiment, and we report them as such.

6 Silent failures

A library that swallows errors. `go-ole`'s `oleutil.ForEach` (v1.3.0, `oleutil.go` lines 118–126) [9] loops while the number of items returned is positive:

```
for item, length, err := enum.Next(1); length > 0;
    item, length, err = enum.Next(1) {
  if err != nil { return err }
  ...
}
return nil
```

When `Next` fails with zero items, the loop condition is false, the error is never inspected and the function returns `nil`. On Server 2019, `SELECT * FROM` a non-existent class fails only at `Next` with `WBEM_E_INVALID_CLASS` (0x80041010); `ForEach` reports success with 0 items, while our strict loop records the error.

Production queries that never worked. Three of Agent A's 23 queries fail at `Next` on every call (Table 2). Before the agent was stopped, the WMI-Activity log recorded 84 `5858` errors for each of them in 7 h, while the agent's audit log shows a success with 0 rows and a 0 ms duration at each of their positions in every collection cycle (the log carries no query text, so this attribution is by position). From the agent's code, the consequences are concrete: firewall rules are shipped without their application path, non-standard event consumers are missing from the persistence inventory, and scheduled tasks lack last-run and next-run times. Each was a plausible-looking query: `Name` exists only on derived consumer classes, `MSFT_NetApplicationFilter` exposes `AppPath` rather than `Program`, and `MSFT_ScheduledTaskInfo` is not a WMI class on this OS.

Table 2: Silent failures observed on Server 2019. All return success to a lenient client.

Query / class	Observed
`SELECT Name FROM __EventConsumer`	`0x80041017` at `Next`, every call
`SELECT InstanceID, Program, Package FROM MSFT_NetApplicationFilter`	`0x80041017` at `Next`, every call
`... FROM MSFT_ScheduledTaskInfo`	`0x80041010` at `Next`, every call
`Win32_SystemDriver` with any configuration property (or `*`)	333 rows; `vwifibus` omitted (binary absent); `SELECT Name` returns 334
`MSFT_ScheduledTask` at $k = 100$	3 of 200 queries one task short as the count changed from 135 to 136

A provider that drops rows. `Win32_SystemDriver` returned 333 drivers whenever the query selected any configuration property (`DisplayName`, `PathName`, `StartMode`, `StartName`, `ServiceType`, `Description`, or `*`), and 334 for `SELECT Name` or `SELECT Name, State`. The missing driver, `vwifibus`, is registered with the service control manager but its binary is absent. No error is returned at any layer; only the comparison with the service control manager reveals it. Because the omission is deterministic, we treat it as a per-key truth baseline and count S2 only above it.

Races are not failures. Ground truth has its own error rate. In 19,716 calibration queries the remaining flags were three scheduled-task counts one short just as the count changed (most likely a task being added) and one process that exited during its query, i.e. timing, not WMI. Separating these requires bracketing truth before and after each query.

7 Fault recovery and refresh

[E-fault results pending.]

8 Discussion

Guidance. (1) Make the client correct first: one STA per connection, all COM calls on it, every `VARIANT` cleared, and a test that runs a few hundred thousand queries and checks

for growth; timed recycling hides neither of the bugs above. (2) Never let an enumeration end without inspecting the last `HRESULT`; audit libraries for this pattern. (3) Validate each query once at start-up and verify results against an independent source where one exists; "0 rows" is a claim, not a fact. (4) Reconnect on connection-level errors (RPC disconnection, `WBEM_E_TRANSPORT_FAILURE`, `WBEM_E_NOT_AVAILABLE`) by inspecting the effective error code, not only the outer `HRESULT`; a timer adds churn and leaves an outage of up to one interval. (5) Do not attribute WmiPrvSE growth to your client without per-host attribution and a foreign-client meter.

Threats to validity. One host, one OS build, one workload. Accelerating the query rate tests count, not age: our longest correct-client connection is 6 h old; the 7-day run is in progress. The ETW meter ran one minute in fifteen during arms, so foreign activity is sampled (it saw one burst of 6 operations, most likely the Windows Update service). Agent A's production numbers come from before/after comparisons of single changes on a few hosts. Cross-OS replication (Windows 10, Server 2016/2022) is in progress.

9 Related work

Microsoft documents the mechanisms we rely on: provider hosting and unloading [1, 2], quotas [4], enumeration semantics [5] and COM apartment rules [6]. We are not aware of published measurements of WMI connection ageing under a verified-correct client, nor of a catalogue of WMI silent failures; we welcome pointers.

10 Conclusion

Long-lived WMI connections, used correctly, did not degrade in our measurements; the symptoms attributed to ageing were produced by the client, and the costliest failures were silent. Refresh is a recovery mechanism, best driven by errors. The probe, catalogue and analysis code are available from the authors.

References

[1] Microsoft. *Provider Hosting and Security*. `https://learn.microsoft.com/en-us/windows/win32/wmisdk/provider-hosting-and-security`

[2] Microsoft. *Unloading a Provider*. `https://learn.microsoft.com/en-us/windows/win32/wmisdk/unloading-a-provider`

[3] Microsoft. *__CacheControl class*. `https://learn.microsoft.com/en-us/windows/win32/wmisdk/--cachecontrol`

[4] Microsoft. *__ProviderHostQuotaConfiguration class*. `https://learn.microsoft.com/en-us/windows/win32/wmisdk/--providerhostquotaconfiguration`

[5] Microsoft. *IEnumWbemClassObject::Next*. `https://learn.microsoft.com/en-us/windows/win32/api/wbemcli/nf-wbemcli-ienumwbemclassobject-next`

[6] Microsoft. *Single-Threaded Apartments*. `https://learn.microsoft.com/en-us/windows/win32/com/single-threaded-apartments`

[7] Microsoft. *VariantClear function*. `https://learn.microsoft.com/en-us/windows/win32/api/oleauto/nf-oleauto-variantclear`

[8] Microsoft. *Tracing WMI Activity*. `https://learn.microsoft.com/en-us/windows/win32/wmisdk/tracing-wmi-activity`

[9] go-ole contributors. *go-ole v1.3.0, oleutil/oleutil.go*. `https://github.com/go-ole/go-ole/blob/v1.3.0/oleutil/oleutil.go`

[10] W. K. Newey and K. D. West. A simple, positive semi-definite, heteroskedasticity and autocorrelation consistent covariance matrix. *Econometrica*, 55(3):703–708, 1987.