

The EUV Snapshot Imaging Spectrograph

ROY T. SMART ¹, HANS T. COURRIER,¹ JACOB D. PARKER ², CHARLES C. KANKELBORG ¹,
AMY R. WINEBARGER ³, KEN KOBAYASHI ³, BRENT BEABOUT,³ DYANA BEABOUT,³ BEN CARROL,¹
JONATHAN CIRTAIN,³ JAMES A. DUFFY,³ ERIC GULLIKSON ⁴, MICAH JOHNSON,¹ LAUREL RACHMELER ³,
LARRY SPRINGER,¹ AND DAVID L. WINDT ⁵

¹Montana State University, Department of Physics, P.O. Box 173840, Bozeman, MT 59717, USA

²NASA Goddard Space Flight Center, Greenbelt, MD 20771, USA

³NASA Marshall Space Flight Center, Huntsville, AL 35812, USA

⁴Lawrence Berkeley National Laboratory, 1 Cyclotron Road, Berkeley, CA 94720, USA

⁵Reflective X-ray Optics LLC, 425 Riverside Dr., #16G, New York, NY 10025, USA

1. INTRODUCTION

The light emitted by the solar transition region (TR) and corona varies significantly as a function of position, wavelength, and time. When viewed from Earth, the spectral radiance from the Sun can be written as: $I(x, y, \lambda, t)$, where x and y are the helioprojective Cartesian coordinates (W. T. Thompson 2006), λ is wavelength, and t is time. The ideal solar imaging spectrograph would capture $I(x, y, \lambda, t)$ with high resolution in x , y , λ , and t and over a wide field of view (FOV), wavelength range, and time period. Of course, the temporal dimension is privileged, so we often reduce the problem to capturing a 3D spatial/spectral cube at a particular time t_0 : $I(x, y, \lambda, t_0)$. Since we use 2D detectors, this means that we must find a way to flatten the 3D cube into two dimensions without losing information.

One obvious way to accomplish this is to multiplex one of the three remaining dimensions in time. Narrowband, tunable filters, such as the GREGOR Fabry–Pérot Interferometer (K. G. Puschmann et al. 2012) or CRISP at the Swedish Solar Telescope (G. B. Scharmer et al. 2008), multiplex the wavelength dimension in time, and can change the selected wavelength in 50 ms or less (G. B. Scharmer et al. 2008), but the technology does not exist to use this technique for wavelengths shorter than ~ 150 nm (J.-P. Wuelser et al. 2000). The nearest extreme ultraviolet (EUV) equivalent is a multilayer-coated imager such as the Transition Region and Coronal Explorer (TRACE) (B. N. Handy et al. 1999) or the Atmospheric Imaging Assembly (AIA) (J. R. Lemen et al. 2012), which abandons the wavelength dimension entirely and integrates over a passband holding many emission lines. Two such passbands can be compared to infer a Doppler shift (T. Sakao et al. 1999), but weaker

lines within them bound the velocity resolution near $\sim 1000 \text{ km s}^{-1}$ (K. Kobayashi et al. 2000), coarser than the flows that characterize TR dynamics.

A spatial dimension can be multiplexed instead. An entrance slit admits a single column of the scene, so the detector records λ against y without ambiguity, and x is recovered by stepping the slit across the target. The Interface Region Imaging Spectrograph (IRIS) (B. De Pontieu et al. 2014) and the Spectral Imaging of the Coronal Environment (SPICE) aboard Solar Orbiter (SPICE Consortium et al. 2020) work this way, and the spectra they return are the most faithful of any technique discussed here. What is sacrificed is simultaneity: neighboring columns of the reconstructed cube are separated in time by the raster, and structure that evolves faster than the raster completes is smeared along x . The Multi-slit Solar Explorer (MUSE) (B. De Pontieu et al. 2020, 2022; M. C. M. Cheung et al. 2022) narrows this gap considerably by ruling 37 slits across the field and separating their overlapping spectra afterward, which shortens the raster of an active region to as little as 12 s.

A third strategy divides the detector rather than the exposure. An integral field spectrograph slices the field of view and reformats those slices so that each is dispersed onto its own region of the detector, so the entire cube arrives in one exposure, at the cost of trading field of view against wavelength range. The microlensed hyperspectral imager of M. van Noort et al. (2022) demonstrates the technique at visible wavelengths, and the Solar eruption Integral Field Spectrograph (SNIFS) (V. L. Herde et al. 2024), flown in 2025, demonstrates it in the far ultraviolet (FUV). Extending it to the EUV remains out of reach of available optics.

The last strategy is to allow the flattening to be ambiguous and to undo it afterward. A spectrograph with no entrance slit disperses the whole field at once, so every emission line forms an image of the Sun and

those images superimpose on the detector. The resulting frame, an *overlappogram*, encodes x and λ along a single axis, and the two cannot be separated within one exposure. Overlappograms are as old as spaceborne solar spectroscopy, having been recorded by the Naval Research Laboratory’s (NRL’s) S082A spectroheliograph (R. Tousey et al. 1973, 1977), which yielded both a census of EUV transitions (U. Feldman et al. 1985) and, much later, flare line ratios (F. P. Keenan et al. 2006); the technique is in use today at soft X-ray wavelengths by the Marshall Grazing Incidence X-ray Spectrometer (MaGIXS) (S. L. Savage et al. 2023). What has changed since S082A is that the ambiguity has become tractable. Reconstructing the cube from superimposed images is a tomographic problem (A. C. Kak & M. Slaney 1988), in which each diffraction order views the cube from a different angle and the number of independent views limits how much of the line profile can be recovered (M. R. Descour et al. 1997). Computed tomography imaging spectrographs (CTISs) (T. Okamoto & I. Yamaguchi 1991; F. V. Bulygin et al. 1991; M. Descour & E. Dereniak 1995) carry this to its extreme, projecting as many as 25 orders onto a single detector, with computational cost rising accordingly (N. Hagen & E. L. Dereniak 2008; N. Hagen & M. W. Kudenov 2013). Fewer views can suffice when the scene is sparse: C. DeForest et al. (2004) synthesized a magnetogram from a single exposure using only two dispersed orders. Inversion methods for overlapping spectral images have advanced considerably since (A. R. Winebarger et al. 2019; J. M. Davila et al. 2019; U. Kamaci & F. Kamalabadi 2026).

The Multi-Order Solar EUV Spectrograph (MOSES) (J. L. Fox et al. 2010; J. L. Fox 2011) brought this strategy to the solar EUV. A single concave grating forms three images at once, the undispersed $m = 0$ order and the $m = \pm 1$ orders, on three detectors, while a multilayer coating narrows the passband to a few emission lines so that the cube to be recovered is sparse enough to invert. Two flights showed that the concept works. J. L. Fox et al. (2010) measured the Doppler shift and width of explosive event line profiles in the TR; T. Rust & C. C. Kankelborg (2019) resolved bimodal profiles in quiet Sun events; H. T. Courrier & C. C. Kankelborg (2018) recovered Doppler maps using local correlation tracking; and J. D. Parker & C. C. Kankelborg (2022) separated the contributions of individual spectral lines. The same flights exposed where the design binds. Only three views are available, one of which is undispersed and therefore contributes no spectral information, which caps the number of degrees of freedom that an inversion can recover; and because the dispersed orders lie in a

plane, they fill the cylindrical volume of a sounding rocket payload poorly.

might just need to go through the whole paper then write this paragraph The EUV Snapshot Imaging Spectrograph (ESIS) was designed to relax both constraints. An array of gratings arranged about the optical axis re-images the prime focus of a single primary mirror, each dispersing at a different angle, so that every detector records a dispersed view and the views are distributed around the payload rather than confined to a plane. ESIS flew for the first time on 2019 September 30, and first results from that flight are reported by J. D. Parker et al. (2022). An earlier form of the design was described by H. T. Courrier (2020); the instrument that flew differs from it, most consequentially in the removal of the primary mask, which admits vignetting into the system. This paper describes the instrument as it was built and flown. In Section 2 we explain how experience with MOSES shaped the design of ESIS. Section ?? states the scientific objectives and the requirements they impose. Section ?? describes the instrument itself, and Section ?? the mission profile.

2. THE ESIS CONCEPT

A primary goal of the ESIS instrument is to improve upon the imaging spectroscopy demonstrated by MOSES. Therefore, the design of the new instrument draws heavily from experiences and lessons learned through two flights of the MOSES instrument. ESIS and MOSES are both CTIS instruments. As such, both produce dispersed images overlappograms of a narrow portion of the solar spectrum, with the goal of enabling the reconstruction of a spectral line profile at every point in the field of view. The similarities end there, however, as the optical layout of ESIS differs significantly from that of MOSES. In this section, we detail some difficulties and limitations encountered with MOSES, then describe how the new design of ESIS addresses these issues.

2.1. Limitations of the MOSES Design

The MOSES design features a single concave diffraction grating forming images on three charge-coupled device (CCD) detectors (J. L. Fox et al. 2010) (Figure ??). The optical path is folded in half by a single flat secondary mirror (omitted in Figure ??). Provided that the three cameras are positioned correctly, this arrangement allows the entire telescope to be brought into focus using only the central (undispersed) order and a visible light source. Unfortunately this design uses volume inefficiently for two reasons. First, the lack of magnification by the secondary mirror limits the folded length

of the entire telescope to be no less than half of the 5 m focal length of the grating (J. L. Fox et al. 2010; J. L. Fox 2011). Second, the resolving power of the instrument is limited by the ratio of camera separation to pixel size. To achieve the maximum dispersion of $29 \text{ km pix}^{-1} \text{ s}^{-1}$ (J. L. Fox et al. 2010), the outboard orders are imaged as far apart as possible in the $\sim 0.6 \text{ m}$ diameter envelope of the rocket payload. This planar arrangement leaves much unused space in the cylindrical volume of the payload.

Furthermore, the monolithic secondary, though it confers the focus advantage noted above, does not allow efficient placement of the $m = \pm 1$ CCDs. For all practical purposes, the payload can only accommodate three diffraction orders ($m = -1, 0, +1$). Therefore, *MOSES can only collect, at most, three pieces of information at each point in the field of view*. From this, it is not reasonable to expect the reconstruction of more than three degrees of freedom for each spectral line, except in the case very compact, isolated features such as those described by J. L. Fox et al. (2010) and T. L. Rust (2017). Consequently, it is a reasonable approximation to say that MOSES is sensitive primarily to spectral line intensities, shifts, and widths (C. C. Kankelborg & R. J. Thomas 2001). With any tomographic apparatus, the degree of detail that can be resolved in the object depends critically on the number of viewing angles (A. C. Kak & M. Slaney 1988; M. R. Descour et al. 1997; N. Hagen & E. L. Dereniak 2008). So it is with the spectrum we observe with MOSES: more dispersed images are required to confer sensitivity to finer spectral details such as higher moments of the spectral line shape.

A related issue stems from the use of a single dispersion plane. Since the solar corona and transition region are structured by magnetic fields, the scene tends to be dominated by field-aligned structures such as loops (R. Rosner et al. 1978; R. M. Bonnet et al. 1980). When the MOSES dispersion direction happens to be aligned nearly perpendicular to the magnetic field, filamentary structures on the transition region serve almost as spectrograph slits unto themselves. The estimation of Doppler shifts then becomes a simple act of triangulation, and broadenings are also readily diagnosed (J. L. Fox et al. 2010; H. T. Courrier & C. C. Kankelborg 2018). A double-peaked profile can also be observed with sufficiently isolated features (T. L. Rust 2017). Unfortunately, solar magnetic fields in the transition region are quite complex and do not have a global preferred direction. In cases where the field is nearly parallel to the instrument dispersion, spectral shifts and broadenings are not readily apparent.

The single diffraction grating also leads to a compromise in the optical performance of the instrument. Since the MOSES grating forms images in three orders simultaneously, there aren't enough degrees of freedom in the optical system to control aberrations in all three spectral orders. During the first mission, MOSES was flown with a small amount of defocus (T. L. Rust 2017), which exacerbated the inter-order point-spread function (PSF) variation and caused the individual PSFs to span several pixels (T. L. Rust 2017; S. Atwood & C. Kankelborg 2018). The outboard PSFs were elongated, with their major axes at different angles. This resulted in spurious spectral features that require additional consideration (S. Atwood & C. Kankelborg 2018) and further increase the complexity of the inversion process (T. L. Rust 2017; H. T. Courrier & C. C. Kankelborg 2018).

As MOSES lacks a field stop, it is possible for the grating to image off-band radiation on the detector from solar features that lie outside the intended FOV. Although the intensity of this off-band radiation is relatively low, it is not negligible. J. D. Parker et al. (2022) compared synthetic MOSES images to the real data and found that approximately ten percent of the intensity in the zeroth order image originated from more than ten dim lines in the MOSES passband, most of them are too faint to be visible in the dispersed images. This study revealed that an undispersed ($m = 0$) channel, although attractive due to its lack of spatial-spectral ambiguity, is of limited utility due to spectral contamination. Moreover the FOV should be clearly defined, and the same, for each image so that the spectral and spatial content of the image is clearly defined.

Finally, the exposure cadence of MOSES is hindered by a $\sim 6 \text{ s}$ readout time for the CCDs (J. L. Fox 2011). The observing interval for a solar sounding rocket flight is typically about five minutes. Consequently, every second of observing time is precious, both to achieve adequate exposure time and to catch the full development of dynamical phenomena. The MOSES observing duty cycle is $\sim 50 \%$ since it is limited by the readout time of its CCDs. Thus, valuable observing time is lost. The readout data gap compelled us to develop a sequence with exposures ranging from 0.25-24 s, a careful trade-off between deep and fast exposures.

In summary, our experience leads us to conclude that the MOSES design has the following primary limitations:

1. inefficient use of volume
2. dispersion constrained by payload dimensions
3. too few dispersed images (orders)

4. single dispersion plane

5. lack of aberration control

6. poorly-defined and wavelength dependent FOV

7. spectral contamination

8. low duty cycle

In designing ESIS, we have sought to improve upon each of these points.

REFERENCES

- Atwood, S., & Kankelborg, C. 2018, *Journal of Astronomical Telescopes, Instruments, and Systems*, 4, 028002, doi: [10.1117/1.JATIS.4.2.028002](https://doi.org/10.1117/1.JATIS.4.2.028002)
- Bonnet, R. M., Decaudin, M., Bruner, Jr., E. C., Acton, L. W., & Brown, W. A. 1980, *ApJL*, 237, L47, doi: [10.1086/183232](https://doi.org/10.1086/183232)
- Bulygin, F. V., Vishnyakov, G. N., Levin, G. G., & Karpukhin, D. V. 1991, *Optics and Spectroscopy*, 71, 561
- Cheung, M. C. M., Martínez-Sykora, J., Testa, P., et al. 2022, *ApJ*, 926, 53, doi: [10.3847/1538-4357/ac4223](https://doi.org/10.3847/1538-4357/ac4223)
- Courrier, H. T. 2020, PhD thesis, Montana State University, Bozeman, MT
- Courrier, H. T., & Kankelborg, C. C. 2018, *Journal of Astronomical Telescopes, Instruments, and Systems*, 4, 018001, doi: [10.1117/1.JATIS.4.1.018001](https://doi.org/10.1117/1.JATIS.4.1.018001)
- Davila, J. M., Oktem, F. S., & Kamalabadi, F. 2019, *ApJ*, 883, 7, doi: [10.3847/1538-4357/ab372a](https://doi.org/10.3847/1538-4357/ab372a)
- De Pontieu, B., Martínez-Sykora, J., Testa, P., et al. 2020, *ApJ*, 888, 3, doi: [10.3847/1538-4357/ab5b03](https://doi.org/10.3847/1538-4357/ab5b03)
- De Pontieu, B., Testa, P., Martínez-Sykora, J., et al. 2022, *ApJ*, 926, 52, doi: [10.3847/1538-4357/ac4222](https://doi.org/10.3847/1538-4357/ac4222)
- De Pontieu, B., Title, A. M., Lemen, J. R., et al. 2014, *SoPh*, 289, 2733, doi: [10.1007/s11207-014-0485-y](https://doi.org/10.1007/s11207-014-0485-y)
- DeForest, C., Elmore, D. F., Bradford, M. P., Elrod, J., & Gilliam, D. L. 2004, *ApJ*, 616, 600, doi: [10.1086/424745](https://doi.org/10.1086/424745)
- Descour, M., & Dereniak, E. 1995, *Appl. Opt.*, 34, 4817, doi: [10.1364/AO.34.004817](https://doi.org/10.1364/AO.34.004817)
- Descour, M. R., Volin, C. E., Dereniak, E. L., et al. 1997, *Appl. Opt.*, 36, 3694, doi: [10.1364/AO.36.003694](https://doi.org/10.1364/AO.36.003694)
- Feldman, U., Doschek, G. A., & Seely, J. F. 1985, *MNRAS*, 212, 41P, doi: [10.1093/mnras/212.1.41P](https://doi.org/10.1093/mnras/212.1.41P)
- Fox, J. L. 2011, PhD thesis, Montana State University
- Fox, J. L., Kankelborg, C. C., & Thomas, R. J. 2010, *ApJ*, 719, 1132, doi: [10.1088/0004-637X/719/2/1132](https://doi.org/10.1088/0004-637X/719/2/1132)
- Hagen, N., & Dereniak, E. L. 2008, *ApOpt*, 47, F85, doi: [10.1364/AO.47.000F85](https://doi.org/10.1364/AO.47.000F85)
- Hagen, N., & Kudenov, M. W. 2013, *Optical Engineering*, 52, 090901, doi: [10.1117/1.OE.52.9.090901](https://doi.org/10.1117/1.OE.52.9.090901)
- Handy, B. N., Acton, L. W., Kankelborg, C. C., et al. 1999, *SoPh*, 187, 229, doi: [10.1023/A:1005166902804](https://doi.org/10.1023/A:1005166902804)
- Herde, V. L., Chamberlin, P. C., Schmit, D., et al. 2024, *SoPh*, 299, 120, doi: [10.1007/s11207-024-02367-y](https://doi.org/10.1007/s11207-024-02367-y)
- Kak, A. C., & Slaney, M. 1988, *Principles of Computerized Tomographic Imaging* (345 East 47th Street, New York, NY 10017-2394: IEEE Press)
- Kamaci, U., & Kamalabadi, F. 2026, *ApJ*, 1006, 124, doi: [10.3847/1538-4357/ae7c6c](https://doi.org/10.3847/1538-4357/ae7c6c)
- Kankelborg, C. C., & Thomas, R. J. 2001, in *Proc. SPIE*, Vol. 4498, *UV/EUV and Visible Space Instrumentation for Astronomy and Solar Physics*, ed. O. H. Siegmund, S. Fineschi, & M. A. Gummin, 16–26, doi: [10.1117/12.450074](https://doi.org/10.1117/12.450074)
- Keenan, F. P., Aggarwal, K. M., Bloomfield, D. S., Msezane, A. Z., & Widing, K. G. 2006, *A&A*, 449, 1203, doi: [10.1051/0004-6361:20054028](https://doi.org/10.1051/0004-6361:20054028)
- Kobayashi, K., Hara, H., Kano, R., et al. 2000, *PASJ*, 52, 1165, doi: [10.1093/pasj/52.6.1165](https://doi.org/10.1093/pasj/52.6.1165)
- Lemen, J. R., Title, A. M., Akin, D. J., et al. 2012, *SoPh*, 275, 17, doi: [10.1007/s11207-011-9776-8](https://doi.org/10.1007/s11207-011-9776-8)
- Okamoto, T., & Yamaguchi, I. 1991, *Opt. Lett.*, 16, 1277, doi: [10.1364/OL.16.001277](https://doi.org/10.1364/OL.16.001277)
- Parker, J. D., & Kankelborg, C. C. 2022, *ApJ*, 932, 130, doi: [10.3847/1538-4357/ac6dd4](https://doi.org/10.3847/1538-4357/ac6dd4)
- Parker, J. D., Smart, R. T., Kankelborg, C., Winebarger, A., & Goldsworth, N. 2022, *The Astrophysical Journal*, 938, 116, doi: [10.3847/1538-4357/ac8eaa](https://doi.org/10.3847/1538-4357/ac8eaa)
- Puschmann, K. G., Denker, C., Kneer, F., et al. 2012, *Astronomische Nachrichten*, 333, 880, doi: [10.1002/asna.201211734](https://doi.org/10.1002/asna.201211734)
- Rosner, R., Tucker, W. H., & Vaiana, G. S. 1978, *ApJ*, 220, 643, doi: [10.1086/155949](https://doi.org/10.1086/155949)
- Rust, T., & Kankelborg, C. C. 2019, *ApJ*, 877, 59, doi: [10.3847/1538-4357/ab12e2](https://doi.org/10.3847/1538-4357/ab12e2)
- Rust, T. L. 2017, PhD thesis, Montana State University, Bozeman, MT
- Sakao, T., Tsuneta, S., Hara, H., et al. 1999, *SoPh*, 187, 303, doi: [10.1023/A:1005127827006](https://doi.org/10.1023/A:1005127827006)
- Savage, S. L., Winebarger, A. R., Kobayashi, K., et al. 2023, *ApJ*, 945, 105, doi: [10.3847/1538-4357/acbb58](https://doi.org/10.3847/1538-4357/acbb58)
- Scharmer, G. B., Narayan, G., Hillberg, T., et al. 2008, *ApJL*, 689, L69, doi: [10.1086/595744](https://doi.org/10.1086/595744)

- 374 SPICE Consortium, Anderson, M., Appourchaux, T.,
 375 Auchère, F., et al. 2020, A&A, 642, A14,
 376 doi: [10.1051/0004-6361/201935574](https://doi.org/10.1051/0004-6361/201935574)
 377 Thompson, W. T. 2006, A&A, 449, 791,
 378 doi: [10.1051/0004-6361:20054262](https://doi.org/10.1051/0004-6361:20054262)
 379 Tousey, R., Bartoe, J.-D. F., Brueckner, G. E., & Purcell,
 380 J. D. 1977, ApOpt, 16, 870
 381 Tousey, R., Bartoe, J. D. F., Bohlin, J. D., et al. 1973,
 382 SoPh, 33, 265, doi: [10.1007/BF00152418](https://doi.org/10.1007/BF00152418)
 383 van Noort, M., Bischoff, J., Kramer, A., Solanki, S. K., &
 384 Kiselman, D. 2022, A&A, 668, A149,
 385 doi: [10.1051/0004-6361/202243464](https://doi.org/10.1051/0004-6361/202243464)
- 386 Winebarger, A. R., Weber, M., Bethge, C., et al. 2019,
 387 ApJ, 882, 12, doi: [10.3847/1538-4357/ab21db](https://doi.org/10.3847/1538-4357/ab21db)
 388 Wuelser, J.-P., Rosenberg, W. A., & Bruner, M. E. 2000, in
 389 Proc. SPIE, Vol. 4139, Instrumentation for UV/EUV
 390 Astronomy and Solar Missions, ed. S. Fineschi, C. M.
 391 Korendyke, O. H. Siegmund, & B. E. Woodgate,
 392 390–401, doi: [10.1117/12.410537](https://doi.org/10.1117/12.410537)