

C.1 Guideline for Cargo Flight Operating with One Cabin Crew (CW1C)

1. At OPC

a. Cabin Crew Dispatcher: CA signs signature in Service Briefing Chart and obtains the following items from Cabin Crew Dispatcher:

- Integrated Route Folder (iRF)
- flight documents as follows:
 - 2 copies of Flight Statistics (1 paper for 1 sector), after complete Flight Statistics, hands both copies to flight crew
 - List of Entry/Departure (If applicable, China route e.g.).

b. Briefing Room:

- cabin crew shall ensure all valid travel documents and updated manuals in the MDM Content Locker are carried
- review hand in hand/EM movie
- update information from SI, Pop Up.

2. Flight Crew to Cabin Crew Briefing

- Briefing from Flight Crew:
 - anticipated weather and flying conditions
 - expected flight time
 - flight deck door procedures
 - security procedure
 - dangerous goods and drill code
 - CA shall inform PIC in case Aircraft Disinfection Procedures (cabin spray) is required.
- Submit flight documents to flight crew:
 - 2 copies of Flight Statistics
 - List of Entry/Departure (If applicable, China route e.g.)

(Flight crew check the validity of List of Entry and return it to CA as flight document for destination).

3. Cabin Safety and Emergency Equipment Check

- Assigned station for CA who operates the cargo flight with one cabin crew is 1L station.
- Check EM equipment at 1L station.
- Check additional EM equipment according to the following:
 - ELT
 - AED
 - Medical Kit (in use and spare)
 - First Aid Kit (most accessible)
 - Fire extinguisher (most accessible).
- PA "STATION 1L EMERGENCY EQUIPMENT CHECK COMPLETED"
- If any discrepancies are found during emergency equipment check, CA shall report to flight crew. Flight crew shall be informed when any discrepancies are replaced.

4. Preparation on Ground

- Check catering uplifted and service items with Catering Foreman and sign Catering Delivery Slip (keep the pin copy in the Route Folder and return the green copy to Catering Foreman).
- Check the catering seals are intact on all carts/units at the station where security seals are used and sign security seal form.
- Check cabin cleanliness (if the cabin is not clean, CA informs ground personal and reports to (PIC).
- Perform Aircraft Disinfection Procedures according to Route Specialities/Sl/Pop Up (if required).

5. Pre-flight Security Check

- Obtain permission to start pre-flight security check from PIC.
- Guard the opened door (safety strap may be used) until the door is closed for departure.
- Check no ground personnel remaining on board.
- In case of any ground personnel is required to remain on board or needed to enter the aircraft during pre-flight security check:
 - CA shall inform PIC of the number of ground personnel and reasons to remain on board
 - record his/her name and duty in the Cabin Pre-flight Security Check Access Control Record form.
- Perform Pre-flight Security Check throughout the aircraft.
- After completing the pre-flight security check, CA reports PIC by PA "ALL STATIONS, PRE-FLIGHT SECURITY CHECK COMPLETED".
- Sign Aircraft Pre-Departure Security Check/Search Form and hand it over to PIC.

After Pre-flight Security Check, if any ground personnel need to board the aircraft, the CA who guards the opened door shall:

- inquire the nature of duty
- check all items carried on board
- record his/her name and duty in the Cabin Pre-flight Security Check Access Control Record form
- complete the Cabin Pre-flight Security Check Access Control Record form upon disembarking at the same exit.

6. Before Closing the Aircraft Door

To prevent Door Re-opening, CA shall strictly adhere to the following:

- ground personnel will inform CA that all formalities are completed and ready for departure before closing the cabin door
- check flight documents as follows:
 - Gen Dec (check correct name list), (if any)
 - Cargo Manifest (if any)
 - NOTOC (if any)

Note: CA put all flight documents in flight bag (if any).

- check Cabin Pre-flight Security Check Access Control Record form (ensure no ground personal remain on board)
- in case that cabin disinfection before door closing is required, CA ensures cabin has been sprayed
- PA "BOARDING COMPLETE" to check if there are any ground personnel on board.

7. Door Closing

- CA and ground personnel agree to close the main entry door. Start Door Closing Procedure.
- Doorman looks out for any possible obstructions around the door area that may hinder the closure of the door.
- Doorman closes the door according to procedure based on aircraft type.
- Doorman checks the door is fully closed and locked.
- Both doorman and ground personnel outside give thumbs up signal.
- Ground personnel informs the aerobridge operator/truck driver to remove the aerobridge.

Door Re-opening (Disarm Mode)

- If door re-opening is required for any reasons, it is strictly required to establish communication between flight deck, cabin and ground personnel before performing door re-opening procedure.
- Doorman requests 1 flight crew to be Assist Doorman.
- Assist Doorman advises Doorman to ensure the door is in disarm mode.

Doorman	Assist Doorman
1) Calls: "Assist"	
	2) Points to the door mode selector and calls: "Confirmed Disarmed".
3) Check mode selector—Disarm. Points and calls: "Disarm checked".	

- Open the door by using the 2-man crew concept.

Doorman	Assist Doorman
	1) Calls: "Clear"
2) Calls: "Step 1". Lift door handle and hold.	
3) Calls: "Step 2". Fully open the door.	
4) Opens the door according to procedure based on aircraft type.	

8. Door Arming

After the cabin door has been closed:

- ensure that all doors are closed and locked
- ensure that slide should be armed as soon as the steps/aerobridge is removed and clear
- doorman performs Door Arming Procedure only at Door 1L (for cargo flight operating with one cabin crew only)
- doorman performs Door Arming Procedure by using Stop Drop Review
- doorman arms the door by using Point and Call concept:
 - points at mode selector, calls: "MODE SELECTOR"
 - calls: "ARM" then simultaneously moves mode selector to armed position.
- doorman reports cabin clear by PA "CABIN CLEAR" to inform PIC
- flight crew check Door Armed in cockpit synoptic display or system display.

Note: When performing door arming/disarming procedure, if abnormalities occur or CA suspect of door malfunction, CA shall not open the door and immediately inform PIC.

Door Re-opening (Arm Mode)

- a. If door re-opening is required for any reasons, it is strictly required to establish communication between flight deck, cabin and ground personnel before performing door re-opening procedure.
- b. Doorman requests 1 flight crew to be an assist doorman.
- c. Doorman and Assist Doorman disarm the door by using the 2-man crew concept.

Doorman	Assist Doorman
	1) Calls: "Doorman" 2) Calls: "Mode Selector"
3) Points to the door mode selector Calls: "Mode Selector".	
	4) Calls "Disarm"
5) Calls: "Disarm" and disarm the door according to procedure based on aircraft type.	
	6) Crosschecks door disarm
If Assist Doorman is unavailable, doorman may perform door disarming by the following procedure: • Points to the door mode selector, calls "Mode Selector" • Calls "Disarm". Move mode selector to Disarm.	

d. Assist doorman advises doorman to ensure the door is in disarm mode.

Doorman	Assist Doorman
2) Calls: "Assist"	
	4) Points to the door mode selector and calls: "Confirmed Disarmed".
5) Check mode selector—Disarm. Points and calls: "Disarm checked".	

e. Open the door by using the 2-man crew concept.

Doorman	Assist Doorman
	1) Calls: "Clear".
2) Calls: "Step 1". Lift door handle and hold.	
3) Calls: "Step 2". Fully open the door.	
4) Opens the door according to procedure based on aircraft type.	

9. Aircraft Pushback/Engine Start

After report cabin clear

- In case the cabin disinfection after door closing is required, PIC shall be informed. Disinfection during aircraft movement on ground can be performed upon PIC discretion provided that safety of cabin crew shall be maintained. (See details of cabin disinfection in Route Specialities/SI/Pop Up).

10. Aircraft Taxi

- Perform final cabin safety check and proceed to the assigned station
- For night flight, dim cabin light to match the outside ambient light conditions
- Report cabin readiness to PIC by PA "CABIN READY"
- Remain seated with safety harness fastened unless there is a safety related occurrence in the cabin
- Visual check cabin condition
- Start sterile flight deck procedures.

11. Takeoff

- Flight crew cycles Seatbelt Sign
- CA makes PA "CABIN CREW PREPARE FOR TAKEOFF"
- CA remains seated with safety harness fastened, in brace position and performs silent review/30-seconds review
- Visual check cabin condition

12. Initial Climb

- CA remains seated until the fasten seatbelt sign is off.

13. Cruise

After Fasten Seatbelt Sign Off:

- after receiving the fasten seatbelt sign off signal from PIC, the sterile flight deck is finished.

During flight, CA shall perform cabin monitoring as follows:

- report any unusual or abnormal situation
- implement appropriate procedures for the handling of any aircraft emergency, medical emergency or abnormal situation
- check lavatories, smoke detectors and waste bins every 20-30 minutes periodically to verify they are free of fire hazards
- inform about failure or defect of electrical equipment in the cabin.

Prepared required documents:

- obtain PIC signature in Gen Dec (if required)
- record number of cabin spray and cargo spray together with cabin crew signature on the Gen Dec under Health Declaration section, (if required).

14. Initial Descent

At Top of Descent:

- start to clear loose objects in the cabin and flight deck
- inform PIC before performing Aircraft Disinfection Procedures (cabin spray), if required at top of descent. (See details in Route Specialities/SI/Pop Up).

Seatbelt Sign On:

- perform final cabin safety check and proceed to the assigned station
- for night flight, adjust the light to match outside ambient light conditions
- report cabin readiness to PIC by PA "CABIN READY"
- remain seated with safety harness fastened unless there is a safety related occurrence in the cabin
- visual check cabin condition
- start sterile flight deck procedures.

15. Final Descent

- Flight crew cycles Seatbelt Sign On
- CA makes PA "CABIN CREW PREPARE FOR LANDING"
- CA remains seated with safety harness fastened, in brace position and performs silent review/30-seconds review
- Visual check cabin condition.

16. Taxi-in

- CA shall remain seated with safety harness fastened unless a safety related occurrence in the cabin.

17. Door Disarming

After Fasten Seatbelt Sign Off:

- perform door disarming procedure by using Stop Drop Review
- doorman disarms the door by using Point and Call concept:
 - points to the door mode selector, calls: "MODE SELECTOR"
 - calls: "DISARM" then simultaneously moves mode selector to disarmed position.
- flight crew check door disarm in cockpit synoptic display or system display:
 - if any door is still in arm mode, PA all "STATION XX DISARM"
 - when all doors are disarmed, PA all "CONFIRMED DISARM".

Note: When performing door arming/disarming procedure, if abnormalities occur or CA suspect of door malfunction, CA shall not open the door and immediately inform PIC.

18. Door Opening

- a. Doorman at main entry door. Once the aerobridge/stairs have been properly positioned, the doorman shall wait for the signal from ground personnel through the door observation window.

Note: CA must obtain permission from the flight crew before opening the door.

WARNING: Problems can occur if a door is forced open when the aircraft has not been fully depressurized. The door will rapidly open, with the associated danger that the person operating the door may be ejected from the cabin with possible serious consequences. Residual pressurization may result from system malfunction or incorrect application of procedures.

- b. Wait for 1 flight crew to be the Assist Doorman.

- c. Perform Door Opening Procedure according to the table below:

Action		Responsible Person								
1.	Doorman waits for a signal from ground personnel outside.	Doorman								
2.	When ready, the doorman must confirm to ground personnel by Thump up signal. If not ready, the doorman must not reply.	Doorman								
3.	Doorman waits for 5 seconds for ground personnel to step back.	Doorman								
4.	Assist Doorman advises the doorman to ensure the door is in disarm mode. <table><tr><th>Assist Doorman</th><th>Doorman</th></tr><tr><td colspan="2">1) Calls: "Assist".</td></tr><tr><td colspan="2">2) Points to the door mode selector and calls: "Confirmed Disarm".</td></tr><tr><td colspan="2">3) Check mode selector disarm. Points and calls: "Disarm checked".</td></tr></table>	Assist Doorman	Doorman	1) Calls: "Assist".		2) Points to the door mode selector and calls: "Confirmed Disarm".		3) Check mode selector disarm. Points and calls: "Disarm checked".		Doorman, Assist Doorman
Assist Doorman	Doorman									
1) Calls: "Assist".										
2) Points to the door mode selector and calls: "Confirmed Disarm".										
3) Check mode selector disarm. Points and calls: "Disarm checked".										

Action		Responsible Person
5.	Open the door by using the 2-man crew concept.	Doorman, Assist Doorman
	Assist Doorman	
	Doorman	
	1) Calls: "Clear".	
	2) Calls: "Step 1". Lift door handle and hold.	
	3) Calls: "Step 2" Fully open door.	
Doorman opens the door according to procedures based on aircraft type.		

- Hand all flight documents and all empty cans of aircraft disinfection spray together with completed Gen Dec to ground personnel (if required).

19. Post-Flight Security Check

- Perform Post-flight Security Check throughout the aircraft (safety strap may be used)
- During Post-flight Security Check, ground personnel should not be allowed to enter the aircraft, unless deemed necessary.
- After completing the Post-flight Security Check, CA reports PIC by PA "ALL STATIONS, POST-FLIGHT SECURITY CHECK COMPLETED". PIC shall be acknowledged.

20. At OPC

Return documents to Cabin Crew Dispatcher:

- Integrated Route Folder (iRF)
- Catering Delivery Slip (Pink copy)

Note: In case there is any irregularity occurred, CA shall write a report via the reporting system.